Fall

(Page 1 of 3)

State of California AIR RESOURCES BOARD

EXECUTIVE ORDER A-10-638 Relating to Certification of New Motor Vehicles

FORD MOTOR COMPANY

Pursuant to the authority vested in the Air Resources Board by the Health and Safety Code, Division 26, Part 5, Chapter 2; and

Pursuant to the authority vested in the undersigned by Health and Safety Code Sections 39515 and 39516 and Executive Order G-45-9;

IT IS ORDERED AND RESOLVED: That 1996 model-year Ford Motor Company exhaust emission control systems are certified as described below for passenger cars:

Emission Standard Category: Transitional Low-Emission Vehicle (TLEV)

<u>Fuel Type</u>: Gasoline

Engine Family: TFM2.0VJG2HK <u>Displacement</u>: 2.0 Liters (122 Cubic Inches)

Exhaust Emission Control Systems and Special Features:

Warm-Up Three Way Catalytic Converter Three Way Catalytic Converter Heated Oxygen Sensors (two) Exhaust Gas Recirculation Sequential Multiport Fuel Injection

Vehicle models, transmissions, engine codes and evaporative emission control families are listed on attachments.

The TLEV certification exhaust emission standards for this engine family in grams per mile are:

<u>Miles</u>	Non-Methane Organic Gas	Carbon <u>Monoxide</u>	Nitrogen Oxides	<u>Formaldehyde</u>	Carbon <u>Monoxide (20°F)</u>
50,000	0.125	3.4	0.4	0.015	10.0
100,000	0.156	4.2	0.6	0.018	n/a

Reactivity Adjustment Factor (RAF) for NMOG Mass Emission: 0.98

The certification exhaust emission values set forth for non-methane organic gas (NMOG) reflect application of a 0.98 RAF for 1996 model-year TLEVs. The TLEV certification exhaust emission values for this engine family in grams per mile are (Values in parentheses are actual certification values before rounding off.):

<u>Miles</u>	Non-Methane <u>Organic Gas</u>	Carbon <u>Monoxide</u>	Nitrogen <u>Oxides</u>	<u>Formaldehyde</u>	Carbon <u>Monoxide (20°F)</u>
50,000	0.069	0.8	0.1	0.000 (0.00049) 6.5
100,000	0.074	0.9	0.1	0.000 (0.00049) n/a

FORD MOTOR COMPANY

BE IT FURTHER RESOLVED: That the vehicle manufacturer is certifying the listed vehicle models to the aforementioned exhaust emission standards based on its submitted plan to comply with the fleet average non-methane organic gas (NMOG) exhaust mass emission requirements as set forth in "California Exhaust Emission Standards and Test Procedures for 1988 and Subsequent Model Passenger Cars, Light-Duty Trucks, and Medium-Duty Vehicles".

BE IT FURTHER RESOLVED: That under the submitted NMOG fleet average compliance plan, if the manufacturer incurs a NMOG debit for the aforementioned model year based on the projected NMOG fleet average exceeding the value required by the above-referenced standards and test procedures, all incurred NMOG debits by the manufacturer shall be equalized as required by the standards and test procedures.

BE IT FURTHER RESOLVED: That the vehicle manufacturer is certifying the listed vehicle models to the 50,000-mile evaporative emission standards applicable to 1980 through 1994 model-year vehicles in the "California Evaporative Emission Standards and Test Procedures for 1978 and Subsequent Model Motor Vehicles", and the listed vehicle models comply with those standards.

BE IT FURTHER RESOLVED: That, based on the evaporative emission phase-in compliance schedule submitted by the vehicle manufacturer, the listed vehicle models shall not be subject to the running loss and useful life standards set forth in the "California Evaporative Emission Standards and Test Procedures for 1978 and Subsequent Model Motor Vehicles."

BE IT FURTHER RESOLVED: That the listed vehicle models also comply with the Board's "Specifications for Fill Pipes and Openings of Motor Vehicle Fuel Tanks" for the aforementioned model year (Title 13, California Code of Regulations, Section 2235).

BE IT FURTHER RESOLVED: That the listed vehicle models also comply with the Board's high-altitude requirements and highway emission standards, and with the California Inspection and Maintenance emission standards in place at the time of certification, as stipulated in "California Exhaust Emission Standards and Test Procedures for 1988 and Subsequent Model Passenger Cars, Light-Duty Trucks, and Medium-Duty Vehicles".

BE IT FURTHER RESOLVED: That the vehicle manufacturer has demonstrated compliance with the exhaust emission standards at 50 degrees Fahrenheit as stipulated in "California Exhaust Emission Standards and Test Procedures for 1988 and Subsequent Model Passenger Cars, Light-Duty Trucks, and Medium-Duty Vehicles."

BE IT FURTHER RESOLVED: That the listed vehicle models also comply with the "California Motor Vehicle Emission Control Label Specifications" for the aforementioned model year (Title 13, California Code of Regulations, Section 1965).

FORD MOTOR COMPANY

BE IT FURTHER RESOLVED: That the manufacturer is certifying the listed vehicle models with a partially complying on-board diagnostic system for the aforementioned model year pursuant to Title 13, California Code of Regulations, Section 1968.1(m)(6.1) ("Malfunction and Diagnostic System Requirements--1994 and Subsequent Model-Year Passenger Cars, Light-Duty Trucks, and Medium-Duty Vehicles and Engines").

BE IT FURTHER RESOLVED: That for the listed vehicles, the manufacturer has submitted and the Executive Officer hereby approves the materials to demonstrate certification compliance with the Board's emission control system warranty provisions (Title 13, California Code of Regulations, Section 2035 et seq.).

Vehicles certified under this Executive Order must conform to all applicable California emission regulations.

The Bureau of Automotive Repair will be notified by copy of this order and attachment.

Executed at El Monte, California this $\frac{27}{27}$ day of July 1995.

John Suns

R. B. Summerfield for Assistant Division Chief Mobile Source Division

1996 AIR RESOURCES BOARD SUPPLEMENTAL DATA SHEET PASSENGER CARS, LIGHT-DUTY TRUCKS AND MEDIUM-DUTY VEHICLES

Exhaust Engine Family: TFM2.0VJG2HK Manufacturer: Ford Motor Company Evap Standard: 50K X Useful Life with R/L Evap Family: TFM1065BYPAB Exhaust Std: Tier 0 __ Tier 1 __ TLEV X_LEV __ ULEV __ ZEV __; EPA Tier 0 ___ Tier 1 ___ Vehicle Class(es): PC X LDT1 LDT2 MDV1 MDV2 MDV3 MDV4 MDV5 Single Cert Std for Multi-Class Eng Fam: <u>N/A</u> (specify N/A, LDT1, MDV1, MDV2, MDV3, MDV4) Exh Cert Fuel(s): Indo ____ Ph2 X ___ Diesel: 13 CCR 2282 ___ or 40 CFR 86.113-90 ___ or -94 ___ M85 __ CNG __ LPG __ Other (specify) ____ Fuel Type(s): Dedicated ____ Flex-Fuel ___ Dual-Fuel ___ Gasoline X__ Diesel ___ M85 ___ CNG ____ LNG ___ LPG ___ Other (specify) _ Hybrid: Type A ____ B ____ C ___, APU Cycle (e.g., Otto, Diesel, Turbine) _____ Liter (CID): 2.0 (121.5) Engine Config: <u>1-4</u> Engine: Front_X_Mid.___ Rear___ Drive: FWD_X_RWD ___ 4WD-FT ___ 4WD-PT ___ (2) Exhaust ECS & Special Features: SFI/HO2S/EGR/TWC/WU-TWC (Use abbreviations per SAE J1930, Sep 91)

Engine Code (California)	Vehicle Models	Trans. Type A-Automatic M-Manual	ETW	DPA	Ignition (PCM) Part No.	EGR System Part No.	Catalyst Part No.
62FSDMON NO A/C	Probe	M5	3000	6.2 ^{*1} 5.8 ^{*2} 5.5 ^{*3}	Distributer: FSB9 ECU: FSC7	FS56	FSC5 B6CK
62FSDM0A 4/C	Probe	M5	3000	6.8 ^{*1} 6.4 ^{*2} 6.0 ^{*3}			
62FSDAON	Probe	L4	3125	6.2 ^{*1} 5.8 ^{*2} 5.5 ^{*3}	Distributer: FSB9 ECU: FSC8		
ezfsjaca a/c	Probe	L4	3125	6.8 ^{*1} 6.4 ^{*2} 6.0 ^{*3}			
"1 P195/65R14 "2 P205 55R15 #UN "1	LX tascia SE tascia			·			
ENGINE FAMILY: TFM ISSUED: 5/26/95 REVISED:	5.041G2HK		20.	09.17.0	2 - 1	۵	· · ·

1996 AIR RESOURCES BOARD SUPPLEMENTAL DATA SHEET PASSENGER CARS, LIGHT-DUTY TRUCKS AND MEDIUM-DUTY VEHICLES

Manufacturer:	Ford Motor Com	ipany	Exha	ust En	gine Family: [•]	TFM2.0VJG2H	IK
Evap Standard	: 50K <u>X</u> U	Iseful Life with	n R/L _		Evap Family:	TFM1065BY	PAB
Exhaust Std: 1	Tier 0 Tier 1 _		ev U	LEV _	_ ZEV ; EF	A Tier 0 `	Tier 1
Vehicle Class(e	es): PC <u>X</u> LD	T1 LDT2 _	_ MD\	/1 N		3 MDV4	MDV5
Single Cert Sto	d for Multi-Class	Eng Fam: <u>N</u>	<u>/A_</u> (sp	ecify N	/A, LDT1, MD	V1, MDV2, ME	0V3, MDV4)
Exh Cert Fuel(s): Indo Ph2 M85 CNG	<u>X</u> Diesel: LPG _ C	13 CO Other (s	CR 228 pecify)	2 or 40 CF	R 86.113-90 _	_ or -94
Fuel Type(s):	Dedicated F	iex-Fuel [LPG)ual-Fu Other	el ((speci	Gasoline <u>X</u> I fy)	Diesel M85	5
Hybrid: Type	АВС_	, APU Cyc	cle (e.g	., Otto,	Diesel, Turbi	ne)	
Engine Config	: <u>1-4</u>	Liter (CID):	<u>2.0 (1</u>	<u>21.5)</u>			
Engine: Front	<u>X</u> Mid Rea	ar Driv	e: FWI	D <u>X</u> I	RWD _ 4WD	-FT 4WD-I	РТ
Exhaust ECS (Use abbrevi	& Special Featur iations per SAE	es: <u>SFI/HO2</u> J1930, Sep 9 ⁻	<u>s/egr/</u> 1)	TWC/V	<u>vu-twc</u>		
Engine Code	Vehicle Models	Trans. Type	ETW	DPA	Ignition (PCM)	EGR System	Catalyst
(California)		M-Manual			Part No.	Part No.	Part No.
62FSDA1N	Probe		3125	6.2 ^{*1}	Distributer:	FS56	FSC5 B6CK
				5.0	-303		

5.5^{*3} ECU: 6.8^{*1} 6.4^{*2} 3125 L4 Probe 62FSDA1A 6.0^{*3}

*1 P195/65R14 *2 P205/55R15 with LX fascia

•

.

*3 P205/55R15 with SE fascia

ENGINE FAMILY: TFM2.0VJG2HK 1SSUED: 8/3/95 REVISED:

20.09.17.02 - 2

FSC8

1996 AIR RESOURCES BOARD SUPPLEMENTAL DATA SHEET PASSENGER CARS, LIGHT-DUTY TRUCKS AND MEDIUM-DUTY VEHICLES

Manufacturer: Ford Motor Company Exhaust Engine Family: TFM2.0VJG2HK
Evap Standard: 50K X Useful Life with R/L Evap Family: TFM1065BYPAB
Exhaust Std: Tier 0 Tier 1 TLEV X_LEV ULEV ZEV ; EPA Tier 0 Tier 1
Vehicle Class(es): PC X LDT1 LDT2 MDV1 MDV2 MDV3 MDV4 MDV5
Single Cert Std for Multi-Class Eng Fam: <u>N/A</u> (specify N/A, LDT1, MDV1, MDV2, MDV3, MDV4)
Exh Cert Fuel(s): Indo Ph2_X Diesel: 13 CCR 2282 or 40 CFR 86.113-90 or -94 M85 CNG LPG Other (specify)
Fuel Type(s): Dedicated Flex-Fuel Dual-Fuel Gasoline X Diesel M85 CNG LNG LNG LPG Other (specify)
Hybrid: Type A B C, APU Cycle (e.g., Otto, Diesel, Turbine)
Engine Config: <u>1-4</u> Liter (CID): <u>2.0 (121.5)</u>
Engine: Front_X_Mid Rear Drive: FWD X_RWD 4WD-FT 4WD-PT
Exhaust ECS & Special Features: SFI/HO2S/EGR/TWC/WU-TWC

(Use abbreviations per SAE J1930, Sep 91)

-

Engine Coo (California	de Vehicle Models 1)	Trans. Type A-Automatic M-Manual	ETW	DPA	Ignition (PCM) Part No.	EGR System Part No.	Catalyst Part No.	
62FSDM1N	Probe	M5	3000	6.2 ^{*1} 5.8 ^{*2} 5.5 ^{*3}	Distributer: FSB9 ECU: FSC7	FS56	FSC5 B6CK	
62FSDM1A	Probe	M5	3000	6.8 ^{*1} 6.4 ^{*2} 6.0 ^{*3}				
62FSDA2N	Probe	L4	3125	6.2 ^{*1} 5.8 ^{*2} 5.5 ^{*3}	Distributer: FSB9 ECU: FSC8			
62FSDA2A	Probe	L4	3125	6.8 ^{*1} 6.4 ^{*2} 6.0 ^{*3}				
^{*1} P195/65R14 ^{*2} P205/55R15 with ^{*3} P205/55R15 with	LX fascia SE fascia							
ENGINE FAMILY. TH	M2.OVJG2HK		20.0	9.17.02	- 3			

and the second second

ENGINE FAMILY: TFM2.0VJG2HK ISSUED: 8/3/95 REVISED:

1996 AIR RESOURCES BOARD SUPPLEMENTAL DATA SHEET PASSENGER CARS, LIGHT-DUTY TRUCKS AND MEDIUM-DUTY VEHICLES

Manufacturer: Ford Motor Company Exhaust Engine Family: TFM2.0VJG2HK
Evap Standard: 50K X Useful Life with R/L Evap Family: TFM1065BYPAB
Exhaust Std: Tier 0 Tier 1 TLEV X_ LEV ULEV ZEV ; EPA Tier 0 Tier 1
Vehicle Class(es): PC X LDT1 LDT2 MDV1 MDV2 MDV3 MDV4 MDV5
Single Cert Std for Multi-Class Eng Fam: <u>N/A</u> (specify N/A, LDT1, MDV1, MDV2, MDV3, MDV4)
Exh Cert Fuel(s): Indo Ph2 X Diesel: 13 CCR 2282 or 40 CFR 86.113-90 or -94 M85 CNG LPG Other (specify)
Fuel Type(s): Dedicated Flex-Fuel Dual-Fuel Gasoline X Diesel M85 CNG LNG LPG Other (specify) Diesel M85
Hybrid: Type A B C, APU Cycle (e.g., Otto, Diesel, Turbine)
Engine Config: <u>1-4</u> Liter (CID): <u>2.0 (121.5)</u>
Engine: Front_X_MidRear Drive: FWD X_RWD 4WD-FT 4WD-PT
Exhaust ECS & Special Features: <u>SFI/HO2S/EGR/TWC/WU-TWC</u> (Use abbreviations per SAE J1930, Sep 91)

Engine Code	Vehicle Models	Trans. Type	ETW	DPA	Ignition (PCM)	EGR System	Catalyst	
(California)		M-Manual			Part No.	Part No.	Part No.	
62FSDA3N	Prob e	L4	3125	6.2 ^{*1} 5.8 ^{*2} 5.5 ^{*3}	Distributer: FSB9 ECU: FSC8	FS56	FSC5 B6CK	
62FSDA3A	Probe	L4	3125	6.8 ^{*1} 6.4 ^{*2} 6.0 ^{*3}				

· · ·

^{*1} P195/65R14 ^{*2} P205/55R15 with LX fascia ^{*3} P205/55R15 with SE fascia

ENGINE FANILY: TFM2.0VJG2HK ISSUED: 8/7/95 REVISED:

20.09.17.02 - 4

المحارجة الشمرجة التاريشين مراجعين

1996 AIR RESOURCES BOARD SUPPLEMENTAL DATA SHEET

PASSENGER CARS, LIGHT-DUTY TRUCKS AND MEDIUM-DUTY VEHICLES

Manufacturer: Ford Motor Company Exhaust Engine Family: TFM2.0VJG2HK
Evap Standard: 50K X Useful Life with R/L Evap Family: TFM1065BYPAB
Exhaust Std: Tier 0 Tier 1 TLEV X_ LEV ULEV ZEV; EPA Tier 0 Tier 1
Vehicle Class(es): PC X LDT1 LDT2 MDV1 MDV2 MDV3 MDV4 MDV5
Single Cert Std for Multi-Class Eng Fam: <u>N/A</u> (specify N/A, LDT1, MDV1, MDV2, MDV3, MDV4)
Exh Cert Fuel(s): Indo Ph2 X_ Diesel: 13 CCR 2282 or 40 CFR 86.113-90 or -94 M85 CNG LPG Other (specify)
Fuel Type(s): Dedicated Flex-Fuel Dual-Fuel Gasoline X Diesel M85 CNG LNG LPG Other (specify)
Hybrid: Type A B C, APU Cycle (e.g., Otto, Diesel, Turbine)
Engine Config: <u>1-4</u> Liter (CID): <u>2.0 (121.5)</u>
Engine: Front_X_ Mid Rear Drive: FWD_X_ RWD 4WD-FT 4WD-PT
(ک) Exhaust ECS & Special Features: <u>SFI/HO2S/EGR/TWC/WU-TWC</u> (Use abbreviations per SAE J1930, Sep 91)

Engine Code (California)	Vehicle Models	Trans. Type A-Automatic M-Manual	ETW	DPA	Ignition (PCM) Part No.	EGR System Part No.	Catalyst Part No.
62FSDM2N	Probe	M5	3000	6.2 ^{°1} 5.8 ^{°2} 5.5 ^{°3}	Distributer: FSB9 ECU: FSC7	FS56	FSC5 B6CK
62FSDM2A	Probe	M5	3000	6.8 ^{*1} 6.4 ^{*2} 6.0 ^{*3}			
62FSDA4N	Probe	L4	3125	6.2 ^{*1} 5.8 ^{*2} 5.5 ^{*3}	Distributer: FSB9 ECU: FSC8		
62FSDA4A	Probe	L4	3125	6.8 ^{*1} 6.4 ^{*2} 6.0 ^{*3}			
¹¹ P195/65R14 ¹² P205/55R15 with LX ¹³ P205/55R15 with SE	(fascia E fascia						
ENGINE FAMILY: TFM2.0VJG2HK ISSUED: 11/17/95			20.09	2.17.02	- 5		

REVISED: