Fiel

(Page 1 of 3)

State of California AIR RESOURCES BOARD

EXECUTIVE ORDER A-14-290 Relating to Certification of New Motor Vehicles

TOYOTA MOTOR CORPORATION

Pursuant to the authority vested in the Air Resources Board by the Health and Safety Code, Division 26, Part 5, Chapter 2; and

Pursuant to the authority vested in the undersigned by Health and Safety Code Sections 39515 and 39516 and Executive Order G-45-9;

IT IS ORDERED AND RESOLVED: That 1996 model-year Toyota Motor Corporation exhaust emission control systems are certified as described below for passenger cars:

Fuel Type: Gasoline

Engine Family: TTY4.0VJGKEK <u>Displacement</u>: 4.0 Liters (242.2 Cubic Inches)

Exhaust Emission Control Systems and Special Features:

Sequential Multiport Fuel Injection Exhaust Gas Recirculation Dual Heated Oxygen Sensors (two) Dual Three Way Catalytic Converters Three Way Catalytic Converter

Vehicle models, transmissions, engine codes and evaporative emission control families are listed on attachments.

The certification exhaust emission standards for this engine family in grams per mile are:

Miles_	Non-Methane	Carbon	Nitrogen	Carbon
	<u>Hydrocarbons</u>	<u>Monoxide</u>	<u>Oxides</u>	<u>Monoxide (20⁰F)</u>
50,000	0.25	3.4	0.4	10.0
100,000	0.31	4.2		n/a

The certification exhaust emission values for this engine family in grams per mile are:

Miles_	Non-Methane	Carbon	Nitrogen	Carbon
	<u>Hydrocarbons</u>	<u>Monoxide</u>	<u>Oxides</u>	<u>Monoxide (20⁰F)</u>
50,000	0.09	0.9	0.1	4.9
100,000		0.9	0.1	n/a

BE IT FURTHER RESOLVED: That the listed vehicle models also comply with the "California Motor Vehicle Emission Control Label Specifications" for the aforementioned model year (Title 13, California Code of Regulations, Section 1965).

BE IT FURTHER RESOLVED: That the vehicle manufacturer is certifying the listed vehicle models to the aforementioned exhaust emission standards based on its submitted plan to comply with the fleet average non-methane organic gas (NMOG) exhaust mass emission requirements as set forth in "California Exhaust Emission Standards and Test Procedures for 1988 and Subsequent Model Passenger Cars, Light-Duty Trucks, and Medium-Duty Vehicles".

BE IT FURTHER RESOLVED: That under the submitted NMOG fleet average compliance plan, if the manufacturer incurs a NMOG debit for the aforementioned model year based on the projected NMOG fleet average exceeding the value required by the above-referenced standards and test procedures, all incurred NMOG debits by the manufacturer shall be equalized as required by the standards and test procedures.

BE IT FURTHER RESOLVED: That the vehicle manufacturer is certifying the listed vehicle models to the 50,000-mile evaporative emission standards applicable to 1980 through 1994 model-year vehicles in the "California Evaporative Emission Standards and Test Procedures for 1978 and Subsequent Model Motor Vehicles", and the listed vehicle models comply with those standards.

BE IT FURTHER RESOLVED: That, based on the evaporative emission phase-in compliance schedule submitted by the vehicle manufacturer, the listed vehicle models shall not be subject to the running loss and useful life standards set forth in the "California Evaporative Emission Standards and Test Procedures for 1978 and Subsequent Model Motor Vehicles."

BE IT FURTHER RESOLVED: That the listed vehicle models also comply with the Board's "Specifications for Fill Pipes and Openings of Motor Vehicle Fuel Tanks" for the aforementioned model year (Title 13, California Code of Regulations, Section 2235).

BE IT FURTHER RESOLVED: That the listed vehicle models also comply with the Board's high-altitude requirements and highway emission standards, and with the California Inspection and Maintenance emission standards in place at the time of certification, as stipulated in "California Exhaust Emission Standards and Test Procedures for 1988 and Subsequent Model Passenger Cars, Light-Duty Trucks, and Medium-Duty Vehicles".

BE IT FURTHER RESOLVED: That the listed vehicle models also comply with the "Malfunction and Diagnostic System Requirements--1994 and Subsequent Model-Year Passenger Cars, Light-Duty Trucks, and Medium-Duty Vehicles and Engines" (Title 13, California Code of Regulations, Section 1968.1) for the aforementioned model year.

BE IT FURTHER RESOLVED: That for the listed vehicles, the manufacturer has submitted and the Executive Officer hereby approves the materials to demonstrate certification compliance with the Board's emission control system warranty provisions (Title 13, California Code of Regulations, Section 2035 et seq.).

Vehicles certified under this Executive Order must conform to all applicable California emission regulations.

The Bureau of Automotive Repair will be notified by copy of this order and attachment.

Executed at El Monte, California this 3rd day of August 1995.

AR. B. Summerfield Assistant Division Chief Mobile Source Division

Regional Surnowity

1996 MODEL-YEAR AIR RESOURCES BOARD SUPPLEMENTAL DATA SHEET PASSENGER CARS, LIGHT-DUTY TRUCKS AND MEDIUM-DUTY VEHICLES

	TTY4.0VJGKEK Evap Fam: TTY1080DYMA0
All Eng Codes in Eng Fam: CA 49S	50S x AB965
Exh Std: CA Tier-1 x TLEV LEV	ULEV ZEV; US EPA Tier-1 x In-Use Exh Std: Full In Use x Alt In Use
Evap std: 50K x Useful Life with R/L	In-Use Exh Std: Full In Use x Alt In Use
Veh Class(es): PC x LDT1 LDT2 M	$\overline{\text{DV}}$ 1 MDV2 MDV3 $\overline{\text{MD}}$ V4 MDV5
Single Cert Std for Multi-Class Eng Fam: N/A	(specify: N/A, LDT1, MDV1, MDV2, MDV3, MDV4)
Fuel Type(s): Dedicated x Flex-Fuel I	Dual-Fuel Bi-Fuel Gasoline x Diesel
CNG LNG LPG	M85 Other(specify)
Emiss Test Fuel(s): Indo x Ph2 CNG	LPG M85 Other(specify)
Diesel: 13CCR 2282	40 CFR 86.113-90 40 CFR 86.113-94
Service Accum: Std AMA X Mod AMA	Mfr ADP Other(specify)
NMOG Test Procedure: N/A x Std Equ	uiv R/L Test Proc: SHED Pt Source
Hybrid: Type A B C , APU Cyc	cle(e.g., Otto, Diesel, Turbine):
Engine Configuration: V-8 Displacement:	4.0 / Liters 242.2 / Cubic Inches
NMOG Test Procedure: N/A x Std Equ Hybrid: Type A B C , APU Cy Engine Configuration: V-8 Displacement: Valves per Cylinder: 4 R	lated HP: 260 @ 5,300 RPM
Engine: Front x Mid Rear Driv	e: FWD RWD x 4WD-FT 4WD-PT
Exhaust ECS(e.g., MFI, EGR, TC, CAC): SFI, EGI	
(us	se abbreviations per SAE J1930 SEP91)

Engine Code/ (also list CA/ 49S/ 50ST)	Vehicle Models (if coded see attachment)	Trans. (M5, A4 etc.)	ETW or Test Wt	DPA or RLHP	Ignition (ECM/PCM) Part No.	EGR System Part No.	Catalytic converter part No.
1, 1R1, 1R2 & 1R3	UZZ30L-ACPZKA	L4	4000	8.3 8.5	89661-24450*1 89661-24451*2 89661-24452*3 89661-24453*4	25620-50030	Front: A01 A03 Rear: L01

Please refer to manufacturer's HP list for correct dyno test HP setting based on model and equipment. Comments:

Note

Before running change 96-TR-2. After running change 96-TR-3 and Before running change 96-TR-3. After running change 96-TR-3 and Before running change 96-TR-5. After running change 96-TR-5.

VEHICLE MODELS:

SC400 UZZ30L-ACPZKA

: 17.11-TTY4.0VJGKEK-1 page

Issued : 04/03/95 96-TR-2: 07/21/95 96-TR-3 : 07/21/95

96-TR-5: 10/06/95

1996 MODEL-YEAR AIR RESOURCES BOARD SUPPLEMENTAL DATA SHEET PASSENGER CARS, LIGHT-DUTY TRUCKS AND MEDIUM-DUTY VEHICLES

1.8

Manufacturer: TOYOTA	Exh Eng Fam	TTY4.0VJGKEK	Evap Fam:	TTY1080DYMA0
All Eng Codes in Eng Fam: C	A 49S	50S x AB965		
Exh Std: CA Tier-1 x T	LEV LEV	ULEV ZE	₹V;	US EPA Tier-1 x
Evap std: 50K x Useful I	Life with R/L	In-Use Exh Std:	Full In Use	
Veh Class(es): PC x LDT	I LDT2 M	DV1 MDV2	MDV3	MDV4 MDV5
Single Cert Std for Multi-Class I	Eng Fam: N/A	(specify: N/A,	LDT1, $M\overline{DV}1$, 1	$MDV2, \overline{M}DV3, MD\overline{V4}$
Fuel Type(s): Dedicated x				soline x Diesel
	LNG LPG		ther(specify)	
Emiss Test Fuel(s): Indo x	Ph2 CNG	_ LPG M85	Other(sp	ecify)
Diesel:	13CCR 2282	40 CFR 86.113-90		CFR 86.113-94
Service Accum: Std AMA X			her(specify)	
NMOG Test Procedure: N/A x		uiv R/L Test		Pt Source
Hybrid: Type A B		cle(e.g., Otto, Diesel,		
Engine Configuration: V-8	Displacement:		Liters 242.2	/ Cubic Inches
Valves per Cylinder: 4	•	Rated HP: 260	@	5,300 RPM
Engine: Front x Mid	Rear Dri		D x 4WD-F	
Exhaust ECS(e.g., MFI, EGR, TO		R,2HO2S(2),2TWC,TV		
		se abbreviations per S.)1)
	(*	or accreviations per c	. 12 01700 0217	••)
	Sect/Page#			Sect/Page #
1 Authorized Representative		Gen Std, increase in	Emiss	occuraço n
2 Fuel Specifications	03.00.00	Safety, Meets all Re		20.03.05
3 Test Equipment		Emission Label Dura		07.00.00
4 Test Procedure		Driveability Stateme		17.01.02
5 Mileage Accumulation Route		Adjustable Paramete		08.16.01.00
6 Emission Warranty Statemen		Tamper Resistance N		08.16.02.00
7 Maint: Cert/Req'd/Recm'd		Fill Pipe Specification		17.04.00
8 Emiss Label/Vac Hose Diag		High Altitude Comp		17.02.00
9 Evap Control System		OBD Sys incl Market		02.06.00
10 Engine Parameters		I&M Test Procedure		17.11.00
11 Fuel System		50 Degree F Compli		N/A
12 Iginition System		Manufacturer's RAF	unoc	N/A
13 Exhaust Control System		Phase-In Plans: Exh	Cert Stds	N/A
14 Proj Sales(LDT/MDV Split)	17.13.00		In-Use Stds	17.18.00
15 Vehicle Description	20.02.08		Cert Stds	17.19.00
16 Evap Bench Test Procedure		NMOG Fleet Averag		17.15.00
17 R/L Temp & Press Profiles		AB965 Credits/With		N/A
18 EDV Selection		EPA Certificate 72	WAT - / DU -	N/A 0/00
19 Prod Veh same as Test Veh	17.01.01	Equiv NMOG Proc-	ADR Approval	N/A
1) I lod ven same as lest ven	Durability		nission	Emission
20 Test Vehicle Information	Data Vehicle		ata Vehicle	Data Vehicle
C/O or C/A MY & ID	C/O 92-D3	96-UZ1	96-UZ1	Data Venicle
Vehicle Log Page(s)	20.03.04		0.03.04	
Zero Mile Book Page(s)	17.12.01(92MY)		0.03.06	
Maint Logs & Engr Eval	17.12.01(92MY)		.02.02	
Munic Pogo & Diigi Lvai	17.12.02(721/11)	11/15 1/	.02.02	

Continued on next page

Page : 17.11-TTY4.0VJGKEK-2 Issued : 04/03/95