State of California AIR RESOURCES BOARD

EXECUTIVE ORDER A-86-200 Relating to Certification of New Motor Vehicles

MITSUBISHI MOTORS CORPORATION

Pursuant to the authority vested in the Air Resources Board by the Health and Safety Code, Division 26, Part 5, Chapter 2; and

Pursuant to the authority vested in the undersigned by Health and Safety Code Sections 39515 and 39516 and Executive Order G-45-9;

IT IS ORDERED AND RESOLVED: That 1996 model-year Mitsubishi Motors Corporation exhaust emission control systems are certified as described below for light-duty trucks:

Fuel Type: Gasoline

Engine Family: TMT2.418GFEK <u>Displacement</u>: 2.4 Liters (143.4 Cubic Inches)

Exhaust Emission Control Systems and Special Features:

Exhaust Gas Recirculation Three Way Catalytic Converter Heated Oxygen Sensors (two) Sequential Multiport Fuel Injection

Vehicle models, transmissions, engine codes and evaporative emission control families are listed on attachments.

The certification exhaust emission standards for this engine family in grams per mile are:

Loaded Vehicle	Miles	Non-Methane	Carbon	Nitrogen	Carbon
<u>Weight(lbs.)</u>		<u>Hydrocarbons</u>	<u>Monoxide</u>	Oxides	<u>Monoxide (20⁰F)</u>
0-3750	50,000	0.25	3.4	0.4	10.0
	100,000	0.31	4.2	0.6	n/a

The certification exhaust emission values for this engine family in grams per mile are:

Loaded Vehicle	Miles	Non-Methane	Carbon	Nitrogen	Carbon
Weight(lbs.)		<u>Hydrocarbons</u>	<u>Monoxide</u>	<u>Oxides</u>	<u>Monoxide (20⁰F)</u>
0-3750	50,000	0.17	1.5	0.2	6.7
	100,000	0.18	1.7	0.3	n/a

BE IT FURTHER RESOLVED: That the vehicle manufacturer is certifying the listed vehicle models to the aforementioned exhaust emission standards based on its submitted plan to comply with the fleet average non-methane organic gas (NMOG) exhaust mass emission requirements as set forth in "California Exhaust Emission Standards and Test Procedures for 1988 and Subsequent Model Passenger Cars, Light-Duty Trucks, and Medium-Duty Vehicles".

MITSUBISHI MOTORS CORPORATION

BE IT FURTHER RESOLVED: That under the submitted NMOG fleet average compliance plan, if the manufacturer incurs a NMOG debit for the aforementioned model year based on the projected NMOG fleet average exceeding the value required by the above-referenced standards and test procedures, all incurred NMOG debits by the manufacturer shall be equalized as required by the standards and test procedures.

BE IT FURTHER RESOLVED: That the vehicle manufacturer is certifying the listed vehicle models to the 50,000-mile evaporative emission standards applicable to 1980 through 1994 model-year vehicles in the "California Evaporative Emission Standards and Test Procedures for 1978 and Subsequent Model Motor Vehicles", and the listed vehicle models comply with those standards.

BE IT FURTHER RESOLVED: That, based on the evaporative emission phase-in compliance schedule submitted by the vehicle manufacturer, the listed vehicle models shall not be subject to the running loss and useful life standards set forth in the "California Evaporative Emission Standards and Test Procedures for 1978 and Subsequent Model Motor Vehicles."

BE IT FURTHER RESOLVED: That the listed vehicle models also comply with the Board's "Specifications for Fill Pipes and Openings of Motor Vehicle Fuel Tanks" for the aforementioned model year (Title 13, California Code of Regulations, Section 2235).

BE IT FURTHER RESOLVED: That the listed vehicle models also comply with the Board's high-altitude requirements and highway emission standards, and with the California Inspection and Maintenance emission standards in place at the time of certification, as stipulated in "California Exhaust Emission Standards and Test Procedures for 1988 and Subsequent Model Passenger Cars, Light-Duty Trucks, and Medium-Duty Vehicles".

BE IT FURTHER RESOLVED: That the listed vehicle models also comply with the "California Motor Vehicle Emission Control Label Specifications" for the aforementioned model year (Title 13, California Code of Regulations, Section 1965).

BE IT FURTHER RESOLVED: That for the listed vehicles, the manufacturer has submitted and the Executive Officer hereby approves the materials to demonstrate certification compliance with the Board's emission control system warranty provisions (Title 13, California Code of Regulations, Section 2035 et seq.).

BE IT FURTHER RESOLVED: That the manufacturer is certifying the listed vehicle models with a partially complying on-board diagnostic system for the aforementioned model year pursuant to Title 13, California Code of Regulations, Section 1968.1(m)(6.1) ("Malfunction and Diagnostic System Requirements--1994 and Subsequent Model-Year Passenger Cars, Light-Duty Trucks, and Medium-Duty Vehicles and Engines").

MITSUBISHI MOTORS CORPORATION

•

EXECUTIVE ORDER A-86-200 (Page 3 of 3)

Vehicles certified under this Executive Order must conform to all applicable California emission regulations.

The Bureau of Automotive Repair will be notified by copy of this order and attachment.

Executed at El Monte, California this 30^{4} day of August 1995.

mulut

R. B//Summerfield Assistant Division Chief Mobile Source Division

17-16.02

E.O.# A-86-200

age 1 of 1

1996 MODEL-YEAR AIR RESOURCES BOARD SUPPLEMENTAL DATA SHEET PASSENGER CARS, LIGHT-DUTY TRUCKS AND MEDIUM DUTY VEHICLES

Manufacturer: Mitsubishi Motors Corp Exh Engine Family: TMT2.418GFEK(2.4TB) Evap Engine Family: TMT1058BYMBF All Engine Codes in Eng Fam: CA____49S____50S_X_AB 965_ Exh Std: CA Tier-1_X_TLEV__LEV__ULEV__ZEV__; US EPA Tier-1_X_ Evap Std: 50K X_ Useful Life with R/L___ In-Use Std: Full In-Use X_ Alt In-Use___ Veh Class(es): PC__LDT1_X_LDT2__MGV1__MDV2__MDV3__MDV4_MDV5 Single Cert Std for Multi-Class Eng Fam: $\overline{N/A}$ (specify: $\overline{N/A}$, LDT1, MDV1, ..., MDV4) Fuel Type(s): Dedicated X Flex-Fuel Dual-Fuel Bi-Fuel Gasoline X Diesel_ CNG_ LNG_ LPG_ M85_ Other (specify) Emis Test Fuel: Indo_X Ph2_ CNG LPG_ M85_ Other (specify) Diesel: 13 CCR 2282_ 40CFR 86.113-90_ 40CFR 86.113-94_ Service Accum: Std AMA Mod AMA Mfr ADP Other (specify) AMA4 (Sec 20.07) NMOG Test Proc: N/AX_Std_ Equiv_ R/L Test Proc: SHED_ Pt Source_ APU Cycle (e.g., Otto, Diesel, Turbine)___ Hybrid: Type A__ B__ C__, Engine Configuration: IL4 Displacement: 2.4 Liters / 143,4 Cubic Inches Rated HP: <u>116 @ 5500 RPM</u> Valves per Cyl: 2 Engine: Front_X_Mid__ Rear__ Drive: FWD__ RWD_X_4WD-FT_X_4WD-PT__ Exhaust ECS (eg., EGR, MPI, TC, CAC): EGR+H02S(2)+TWC+SFI (abbreviations per SAE J1930 SEP91)

Engine Code (also list CAL/FED/BOTH)	Vehicle Models (if coded see attachment)	Trans. Type *1	BTW	DPA or RLHP	Ignition (ECM/PCM) Part No.	EGR System Part No.	Catalytic Converter Part No.
BM(BOTH)	Mitsubishi Truck 2WD	M5	3000	11.0	Distributor: MD143571 (T1T42075)	EGR Valve: MD155224 (HE#)	мв906611 (P4)
BA(BOTH)		L4	3125		ECM: MD318462 (E2T34182)	Solenoid: MR161746 (K5T49681)	

*1: M-Manual transmission

L-Automatic transmission with lock-up