

State of California  
AIR RESOURCES BOARD

EXECUTIVE ORDER A-30-108  
Relating to Certification of New Motor Vehicles

AUDI AG

Pursuant to the authority vested in the Air Resources Board by the Health and Safety Code, Division 26, Part 5, Chapter 2; and

Pursuant to the authority vested in the undersigned by Health and Safety Code Sections 39515 and 39516 and Executive Order G-45-9;

IT IS ORDERED AND RESOLVED: That 1996 model-year Audi AG exhaust emission control systems are certified as described below for passenger cars:

Emission Standard Category: Transitional Low-Emission Vehicle (TLEV)

Fuel Type: Gasoline

Engine Family: TAD2.8V8G2EM Displacement: 2.8 Liters (169 Cubic Inches)

Exhaust Emission Control Systems and Special Features:

- Sequential Multiport Fuel Injection
- Dual Three Way Catalytic Converters
- Dual Heated Oxygen Sensors (Two)
- Exhaust Gas Recirculation
- Secondary Air Injection

Vehicle models, transmissions, engine codes and evaporative emission control families are listed on attachments.

The TLEV certification exhaust emission standards for this engine family in grams per mile are:

<u>Miles</u>	<u>Non-Methane Organic Gas</u>	<u>Carbon Monoxide</u>	<u>Nitrogen Oxides</u>	<u>Formaldehyde</u>	<u>Carbon Monoxide (20° F)</u>
50,000	0.125	3.4	0.4	0.015	10.0
100,000	0.156	4.2	0.6	0.018	n/a

Reactivity Adjustment Factor (RAF) for NMOG Mass Emission: 0.98

The certification exhaust emission values set forth for non-methane organic gas (NMOG) reflect application of a 0.98 RAF for 1996 model-year TLEVs. The TLEV certification exhaust emission values for this engine family in grams per mile are:

<u>Miles</u>	<u>Non-Methane Organic Gas</u>	<u>Carbon Monoxide</u>	<u>Nitrogen Oxides</u>	<u>Formaldehyde</u>	<u>Carbon Monoxide (20° F)</u>
50,000	0.102	1.2	0.1	0.004	2.2
100,000	0.102	1.2	0.1	0.004	n/a

BE IT FURTHER RESOLVED: That the vehicle manufacturer is certifying the listed vehicle models to the aforementioned exhaust emission standards based on its submitted plan to comply with the fleet average non-methane organic gas (NMOG) exhaust mass emission requirements as set forth in "California Exhaust Emission Standards and Test Procedures for 1988 and Subsequent Model Passenger Cars, Light-Duty Trucks, and Medium-Duty Vehicles".

BE IT FURTHER RESOLVED: That under the submitted NMOG fleet average compliance plan, if the manufacturer incurs a NMOG debit for the aforementioned model year based on the projected NMOG fleet average exceeding the value required by the above-referenced standards and test procedures, all incurred NMOG debits by the manufacturer shall be equalized as required by the standards and test procedures.

BE IT FURTHER RESOLVED: That the vehicle manufacturer is certifying the listed vehicle models to the running loss and useful life standards applicable to 1995 and subsequent model-year vehicles in the "California Evaporative Emission Standards and Test Procedures for 1978 and Subsequent Model Motor Vehicles", and the listed vehicle models comply with those standards.

BE IT FURTHER RESOLVED: That the listed vehicle models also comply with the Board's "Specifications for Fill Pipes and Openings of Motor Vehicle Fuel Tanks" for the aforementioned model year (Title 13, California Code of Regulations, Section 2235).

BE IT FURTHER RESOLVED: That the listed vehicle models also comply with the Board's high-altitude requirements and highway emission standards, and with the California Inspection and Maintenance emission standards in place at the time of certification, as stipulated in "California Exhaust Emission Standards and Test Procedures for 1988 and Subsequent Model Passenger Cars, Light-Duty Trucks, and Medium-Duty Vehicles".

BE IT FURTHER RESOLVED: That the manufacturer is certifying the listed vehicle models with a partially complying on-board diagnostic system for the aforementioned model year pursuant to Title 13, California Code of Regulations, Section 1968.1(m)(6.1) ("Malfunction and Diagnostic System Requirements--1994 and Subsequent Model-Year Passenger Cars, Light-Duty Trucks, and Medium-Duty Vehicles and Engines").

BE IT FURTHER RESOLVED: That the listed vehicle models also comply with the "California Motor Vehicle Emission Control Label Specifications" for the aforementioned model year (Title 13, California Code of Regulations, Section 1965).

BE IT FURTHER RESOLVED: That the vehicle manufacturer has demonstrated compliance with the exhaust emission standards at 50 degrees Fahrenheit as stipulated in "California Exhaust Emission Standards and Test Procedures for 1988 and Subsequent Model Passenger Cars, Light-Duty Trucks, and Medium-Duty Vehicles."

BE IT FURTHER RESOLVED: That for the listed vehicles, the manufacturer has submitted and the Executive Officer hereby approves the materials to demonstrate certification compliance with the Board's emission control system warranty provisions (Title 13, California Code of Regulations, Section 2035 et seq.).

Vehicles certified under this Executive Order must conform to all applicable California emission regulations.

The Bureau of Automotive Repair will be notified by copy of this order and attachment.

Executed at El Monte, California this 27<sup>th</sup> day of September 1995.



R. B. Summerfield  
Assistant Division Chief  
Mobile Source Division

1996 AIR RESOURCES BOARD SUPPLEMENTAL DATA SHEET  
PASSENGER CARS, LIGHT-DUTY TRUCKS AND MEDUM-DUTY VEHICLES

Manufacturer: AUDI AG Exh Eng Fam: TAD2.8V8G2EM Evap Fam: TAD1240BYMEV  
 All Eng Codes in Eng Fam: CA X 49S 50S AB965  
 Exh Std: CA Tier-1 TLEV X LEV ULEV ZEV US EPA Tier-1  
 Evap Std: 50K Useful Life with R/L X In-use Exh Std: Full In Use X Alt In Use  
 Veh Class(es): PC X LDT1 LDT2 MDV1 MDV2 MDV3 MDV4 MDV5  
 Single Cert Std for Multi-Class Eng Fam: N/A (specify: N/A, LDT1, MDV1, MDV2, MDV3, MDV4)  
 Fuel Type(s): Dedicated X Flex-Fuel Dual-Fuel Bi-Fuel Gasoline X Diesel  
CNG LNG LPG M85 Other (specify) \_\_\_\_\_  
 Emiss Test Fuel(s): Indo Ph2 X CNG LPG M85 Other (specify) \_\_\_\_\_  
Diesel: 13 CCR 2282 40 CFR 86.113-90 40 CFR 86.113-94  
 Service Accum: Std AMA X Mod AMA Mfr ADP Other (specify) \_\_\_\_\_  
 NMOG Test Procedure: N/A Std X Equip R/L Test Proc: SHED Pt Source X  
 Hybrid: Type A B C APU Cycle (e.g., Otto, Diesel, Turbine) \_\_\_\_\_  
 Engine Config. V6 Displacement: 2.8 Liters 169 Cubic Inches  
 Valves per Cylinder: 2 Rated HP: 172 @ 5500 RPM  
 Engine: Front X Mid. Rear Drive: FWD X RWD 4WD-FT X 4WD-PT  
 Exhaust ECS (eg., EGR, MFI, TC, CAC, etc.) SFI / 2TWC / 2 HO2S / 2 EGR / AIR  
 (use abbreviations per SAE 1930 SEP91)

Engine Code (also list CA/49ST/50ST)	Vehicles Models (if coded see attachment)	Trans. Type A-auto M-man.	EIW or Test WT	DPA or RLHP	Ignition (ECM/PCM) Part No.	EGR System Part No.	Catalytic Converter Part No.
AJSE	A6	L4	3750	7.0	8D0 906 266 A	078 191 503	4A0 178 J and 4A0 178 H
"		L4	3875	7.0	"	"	"
"	A6 Quattro	L4Q	4000	8.2	"	"	"
		L4Q	4250	8.2	"	"	"

Date Issued: 07-07-96

Revisions: \_\_\_\_\_