State of California AIR RESOURCES BOARD

EXECUTIVE ORDER A-9-356 Relating to Certification of New Motor Vehicles

CHRYSLER CORPORATION

Pursuant to the authority vested in the Air Resources Board by the Health and Safety Code, Division 26, Part 5, Chapter 2; and

Pursuant to the authority vested in the undersigned by Health and Safety Code Sections 39515 and 39516 and Executive Order G-45-9;

IT IS ORDERED AND RESOLVED: That 1997 model-year Chrysler Corporation exhaust emission control systems are certified as described below for light-duty trucks:

Emission Standard Category: Transitional Low-Emission Vehicle (TLEV)

Fuel Type: Gasoline

Engine Family: VCR24228G2JK Displacement: 4.0 Liters (242 Cubic Inches)

Exhaust Emission Control Systems and Special Features:

Warm Up Oxidation Catalytic Converter Three Way Catalytic Converter Heated Oxygen Sensors (two) Sequential Multiport Fuel Injection

Vehicle models, transmissions, engine codes and evaporative emission control families are listed on attachments.

The non-methane organic gas (NMOG), carbon monoxide (CO), oxides of nitrogen (NOx), and formaldehyde (HCHO) TLEV certification exhaust emission standards for this engine family in grams per mile are:

Loaded Vehicle Weight (lbs.)	<u>Miles</u>	NMOG_	CO	<u>NOx</u>	нсно	co (20°F)
3751-5750	50,000	0.160	4.4	0.7	0.018	12.5
	100,000	0.200	5.5	0.9	0.023	n/a

Reactivity Adjustment Factor (RAF) for NMOG Mass Emission: 0.98

The certification exhaust emission values set forth for NMOG reflect application of a 0.98 RAF for 1997 model-year TLEVs. The TLEV certification exhaust emission values for this engine family in grams per mile are:

Loaded Vehicle Weight (lbs.)	<u>Miles</u>	NMOG	_co_	<u>NOx</u>	<u>нсно</u>	CO (20°F)
3751-5750	50,000	0.083	0.9	0.2	0.003	3.6
	100,000	0.090	1.0	0.3	0.005	n/a

BE IT FURTHER RESOLVED: That the vehicle manufacturer is certifying the listed vehicle models to the aforementioned exhaust emission standards based on its submitted plan to comply with the fleet average NMOG exhaust mass emission requirements as set forth in "California Exhaust Emission Standards and Test Procedures for 1988 and Subsequent Model Passenger Cars, Light-Duty Trucks, and Medium-Duty Vehicles."

BE IT FURTHER RESOLVED: That under the submitted NMOG fleet average compliance plan, if the manufacturer incurs a NMOG debit for the aforementioned model year based on the projected NMOG fleet average exceeding the value required by the above-referenced standards and test procedures, all incurred NMOG debits by the manufacturer shall be equalized as required by the standards and test procedures.

BE IT FURTHER RESOLVED: That the vehicle manufacturer is certifying the listed vehicle models to the running loss and useful life standards applicable to 1995 and subsequent model-year vehicles in the "California Evaporative Emission Standards and Test Procedures for 1978 and Subsequent Model Motor Vehicles", and the listed vehicle models comply with those standards.

BE IT FURTHER RESOLVED: That the listed vehicle models also comply with the Board's "Specifications for Fill Pipes and Openings of Motor Vehicle Fuel Tanks" for the aforementioned model year (Title 13, California Code of Regulations, Section 2235).

BE IT FURTHER RESOLVED: That the listed vehicle models also comply with the Board's high-altitude requirements and highway emission standards, and with the California Inspection and Maintenance emission standards in place at the time of certification, as stipulated in "California Exhaust Emission Standards and Test Procedures for 1988 and Subsequent Model Passenger Cars, Light-Duty Trucks, and Medium-Duty Vehicles."

BE IT FURTHER RESOLVED: That the listed vehicle models also comply with the "California Motor Vehicle Emission Control Label Specifications" for the aforementioned model year (Title 13, California Code of Regulations, Section 1965).

BE IT FURTHER RESOLVED: That the vehicle manufacturer has demonstrated compliance with the exhaust emission standards at 50 degrees Fahrenheit as stipulated in "California Exhaust Emission Standards and Test Procedures for 1988 and Subsequent Model Passenger Cars, Light-Duty Trucks, and Medium-Duty Vehicles."

BE IT FURTHER RESOLVED: That the listed vehicle models also comply with the "Malfunction and Diagnostic System Requirements--1994 and Subsequent Model-Year Passenger Cars, Light-Duty Trucks, and Medium-Duty Vehicles and Engines" (Title 13, California Code of Regulations, Section 1968.1) for the aforementioned model year.

BE IT FURTHER RESOLVED: That for the listed vehicles, the manufacturer has submitted and the Executive Officer hereby approves the materials to demonstrate certification compliance with the Board's emission control system warranty provisions (Title 13, California Code of Regulations, Section 2035 et seq.).

Vehicles certified under this Executive Order must conform to all applicable California emission regulations.

The Bureau of Automotive Repair will be notified by copy of this order and attachment.

Executed at El Monte, California this

R. B. Summerfield

Assistant Division Chief Mobile Source Division

E.O. # <u>A-9-356</u> Page <u>1</u> of <u>1</u>

1997 MODEL YEAR AIR RESOURCES BOARD SUPPLEMENTAL DATA SHEET PASSENGER CARS, LIGHT-DUTY TRUCKS AND MEDIUM-DUTY VEHICLES

Manufacturer: Chrysler Corporation Exh Eng Fam: VCR24228G2JK Evap Fam: VCR1098AYP1N
All Eng Codes in Eng Fam: CA_X_ 49S 50S AB965
Exh Std: CA Tier-1 TLEV_X LEV ULEV ZEV; US EPA Tier-1
Evap Std: 50K Useful Life with R/L_X In-Use Exh Std: Full In Use_X Alt In Use_
Veh Class(es): PC LDT1 LDT2_X MDV1 MDV2 MDV3 MDV4 MDV5
Single Cert Std for Multi-Class Eng Fam: N/A (Specify: N/A, LDT1, MDV1, MDV2, MDV3, MDV4)
Fuel Type(s): Dedicated X Flex-Fuel Dual-Fuel Bi-Level Gasoline X Diesel
CNGLNGLPGM85Other (specify)
Emis Test Fuel(s): Indo Ph2_X _ CNG LPG M85 Other(specify)
Diesel: 13 CCR 2282 or 40 CFR 86.113-90 or 40 CFR 86.113-94
Service Accum: Std AMA Mod AMA X Mfr ADP Other (Specify)
NMOG Test Procedure: N/A Std Equiv X R/L Test Proce: SHED Pt Source X
Hybrid: Type A B C, APU Cycle (e.g., Otto, Diesel, Turbine)
Engine Configuration: I-6 Displacement: / 4.0 Liters / 242 Cubic Inches
Valves per Cylinder: 2 Rated HP: 185 @ 4600 RPM
Engine: Front X Mid Rear Drive: FWD RWD X 4WD-FT X 4WD-PT
Exhaust ECS (eg., EGR, MFI, TC, CAC): WUOC, TWC, HO2S(2), OBD II, SFI (use abbreviations per SAE J1930 SEP91)

Engine Code	Vehicle Models	Trans. Type	ETW	DPA	Ignition	EGR	Catalyst
(also list	(if coded see	M5	or	or	(ECM/PCM)	System	Converter
CA/49ST/50ST)	attachment)	A4	Test Wt.	RLHP	Part No.	Part No.	Part No.
CA-100 (CA)	ZJTL74 ZJJL74	A4	4000	S E E A T T A C H E D	56042399 56041399	None	52018935 52101401

Date Issued:	04-01-96			
Revisions:		<u>-</u>	<u> </u>	

ATTACHMENT TO SDS PAGE 1 OF EXECUTIVE ORDER A-9-356

VEHICLE MODELS/CARLINE

Engine Family:

VCR24228G2JK

Evaporative Family:

VCR1098AYP1N

Exhaust Control System:

WUOC, TWC, HO2S(2), OBD II, SFI

Evap. Control System:

Canister

Engine Displacement:

4.0L

Carline	Model Code	
Jeep® Grand Cherokee 4WD	ZJJL74	
Jeep® Grand Cherokee 2WD	ZJTL74	

ATTACHMENT TO SDS PAGE 1 OF EXECUTIVE ORDER A-9-356

1997 VCR24228G2JK

Chrysler Corporation Family Tire Usage

LOADED VEHICLE WEIGHT

												COAST		TI	RE		(တောင်	ELECTRIC	DYNC	COE	PICIE	NTS	
			A		MKT		TIRE	DE	SCRI	PTIO	N	DOWN	*DYNO	PR	ES	TARGET	A	В	С	SI	ET A	E		С
MODEL	ENG	TRANS	C	GVW	TYPE	LVW	USE	YR	COD	MFG	OPT	TIME	н₽	P	R	(LINE 1	IS	20 DEG	COEFFS, L	NE	IS!	O DEG	WHEN	NEEDED)
	-		-										·					. 					-	
ZJJL74	erh	DGK 4	Y	5300	Ç	4250	STD	97	TM6	TZA		13.65	13.5	36	36									
							OPT	97	TRD	TZA		13.09	13.5	36	36									
							OPT	97	TRH	TZA		12.98	14.1	36	36	66.40			0.03664	51	84	-1.2	268	0.04786
							OPT	97	TRL	TZA		13.11	13.4	36	36									
							OPT	97	TRT	TZA		13.28	13.7	36	36	٠,_								
							OPT	97	TYR	TZA		13.22	12.8	36	36									
ZJJL74	erh	DGK 4E	Y	5300	С	4250	STD	97	TM6	TZA		13.65	13.5	36	36									
							OPT	97	TRD	TZA		13.09	13.5	36	36									
							OPT	97	TRH	TZA		12.98	14.1	36	36	66.40			0.03664	51.	84	-1.2	268	0.04786
							OPT	97	TRL	TZA		13.11	13.4	36	36									
							OPT	97	TRT	TZA		13.28	13.7	36	36									
							OPT	97	TYR	TZA		13.22	12.8	36	36									
ZJTL74	ERH	DGK RW	Y	5000	c ·	4000	STD	97	TM6	TZA		14.13	12.4	36	36									
							OPT	97 '	TRH	TZA		13.59	13.0	36	36									
							OPT	97 '	TRL	TZA		13.56	12.3	36	36									
							OPT	97 '	TRT	TZA		13.75			36									

REPORT DATE: 04-01-96