Fill

(Page 1 of 3)

State of California AIR RESOURCES BOARD

EXECUTIVE ORDER A-3-159-A Relating to Certification of New Motor Vehicles

MERCEDES-BENZ AG

Pursuant to the authority vested in the Air Resources Board by the Health and Safety Code, Division 26, Part 5, Chapter 2; and

Pursuant to the authority vested in the undersigned by Health and Safety Code Sections 39515 and 39516 and Executive Order G-45-9;

IT IS ORDERED AND RESOLVED: That 1997 model-year Mercedes-Benz AG exhaust emission control systems are certified as described below for passenger cars:

Emission Standard Category: Transitional Low-Emission Vehicle (TLEV)

Fuel Type: Gasoline

×

٠

Engine Family: VMB5.0VJGKEK <u>Displacement</u>: 4.2 Liters (256 Cubic Inches) 5.0 Liters (303 Cubic Inches)

Exhaust Emission Control Systems and Special Features:

Secondary Air Injection Dual Warm Up Three-Way Catalytic Converters Dual Three Way Catalytic Converters Dual Heated Oxygen Sensors (two) Sequential Multiport Fuel Injection

Vehicle models, transmissions, engine codes and evaporative emission control families are listed on attachments.

The TLEV certification exhaust emission standards for this engine family in grams per mile are:

	Non-Methane	Carbon	Nitrogen		Carbon
<u>Miles</u>	<u>Organic Gas</u>	<u>Monoxide</u>	<u>Oxides</u>	<u>Formaldehyde</u>	<u>Monoxide (20⁰F)</u>
50,000 100,000	0.125 0.156	3.4 4.2	0.4	0.015 0.018	10.0 n/a

Reactivity Adjustment Factor (RAF) for NMOG Mass Emission: 0.98

The certification exhaust emission values set forth for non-methane organic gas (NMOG) reflect application of a 0.98 RAF for 1997 model-year TLEVs. The TLEV certification exhaust emission values for this engine family in grams per mile are:

	Non-Methane	Carbon	Nitrogen		Carbon
<u>Miles</u>	<u>Organic Gas</u>	<u>Monoxide</u>	<u>Oxides</u>	<u>Formaldehyde</u>	<u>Monoxide (20⁰F)</u>
50,000 100,000	0.036 0.039	0.5 0.7	0.2 0.2	0.0004 0.001	5.4 n/a

BE IT FURTHER RESOLVED: That the vehicle manufacturer is certifying the listed vehicle models to the aforementioned exhaust emission standards based on its submitted plan to comply with the fleet average NMOG exhaust mass emission requirements as set forth in "California Exhaust Emission Standards and Test Procedures for 1988 and Subsequent Model Passenger Cars, Light-Duty Trucks, and Medium-Duty Vehicles".

BE IT FURTHER RESOLVED: That under the submitted NMOG fleet average compliance plan, if the manufacturer incurs a NMOG debit for the aforementioned model year based on the projected NMOG fleet average exceeding the value required by the above-referenced standards and test procedures, all incurred NMOG debits by the manufacturer shall be equalized as required by the standards and test procedures.

BE IT FURTHER RESOLVED: That the vehicle manufacturer is certifying the listed vehicle models to the running loss and useful life standards applicable to 1995 and subsequent model-year vehicles in the "California Evaporative Emission Standards and Test Procedures for 1978 and Subsequent Model Motor Vehicles", and the listed vehicle models comply with those standards.

BE IT FURTHER RESOLVED: That the listed vehicle models also comply with the Board's "Specifications for Fill Pipes and Openings of Motor Vehicle Fuel Tanks" for the aforementioned model year (Title 13, California Code of Regulations, Section 2235).

BE IT FURTHER RESOLVED: That the listed vehicle models also comply with the Board's high-altitude requirements and highway emission standards, and with the California Inspection and Maintenance emission standards in place at the time of certification, as stipulated in "California Exhaust Emission Standards and Test Procedures for 1988 and Subsequent Model Passenger Cars, Light-Duty Trucks, and Medium-Duty Vehicles".

BE IT FURTHER RESOLVED: That the listed vehicle models also comply with the "California Motor Vehicle Emission Control Label Specifications" for the aforementioned model year (Title 13, California Code of Regulations, Section 1965).

BE IT FURTHER RESOLVED: That the listed vehicle models also comply with the "Malfunction and Diagnostic System Requirements--1994 and Subsequent Model-Year Passenger Cars, Light-Duty Trucks, and Medium-Duty Vehicles and Engines" (Title 13, California Code of Regulations, Section 1968.1) for the aforementioned model year.

BE IT FURTHER RESOLVED: That for the listed vehicles, the manufacturer has submitted and the Executive Officer hereby approves the materials to demonstrate certification compliance with the Board's emission control system warranty provisions (Title 13, California Code of Regulations, Section 2035 et seq.). BE IT FURTHER RESOLVED: That the vehicle manufacturer has demonstrated compliance with the exhaust emission standards at 50 degrees Fahrenheit as stipulated in "California Exhaust Emission Standards and Test Procedures for 1988 and Subsequent Model Passenger Cars, Light-Duty Trucks, and Medium-Duty Vehicles."

Vehicles certified under this Executive Order must conform to all applicable California emission regulations.

The Bureau of Automotive Repair will be notified by copy of this order and attachment.

Executed at El Monte, California this 2! day of March 1996.

R, B. Summerfield Assistant Division Chief Mobile Source Division

E. O. #<u>A-3-159-A</u>

Page 1 of _______ 1997 MODEL-YEAR AIR RESOURCES BOARD SUPPLEMENTAL DATA SHEET PASSENGER CARS, LIGHT-DUTY TRUCKS AND MEDIUM-DUTY VEHICLES

Manufacturer: Mercede	s-Benz AG	Exh. Eng Family: <u>V</u>	MB5.0VJGKEK Ev	ap. Eng Family: VI	MB1155AYME0
All Eng Codes in Eng Fa	ım: CA	_ 498 5	OS X AB	965	
Exh Std:					PA Tier-1 X
Evap Std:					
Veh Class(es): PC _					
Single Cert Std for Multi-	-Class Eng Fan	n: <u>N/A</u> (sp	ecify: N/A, LDT1,	MDV1, MDV2,	MDV3, MDV4)
Fuel Type(s): Dedic	cated <u>X</u> F	lex-Fuel Dua	d-Fuel Bi-Fue	el Gasoline X	Diesel
CNG	L	.NG LP(3 M85	Other (specify)	
Emiss Test Fuel(s):					
		CR 2282			
Service Accum:	Std AMA X	Mod AMA	_ Mfr ADP	Other (specify)	
NMOG Test Procedure:	N/A S	Std X Equiv	_ R/L Test Proc.	SHED X	Pt Source
Hybrid: Type A	BC	APU Cycle (e. g.	, Otto, Diesel, Turbin	8)	
Engine Configuration:	<u>V-8</u>)isplacement:4	.2/5.0 Liters	256 / 303	Cubic Inches
Valves per Cylinder:	4		Rated HP: 275 / 3	315 5700/5	5600 RPM
Engine: Front X					
Exhaust ECS (eg., MFI,	EGR, TC, CA	AC): SFI / AIR / 2HC	2S(2) / 2WU-TWC / :	2TWC +080 	
		(use	abbreviations per SA	E J1930 SEP91)	

Engine Code (also list CA/49ST/50ST)	Vehicle Models (If coded see attachment)	Trans. Type A-automatic M-manual	ETW or Test Wt	DPA or RLHP	Ignition (ECM/PCM) Part No.	EGR System Part No.	Catalytic Converter Part No.
M 119-42-1	E 420	A 5	4 000	6 .5	021 545 20 32		140 490 36 36 140 490 33 36
M 119-42-1	S 420	A 5	5 000	8.9	021 545 20 32	_	140 490 36 36 140 490 34 36
M 119-50-1	S 500	A 5	5 000	8.9	021 545 21 32		140 490 36 38 140 490 34 36
1							

Date issued:

Revisions:

. . .