(Page 1 of 3)

State of California AIR RESOURCES BOARD

EXECUTIVE ORDER A-8-102 Relating to Certification of New Motor Vehicles

BAYERISCHE MOTOREN WERKE AG

Pursuant to the authority vested in the Air Resources Board by the Health and Safety Code, Division 26, Part 5, Chapter 2; and

Pursuant to the authority vested in the undersigned by Health and Safety Code Sections 39515 and 39516 and Executive Order G-45-9;

IT IS ORDERED AND RESOLVED: That 1997 model-year Bayerische Motoren Werke AG exhaust emission control systems are certified as described below for passenger cars:

Fuel Type: Gasoline

Engine Family: VBM1.9VJGFEK Displacement: 1.9 Liters (115.6 Cubic Inches)

Exhaust Emission Control Systems and Special Features:

Three Way Catalytic Converter Heated Oxygen Sensors (two) Sequential Multiport Fuel Injection

Vehicle models, transmissions, engine codes and evaporative emission control families are listed on attachments.

The certification exhaust emission standards for this engine family in grams per mile are:

Miles	Non-Methane	Carbon	Nitrogen	Carbon
	<u>Hydrocarbons</u>	<u>Monoxide</u>	<u>Oxides</u>	<u>Monoxide (20⁰F)</u>
50,000	0.25	3.4	0.4	10.0
100,000	0.31	4.2	0.6	n/a

The certification exhaust emission values for this engine family in grams per mile are:

Miles	Non-Methane	Carbon	Nitrogen	Carbon	
	<u>Hydrocarbons</u>	<u>Monoxide</u>	_Oxides	<u>Monoxide (20⁰F)</u>	
50,000	0.10	1.0	0.2	4. 5	
100,000	0.12	1.2	0.2	n/a	

BE IT FURTHER RESOLVED: That the vehicle manufacturer is certifying the listed vehicle models to the aforementioned exhaust emission standards based on its submitted plan to comply with the fleet average non-methane organic gas (NMOG) exhaust mass emission requirements as set forth in "California Exhaust Emission Standards and Test Procedures for 1988 and Subsequent Model Passenger Cars, Light-Duty Trucks, and Medium-Duty Vehicles".

BE IT FURTHER RESOLVED: That under the submitted NMOG fleet average compliance plan, if the manufacturer incurs a NMOG debit for the aforementioned model year based on the projected NMOG fleet average exceeding the value required by the above-referenced standards and test procedures, all incurred NMOG debits by the manufacturer shall be equalized as required by the standards and test procedures.

BE IT FURTHER RESOLVED: That the vehicle manufacturer is certifying the listed vehicle models to the 50,000-mile evaporative emission standards applicable to 1980 through 1994 model-year vehicles in the "California Evaporative Emission Standards and Test Procedures for 1978 and Subsequent Model Motor Vehicles", and the listed vehicle models comply with those standards.

BE IT FURTHER RESOLVED: That, based on the evaporative emission phase-in compliance schedule submitted by the vehicle manufacturer, the listed vehicle models shall not be subject to the running loss and useful life standards set forth in the "California Evaporative Emission Standards and Test Procedures for 1978 and Subsequent Model Motor Vehicles."

BE IT FURTHER RESOLVED: That the listed vehicle models also comply with the "California Motor Vehicle Emission Control Label Specifications" for the aforementioned model year (Title 13, California Code of Regulations, Section 1965).

BE IT FURTHER RESOLVED: That the listed vehicle models also comply with the Board's "Specifications for Fill Pipes and Openings of Motor Vehicle Fuel Tanks" for the aforementioned model year (Title 13, California Code of Regulations, Section 2235).

BE IT FURTHER RESOLVED: That the listed vehicle models also comply with the Board's high-altitude requirements and highway emission standards, and with the California Inspection and Maintenance emission standards in place at the time of certification, as stipulated in "California Exhaust Emission Standards and Test Procedures for 1988 and Subsequent Model Passenger Cars, Light-Duty Trucks, and Medium-Duty Vehicles".

BE IT FURTHER RESOLVED: That the listed vehicle models also comply with the "Malfunction and Diagnostic System Requirements--1994 and Subsequent Model-Year Passenger Cars, Light-Duty Trucks, and Medium-Duty Vehicles and Engines" (Title 13, California Code of Regulations, Section 1968.1) for the aforementioned model year.

BE IT FURTHER RESOLVED: That for the listed vehicles, the manufacturer has submitted and the Executive Officer hereby approves the materials to demonstrate certification compliance with the Board's emission control system warranty provisions (Title 13, California Code of Regulations, Section 2035 et seq.).

Vehicles certified under this Executive Order must conform to all applicable California emission regulations.

The Bureau of Automotive Repair will be notified by copy of this order and attachment.

Executed at El Monte, California this 13 day of June 1996.

Assistant Division Chief Mobile Source Division

1997 AIR RESOURCES BOARD SUPPLEMENTAL DATA SHEET PASSENGER CARS, LIGHT DUTY TRUCKS AND MEDIUM DUTY VEHICLES

Fuel Type (s): Dedicated Flex-Fuel Dual Fuel Bi - Fuel Gasoline X Diesel CNG LNG LPG M85 Other (specify) Diesel: 13 CCR 2282 40 CFR86.113-90 40 CFR86.113-94 Service Accum: Std AMA Mod AMA Mfr ADP X Other (specify) NMOG Test Procedure: N/A X Std Equiv R/L Test Proc: SHED Pt Source Singine Configuration: 4-inline Displacement: 1.9 Liters 115.6 Cubic Inches Rated HP: 138 @ 6 000 RPM	Manufacturer: BMW Exh Engine Family: VBM1.9VJGFEK Evap. Fam: VBM1025BYPA0 All Eng Codes in Eng Fam: CA 49S 50S X AB965 Exh Std: CA Tier-1 X TLEV LEV ULEV ZEV : US EPA Tier-1 X Evap Std: 50K X Useful Life with R/L In-Use Exh Std: Full In Use X Alt In Use Veh Class(es): PC X LDT1 LDT2 MDV1 MDV2 MDV3 MDV4 MDV5 Single Cert Std for Multi - Class Eng Fam: N/A (specific N/A LDT4 MDV4 MDV5
CNG LNG LPG M85 Other (specify) Diesel: 13 CCR 2282 40 CFR86.113-90 40 CFR86.113-94 Service Accum: Std AMA Mod AMA Mfr ADP X Other (specify) NMOG Test Procedure: N/A X Std Equiv R/L Test Proc: SHED Pt Source Engine Configuration: 4-inline Displacement: 1.9 Liters 115.6 Cubic Inches (alves per Cylinder: 4 Rated HP: 138 @ 6 000 RPM	Single Cert Std for Multi - Class Eng Fam: N/A (specify: N/A LDT1 MDV4 ARDV4 ARDV4
Emiss Test Fuel (s): Indo Ph2 X CNG LPG M85 Other (specify) Diesel: 13 CCR 2282 40 CFR86.113-90 40 CFR86.113-94 Service Accum: Std AMA Mod AMA Mfr ADP X Other (specify) NMOG Test Procedure: N/A X Std Equiv R/L Test Proc: SHED Pt Source Supplied: Type A B C APU Cycle (e.g., Otto, Diesel, Turbine) Engine Configuration: 4-inline Displacement: 1.9 Liters 115.6 Cubic Inches Rated HP: 138 @ 6 000 RPM	
Diesel: 13 CCR 2282 40 CFR86.113-90 40 CFR86.113-94 Service Accum: Std AMA Mod AMA Mfr ADP X Other (specify) WMOG Test Procedure: N/A X Std Equiv R/L Test Proc: SHED Pt Source Sybrid: Type A B C , APU Cycle (e.g., Otto, Diesel, Turbine) Engine Configuration: 4-inline Displacement: 1.9 Liters 115.6 Cubic Inches Calves per Cylinder: 4 Rated HP: 138 @ 6 000 RPM	CNG LNG LPG M85 Other (specify) Emiss Test Fuel (s): Indo
Service Accum: Std AMA	
ringine Configuration: 4-inline Displacement: 1.9 Liters 115.6 Cubic Inches (alves per Cylinder: 4 Rated HP: 138 @ 6 000 RPM	Service Accum: Std AMA Mod AMA Mfr ADP _X Other (specify)
ringine Configuration: 4-inline Displacement: 1.9 Liters 115.6 Cubic Inches (alves per Cylinder: 4 Rated HP: 138 @ 6 000 RPM	Hybrid: Type A B C ABU Control Pt Source
/alves per Cylinder: 4	Engine Configuration: 4 inline - Division - Otto, Diesel, Turbine)
	Liters 115.6 Cubic Inches Valves per Cylinder: 4 Rated HP: 138 @ 6 000 RPM Lingine: Front X Mid Rear Drive: FWD RWD X 4WD-FT 4WD-PT Exhaust ECS: TWC, HO2S-2, SFI

Engine Code (50 ST)	Vehicle Models	Trans. Type	ETW (lbs.)	DPA or RLHP (hp)	Ignition (ECM/PCM) Part No.	EGR System Part No.	Catalytic Converter Part No.
1.9/3/C M5	318iC	M5	3 375	6.6	1 429 812		1 743 613
1.9/3/C M5	318i, is	M5	3 250	6.5	1 429 812		1 432 446
1.9/3/C M5	318ti	M5	3 000	6.8	1 429 812		
1 9/3/C M5	Z 3	M5	3 000	7.5	1 429 812		
1.9/3/C A4	318iAC	A4	3 500	6.6	1 429 813		
1.9/3/C A4	318iA, isA	A4	3 375	6.5	1 429 813		
1.9/3/C A4	318tiA	A4	3 125	6.8	1 429 813		
1.9/3/C A4	Z3A	A4	3 125	7.5	1 429 813		