#### State of California AIR RESOURCES BOARD

# EXECUTIVE ORDER A-10-711 Relating to Certification of New Motor Vehicles

#### FORD MOTOR COMPANY

Pursuant to the authority vested in the Air Resources Board by the Health and Safety Code, Division 26, Part 5, Chapter 2; and

Pursuant to the authority vested in the undersigned by Health and Safety Code Sections 39515 and 39516 and Executive Order G-45-9;

IT IS ORDERED AND RESOLVED: That 1997 model-year Ford Motor Company exhaust emission control systems are certified as described below for light-duty trucks:

Emission Standard Category: Transitional Low-Emission Vehicle (TLEV)

Fuel Type: Gasoline

Engine Family: VFM4.028G2EK Displacement: 4.0 Liters (244 Cubic Inches)

Exhaust Emission Control Systems and Special Features:

Three Way Catalytic Converters (two)
Dual Heated Oxygen Sensors
Heated Oxygen Sensor
Exhaust Gas Recirculation
Sequential Multiport Fuel Injection

Vehicle models, transmissions, engine codes and evaporative emission control families are listed on attachments.

The non-methane organic gases (NMOG), carbon monoxide (CO), oxides of nitrogen (NOx), and formaldehyde (HCHO) TLEV certification exhaust emission standards for this engine family in grams per mile are:

Loaded Vehicle Weight (lbs.)	Miles	NMOG	со	NOx	нсно_	CO (20°F)
3751-5750	50,000	0.160	4.4	0.7	0.018	12.5
	100,000	0.200	5.5	0.9	0.023	n/a

Reactivity Adjustment Factor (RAF) for NMOG Mass Emission: 0.98

The certification exhaust emission values set forth for NMOG reflect application of a 0.98 RAF for 1997 model-year TLEVs. The TLEV certification exhaust emission values for this engine family in grams per mile are:

Loaded Vehicle Weight (lbs.)	Miles	NMOG	<u>co</u>	<u>NOx</u>	нсно	CO (20°F)
3751-5750	50,000 100,000	0.081	1.0 1.4	0.2 0.3	0.002 0.003	3.8 n/a

BE IT FURTHER RESOLVED: That the vehicle manufacturer is certifying the listed vehicle models to the aforementioned exhaust emission standards based on its submitted plan to comply with the fleet average NMOG exhaust mass emission requirements as set forth in "California Exhaust Emission Standards and Test Procedures for 1988 and Subsequent Model Passenger Cars, Light-Duty Trucks, and Medium-Duty Vehicles."

BE IT FURTHER RESOLVED: That under the submitted NMOG fleet average compliance plan, if the manufacturer incurs a NMOG debit for the aforementioned model year based on the projected NMOG fleet average exceeding the value required by the above-referenced standards and test procedures, all incurred NMOG debits by the manufacturer shall be equalized as required by the standards and test procedures.

BE IT FURTHER RESOLVED: That the vehicle manufacturer is certifying the listed vehicle models to the 50,000-mile evaporative emission standards applicable to 1980 through 1994 model-year vehicles in the "California Evaporative Emission Standards and Test Procedures for 1978 and Subsequent Model Motor Vehicles," and the listed vehicle models comply with those standards.

BE IT FURTHER RESOLVED: That, based on the evaporative emission phase-in compliance schedule submitted by the vehicle manufacturer, the listed vehicle models shall not be subject to the running loss and useful life standards set forth in the "California Evaporative Emission Standards and Test Procedures for 1978 and Subsequent Model Motor Vehicles."

BE IT FURTHER RESOLVED: That the listed vehicle models also comply with the Board's "Specifications for Fill Pipes and Openings of Motor Vehicle Fuel Tanks" for the aforementioned model year (Title 13, California Code of Regulations, Section 2235).

BE IT FURTHER RESOLVED: That the listed vehicle models also comply with the Board's high-altitude requirements and highway emission standards, and with the California Inspection and Maintenance emission standards in place at the time of certification, as stipulated in "California Exhaust Emission Standards and Test Procedures for 1988 and Subsequent Model Passenger Cars, Light-Duty Trucks, and Medium-Duty Vehicles."

BE IT FURTHER RESOLVED: That the listed vehicle models also comply with the "California Motor Vehicle Emission Control Label Specifications" for the aforementioned model year (Title 13, California Code of Regulations, Section 1965).

BE IT FURTHER RESOLVED: That the vehicle manufacturer has demonstrated compliance with the exhaust emission standards at 50 degrees Fahrenheit as stipulated in "California Exhaust Emission Standards and Test Procedures for 1988 and Subsequent Model Passenger Cars, Light-Duty Trucks, and Medium-Duty Vehicles."

BE IT FURTHER RESOLVED: That the manufacturer is certifying the listed vehicle models with a partially complying on-board diagnostic system for the aforementioned model year pursuant to Title 13, California Code of Regulations, Section 1968.1(m)(6.2) ("Malfunction and Diagnostic System Requirements--1994 and Subsequent Model-Year Passenger Cars, Light-Duty Trucks, and Medium-Duty Vehicles and Engines").

BE IT FURTHER RESOLVED: That for the listed vehicles, the manufacturer has submitted and the Executive Officer hereby approves the materials to demonstrate certification compliance with the Board's emission control system warranty provisions (Title 13, California Code of Regulations, Section 2035 et seq.).

Vehicles certified under this Executive Order must conform to all applicable California emission regulations.

The Bureau of Automotive Repair will be notified by copy of this order and attachment.

Executed at El Monte, California this 27

day of June 1996.

R. W. Summerfield

Assistant Division Chief Mobile Source Division

## 1997 AIR RESOURCES BOARD SUPPLEMENTAL DATA SHEET

PASSENGER CARS, LIGHT-DUTY TRUCKS AND MEDIUM-DUTY VEHICLES

Manufacturer: Ford Motor Company Exhaust E	ngine Family: <u>VFM4.028G2EK</u>
Evap Standard: 50K X Useful Life with R/L Evap Standard:	vap Family: <u>VFM1045AYPBA</u>
Exhaust Std: Tier 0 _ Tier 1 _ TLEV X LEV _ ULEV _	ZEV; EPA Tier 0 Tier 1
Vehicle Class(es): PC _ LDT1 _ LDT2 <u>X</u> MDV1 _ M	MDV2 _ MDV3 _ MDV4 _ MDV5 _
Single Cert Std for Multi-Class Eng Fam: N/A (specify N/A	A, LDT1, MDV1, MDV2, MDV3, MDV4)
Exh Cert Fuel(s): Indo Ph2 _X Diesel: 13 CCR 228.  M85 _ CNG _ LPG _ Other (specify) _	
Fuel Type(s): Dedicated Flex-Fuel Dual-Fuel Ga CNG LNG LPG Other (specify)	asoline X Diesel _ M85 _
Hybrid: Type A B C, APU Cycle (e.g., Otto, Di	esel, Turbine)
Engine Config: <u>V-6</u> Liter (CID): <u>4.0 (244.1)</u>	
Engine: Front_X_Mid Rear Drive: FWD RWD _	X 4WD-FT 4WD-PT X
Exhaust ECS & Special Features: <u>SFI/2HO2S/EGR/TWC</u> (Use abbreviations per SAE J1930, Sep 91)	(2) (HO2S

Engine Code Ve		Trans. Type A-Automatic		DPA	Ignition (PCM)	EGR System	Catalyst
(California)		M-Manual			Part No. -12A650-	Part No. <u>-9D475-</u>	Part No. <u>- 5E212-</u>
758TR00A Ra	anger 4x2 SKS	L5	3875	12.3	F77F-AAA	F37E-CA	F77A-LB
	Series 4x2 SKS	L5	3875	12.3			1
Ra	anger 4x4 RKL	L5	4000	14.1&			•
Ra	anger 4x4 RKS	L5	3875*	14.1&			
	anger 4x4 SKS	L5	4250	14.1&			
	Series 4x4 RKL	L5	4000	14.1&			
B-	Series 4x4 RKS	L5	4000	14.1&			
B-	-Series 4x4 SKS	L5	4250	14.1&			
758TR00N R	anger 4x2 SKS	L5	3875	11.2			
	-Series 4x2 SKS	L5	3875	11.2			
R	anger 4x4 RKL	L5	4000	12.8#			
	anger 4x4 RKS	L5	3875	12.8#			
	anger 4x4 SKS	L5	4250	12.8#			
	-Series 4x4 RKL	. L5	4000	12.8#			
	-Series 4x4 RKS		3875	12.8#			
	-Series 4x4 SKS		4250	12.8#			

<sup>\*</sup> Ford elects to conduct certification tests in the next higher ETW.

ENGINE FAMILY: VFM4.028G2EK ISSUED: 04/15/96

REVISED: 11/19/96

<sup>&</sup>amp; If tire is P215/75R15 use DPA of 13.6.

<sup>#</sup> If tire is P215/75R15 use DPA of 12.4.

### 1997 AIR RESOURCES BOARD SUPPLEMENTAL DATA SHEET PASSENGER CARS, LIGHT-DUTY TRUCKS AND MEDIUM-DUTY VEHICLES

Manufacturer: Ford Motor Company Exhaust Engine Family: VFM4.028G2EK
Evap Standard: 50K X Useful Life with R/L Evap Family: VFM1045AYPBA
Exhaust Std: Tier 0 _ Tier 1 _ TLEV <u>X</u> LEV _ ULEV _ ZEV _ ; EPA Tier 0 _ Tier 1 _
Vehicle Class(es): PC _ LDT1 _ LDT2 <u>X</u> MDV1 _ MDV2 _ MDV3 _ MDV4 _ MDV5 _
Single Cert Std for Multi-Class Eng Fam: <u>N/A</u> (specify N/A, LDT1, MDV1, MDV2, MDV3, MDV4)
Exh Cert Fuel(s): Indo Ph2 _X Diesel: 13 CCR 2282 or 40 CFR 86.113-90 or -94 M85 CNG LPG Other (specify)
Fuel Type(s): Dedicated Flex-Fuel Dual-Fuel Gasoline X_ Diesel M85 CNG LNG LPG Other (specify)
Hybrid: Type A B C, APU Cycle (e.g., Otto, Diesel, Turbine)
Engine Config: <u>V-6</u> Liter (CID): <u>4.0 (244.1)</u>
Engine: Front_X_Mid Rear Drive: FWD RWD_X_4WD-FT _ 4WD-PT_X
Exhaust ECS & Special Features: <u>SFI/2HO2S/EGR/TWC(2)</u> /HO2 <i>S</i> (Use abbreviations per SAE J1930, Sep 91)

Engine Code	Vehicle Models	Trans. Type A-Automatic		DPA	Ignition (PCM)	EGR System	Catalyst
(California)		M-Manual			Part No. -12A650-	Part No. -9D475-	Part No. - 5E212-
758TR05A	Ranger 4x2 SKS	L5	3875	12.3	F77F-AAA	F37E-CA	F77A-LB
	B-Series 4x2 SKS	L5	3875	12.3			
	Ranger 4x4 RKL	L5	4000	14.1&			
	Ranger 4x4 RKS	L5	3875	14.1&			
	Ranger 4x4 SKS	L5	4250	14.1&			
	B-Series 4x4 RKL	. L5	4000	14.1&			
	B-Series 4x4 RKS	L5	3875*	14.1&			
	B-Series 4x4 SKS		4250	14.1&			
758TR05N	Ranger 4x2 SKS	L5	3875	11.2			
	B-Series 4x2 SKS	L5	3875	11.2			
	Ranger 4x4 RKL	L5	3875	12.8#			
	Ranger 4x4 RKS	L5	3875	12.8#			
	Ranger 4x4 SKS	L5	4250	12.8#			
	B-Series 4x4 RKL	. L5	4000	12.8#			
	B-Series 4x4 RKS	3 L5	3875	12.8#			
	B-Series 4x4 SKS		4250	12.8#			

<sup>\*</sup> Ford elects to conduct certification tests in the next higher ETW. & If tire is P215/75R15 use DPA of 13.6. # If tire is P215/75R15 use DPA of 12.4. ENGINE FAMILY: VFM4.028G2EK 20.09.17.02 - 2

ISSUED: 11/19/96

REVISED:

## 1997 AIR RESOURCES BOARD SUPPLEMENTAL DATA SHEET

PASSENGER CARS, LIGHT-DUTY TRUCKS AND MEDIUM-DUTY VEHICLES

Manufacturer: Ford Motor Company Exhaus	st Engine Family: <u>VFM4.028G2EK</u>
Evap Standard: 50K X Useful Life with R/L	Evap Family: <u>VFM1045AYPBA</u>
Exhaust Std: Tier 0 _ Tier 1 _ TLEV X LEV _ ULE\	/ _ ZEV _ ; EPA Tier 0 Tier 1
Vehicle Class(es): PC _ LDT1 _ LDT2 <u>X</u> MDV1	MDV2 MDV3 MDV4 MDV5
Single Cert Std for Multi-Class Eng Fam: <u>N/A</u> (specify	/ N/A, LDT1, MDV1, MDV2, MDV3, MDV4)
Exh Cert Fuel(s): Indo Ph2 <u>X</u>	
Fuel Type(s): Dedicated Flex-Fuel Dual-Fuel CNG LNG LPG Other (spec	
Hybrid: Type A B C, APU Cycle (e.g., Otto	, Diesel, Turbine)
Engine Config: <u>V-6</u> Liter (CID): <u>4.0 (244.1)</u>	
Engine: Front_X_Mid Rear Drive: FWD RW	D X 4WD-FT 4WD-PT X
Exhaust ECS & Special Features: <u>SFI/2HO2S/EGR/TV</u> (Use abbreviations per SAE J1930, Sep 91)	NC(2)/HO25

Engine Code	Vehicle Models	Trans. Type A-Automatic		DPA	Ignition (PCM)	EGR System	Catalyst
(California)		M-Manual			Part No.	Part No.	Part No.
					-12A650-	-9D475-	- 5E212-
758TR10A	Ranger 4x2 SKS	L5	3875	12.3	F77F-AAA	F37E-ÇA	F77A-LB
	B-Series 4x2 SKS	L5	3875	12.3			
	Ranger 4x4 RKL	L5	4000	14.1&			
	Ranger 4x4 RKS	L5	3875*	14.1&			
	Ranger 4x4 SKS	L5	4250	14.1&			
	B-Series 4x4 RKL	L5	4000	14.1&			
	B-Series 4x4 RKS	L5	3875*	14.1&			
	B-Series 4x4 SKS	L5	4250	14.1&			
758TR10N	Ranger 4x2 SKS	L5	3875	11.2			
	B-Series 4x2 SKS	L5	3875	11.2			
	Ranger 4x4 RKL	L5	3875	12.8#			
	Ranger 4x4 RKS	L5	3875	12.8#			
	Ranger 4x4 SKS	L5	4250	12.8#			
	B-Series 4x4 RKL	L5	4000	12.8#			
	B-Series 4x4 RKS	L5	3875	12.8#			
	B-Series 4x4 SKS	L5	4250	12.8#			

<sup>\*</sup> Ford elects to conduct certification tests in the next higher ETW.

& If tire is P215/75R15 use DPA of 13.6. # If tire is P215/75R15 use DPA of 12.4.

ENGINE FAMILY: VFM4.028G2EK

ISSUED: 11/19/96

20.09.17.02 - 3

REVISED: