## State of California AIR RESOURCES BOARD

## EXECUTIVE ORDER A-10-734 Relating to Certification of New Motor Vehicles

## FORD MOTOR COMPANY

Pursuant to the authority vested in the Air Resources Board by the Health and Safety Code, Division 26, Part 5, Chapter 2; and

Pursuant to the authority vested in the undersigned by Health and Safety Code Sections 39515 and 39516 and Executive Order G-45-9;

IT IS ORDERED AND RESOLVED: That Ford Motor Company 1997 model-year exhaust emission control systems are certified as described below for passenger cars:

Fuel Type: Fuel Flexible (E85 Ethanol, Gasoline)

Engine Family: VFM3.0V8NKGK <u>Displacement</u>: 3.0 Liters (182 Cubic Inches)

## Exhaust Emission Control Systems & Special Features:

Dual Three Way Catalytic Converters Dual Heated Oxygen Sensors Exhaust Gas Recirculation Sequential Multiport Fuel Injection

Vehicle models, transmissions, engine codes and evaporative emission control families are listed on attachments.

The certification exhaust emission standards for this engine family in grams per mile are:

Miles	Non-Methane	Carbon	Nitrogen	Carbon	
	<u>Hydrocarbons</u>	<u>Monoxide</u>	<u>Oxides</u>	<u>Monoxide (20°F)</u>	
50,000	0.25	3.4	0.4	10.0	
100,000	0.31	4.2	0.6	n/a	

The certification exhaust emission values for this engine family in grams per mile are: (The values in parentheses are for gasoline.)

Miles	Non-Methane	Carbon	Nitrogen	Carbon	
	<u>Hydrocarbons</u>	<u>Monoxide</u>	<u>Oxides</u>	<u>Monoxide (20°F)</u>	
50,000	0.10 (0.24)	1.1 (1.5)	0.1 (0.1)	7.0 (7.0)	
100,000	0.10 (0.28)	1.1 (1.8)	0.1 (0.1)	n/a	

BE IT FURTHER RESOLVED: That the vehicle manufacturer is certifying the listed vehicle models to the aforementioned exhaust emission standards based on its submitted plan to comply with the fleet average non-methane organic gases (NMOG) exhaust mass emission requirements as set forth in "California Exhaust Emission Standards and Test Procedures for 1988 and Subsequent Model Passenger Cars, Light-Duty Trucks, and Medium-Duty Vehicles."

BE IT FURTHER RESOLVED: That under the submitted NMOG fleet average compliance plan, if the manufacturer incurs a NMOG debit for the aforementioned model year based on the projected NMOG fleet average exceeding the value required by the above-referenced standards and test procedures, all incurred NMOG debits by the manufacturer shall be equalized as required by the standards and test procedures.

BE IT FURTHER RESOLVED: That the vehicle manufacturer is certifying the listed vehicle models to the 50,000-mile evaporative emission standards applicable to 1980 through 1994 model-year vehicles in the "California Evaporative Emission Standards and Test Procedures for 1978 and Subsequent Model Motor Vehicles", and the listed vehicle models comply with those standards.

BE IT FURTHER RESOLVED: That, based on the evaporative emission phase-in compliance schedule submitted by the vehicle manufacturer, the listed vehicle models shall not be subject to the running loss and useful life standards set forth in the "California Evaporative Emission Standards and Test Procedures for 1978 and Subsequent Model Motor Vehicles."

BE IT FURTHER RESOLVED: That the listed vehicle models also comply with the Board's "Specifications for Fill Pipes and Openings of Motor Vehicle Fuel Tanks" for the aforementioned model year (Title 13, California Code of Regulations, Section 2235).

BE IT FURTHER RESOLVED: That the listed vehicle models also comply with the Board's high-altitude requirements and highway emission standards, and with the California Inspection and Maintenance emission standards in place at the time of certification, as stipulated in "California Exhaust Emission Standards and Test Procedures for 1988 and Subsequent Model Passenger Cars, Light-Duty Trucks, and Medium-Duty Vehicles."

BE IT FURTHER RESOLVED: That the listed vehicle models also comply with the "California Motor Vehicle Emission Control and Smog Index Label Specifications" for the aforementioned model year (Title 13, California Code of Regulations, Section 1965).

BE IT FURTHER RESOLVED: That the manufacturer is certifying the listed vehicle models with a partially complying on-board diagnostic system for the aforementioned model year pursuant to Title 13, California Code of Regulations, Section 1968.1(m)(5.1) ("Malfunction and Diagnostic System Requirements--1994 and Subsequent Model-Year Passenger Cars, Light-Duty Trucks, and Medium-Duty vehicles and Engines").

BE IT FURTHER RESOLVED: That for the listed vehicles, the manufacturer has submitted and the Executive Officer hereby approves the materials to demonstrate certification compliance with the Board's emission control system warranty provisions (Title 13, California Code of Regulations, Section 2035 et seq.).

Vehicles certified under this Executive Order must conform to all applicable California emission regulations,

The Bureau of Automotive Repair will be notified by copy of this order and attachment.

Executed at El Monte, California this

\_\_day of December 1996.

R) B. Summerfield, Chief Hobile Source Operations Division

E.O.# A-10-734	
----------------	--

MODEL-YEAR AIR RESOURCES BOARD SUPPLEMENTAL DATA SHEET Page 1 PASSENGER CARS, LIGHT-DUTY TRUCKS AND MEDIUM-DUTY VEHICLES Exh Eng Fam: VFM3.0V8NKGK Manufacturer: FORD MOTOR COMPANY Evap Fam: VFM1230A2MAD SULEV\_\_\_\_, Exh Std: CA Tier-1 X TLEV LEV ULEV ULEV Evap Std: 50K x US EPA Tier-1<u>X</u> LEV\_\_\_\_ ULEV SULEV ILEV TLEV\_\_\_\_ 495\_\_\_\_ 50S\_X All Engine Codes in Engine Familiy: CA\_\_\_\_\_ AB965 Veh Class(es): PC<u>X</u> LDT1\_\_\_\_ LDT2\_\_\_ MDV1\_\_\_ MDV2 MDV3 MDV4 Single Cert Std for Multi-Class Eng Fam: N/A (specify: N/A, LDT1, MDV1, MDV2, MDV3, MDV4) Fuel Type(s): Dedicated\_\_\_ Flex-Fuel\_X Dual-Fuel\_\_\_ Bi-Fuel\_\_ Gasoline\_X Diesel\_\_ LNG\_\_\_ LPG\_\_ M85\_\_ Other (specify) <u>E85</u> Indo\_\_\_CBG\_X CNG\_\_LPG\_\_M85\_\_Other(specify)\_E85 Emiss Test Fuel(s): Diesel: 13 CCR 2282\_\_\_\_ 40 CFR 86.113-90\_\_\_\_ 40 CFR 86.113-94\_\_\_ Service Accum: Std AMA Mod AMA X Mfr ADP\_\_\_ Other (specify)\_ Std\_\_\_ NMOG Test Procedure: N/A X Equiv\_\_\_ R/L Test Proc: SHED\_\_\_ Pt Source\_ Engine Configuration: V-6 Displacement: 3.0 / Liters 182 / Cubic Inches Rated HP: <u>145 @ 5000 RPM</u> (GAS), <u>150 @ 5200 RPM</u> (ETHANOL) Valves per Cylinder: 2 Drive: FWD\_X RWD\_\_\_\_ 4WD-FT\_\_\_\_ Engine: Front X Mid\_\_\_\_ Rear\_\_\_\_ Exhaust ECS (e.g., MFI, EGR, TC, CAC):\_\_\_\_\_ 2TWC, 2HO2S, EGR, SFI (use abbreviations per SAE J1930 JUN93) Engine Code | Vehicle Models Trans. ETW Ignition Catalytic also list | (if coded see |(M5, A4 | or... (ECM/PCM) System Converter or

A/49ST/50ST	`attachment)	`etc.)	Test Wt.	RLHP	Part No.	Part No.	Part No.
710CR05A	TAURUS SEDAN	L4	3750	5.9	F7DF-AB	F7DE-BA	F6DC-RG F6DC-RM
710CR06A	TAURUS SEDAN	L4	3750	5.9	F7DF-AC	F7DE-BA	F6DC-RM
710CR10A	TAURUS SEDAN (Ethanol FFV)	L4	3750	5.9	F7DF-AD  Evap 50K 0.67 gltest	F7DE-BA	F6DC-RM

Date Issued: 11/8/96 Revisions: 12/13/96, 4/29/97