### State of California AIR RESOURCES BOARD

# EXECUTIVE ORDER A-16-215 Relating to Certification of New Motor Vehicles

#### MAZDA MOTOR CORPORATION

Pursuant to the authority vested in the Air Resources Board by the Health and Safety Code, Division 26, Part 5, Chapter 2; and

Pursuant to the authority vested in the undersigned by Health and Safety Code Sections 39515 and 39516 and Executive Order G-45-9;

IT IS ORDERED AND RESOLVED: That Mazda Motor Corporation 1997 model-year exhaust emission control systems are certified as described below for passenger cars:

Fuel Type: Gasoline

Engine Family: VTK1.8VJGKEK Displacement: 1.8 Liters (112 Cubic Inches)

## Exhaust Emission Control Systems & Special Features:

Three Way Catalytic Converter Heated Oxygen Sensors (two) Exhaust Gas Recirculation Sequential Multiport Fuel Injection

Vehicle models, transmissions, engine codes and evaporative emission control families are listed on attachments.

The certification exhaust emission standards for this engine family in grams per mile are:

Miles	Non-Methane	Carbon	Nitrogen	Carbon
	<u>Hydrocarbons</u>	<u>Monoxide</u>	<u>Oxides</u>	<u>Monoxide (20°F)</u>
50,000	0.25	3.4	0.4	10.0
100,000	0.31	4.2	0.6	n/a

The certification exhaust emission values for this engine family in grams per mile are:

Miles	Non-Methane <u>Hydrocarbons</u>	Carbon <u>Monoxide</u>	Nitrogen <u>Oxides</u>	Carbon <u>Monoxide (20°F)</u>
50,000	0.16	1.1	0.2	5.4
100,000	0.17	1.2	0.2	n/a

BE IT FURTHER RESOLVED: That the vehicle manufacturer is certifying the listed vehicle models to the aforementioned exhaust emission standards based on its submitted plan to comply with the fleet average NMOG exhaust mass emission requirements as set forth in "California Exhaust Emission Standards and Test Procedures for 1988 and Subsequent Model Passenger Cars, Light-Duty Trucks, and Medium-Duty Vehicles."

BE IT FURTHER RESOLVED: That under the submitted NMOG fleet average compliance plan, if the manufacturer incurs a NMOG debit for the aforementioned model year based on the projected NMOG fleet average exceeding the value required by the above-referenced standards and test procedures, all incurred NMOG debits by the manufacturer shall be equalized as required by the standards and test procedures.

BE IT FURTHER RESOLVED: That the vehicle manufacturer is certifying the listed vehicle models to the 50,000-mile evaporative emission standards applicable to 1980 through 1994 model-year vehicles in the "California Evaporative Emission Standards and Test Procedures for 1978 and Subsequent Model Motor Vehicles," and the listed vehicle models comply with those standards.

BE IT FURTHER RESOLVED: That, based on the evaporative emission phase-in compliance schedule submitted by the vehicle manufacturer, the listed vehicle models shall not be subject to the running loss and useful life standards set forth in the "California Evaporative Emission Standards and Test Procedures for 1978 and Subsequent Model Motor Vehicles."

BE IT FURTHER RESOLVED: That the listed vehicle models also comply with the Board's "Specifications for Fill Pipes and Openings of Motor Vehicle Fuel Tanks" for the aforementioned model year (Title I3, California Code of Regulations, Section 2235).

BE IT FURTHER RESOLVED: That the listed vehicle models also comply with the Board's high-altitude requirements and highway emission standards, and with the California Inspection and Maintenance emission standards in place at the time of certification, as stipulated in "California Exhaust Emission Standards and Test Procedures for 1988 and Subsequent Model Passenger Cars, Light-Duty Trucks, and Medium-Duty Vehicles."

BE IT FURTHER RESOLVED: That the listed vehicle models also comply with the "California Motor Vehicle Emission Control Label Specifications" for the aforementioned model year (Title 13, California Code of Regulations, Section 1965).

BE IT FURTHER RESOLVED: That the manufacturer is certifying the listed vehicle models with a partially complying on-board diagnostic system for the aforementioned model year pursuant to Title 13, California Code of Regulations, Section 1968.1(m)(6.2) ("Malfunction and Diagnostic System Requirements--1994 and Subsequent Model-Year Passenger Cars, Light-Duty Trucks, and Medium-Duty vehicles and Engines").

BE IT FURTHER RESOLVED: That for the listed vehicles, the manufacturer has submitted and the Executive Officer hereby approves the materials to demonstrate certification compliance with the Board's emission control system warranty provisions (Title 13, California Code of Regulations, Section 2035 et seq.).

Vehicles certified under this Executive Order must conform to all applicable California emission regulations,

The Bureau of Automotive Repair will be notified by copy of this order and attachment.

Executed at El Monte, California this 3/

o I mm

R. B. Summerfield
Assistant Division Chief
Mobile Source Division

day of July 1996.

# 1997 AIR RESOURCES BOARD SUPPLEMENTAL DATA SHEET E.O.# A-16-215page 1 of 1

Rev. No. Date

Manufacturer Mazda Motor Corporation		poration	_ Engine Family			VTK1.8VJGKEK			
			Evap F			V	TK1078BYMA	.1	
	n Eng Fam: CA								
Stds. Type : CA Tier-1 X AB965 TLEV			LE\	LEVULEV_			' US E	EPA Tier 1	
Evap Std:		<del></del>	In-Use Exh Std: Full In Use						
Veh. Calss: _	PC		Single Cert Std for Multi-Class Eng Fam: N/A						
Fuel Type(s): Gasoline			Emission Test Fuel(s): Indolene						
Service Accum:		<u> </u>	<u>.</u>	_					
NMOG Test Procedure: N/A			R/L Test Procedure: N/A						
Hybrid: N/A			•	APU Cycle:					
Engine Config : I-4			•	lacemen			s <u>(112.3)</u>	Cu. inches	
/alves/Cly	4		•	ed HP _			6500 F	RPM	
Engine : Front	XMid	Rear	. Drive	e: FWD		RWD X	4WD-FT	4WD-PT	
	Special Feature (in tions per SAE J19	· · · · · · · · · · · · · · · · · · ·	etc.)	·		(2) HO2S/TW	C/EGR/SFI		
,000 200,0112	1	· · · · · · · · · · · · · · · · · · ·		T ==:			<u> </u>	<u> </u>	
	Vehicle Model	Trans. Type		DPA	i	Ignition	EGR		
Engine Code	(if coded see	A-autonatic	ETW	or	1	ECM/PCM)	1 1	Catalyst	
(Cert, Std.)	attachment)	M-manual		RLH		Part No.	Part No.	Part No.	
KBPD2LA6	MX-5 Miata			8.0	*1   Cr	ank Angle	B6BF 20 300	Monolith	
		M5	2625	7.3	*2	Sensor:		Converter:	
KBPD2LAT	-			8.8	*1 BF	E8 18 230		BPS1 20 600	
AK				<del></del>	2	20 10 250		DI 51 20 000	
KBPDTLA6	1			<u> </u>					
REFEILAG					1 EC				
	i	A4		7.3	'2 BF	3A 18 221A			
KBPDTLAT				8.8	1				
A/C				8.0 *	2				
						·			