State of California AIR RESOURCES BOARD

EXECUTIVE ORDER A-22-75 Relating to Certification of New Motor Vehicles

SAAB AUTOMOBILE AB

Pursuant to the authority vested in the Air Resources Board by the Health and Safety Code, Division 26, Part 5, Chapter 2; and

Pursuant to the authority vested in the undersigned by Health and Safety Code Sections 39515 and 39516 and Executive Order G-45-9;

IT IS ORDERED AND RESOLVED: That 1997 model-year Saab Automobile AB exhaust emission control systems are certified as described below for passenger cars:

Fuel Type: Gasoline

Engine Family: VSA2.0VJGKEK Displacement: 2.0 Liters (121 Cubic Inches)

Exhaust Emission Control Systems & Special Features:

Sequential Multiport Fuel Injection Heated Oxygen Sensors (Two) Three Way Catalytic Converter Turbocharger Charge Air Cooler

Vehicle models, transmissions, engine codes and evaporative emission control families are listed on attachments.

The certification exhaust emission standards for this engine family in grams per mile are:

Miles	Non-Methane	Carbon	Nitrogen	Carbon	
	<u>Hydrocarbons</u>	<u>Monoxide</u>	<u>Oxides</u>	<u>Monoxide (20°F)</u>	
50,000	0.25	3.4	0.4	10.0	
100,000	0.31	4.2	0.6	n/a	

The certification exhaust emission values for this engine family in grams per mile are:

Miles	Non-Methane	Carbon	Nitrogen	Carbon	
	<u>Hydrocarbons</u>	<u>Monoxide</u>	<u>Oxides</u>	<u>Monoxide (20°F)</u>	
50,000	0.10	1.4	0.2	7.5	
100,000	0.11	1.7	0.2	n/a	

BE IT FURTHER RESOLVED: That the vehicle manufacturer is certifying the listed vehicle models to the 50,000-mile evaporative emission standards applicable to 1980 through 1994 model-year vehicles in the "California Evaporative Emission Standards and Test Procedures for 1978 and Subsequent Model Motor Vehicles," and the listed vehicle models comply with those standards.

BE IT FURTHER RESOLVED: That the listed vehicle models shall not be subject to the running loss and useful life standards set forth in the "California Evaporative Emission Standards and Test Procedures for 1978 and Subsequent Model Motor Vehicles," pursuant to provisions in said standards and test procedures applicable to small-volume manufacturers.

BE IT FURTHER RESOLVED: That the listed vehicle models also comply with the Board's "Specifications for Fill Pipes and Openings of Motor Vehicle Fuel Tanks" for the aforementioned model year (Title 13, California Code of Regulations, Section 2235).

BE IT FURTHER RESOLVED: That the listed vehicle models also comply with the Board's high-altitude requirements and highway emission standards, and with the California Inspection and Maintenance emission standards in place at the time of certification, as stipulated in "California Exhaust Emission Standards and Test Procedures for 1988 and Subsequent Model Passenger Cars, Light-Duty Trucks, and Medium-Duty Vehicles."

BE IT FURTHER RESOLVED: That the listed models also comply with the "Malfunction and Diagnostic System Requirements--1994 and Subsequent Model-Year Passenger Cars, Light-Duty Trucks, and Medium-Duty Vehicles and Engines" (Title 13, California Code of Regulations, Section 1968.1) for the aforementioned model year.

BE IT FURTHER RESOLVED: That the listed vehicle models also comply with the "California Motor Vehicle Emission Control Label Specifications" for the aforementioned model year (Title 13, California Code of Regulations, Section 1965).

BE IT FURTHER RESOLVED: That for the listed vehicles, the manufacturer has submitted and the Executive Officer hereby approves the materials to demonstrate certification compliance with the Board's emission control system warranty provisions (Title 13, California Code of Regulations, Section 2035 et seq.).

Vehicles certified under this Executive Order must conform to all applicable California emission regulations.

The Bureau of Automotive Repair will be notified by copy of this order and attachment.

Executed at El Monte, California this 12 day of September 1996.

R. B. Summerfield

Assistant Division Chief
Mobile Source Division

E.O.# A-22-75

199 7 MODEL-YEAR	AIR RESOURCES BOARD	SUPPLEMENTAL DATA SHEET
PASSENGER CARS,	LIGHT-DUTY TRUCKS A	ND MEDIUM-DUTY VEHICLES

Page___

Manufacture	r: SAAB		Exh Eng F	am: V≤A	1.0VJ GKEK	Evan Fam: v<	A I I A O/R A V DE A
All Eng Code	es in Eng Fam: (CA	49 S	50S ×	AROSS		
Exh Std: C	A Tier-1 <u>X</u>	LEV	LEV	ULE	V ZEV	— : IIS F	PA Tior-1
Evap Std: !	50K <u></u> Usefu⊺ (ife with	R/L	In-Use	Exh Std: Full	, VS L I In lice Y	Alt In Heav
Veh Class(e:	s): PC_XLDT	LLDT	2_ MD'	V 1	MDV2 MDV	/3 MDV4	MOVE
Single Cert	Std for Multi-Cl	ass Eng F	 am:_N/A	 {speci	fy: N/A. LDT	I. MOV1 MOV2	MUNA MUNA)
Fuel Type(s)): Dedicated	Flex-Fue	1 Dua	l-Fuel	Bi-Fuel	Gacoline)	, nots, mote)
	CNG LNG	LPG	M85	Other	(specify)		7 016261
Emiss Test A	$\frac{1}{\text{uel}(s)}$: $\frac{1}{\text{Indo} \times 1}$	 Ph2	CNG	LPG	M85 Othe	r (specify)	
	Diesel:	13 CCR 2	2282	40 (CFR 86 113-90	40 050	95 112 04
Service Accu	im: Std AMA_X_	Mod AMA	<u></u> Mfr	ADP	Other (spec	40 CFR	00.113-94
NMOG Test Pr	rocedure: N/A X	Std	— Fauiv		R/I Test Proc	·· GRED	De Cayana ALA
Hybrid: Typ	De A B C	. APU Cyc	:le (e.a	 Otto.	Diesel Turbi	. SUED	Pt Source <u>iv</u>
Engine Confi	guration: <u>14</u>	Displace	ement: 2	2.ø /	liters	121 /	Cubic Inches
valves ber C	ylinder: <u> </u>		Rate	ed HP:	/85	8 5500	Dovi
Engine: Fro	nt_X Mid	Rear	Driv	/e: FWD	X RWD		KPM
Thaust ECS	(e.g., MFI, EGR,	TC, CAC):	SFI. HO	25(2) T	WC TE CAC		4MD-P1
<i>الح</i> :		•	(u	se abbr	eviations per	SAE J1930 SE	P91)
Engine Code	Vehicle Models	Trans.	ETW	DPA	Ignition	EGR	Catalytic
(also list CA/49ST/50ST	(if coded see attachment)	(M5, A4 etc.)	or Took Us	or	(ECM/PCM)	System	Converter
B204L3	900SE COUPE	1	Test Wt.	KLHP	Part No.	Part No.	Part No.
_	900SE HATCHBACK	1-4	7 ~		47 80 284		
	900SE CONVERTIBLE	M5	3500	7.2	47 80 276	N/A	46 23 104
i			ĺ		1, da 216	1	
i		1	ĺ	ł			Ì
				i		Í	
		1					1
ļ							
İ		1					
ľ		i i					
ĺ			ĺ	1			1
_			- 1			1	
)			ł				
		,	ľ	- 1			
ate Issued:		<u>-</u>					

Revisions: