## State of California AIR RESOURCES BOARD

## EXECUTIVE ORDER A-22-80 Relating to Certification of New Motor Vehicles

## SAAB AUTOMOBILE AB

Pursuant to the authority vested in the Air Resources Board by the Health and Safety Code, Division 26, Part 5, Chapter 2; and

Pursuant to the authority vested in the undersigned by Health and Safety Code Sections 39515 and 39516 and Executive Order G-45-9;

IT IS ORDERED AND RESOLVED: That 1997 model-year Saab Automobile AB exhaust emission control systems are certified as described below for passenger cars:

Fuel Type: Gasoline

Engine Family: VSA3.0VJGFEK Displacement: 3.0 Liters (181 Cubic Inches)

Exhaust Emission Control Systems & Special Features:

Sequential Multiport Fuel Injection Secondary Air Injection Dual Heated Oxygen Sensors (Two) Dual Three Way Catalytic Converters

Vehicle models, transmissions, engine codes and evaporative emission control families are listed on attachments.

The certification exhaust emission standards for this engine family in grams per mile are:

<u>Miles</u>	Non-Methane	Carbon	Nitrogen	Carbon	
	<u>Hydrocarbons</u>	<u>Monoxide</u>	<u>Oxides</u>	<u>Monoxide (20°F)</u>	
50,000	0.25	3.4	0.4	10.0	
100,000	0.31	4.2	0.6	n/a	

The certification exhaust emission values for this engine family in grams per mile are:

Miles	Non-Methane	Carbon	Nitrogen	Carbon	
	<u>Hydrocarbons</u>	<u>Monoxide</u>	Oxides	<u>Monoxide (20°F)</u>	
50,000	0.04	0.3	0.1	2.8	
100,000	0.04	0.4	0.1	n/a	

BE IT FURTHER RESOLVED: That the vehicle manufacturer is certifying the listed vehicle models to the 50,000-mile evaporative emission standards applicable to 1980 through 1994 model-year vehicles in the "California Evaporative Emission Standards and Test Procedures for 1978 and Subsequent Model Motor Vehicles," and the listed vehicle models comply with those standards.

BE IT FURTHER RESOLVED: That the listed vehicle models shall not be subject to the running loss and useful life standards set forth in the "California Evaporative Emission Standards and Test Procedures for 1978 and Subsequent Model Motor Vehicles," pursuant to provisions in said standards and test procedures applicable to small-volume manufacturers.

BE IT FURTHER RESOLVED: That the listed vehicle models also comply with the Board's "Specifications for Fill Pipes and Openings of Motor Vehicle Fuel Tanks" for the aforementioned model year (Title 13, California Code of Regulations, Section 2235).

BE IT FURTHER RESOLVED: That the listed vehicle models also comply with the Board's high-altitude requirements and highway emission standards, and with the California Inspection and Maintenance emission standards in place at the time of certification, as stipulated in "California Exhaust Emission Standards and Test Procedures for 1988 and Subsequent Model Passenger Cars, Light-Duty Trucks, and Medium-Duty Vehicles."

BE IT FURTHER RESOLVED: That the listed models also comply with the "Malfunction and Diagnostic System Requirements--1994 and Subsequent Model-Year Passenger Cars, Light-Duty Trucks, and Medium-Duty Vehicles and Engines" (Title 13, California Code of Regulations, Section 1968.1) for the aforementioned model year.

BE IT FURTHER RESOLVED: That the listed vehicle models also comply with the "California Motor Vehicle Emission Control Label Specifications" for the aforementioned model year (Title 13, California Code of Regulations, Section 1965).

BE IT FURTHER RESOLVED: That for the listed vehicles, the manufacturer has submitted and the Executive Officer hereby approves the materials to demonstrate certification compliance with the Board's emission control system warranty provisions (Title 13, California Code of Regulations, Section 2035 et seq.).

Vehicles certified under this Executive Order must conform to all applicable California emission regulations.

The Bureau of Automotive Repair will be notified by copy of this order and attachment.  $\mathcal{L}$ 

Executed at El Monte, California this 12 day of September 1996.

R.) B. Summerfield

Assistant Division Chief Mobile Source Division

In Kourlehi f-

E.O.# A-22-80

199 7 MODEL-YEAR	AIR RESOURCES BOARD SUPPLEMENTAL DATA SHEET	
PASSENGER CARS,	LIGHT-DUTY TRUCKS AND MEDIUM-DUTY VEHICLES	

Page\_\_\_

Manufacture	r: <u>Saab</u>		Exh Eng I	Fam:_òA	3.0VJGFEK	Evan Fam. V.	
4113 000	III LIIV FAXI. I		Æu\	Enc v	4 Dece		
exn Sta: C	A lier-l <u>X</u> T	LEV	LEV	tii F	V 7FV	. He e	DA Tion 1 V
	Azeidi F	TIC WILL	K/L	in-use	tyh Sta. Ful	l In Hea v	ATA To It.
1011 01433 ( C.	3)	LU !	2_ MD	)V1	MDV2 MD1	/A MDV/	MOUT
Single cert	arm ton whiti-fi	ass eng F	am: N/A	(speci	fv: N/A Int'	MANA MONO	MOUS MONEY
Fuel Type(s)	): Dedicated CNG LNG Eugl(s): Indo	Flex-Fue	l Dua	ı]-Fuel	Bi-Fuel	Gasolino	V Diacol
Emiss Test I	Fuel(s): Indo <u>×</u>		CNG	I PG	MRS O+bo	in (analifi)	
	Diesel:	13 CCR	2282	40 (	CFR 86.113-90_	r (specity)_	45 110 01
Service Accu	ım: Std AMA_X	Mod AMA		ΔDP	Othom (rps_	4U CFK	86.113-94
NMOG Test Pr	rocedure: N/A ×	Std	— Fauiv	70°	D/I Took Dage	11TY)	<u> </u>
Hybrid: Typ	De A B C	- APU Cvr	- Equit		Diogram Turks	: SHEU	Pt Source
Engine Confi	guration: V6	Displace	ement.	20/	litana	ne):	
Valves per C	ylinder: 4	- (op)	Rati	ad HD.	rirers	_181 /	_Cubic Inches
Engine: Fro	nt X Mid_	Rear	Driv	νΔ· ΕΜΓ	210	6 <u>6200</u>	RPM
- haust ECS	(e.g., MFI, EGR,	TC. CAC):	SET AT	TO 2 1 4 5	-	4WD-F1	4WD-PT
_d	, , , , , , , , , , , , , , , , , , , ,	,	(1	use abbr	eviations per	SAE J1930 SE	:PQ1)
Engine Code	Vehicle Models	Trans.		DPA			·
(also list	(if coded see attachment)	(M5, A4	or	or	(ECM/PCM)	EGR System	Catalytic Converter
830814	9000 CSE	etc.)	Test Wt.	RLHP	Part No.	Part No.	Part No.
(50 ST)	HATCHBACK	PA	3625	7.1	47.0- 27.5	N/A	No = 1 = 2
ı				1	47 80 235	1 1	45 26 877
				1	<u> </u>		
		ļ	ĺ	ł			
				]			
					li .		
						1	1
				1			
				]		} [	
1	ĺ					1	ł
į							1
			ı				
	1	1					1
			-				
<i>&gt;</i>			1	ļ			
ate Issued:							
R.							<del></del>

Revisions: