State of California AIR RESOURCES BOARD

EXECUTIVE ORDER A-254-47 Relating to Certification of New Motor Vehicles

HYUNDAI MOTOR COMPANY

Pursuant to the authority vested in the Air Resources Board by the Health and Safety Code, Division 26, Part 5, Chapter 2; and

Pursuant to the authority vested in the undersigned by Health and Safety Code Sections 39515 and 39516 and Executive Order G-45-9;

IT IS ORDERED AND RESOLVED: That 1997 model-year Hyundai Motor Company exhaust emission control systems are certified as described below for passenger cars:

Fuel Type: Gasoline

Engine Family: VHY3.0V8G1EK Displacement: 3.0 Liters (181.4 Cubic Inches)

Exhaust Emission Control Systems and Special Features:

Heated Oxygen Sensors (two) Exhaust Gas Recirculation Three Way Catalytic Converter Sequential Multiport Fuel Injection

Vehicle models, transmissions, engine codes and evaporative emission control families are listed on attachments.

The certification exhaust emission standards for this engine family in grams per mile are:

_Miles	Non-Methane	Carbon	Nitrogen	Carbon	
	<u>Hydrocarbons</u>	<u>Monoxide</u>	<u>Oxides</u>	<u>Monoxide (20⁰F)</u>	
50,000	0.25	3.4	0.4	10.0	
100,000	0.31	4.2	0.6	n/a	

The certification exhaust emission values for this engine family in grams per mile are:

<u>Miles</u>	Non-Methane	Carbon	Nitrogen	Carbon	
	<u>Hydrocarbons</u>	<u>Monoxide</u>	<u>Oxides</u>	<u>Monoxide (20⁰F)</u>	
50,000	0.14	0.9	0.1	7.9	
100,000	0.15	0.9	0.2	n/a	

BE IT FURTHER RESOLVED: That the vehicle manufacturer is certifying the listed vehicle models to the aforementioned exhaust emission standards based on its submitted plan to comply with the fleet average non-methane organic gas (NMOG) exhaust mass emission requirements as set forth in "California Exhaust Emission Standards and Test Procedures for 1988 and Subsequent Model Passenger Cars, Light-Duty Trucks, and Medium-Duty Vehicles".

BE IT FURTHER RESOLVED: That under the submitted NMOG fleet average compliance plan, if the manufacturer incurs a NMOG debit for the aforementioned model year based on the projected NMOG fleet average exceeding the value required by the above-referenced standards and test procedures, all incurred NMOG debits by the manufacturer shall be equalized as required by the standards and test procedures.

BE IT FURTHER RESOLVED: That the vehicle manufacturer is certifying the listed vehicle models to the 50,000-mile evaporative emission standards applicable to 1980 through 1994 model-year vehicles in the "California Evaporative Emission Standards and Test Procedures for 1978 and Subsequent Model Motor Vehicles", and the listed vehicle models comply with those standards.

BE IT FURTHER RESOLVED: That, based on the evaporative emission phase-in compliance schedule submitted by the vehicle manufacturer, the listed vehicle models shall not be subject to the running loss and useful life standards set forth in the "California Evaporative Emission Standards and Test Procedures for 1978 and Subsequent Model Motor Vehicles."

BE IT FURTHER RESOLVED: That the listed vehicle models also comply with the Board's "Specifications for Fill Pipes and Openings of Motor Vehicle Fuel Tanks" for the aforementioned model year (Title 13, California Code of Regulations, Section 2235).

BE IT FURTHER RESOLVED: That the listed vehicle models also comply with the Board's high-altitude requirements and highway emission standards, and with the California Inspection and Maintenance emission standards in place at the time of certification, as stipulated in "California Exhaust Emission Standards and Test Procedures for 1988 and Subsequent Model Passenger Cars, Light-Duty Trucks, and Medium-Duty Vehicles".

BE IT FURTHER RESOLVED: That the listed vehicle models also comply with the "California Motor Vehicle Emission Control Label Specifications" for the aforementioned model year (Title 13, California Code of Regulations, Section 1965).

BE IT FURTHER RESOLVED: That the listed vehicle models also comply with the "Malfunction and Diagnostic System Requirements--1994 and Subsequent Model-Year Passenger Cars, Light-Duty Trucks, and Medium-Duty Vehicles and Engines" (Title 13, California Code of Regulations, Section 1968.1) for the aforementioned model year.

BE IT FURTHER RESOLVED: That for the listed vehicles, the manufacturer has submitted and the Executive Officer hereby approves the materials to demonstrate certification compliance with the Board's emission control system warranty provisions (Title 13, California Code of Regulations, Section 2035 et seq.).

Vehicles certified under this Executive Order must conform to all applicable California emission regulations.

The Bureau of Automotive Repair will be notified by copy of this order and attachment.

Executed at El Monte, California this 1976 day of June 1996.

Assistant Division Chief Mobile Source Division

1997 AIR RESOURCES SUPPLEMENTAL DATA SHEET PASSENGER CARS, LIGHT-DUTY TRUCKS AND MEDIUM-DUTY VEHICLES

Mariufacturer: Hvundai Motor CO. Exh Eng Fam: VHY3.0V8G1EK, Evap Fam: VHY1042BYVI04
All Eng Codes in Eng Fam : CA X 49S 50S AB965
Exh Std: CA Tier-1 X TLEV LEV ULEV ZEV ; US EPA Tier-1
Evap Std: 50K X Useful life with R/L In-Use Exh Std: Full In Use X Alt In Use
Veh Class(es): PC_X_ LDT1 LDT2 MDV1 MDV2 MDV3 MDV4 MDV5
Single Cert Std for Muli-Class Eng Fam: NA (specify: NA, LDT1, MDV1, MDV2, MDV3, MDV4)
Fuel Type(s): Dedicated Flex-Fuel Dual-Fuel Bi-Fuel Gasoline X Diesel
CNG LNG LPG M85 Other (specify)
Emiss Test Fuel(s): Indo X PH2 CNG LPG M85 other(specify)
Diesel: 13CCR 2282 40CFR 86.113-90 40CFR 86.113-94
Service Accum: Std AMA_X Mod AMA_ Mfr ADV_ OTHER(SPECIFY)
NMOG Test procedure: N/A X Std Equiv R/L Test Proc: SHED Pt Source
Hybrid: Type A B C, APU Cycle(e.g., Otto, Diesel, Turbine)
Engine Configuration: V-6 Displacement: 3.0 / Liters 181.4 / Cubic Inches
Valves Per Cylinder: 2
Engine: Front X Mid_ Rear_ Drive: FWD X_RWD_ 4WD-FT_ 4WD-PT_
Exhaust ECS (e.g., MFI, TC, CAC): HO2S(2) + EGR + TWC + SFI + OBD II
(use abbreviations per SAE J1930 SEP91)

Eng. Code (list CA/ 49ST/50ST)	Veh. Models (If Coded see Attachment)	Trans. Type: L-Auto. M-Man.	Equiv. Test Weight	DPA or RLHP	Ign. Sys. (ECM/PCM) part No.	EGR System. Part No.	Catalyst Part No.
ACL4-T /CL4-T (CA)	SONATA	L4	3375	7.7	39110-35365 (CLVM2) or 39110-35360 (CLVM2)	28450-35190 (HFT1)	28950-35650

Issued : 5-1-96

Revised: