## State of California AIR RESOURCES BOARD

## EXECUTIVE ORDER A-259-54-A Relating to Certification of New Motor Vehicles

## SUZUKI MOTOR CORPORATION

Pursuant to the authority vested in the Air Resources Board by the Health and Safety Code, Division 26, Part 5, Chapter 2; and

Pursuant to the authority vested in the undersigned by Health and Safety Code Sections 39515 and 39516 and Executive Order G-45-9;

IT IS ORDERED AND RESOLVED: That 1997 model-year Suzuki Motor Corporation exhaust emission control systems are certified as described below for passenger cars:

Emission Standard Category: Transitional Low-Emission Vehicle (TLEV)

<u>Fuel Type</u>: Gasoline

Engine Family: VSK1.0V5G2EK Displacement: 1.0 Liters (61 Cubic Inches)

Exhaust Emission Control Systems & Special Features:

Throttle Body Fuel Injection Heated Oxygen Sensors (Two) Warm Up Three Way Catalytic Converter Three Way Catalytic Converter Exhaust Gas Recirculation

Vehicle models, transmissions, engine codes and evaporative emission control families are listed on attachments.

The TLEV certification exhaust emission standards for this engine family in grams per mile are:

Miles	Non-Methane Organic Gas	Carbon <u>Monoxide</u>	Nitrogen <u>Oxides</u>	<u>Formaldehyde</u>	Carbon <u>Monoxide (20°F)</u>	
50,000	0.125	3.4	0.4	0.015	10.0	
100,000	0.156	4.2	0.6	0.018	n/a	

Reactivity Adjustment Factor (RAF) for NMOG Mass Emission: 0.98

The certification exhaust emission values set forth for non-methane organic gas (NMOG) reflect application of a 0.98 RAF for 1997 model-year TLEVs. The TLEV certification exhaust emission values for this engine family in grams per mile are:

Miles	Non-Methane <u>Organic Gas</u>	Carbon <u>Monoxide</u>	Nitrogen <u>Oxides</u>	<u>Formaldehyde</u>	Carbon <u>Monoxide (20°F)</u>
50,000	0.053	0.5	0.1	0.001	1.4
100,000	0.059	0.6	0.1	0.001	n/a

BE IT FURTHER RESOLVED: That the vehicle manufacturer is certifying the listed vehicle models to the aforementioned exhaust emission standards based on its submitted plan to comply with the fleet average NMOG exhaust mass emission requirements as set forth in "California Exhaust Emission Standards and Test Procedures for 1988 and Subsequent Model Passenger Cars, Light-Duty Trucks, and Medium-Duty Vehicles."

BE IT FURTHER RESOLVED: That under the submitted NMOG fleet average compliance plan, if the manufacturer incurs a NMOG debit for the aforementioned model year based on the projected NMOG fleet average exceeding the value required by the above-referenced standards and test procedures, all incurred NMOG debits by the manufacturer shall be equalized as required by the standards and test procedures.

BE IT FURTHER RESOLVED: That the vehicle manufacturer is certifying the listed vehicle models to the running loss and useful life standards applicable to 1995 and subsequent model-year vehicles in the "California Evaporative Emission Standards and Test Procedures for 1978 and Subsequent Model Motor Vehicles," and the listed vehicle models comply with those standards.

BE IT FURTHER RESOLVED: That the listed vehicle models also comply with the Board's "Specifications for Fill Pipes and Openings of Motor Vehicle Fuel Tanks" for the aforementioned model year (Title 13, California Code of Regulations, Section 2235).

BE IT FURTHER RESOLVED: That the listed vehicle models also comply with the Board's high-altitude requirements and highway emission standards, and with the California Inspection and Maintenance emission standards in place at the time of certification, as stipulated in "California Exhaust Emission Standards and Test Procedures for 1988 and Subsequent Model Passenger Cars, Light-Duty Trucks, and Medium-Duty Vehicles."

BE IT FURTHER RESOLVED: That the vehicle manufacturer has demonstrated compliance with the exhaust emission standards at 50 degrees Fahrenheit as stipulated in "California Exhaust Emission Standards and Test Procedures for 1988 and Subsequent Model Passenger Cars, Light-Duty Trucks, and Medium-Duty Vehicles."

BE IT FURTHER RESOLVED: That the listed models also comply with the "Malfunction and Diagnostic System Requirements--1994 and Subsequent Model-Year Passenger Cars, Light-Duty Trucks, and Medium-Duty Vehicles and Engines" (Title 13, California Code of Regulations, Section 1968.1) for the aforementioned model year.

BE IT FURTHER RESOLVED: That the listed vehicle models also comply with the "California Motor Vehicle Emission Control and Smog Index Label Specifications" for the aforementioned model year (Title 13, California Code of Regulations, Section 1965).

BE IT FURTHER RESOLVED: That for the listed vehicles, the manufacturer has submitted and the Executive Officer hereby approves the materials to demonstrate certification compliance with the Board's emission control system warranty provisions (Title 13, California Code of Regulations, Section 2035 et seq.).

Vehicles certified under this Executive Order must conform to all applicable California emission regulations.

The Bureau of Automotive Repair will be notified by copy of this order and attachment.

Executed at El Monte, California this 16 day of January 1997.

R. B. Summerfield Chief Mobile Source Operations Division

1.0

E.O.#<u>A-259-54-A</u> Page 1 of 1

## 1997 MODEL YEAR AIR RESOURCE BOARD SUPPLEMENTAL DATA SHEET PASSENGER CARS, LIGHT DUTY TRUCKS AND MEDIUM DUTY VEHICLES

Manufacturer: SUZI	UKI MOTOR CORE	Exh E	ng Fam:	VSK1.	0V5G2EK	EVAP Fam: VS	K1089AYME1
All Engine Codes in E	ing Fam: CA X 495	50S					
Exh Std: Tier 0 T	ier 1TLEV_X_L	EVUī	.EV;	ZEV	: US EF	A Tie	r <b>1</b>
EVAP Std: 50K	Useful Life with f	₹/L_X		In Use E	xh Std: FULL I	In Use X Alt I	n Use
Veh Class(es): PC_X	(_LDT1LDT2 N	1DV1I	MDV2	MDV3	MDV4	MDV5	<del></del>
Single Cert Std for Mi	ulti-Class Eng Fam:	(speci	fy: N/A. L	DT1. LD3	2 MDV1 MDV2	MDV3 MDV4 M	IDV5)
Fuel Type (s): Dedica	ited 🗶 Flex-Fuel	\ .	ual-Fuel	Bi	-Fuel Gase	nline Y Dies	:el
CNG	LNG LF		M85	Other (	snecify)	Dille X Dies	
Emiss Test Fuel (s): In	ndo Ph2 X C	NG	LPG	Other (	Other (sn	acifu)	<del></del>
D	iesel: 13CCR 2282	40	CER 86 1	 13-90	Other (spr	2 86 112 D4	
Service Accum; S	td AMA X Mod	AMA t	M	fr ADP	Other (see	( 00.   15-94 cifu)	
NMOG Test Procedur	e: N/A Std	x —		, , , , , , , , , , , , , , , , , , ,	2/ Test Proc S	UED DEC	- V
Hybrid: Type A	ВС	APU Cvo	ie (e.a. C	Mto Diece	ot Turbina)	PI S	onicex_
Engine configuration:	L3 (in line) Displace	ment 10	it (c.y. c 11 items o	r 81 c	ubic inches		
Valves per Cylinder:	2	Rated I	<u>Z</u> entora o HP	. <u>01</u> 0	ADIC FICHES	O DDM	
Engine: Front X	Mid Rear	Drive	EWD.	Y PMD	4WD ET	U KPIVI	
Exhaust ECS (eq. EG	GR, MFI, TC, CAC):	TRI	/ HO26	(3) ( )()() ( )	4VVD-1-1	4WD-P1 _	<del></del> -
	=======================================	(pe	SAF JIS	30 SEP	11407 1440 7 E	GR	
		723					
Engine Code		Trans	ETW	DPA	Ignition	EGR System	Catalytic
(also list	(re: p.21.00)	type		or	(ECM/PCM)		Converter
CA/49ST/50ST)				RLHP	Part No.		Part No.
CVTBM	Motes (Lletchhaul)	1.25					14150-51G00
(CA NY MA)	Metro (Hatchback)	M5	2125	7.5	33920-DMY1	18111-86010	14150 50005

Date Issued: 08NOV96 (RC4) Revised: 09JAN97 (R6)

J:\CERT\LD97\APP+PC\REV-PC\RC4\PV17BA4.54B