(Page 1 of 3)

State of California AIR RESOURCES BOARD

EXECUTIVE ORDER A-259-54 Relating to Certification of New Motor Vehicles

SUZUKI MOTOR CORPORATION

Pursuant to the authority vested in the Air Resources Board by the Health and Safety Code, Division 26, Part 5, Chapter 2; and

Pursuant to the authority vested in the undersigned by Health and Safety Code Sections 39515 and 39516 and Executive Order G-45-9;

IT IS ORDERED AND RESOLVED: That 1997 model-year Suzuki Motor Corporation exhaust emission control systems are certified as described below for passenger cars:

Emission Standard Category: Transitional Low-Emission Vehicle (TLEV)

Fuel Type: Gasoline

Engine Family: VSK1.0V5G2EK <u>Displacement</u>: 1.0 Liters (61 Cubic Inches)

Exhaust Emission Control Systems & Special Features:

Throttle Body Fuel Injection Heated Oxygen Sensors (Two)

Warm-Up Three Way Catalytic Converter

Three Way Catalytic Converter Exhaust Gas Recirculation

Vehicle models, transmissions, engine codes and evaporative emission control families are listed on attachments.

The TLEV certification exhaust emission standards for this engine family in grams per mile are:

Miles	Non-Methane Organic Gas	Carbon <u>Monoxide</u>	Nitrogen <u>Oxides</u>	<u>Formaldehyde</u>	Carbon <u>Monoxide (20⁰F)</u>
50,000	0.125	3.4	0.4	0.015	10.0
100,000	0.156	4.2	0.6	0.018	n/a

Reactivity Adjustment Factor (RAF) for NMOG Mass Emission: 0.98

The certification exhaust emission values set forth for non-methane organic gas (NMOG) reflect application of a 0.98 RAF for 1997 model-year TLEVs. The TLEV certification exhaust emission values for this engine family in grams per mile are:

Miles_	Non-Methane Organic Gas	Carbon <u>Monoxide</u>	Nitrogen <u>Oxides</u>	<u>Formaldehyde</u>	Carbon <u>Monoxide (20⁰F)</u>
50,000	0.053	0.5	0.1	0.001	1.4
100,000	0.059	0.6	0.1	0.001	n/a

BE IT FURTHER RESOLVED: That the vehicle manufacturer is certifying the listed vehicle models to the aforementioned exhaust emission standards based on its submitted plan to comply with the fleet average non-methane organic gas (NMOG) exhaust mass emission requirements as set forth in "California Exhaust Emission Standards and Test Procedures for 1988 and Subsequent Model Passenger Cars, Light-Duty Trucks, and Medium-Duty Vehicles".

BE IT FURTHER RESOLVED: That under the submitted NMOG fleet average compliance plan, if the manufacturer incurs a NMOG debit for the aforementioned model year based on the projected NMOG fleet average exceeding the value required by the above-referenced standards and test procedures, all incurred NMOG debits by the manufacturer shall be-equalized as required by the standards and test procedures.

BE IT FURTHER RESOLVED: That the vehicle manufacturer is certifying the listed vehicle models to the 50,000-mile evaporative emission standards applicable to 1980 through 1994 model-year vehicles in the "California Evaporative Emission Standards and Test Procedures for 1978 and Subsequent Model Motor Vehicles", and the listed vehicle models comply with those standards.

BE IT FURTHER RESOLVED: That, based on the evaporative emission phase-in compliance schedule submitted by the vehicle manufacturer, the listed vehicle models shall not be subject to the running loss and useful life standards set forth in the "California Evaporative Emission Standards and Test Procedures for 1978 and Subsequent Model Motor Vehicles."

BE IT FURTHER RESOLVED: That the listed vehicle models also comply with the Board's "Specifications for Fill Pipes and Openings of Motor Vehicle Fuel Tanks" for the aforementioned model year (Title 13, California Code of Regulations, Section 2235).

BE IT FURTHER RESOLVED: That the listed vehicle models also comply with the Board's high-altitude requirements and highway emission standards, and with the California Inspection and Maintenance emission standards in place at the time of certification, as stipulated in "California Exhaust Emission Standards and Test Procedures for 1988 and Subsequent Model Passenger Cars, Light-Duty Trucks, and Medium-Duty Vehicles".

BE IT FURTHER RESOLVED: That the vehicle manufacturer has demonstrated compliance with the exhaust emission standards at 50 degrees Fahrenheit as stipulated in "California Exhaust Emission Standards and Test Procedures for 1988 and Subsequent Model Passenger Cars, Light-Duty Trucks, and Medium-Duty Vehicles."

BE IT FURTHER RESOLVED: That the listed models also comply with the "Malfunction and Diagnostic System Requirements--1994 and Subsequent Model-Year Passenger Cars, Light-Duty Trucks, Medium-Duty Vehicles and Engines" (Title 13, California Code of Regulations, Section 1968.1) for the aforementioned model year.

BE IT FURTHER RESOLVED: That the listed vehicle models also comply with the "California Motor Vehicle Emission Control Label Specifications" for the aforementioned model year (Title 13, California Code of Regulations, Section 1965).

BE IT FURTHER RESOLVED: That for the listed vehicles, the manufacturer has submitted and the Executive Officer hereby approves the materials to demonstrate certification compliance with the Board's emission control system warranty provisions (Title 13, California Code of Regulations, Section 2035 et seq.).

Vehicles certified under this Executive Order must conform to all applicable California emission regulations.

The Bureau of Automotive Repair will be notified by copy of this order and attachment.

Executed at El Monte, California this $\sqrt{29^{-9}}$

R. B. Summerfield

Assistant Division Chief Mobile Source Division

E.O.# A-259-54 Page 1 of 1

1997 MODEL YEAR AIR RESOURCE BOARD SUPPLEMENTAL DATA SHEET PASSENGER CARS, LIGHT DUTY TRUCKS AND MEDIUM DUTY VEHICLES

Manufacturer: SUZ	UKI MOTOR CORE	Exh E	ng Fam:	<u>VSK1.0</u>	V5G2EK E	VAP Fam: VSK	1030BYMA1
All Engine Codes in Exh Std: Tier 0	Eng Fam: CA_X_49S_ Fier 1TLEV_X_L Useful Life with R/	50S _ EVUL L	;	ZEV; In Use E	US EPA	A Tier in Use _X _Alt in	1
Exh Std: Tier 0 Tier 1 ILEV X LEV ULEV ULEV In Use Exh Std: FULL In UseX Alt In Use EVAP Std: 50KX Useful Life with R/L In Use Exh Std: FULL In UseX Alt In Use							
Single Cart Std for Multi-Class Eng Fam: (specify: N/A, LDT1, LD12,MDV1,MDV2,MDV3,MDV4,MDV3)							
Fuel Type (s): Dedicated Flex-Fuel Dual-Fuel Bi-Fuel Gasoline X Diesel CNG LNG LPG M85 Other (specify)							
CNC	S LNG LI	°G	_M85	Other (s	specify)	-16.3	 _
Emiss Test Fuel (s):	ndo Ph2X0	CNG	_ LPG	M85_	Other (spe	OC 142 04	-
Diesel: 13CCR 2282 40CFR 86.113-90 40CFR 86.113-94							
Service Accum: Std AMA Y Mod AMA Mfr ADP - Other (specify)							
NIMOG Test Procedure: N/A Std X Equiv R/L Test Proc. SHED Pt Source							
Hybrid: Type A B C . APU Cycle (e.g. Otto, Diesel, Turbine)							
Engine configuration: L3 (in line) Displacement: 1.0 Liters or 61 cubic inches Valves per Cylinder: 2 Rated HP 55 @ 5,700 RPM							
Values per Cylinder:	2	Rated	HP	55	<u> </u>	DRPM	
Engine: Front X Mid Rear Drive: FWD X, RWD 4WD-F1 4VVD-F1							
Exhaust ECS (eg., EGR, MFI, TC, CAC): TBI / HO2S WU-TWC / TWC / EGR							
(per SAE J1930 SEP91)							
Engine Code	Vehicle Models	Trans	ETW	DPA	Ignition	EGR System	Catalytic
Engine Code (also list CA/49ST/50ST)	(re; p.21.00)	type		or RLHP	(ECM/PCM) Part No.		Converter Part No.
<u> </u>		N45	2125	_	33920-50GG	18111-86010	14150-51G00
CVTBM	Metro (Hatchback)	M5	2125	1.5			14150-50G00

Date Issued: 31MAR96

Revised:

PV17BJ3.54