(Page 1 of 3)

#### State of California AIR RESOURCES BOARD

# EXECUTIVE ORDER A-259-56 Relating to Certification of New Motor Vehicles

#### SUZUKI MOTOR CORPORATION

Pursuant to the authority vested in the Air Resources Board by the Health and Safety Code, Division 26, Part 5, Chapter 2; and

Pursuant to the authority vested in the undersigned by Health and Safety Code Sections 39515 and 39516 and Executive Order G-45-9;

IT IS ORDERED AND RESOLVED: That 1997 model-year Suzuki Motor Corporation exhaust emission control systems are certified as described below for passenger cars:

Fuel Type: Gasoline

Engine Family: VSK1.6VHGFEK <u>Displacement</u>: 1.6 Liters (97 Cubic inches)

### Exhaust Emission Control Systems & Special Features:

Multiport Fuel Injection
Heated Oxygen Sensors (Two)
Warm Up Three Way Catalytic Converter
Three Way Catalytic Converter
Exhaust Gas Recirculation

Vehicle models, transmissions, engine codes and evaporative emission control families are listed on attachments.

The certification exhaust emission standards for this engine family in grams per mile are:

<u>Mile</u>	Non-Methane	Carbon	Nitrogen	Carbon	
	<u>Hydrocarbons</u>	<u>Monoxide</u>	<u>Oxides</u>	<u>Monoxide (20°F)</u>	
50,000	0.25	3.4	0.4	10.0	
100,000	0.31	4.2	0.6	n/a	

The certification exhaust emission values for this engine family in grams per mile are:

<u>Mile</u>	Non-Methane	Carbon	Nitrogen	Carbon
	<u>Hydrocarbons</u>	<u>Monoxide</u>	Oxides	<u>Monoxide (20°F)</u>
50,000	0.11	0.6	0.1	2.4
100,000	0.12	0.7	0.1	n/a

BE IT FURTHER RESOLVED: That the vehicle manufacturer is certifying the listed vehicle models to the aforementioned exhaust emission standards based on its submitted plan to comply with the fleet average non-methane organic gas (NMOG) exhaust mass emission requirements as set forth in "California Exhaust Emission Standards and Test Procedures for 1988 and Subsequent Model Passenger Cars, Light-Duty Trucks, and Medium-Duty Vehicles."

BE IT FURTHER RESOLVED: That under the submitted NMOG fleet average compliance plan, if the manufacturer incurs a NMOG debit for the aforementioned model year based on the projected NMOG fleet average exceeding the value required by the above-referenced standards and test procedures, all incurred NMOG debits by the manufacturer shall be equalized as required by the standards and test procedures.

BE IT FURTHER RESOLVED: That the vehicle manufacturer is certifying the listed vehicle models to the 50,000-mile evaporative emission standards applicable to 1980 through 1994 model-year vehicles in the "California Evaporative Emission Standards and Test Procedures for 1978 and Subsequent Model Motor Vehicles," and the listed vehicle models comply with those standards.

BE IT FURTHER RESOLVED: That, based on the evaporative emission phase-in compliance schedule submitted by the vehicle manufacturer, the listed vehicle models shall not be subject to the running loss and useful life standards set forth in the "California Evaporative Emission Standards and Test Procedures for 1978 and Subsequent Model Motor Vehicles."

BE IT FURTHER RESOLVED: That the listed vehicle models also comply with the Board's "Specifications for Fill Pipes and Openings of Motor Vehicle Fuel Tanks" for the aforementioned model year (Title 13, California Code of Regulations, Section 2235).

BE IT FURTHER RESOLVED: That the listed vehicle models also comply with the Board's high-altitude requirements and highway emission standards, and with the California Inspection and Maintenance emission standards in place at the time of certification, as stipulated in "California Exhaust Emission Standards and Test Procedures for 1988 and Subsequent Model Passenger Cars, Light-Duty Trucks, and Medium-Duty Vehicles."

BE IT FURTHER RESOLVED: That the listed models also comply with the "Malfunction and Diagnostic System Requirements--1994 and Subsequent Model-Year Passenger Cars, Light-Duty Trucks, and Medium-Duty Vehicles and Engines" (Title 13, California Code of Regulations, Section 1968.1) for the aforementioned model year.

BE IT FURTHER RESOLVED: That the listed vehicle models also comply with the "California Motor Vehicle Emission Control Label Specifications" for the aforementioned model year (Title 13, California Code of Regulations, Section 1965).

BE IT FURTHER RESOLVED: That for the listed vehicles, the manufacturer has submitted and the Executive Officer hereby approves the materials to demonstrate certification compliance with the Board's emission control system warranty provisions (Title 13, California Code of Regulations, Section 2035 et seq.).

Vehicles certified under this Executive Order must conform to all applicable California emission regulations.

The Bureau of Automotive Repair will be notified by copy of this order and attachment.

Executed at El Monte, California this 16 day of July 1996.

Assistant Division Chief

Mobile Source-Division

E.O.# A-259-56 Page 1 of 1

## 1997 MODEL YEAR AIR RESOURCE BOARD SUPPLEMENTAL DATA SHEET PASSENGER CARS, LIGHT DUTY TRUCKS AND MEDIUM DUTY VEHICLES

Manufacturer: S	UZUKI MO	TOR CO	RP B	Exh Eng f	am: <u>VSK1.6</u>	VHGFEK EV	AP Fam: VSK1030BYMA1	
All Engine Codes	s in Eng Fam:	CA_X_4	9\$ <u>X</u> 5	0S	7C) / ,	LICEDA	Tior 1 V	
Exh Std: Tier 0_	Tier 1_X_	TLEV	LEV _	ULEV_	; ; ;	. USEFA Evh Stát FULL Ir	Tier 1 X	
EVAP Std: 50K	X User	II Lite Witi	N/L	· MDV	, MDV3	MDV4!	Use X Alt In Use	
ven Class(es): F	-C_X_LDTT	_LD12	_ 10100	n IVID V	VA LOT1 LOT	NDV4 MDV2 M	DV3,MDV4,MDV5)	
Single Cert Sta to	or Multi-Class	Eng Fam	: (;	Specify. in	Sual Bi-	2,1410 v 1,1410 v2,14 Eupl Gasolir	ne X Diesel	
Fuel Type (S): U	edicated	riex-r	L PG	Dual-	fuel Di-	necify)		
Emiss Test Fuel (s): Indo Ph2X _ CNG LPG M85 Other (specify) Diesel: 13CCR 2282 40CFR 86.113-90 40CFR 86.113-94								
Social Acquire: Std AMA Y Mod AMA: Mfr ADP Other (specify)								
NMOG Test Procedure : N/A Std Equiv RAL Test Proc: SHED Pt Source Pt Source								
Hybrid: Type A B C, APU Cycle (e.g. Otto, Diesel, Turbine)								
Engine configura	tion: <u>L4 (in lir</u>	ne) Displ	acemen	t: <u>1.6 L</u> ite	ers or <u>97</u> cu	ubic inches		
Valves per Cylind	der: <u>4</u>		R	ated HP_	98	<u>@ 6,000</u>	RPM	
Engine: Front	X Mid	Rear	ם	rive: FW	D X RWD	4WD-FT	4WD-PT	
Exhaust ECS (eg	,, EGR, MFI,	TC, CAC)	: <u>MFI</u>	/HO25	WUTWC+TW	C / EGR		
				(per SA	E J1930 SEP9	<u>1)</u>		
Engine Code	Vobiala	Trops	ETW	DPA	Ignition	EGR System	Catalytic	
Engine Code (also list	Vehicle Models	Trans type	T	or	(ECM/PCM)	•	Converter Part	
A/49ST/50ST)	(re: p.21.00)	1,50		RLHP	Part No.		No.	
OVOEM		145	2500	7.5	33920-61G4			
CVCEM (CA,NY,MA)		M5	2500	7.5	33920-0164			
(OM, INT.)			-					
CVCEB		A4	2625	7.6	33920-61G5			
(CA,NY,MA)		1						
	ESTEEM					18111-60G00	14240-60G00	
	ESTEEM					18111-60G00	14240-60G00 (manifold)	
FVCEM	ESTEEM	M5	2500	7.5	33920-61G4	18111-60G00	(manifold) 14150-60G10	
FVCEM (Federal)	ESTEEM	M5	2500	7.5	33920-61G4	18111-60G00	(manifold)	
	ESTEEM	M5	2500	7.5	33920-61G4	18111-60G00	(manifold) 14150-60G10	
(Federal)  FVCEB	ESTEEM	M5	2500 2625	7.5 7.6	33920-61G4 33920-61G5	18111-60G00	(manifold) 14150-60G10	
(Federal)	ESTEEM					18111-60G00	(manifold) 14150-60G10	

Date Issued: 31MAR96

Revised:

PV17EJ3.56