(Page 1 of 2)

## State of California AIR RESOURCES BOARD

## EXECUTIVE ORDER A-323-2 Relating to Certification of New Motor Vehicles

## PANOZ AUTO-DEVELOPMENT COMPANY

Pursuant to the authority vested in the Air Resources Board by the Health and Safety Code, Division 26, Part 5, Chapter 2; and

Pursuant to the authority vested in the undersigned by Health and Safety Code Sections 39515 and 39516 and Executive Order G-45-9;

IT IS ORDERED AND RESOLVED: That 1997 model-year Panoz Auto-Development Company exhaust emission control systems are certified as described below for passenger cars:

Fuel Type: Gasoline

Engine Family: VP34.6VJGKEK Displacement: 4.6 Liters (280 Cubic Inches)

Exhaust Emission Control Systems & Special Features:

Dual Three Way Catalytic Converters (two)
Dual Heated Oxygen Sensors (two)
Exhaust Gas Recirculation
Secondary Air Injection
Sequential Multiport Fuel Injection

Vehicle models, transmissions, engine codes and evaporative emission control families are listed on attachments.

The certification exhaust emission standards for this engine family in grams per mile are:

<u>Miles</u>	Non-Methane	Carbon	Nitrogen	Carbon	
	<u>Hydrocarbons</u>	<u>Monoxide</u>	<u>Oxides</u>	<u>Monoxide (20°F)</u>	
50,000	0.25	3.4	0.4	10.0	
100,000	0.31	4.2	0.6	n/a	

The certification exhaust emission values for this engine family in grams per mile are:

Miles	Non-Methane	Carbon	Nitrogen	Carbon	
	<u>Hydrocarbons</u>	<u>Monoxide</u>	<u>Oxides</u>	<u>Monoxide (20°F)</u>	
50,000	0.18	1.2	0.2	5.6	
100,000	0.21	1.6	0.2	n/a	

BE IT FURTHER RESOLVED: That the vehicle manufacturer is certifying the listed vehicle models to the 50,000-mile evaporative emission standards applicable to 1980 through 1994 model-year vehicles in the "California Evaporative Emission Standards and Test Procedures for 1978 and Subsequent Model Motor Vehicles," and the listed vehicle models comply with those standards.

BE IT FURTHER RESOLVED: That the vehicle models shall not be subject to the running loss and useful life standards set forth in the "California Evaporative Emission Standards and Test Procedures for 1978 and Subsequent Model Motor Vehicles" pursuant to provisions in the said standards and test procedures applicable to small-volume manufacturers.

BE IT FURTHER RESOLVED: That the listed vehicle models also comply with the Board's "Specifications for Fill Pipes and Openings of Motor Vehicle Fuel Tanks" for the aforementioned model year (Title 13, California Code of Regulations, Section 2235).

BE IT FURTHER RESOLVED: That the listed vehicle models also comply with the Board's high-altitude requirements and highway emission standards, and with the California Inspection and Maintenance emission standards in place at the time of certification, as stipulated in "California Exhaust Emission Standards and Test Procedures for 1988 and Subsequent Model Passenger Cars, Light-Duty Trucks, and Medium-Duty Vehicles."

BE IT FURTHER RESOLVED: That the listed vehicle models also comply with the "California Motor Vehicle Emission Control and Smog Index Label Specifications" for the aforementioned model year (Title 13, California Code of Regulations, Section 1965).

BE IT FURTHER RESOLVED: That the manufacturer is certifying the listed vehicle models with a partially complying on-board diagnostic system for the aforementioned model year pursuant to Title 13, California Code of Regulations, Section 1968.1(m)(6.2) ("Malfunction and Diagnostic System Requirements--1994 and Subsequent Model-Year Passenger Cars, Light-Duty Trucks, and Medium-Duty vehicles and Engines").

BE IT FURTHER RESOLVED: That for the listed vehicles, the manufacturer has submitted and the Executive Officer hereby approves the materials to demonstrate certification compliance with the Board's emission control system warranty provisions (Title 13, California Code of Regulations, Section 2035 et seq.).

Vehicles certified under this Executive Order must conform to all applicable California emission regulations,

The Bureau of Automotive Repair will be notified by copy of this order and attachment.

Executed at El Monte, California this 3 day of January 1997.

R. B. Summerfield, Chief

Mobile Source Operations Division

## 199 7 MODEL-YEAR AIR RESOURCES BOARD SUPPLEMENTAL DATA SHEET PASSENGER CARS, LIGHT-DUTY TRUCKS AND MEDIUM-DUTY VEHICLES

Page 1

Manufacture	r: Panoz Auto-Deve	lopment	Exh Eng F	am: VP34	.6VJGKEK	Evan Fam: VP3	1045AYM1.A
All Eng Code	es in Eng Fam: C	A	<b>49</b> S	50S X	A8965		
Exh Std: CA	A Tier-1_X T	LEV	LEV	ULE	<u> </u>	— · IIS FE	PA Tion 1 Y
Evap Std:	50K <u>X</u> Useful L	ife with	R/L	In-Use	Fxh Std· Full	, US L	A Her-I A
Veh Class(es	s): PC <u>X</u> LDT1	LDT	2 MD	V 1	MDV2 MDV	3 MUNA	MDAE
Single Cert	Std for Multi-Cl	ass Eng F	am: N/A	(sneci:	fv: N/A IDTI	MDV1 MDV2	NDV3
Fuel Type(s)	: Dedicated	Flex-Fue	Dua	(Speci	Ri-Fuel	Casalina	איטא, אטע4) X איי א
	CNG LNG	LPG	M85	Other	(specify)	dazoiine	Diesel
Emiss Test F	uel(s): Indo X		CNG I	PG .	M85 0+ha	- (anasi fu)	
	Diesel:	13 CCR 2	282	40 (	CFR 86.113-90_	r (specity)	06 113 04
Service Accu	m: Std AMA	Mod AMA	X Mfr	מחם	Othon (case	40 CFK	86.113-94
NMOG Test Pr	ocedure: N/A_X	Std.	— Fouriv	~Dr	D/I Tost Dres	. SHED	Di C
Hybrid: Typ	e A B C,	APU Cvo	·le (e d	Otto	Discal Tumbi	: 2UED	Pt Source
Engine Confi	guration: <u>v8</u>	Displace	ment: /	6 /	litans 20	ne):_ <i>N/4</i>	
Valves per C	ylinder: 4	013p14cc	Rate	N ND·	Liters <u>_2</u> 2	80.0 /	Cubic Inches
Engine: Fro	nt_X_Mid	Rear	Driv	'A FWD	DIAD A		RPM
Tyhaust ECS	(e.g., MFI, EGR,	TC. CAC):	SFI/2HO	(2) 2 TUC	(2)/FCP/AIR	4WU-FI	4WD-P1
	, 3, , , , , , , , , , , , , , , , , ,		_ <u></u>	se abbr	eviations per	SAE J1930 SE	P91)
Engine Code	Vehicle Models	Trans.		DPA	Ignition		
(also list	(if coded see	(M5, A4	or	or	(ECM/PCM)	EGR System	Catalytic Converter
CA/ 4331/ 3031	`attachment)	etc.)	Test Wt.	RLHP	Part No.		Part No.
	Panoz AIV	M5	2875	10.1	ECM	F67F-00475	P670 58050 M
(50 ST)	Roadster				F6ZF-12A650-	or 90477-DF	F6ZC-5F250-MI F6ZC-5F250-MC
			•		JE		(alt.)
		1		ĺ			
J		!					
ļ							
			,			ļ	
]							
	i		ĺ		1		
		İ		}			
nto Joseph							
ate Issued:							<del></del>

Revisions: