(Page 1 of 2)

State of California AIR RESOURCES BOARD

EXECUTIVE ORDER A-40-40 Relating to Certification of New Motor Vehicles

FERRARI S.p.A.

Pursuant to the authority vested in the Air Resources Board by the Health and Safety Code, Division 26, Part 5, Chapter 2; and

Pursuant to the authority vested in the undersigned by Health and Safety Code Sections 39515 and 39516 and Executive Order G-45-9;

IT IS ORDERED AND RESOLVED: That 1997 model-year Ferrari S.p.A. exhaust emission control systems are certified as described below for passenger cars:

Fuel Type: Gasoline

Engine Family: VFE3.5VJGKEK Displacement: 3.5 Liters (213 Cubic Inches)

Exhaust Emission Control Systems and Special Features:

Sequential Multiport Fuel Injection Secondary Air Injection Dual Heated Oxygen Sensors (two) Four Three Way Catalytic Converters

Vehicle models, transmissions, engine codes and evaporative emission control families are listed on attachments.

The certification exhaust emission standards for this engine family in grams per mile are:

	Non-Methane	Carbon	Nitrogen	Carbon	
<u>Miles</u>	<u>Hydrocarbons</u>	<u>Monoxide</u>	Oxidés	Monoxide (20°F)	
50,000	0.25	3.4	0.4	10.0	
100,000	0.31	4.2	0.6	n/a	

The certification exhaust emission values for this engine family in grams per mile are:

Miles	Non-Methane	Carbon	Nitrogen	Carbon	
	<u>Hydrocarbons</u>	<u>Monoxide</u>	<u>Oxides</u>	<u>Monoxide (20°F)</u>	
50,000	0.16	1.7	0.2	6.4	
100,000	0.21	2.5	0.3	n/a	

BE IT FURTHER RESOLVED: That the vehicle manufacturer is certifying the listed vehicle models to the 50,000-mile evaporative emission standards applicable to 1980 through 1994 model-year vehicles in the "California Evaporative Emission Standards and Test Procedures for 1978 and Subsequent Model Motor Vehicles", and the listed vehicle models comply with those standards.

BE IT FURTHER RESOLVED: That the listed vehicle models shall not be subject to the running loss and useful life standards set forth in the "California Evaporative Emission Standards and Test Procedures for 1978 and Subsequent Model Motor Vehicles", pursuant to provisions in said standards and test procedures applicable to small-volume manufacturers.

BE IT FURTHER RESOLVED: That the listed vehicle models also comply with the "California Motor Vehicle Emission Control Label Specifications" for the aforementioned model year (Title 13, California Code of Regulations, Section 1965).

BE IT FURTHER RESOLVED: That the listed vehicle models also comply with the Board's "Specifications for Fill Pipes and Openings of Motor Vehicle Fuel Tanks" for the aforementioned model year (Title 13, California Code of Regulations, Section 2235).

BE IT FURTHER RESOLVED: That the listed vehicle models also comply with the Board's high-altitude requirements and highway emission standards, and with the California Inspection and Maintenance emission standards in place at the time of certification, as stipulated in "California Exhaust Emission Standards and Test Procedures for 1988 and Subsequent Model Passenger Cars, Light-Duty Trucks, and Medium-Duty Vehicles".

BE IT FURTHER RESOLVED: That the manufacturer is certifying the listed vehicle models with a partially complying on-board diagnostic system for the aforementioned model year pursuant to Title 13, California Code of Regulations, Section 1968.1(m)(6.2) ("Malfunction and Diagnostic System Requirements--1994 and Subsequent Model-Year Passenger Cars, Light-Duty Trucks, and Medium-Duty Vehicles and Engines").

BE IT FURTHER RESOLVED: That for the listed vehicles, the manufacturer has submitted and the Executive Officer hereby approves the materials to demonstrate certification compliance with the Board's emission control system warranty provisions (Title 13, California Code of Regulations, Section 2035 et seq.).

Vehicles certified under this Executive Order must conform to all applicable California emission regulations.

The Bureau of Automotive Repair will be notified by copy of this order and attachment.

Executed at El Monte, California this

day of September 1996.

Assistant Division Chief

Mobile Source Division

1997 MODEL-YEAR AIR RESOURCES BOARD SUPPLEMENTAL DATA SHEET PASSENGER CARS, LIGHT-DUTY TRUCKS AND MEDIUM-DUTY VEHICLES

Page 1

	r: FERRARI S.p.	Α	Exh Eng F	am:vF	E3.5VJGKEK	Evap Fam: v	FE1Ø97AYMA5
/ ing Code	es in Eng Fam: C	A	495	50S_X	AB965		
Ex., Std: C/	A Tier-1 <u>x</u> Ti	LEV	LEV	ULE	V ZEV_	- ; USE	PA Tier-1 X
Evap Std: !	50K <u>x</u> Useful L	ife with	R/L :	In-Use	Exh Std: Full	In Use x	Alt In Use
Veh Class(es	s): PC <u>x</u> LDT1_	LDT:	2 MD\	/1	MDV2 MDV:	 3 MDV4	MDV5
Single Cert	Std for Multi-Cla	iss Eng Fa	am: <u>N/A</u>	_(speci	fy: N/A, LDT1.	, MDVI, MDV2	, MDV3, MDV4)
Fuel Type(s)	: Dedicated <u>x</u>	Flex-Fue	1 Dua1	l-Fuel_	Bi-Fuel	Gasoline	X Diesel
	CNGLNG	LPG	M85	Other	(specify)	_	
Emiss Test F	Fuel(s): Indo \underline{x}	Ph2	CNGL	.PG	M85Other	(specify)	· · · · · · · · · · · · · · · · · · ·
	Diesel:	13 CCR 2	2282	40 (CFR 86.113-90	40 CFR	86.113-94
Service Accu	m: Std AMA	Mod AMA	Mfr	ADP	Other (speci	fy) ADFs	
NMOG Test Pr	ocedure: N/A <u>x</u>	Std	_ Equiv_		R/L Test Proc:	SHED	Pt Source
Hybrid: Typ	e A B C,	APU Cyc	:le (e.g.,	Otto,	Diesel, Turbin	ie):	
Engine Confi	guration: <u>V8-90</u> °	Displace	ement: <u> </u>	.5 /	<u> Liters </u>	213 / -	Cubic Inches
Valves per C	ylinder: <u> </u>		Rate	d HP:	375	@ 8200	RPM
Engine: Fro	nt Mid <u>x</u>	Rear	Driv	e: FWD) RWD <u>x</u>	4WD-FT	4WD-PT
Exhaust ECS	(e.g., MFI, EGR,	TC, CAC):	SFI/	IR/4TW	C/2H02S(2)		
			(u	se abbr	eviations per	SAE J1930 SE	P91)
≓r ine Code list		Trans.		-DPA		EGR	
	(if coded see attachment)	(M5, A4 etc.)	or T est=Wt .	or RIHP	(ECM/PGM+) Part No.	System Part No.	Converter
	F355 berlinetta		3,625	1			
	F355 GTS		0,023		1/2 659	N/A	FERRARI CAT 129 RO3
	F355 spider						(right)
							FERRARI
			ļ				CAT 129 LO3
		ı					(left)
!							FERRARI
							CAT 129 CO2
							(secondary)
		1					
		j					
<u> </u>							
lissued:							

Revisions: