(Page 1 of 2)

State of California AIR RESOURCES BOARD

EXECUTIVE ORDER A-40-41 Relating to Certification of New Motor Vehicles

FERRARI S.p.A.

Pursuant to the authority vested in the Air Resources Board by the Health and Safety Code, Division 26, Part 5, Chapter 2; and

Pursuant to the authority vested in the undersigned by Health and Safety Code Sections 39515 and 39516 and Executive Order G-45-9;

IT IS ORDERED AND RESOLVED: That 1997 model-year Ferrari S.p.A. exhaust emission control systems are certified as described below for passenger cars:

Fuel Type: Gasoline

Engine Family: VFE5.5VJGKEK Displacement: 5.5 Liters (334 Cubic Inches)

Exhaust Emission Control Systems and Special Features:

Sequential Multiport Fuel Injection Secondary Air Injection Dual Heated Oxygen Sensors (two) Dual Three Way Catalytic Converters

Vehicle models, transmissions, engine codes and evaporative emission control families are listed on attachments.

The certification exhaust emission standards for this engine family in grams per mile are:

Miles	Non-Methane	Carbon	Nitrogen	Carbon
	<u>Hydrocarbons</u>	<u>Monoxide</u>	<u>Oxidés</u>	<u>Monoxide (20ºF)</u>
50,000	0.25	3.4	0.4	10.0
100,000	0.31	4.2	0.6	n/a

The certification exhaust emission values for this engine family in grams per mile are:

Miles	Non-Methane	Carbon	Nitrogen	Carbon	
	Hydrocarbons	<u>Monoxide</u>	Oxides	<u>Monoxide (20ºF)</u>	
50,000	0.20	1.7	0.1	8.6	
100,000	0.25	2.5	0.1	n/a	

BE IT FURTHER RESOLVED: That the vehicle manufacturer is certifying the listed vehicle models to the 50,000-mile evaporative emission standards applicable to 1980 through 1994 model-year vehicles in the "California Evaporative Emission Standards and Test Procedures for 1978 and Subsequent Model Motor Vehicles", and the listed vehicle models comply with those standards.

FERRARI S.p.A.

EXECUTIVE ORDER A-40-41 (Page 2 of 2)

BE IT FURTHER RESOLVED: That the listed vehicle models shall not be subject to the running loss and useful life standards set forth in the "California Evaporative Emission Standards and Test Procedures for 1978 and Subsequent Model Motor Vehicles", pursuant to provisions in said standards and test procedures applicable to small-volume manufacturers.

BE IT FURTHER RESOLVED: That the listed vehicle models also comply with the "California Motor Vehicle Emission Control Label Specifications" for the aforementioned model year (Title 13, California Code of Regulations, Section 1965).

BE IT FURTHER RESOLVED: That the listed vehicle models also comply with the Board's "Specifications for Fill Pipes and Openings of Motor Vehicle Fuel Tanks" for the aforementioned model year (Title 13, California Code of Regulations, Section 2235).

BE IT FURTHER RESOLVED: That the listed vehicle models also comply with the Board's high-altitude requirements and highway emission standards, and with the California Inspection and Maintenance emission standards in place at the time of certification, as stipulated in "California Exhaust Emission Standards and Test Procedures for 1988 and Subsequent Model Passenger Cars, Light-Duty Trucks, and Medium-Duty Vehicles".

BE IT FURTHER RESOLVED: That the manufacturer is certifying the listed vehicle models with a partially complying on-board diagnostic system for the aforementioned model year pursuant to Title 13, California Code of Regulations, Section 1968.1(m)(6.2) ("Malfunction and Diagnostic System Requirements--1994 and Subsequent Model-Year Passenger Cars, Light-Duty Trucks, and Medium-Duty Vehicles and Engines").

BE IT FURTHER RESOLVED: That for the listed vehicles, the manufacturer has submitted and the Executive Officer hereby approves the materials to demonstrate certification compliance with the Board's emission control system warranty provisions (Title 13, California Code of Regulations, Section 2035 et seq.).

Vehicles certified under this Executive Order must conform to all applicable California emission regulations.

The Bureau of Automotive Repair will be notified by copy of this order and attachment.

Executed at El Monte, California this 💆 day of

September 1996. Summerfield R.B

Assistant Division Chief Mobile Source Division

E.O.# A-40-41

1997 MODEL-YEAR AIR RESOURCES BOARD SUPPLEMENTAL DATA SHEET Page 1 PASSENGER CARS, LIGHT-DUTY TRUCKS AND MEDIUM-DUTY VEHICLES

Manufacturer: FERRARI S.p.A. Exh Eng Fam: VFE5.5VJGKEK Evap Fam: VFE1Ø97AYMAC All Eng Codes in Eng Fam: CA____ 49S____ 50S X AB965 LEV____ ULEV____ ZEV___; US EPA Tier-1_X__ Exh Std: CA Tier-1 X TLEV Evap Std: 50K X Useful Life with R/L___ In-Use Exh Std: Full In Use X Alt In Use___ Veh Class(es): PC_x_LDT1___LDT2___MDV1____MDV2___MDV3___MDV4____MDV5____ Single Cert Std for Multi-Class Eng Fam: N/A (specify: N/A, LDT1, MDV1, MDV2, MDV3, MDV4) Fuel Type(s): Dedicated X Flex-Fuel Dual-Fuel Bi-Fuel Gasoline Diesel CNG____LNG___LPG____M85___Other (specify)____ Emiss Test Fuel(s): Indo<u>x</u> Ph2___ CNG___ LPG___ M85____ Other (specify)__ Diesel: 13 CCR 2282____ 40 CFR 86.113-90____ 40 CFR 86.113-94___ Service Accum: Std AMA ____ Mod AMA ____ Mfr ADP ___ Other (specify) ADFs NMOG Test Procedure: N/A_X___Std____Equiv_____R/L Test Proc: SHED_____Pt Source____ Hybrid: Type A____ B___ C___, APU Cycle (e.g., Otto, Diesel, Turbine):_____ Engine Configuration: V12-65° Displacement: 5.5 / - Liters 334 / - Cubic Inches Rated HP: _____436 @___6200 Valves per Cylinder: ___4___ RPM Engine: Front<u>x</u> Mid____ Rear____ Drive: FWD_____ RWD_X___4WD-FT_____4WD-PT_____

(use abbreviations per SAE J1930 SEP91)

Engine Code (also list CA/49ST/50ST	Vehicle Models (if coded see attachment)	Trans. (M5, A4 etc.)	ETW or T est W t.	D P A or RLHP	Ignition (ECM/ PCM) Part No.	EGR System Part No.	Catalytic Converter Part No.
SFI/EI/C/X (50ST)	Ferrari 456 GTA	L-4	4,750	11.3	170 135	N/A	FERRARI CAT-116-R
	Ferrari 456 GT	M-6	4,500		168 893		(right) FERRARI CAT-116-L (left)

Date Issued:

Revisions: