(Page 1 of 2)

State of California AIR RESOURCES BOARD

EXECUTIVE ORDER A-40-42 Relating to Certification of New Motor Vehicles

FERRARI S.p.A.

Pursuant to the authority vested in the Air Resources Board by the Health and Safety Code, Division 26, Part 5, Chapter 2; and

Pursuant to the authority vested in the undersigned by Health and Safety Code Sections 39515 and 39516 and Executive Order G-45-9;

IT IS ORDERED AND RESOLVED: That 1997 model-year Ferrari S.p.A. exhaust emission control systems are certified as described below for passenger cars:

Fuel Type: Gasoline

Engine Family: VFE5.5VJGKFK Displacement: 5.5 Liters (334 Cubic Inches)

Exhaust Emission Control Systems and Special Features:

Sequential Multiport Fuel Injection Secondary Air Injection Dual Heated Oxygen Sensors (two) Dual Three Way Catalytic Converters

Vehicle models, transmissions, engine codes and evaporative emission control families are listed on attachments.

The certification exhaust emission standards for this engine family in grams per mile are:

Miles	Non-Methane	Carbon	Nitrogen	Carbon	
	<u>Hydrocarbons</u>	<u>Monoxide</u>	<u>Oxides</u>	<u>Monoxide (20°F)</u>	
50,000	0.25	3.4	0.4	10.0	
100,000	0.31	4.2	0.6	n/a	

The certification exhaust emission values for this engine family in grams per mile are:

Miles	Non-Methane	Carbon	Nitrogen	Carbon	
	<u>Hydrocarbons</u>	<u>Monoxide</u>	Oxides	<u>Monoxide (20⁰F)</u>	
50,000	0.15	0.8	0.1	6.9	
100,000	0.19	1.2	0.2	n/a	

BE IT FURTHER RESOLVED: That the vehicle manufacturer is certifying the listed vehicle models to the 50,000-mile evaporative emission standards applicable to 1980 through 1994 model-year vehicles in the "California Evaporative Emission Standards and Test Procedures for 1978 and Subsequent Model Motor Vehicles", and the listed vehicle models comply with those standards.

BE IT FURTHER RESOLVED: That the listed vehicle models shall not be subject to the running loss and useful life standards set forth in the "California Evaporative Emission Standards and Test Procedures for 1978 and Subsequent Model Motor Vehicles", pursuant to provisions in said standards and test procedures applicable to small-volume manufacturers.

BE IT FURTHER RESOLVED: That the listed vehicle models also comply with the "California Motor Vehicle Emission Control and Smog Index Label Specifications" for the aforementioned model year (Title 13, California Code of Regulations, Section 1965).

BE IT FURTHER RESOLVED: That the listed vehicle models also comply with the Board's "Specifications for Fill Pipes and Openings of Motor Vehicle Fuel Tanks" for the aforementioned model year (Title 13, California Code of Regulations, Section 2235).

BE IT FURTHER RESOLVED: That the listed vehicle models also comply with the Board's high-altitude requirements and highway emission standards, and with the California Inspection and Maintenance emission standards in place at the time of certification, as stipulated in "California Exhaust Emission Standards and Test Procedures for 1988 and Subsequent Model Passenger Cars, Light-Duty Trucks, and Medium-Duty Vehicles".

BE IT FURTHER RESOLVED: That the manufacturer is certifying the listed vehicle models with a partially complying on-board diagnostic system for the aforementioned model year pursuant to Title 13, California Code of Regulations, Section 1968.1(m)(6.2) ("Malfunction and Diagnostic System Requirements--1994 and Subsequent Model-Year Passenger Cars, Light-Duty Trucks, and Medium-Duty Vehicles and Engines").

BE IT FURTHER RESOLVED: That for the listed vehicles, the manufacturer has submitted and the Executive Officer hereby approves the materials to demonstrate certification compliance with the Board's emission control system warranty provisions (Title 13, California Code of Regulations, Section 2035 et seq.).

Vehicles certified under this Executive Order must conform to all applicable California emission regulations.

The Bureau of Automotive Repair will be notified by copy of this order and attachment.

Executed at El Monte, California this 20 day of February 1997.

R. B. Summerfield, Chief

Mobile Source Operations Division

1997 MODEL-YEAR AIR RESOURCES BOARD SUPPLEMENTAL DATA SHEET PASSENGER CARS, LIGHT-DUTY TRUCKS AND MEDIUM-DUTY VEHICLES

Page 1

manufacture	FERRARI S.p	.A.	Exh Eng F	am:_VFE	5.5VJGKFK	Evap Fam:	VFE1194AYMA2
All Eng Code	es in Eng Fam: C	A	49S	50Sx	AB965		
Exh Std: CA	Tier-1_x_ T	LEV	LEV	ULE	V ZEV_	; US	EPA Tier-1_x
cvap sta: :	OUKX_ Useful L	ife with	R/L	In-Use	Exh Std: Full	In Use x	Alt In ilsa
ven Class(es	;): PC <u>X</u> LDT1	LDT	2 MD	V1	MDV2 MD\	/3 MDV4	MOVE
Single Cert	Std for Multi-Cla	ass Eng F	am: <u>N/A</u>	_(specif	fy: N/A, LDT]	. MDV1. MDV	2. MOV3 MOVA)
Fuel Type(s)	: Dedicated_X	Flex-Fue	1 Dua	1-Fuel	Bi-Fuel	Gasoline	X Diesel
Emiss Test F	CNG LNG uel(s): Indo_X	Ph2	CNG	LPG	M85Othe	r (specify)	
	Diesel:	13 CCR 2	2282	40 C	FR 86.113-90	40 CF	R 86 113-94
Service Accu	m: Std AMA	Mod AMA	Mfr	ADP	Other (spec	ifv) ADFs	
MMUG Test Pr	ocedure: N/A $_{ m X}$	Std	_ Equiv_		R/L Test Proc	: SHED	Pt Source
Hybrid: Type	e A B C,	APU Cyc	le (e.g.	, Otto,	Diesel, Turbi	ne):	10 0041 00
Engine Confi	guration: V12-65°	Displace	ement:	5.5 / -	Liters	334 /	Cubic Inches
valves per C	ylinder: 4		Rate	ed HP:	475	@ 7000	DDM
Engine: From	nt <u>X</u> Mid	Rear	Driv	∕e: FWD	RWD X	4WD-FT	4WD-PT
Exhaust ECS	(e.g., MFI, EGR,	TC, CAC):	SFI/	AIR/2TWC	(/2H02S(2)		
			(u	ise abbr	eviations per	SAE J1930 S	SEP91)
(also list)	Vehicle Models (if coded see	Trans. (M5, A4	ETW	1	Ignition	EGR	Catalytic
CA/49ST/50ST	attachment)		T est ₩t.	or RLHP	Part No.	Part No.	Catalytic Converter Part No.
SFI/ET/4/X	Ferrari					1	
	550 maranello	141-Q	4,250	11.0	172 432	N/A	
			į				CAT-133-RO2
							(right)
							FERRARI
							CAT-133-L02
							(left)
1		į					
	1		i				
				İ			
Date Issued:			ļ	1		İ	ı

Revisions: