State of California AIR RESOURCES BOARD

EXECUTIVE ORDER A-3-168-A Relating to Certification of New Motor Vehicles

MERCEDES-BENZ AG

Pursuant to the authority vested in the Air Resources Board by the Health and Safety Code, Division 26, Part 5, Chapter 2; and

Pursuant to the authority vested in the undersigned by Health and Safety Code Sections 39515 and 39516 and Executive Order G-45-9;

IT IS ORDERED AND RESOLVED: That 1998 model-year Mercedes-Benz AG exhaust emission control systems are certified as described below for passenger cars:

Emission Standard Category: Transitional Low-Emission Vehicle (TLEV)

Fuel Type: Gasoline

Engine Family: WMBXV05.0GNB <u>Displacement</u>: 5.0 Liters (303 Cubic Inches)

Exhaust Emission Control Systems & Special Features:

Dual Three Way Catalytic Converters
Dual Warm Up Three Way Catalytic Converters
Dual Heated Oxygen Sensors (two)
Secondary Air Injection
Sequential Multiport Fuel Injection

Vehicle models, transmissions, engine codes and evaporative emission control families are listed on attachments.

The TLEV certification exhaust emission standards for this engine family in grams per mile are:

Non-Methane	Carbon	Nitrogen	<u>Formaldehyde</u>	Carbon
<u>Miles</u> <u>Organic Gases</u>	<u>Monoxide</u>	<u>Oxides</u>		<u>Monoxide (20°F)</u>
50,000 0.125	3.4	0.4	0.015	10.0
100,000 0.156	4.2		0.018	n/a

Reactivity Adjustment Factor (RAF) for NMOG Mass Emission: 0.98

The certification exhaust emission values set forth for non-methane organic gases (NMOG) reflect application of a 0.98 RAF for 1998 model-year TLEVs. The TLEV certification exhaust emission values for this engine family in grams per mile are:

Miles	Non-Methane Organic Gases	Carbon <u>Monoxide</u>	Nitrogen <u>Oxides</u>	<u>Formaldehyde</u>	Carbon Monoxide (20°F)
50,000	0.052	0.5	0.2	0.001	3.8
100,000	0.057	0.8		0.002	n/a

BE IT FURTHER RESOLVED: That the vehicle manufacturer is certifying the listed vehicle models to the aforementioned exhaust emission standards based on its submitted plan to comply with the fleet average NMOG exhaust mass emission requirements as set forth in "California Exhaust Emission Standards and Test Procedures for 1988 and Subsequent Model Passenger Cars, Light-Duty Trucks, and Medium-Duty Vehicles."

BE IT FURTHER RESOLVED: That under the submitted NMOG fleet average compliance plan, if the manufacturer incurs a NMOG debit for the aforementioned model year based on the projected NMOG fleet average exceeding the value required by the above-referenced standards and test procedures, all incurred NMOG debits by the manufacturer shall be equalized as required by the standards and test procedures.

BE IT FURTHER RESOLVED: That the listed vehicle models are conditionally certified to the running loss and useful life standards applicable to 1995 and subsequent model-year vehicles in the "California Evaporative Emission Standards and Test Procedures for 1978 and Subsequent Model Motor Vehicles," and are conditionally certified to the "California Refueling Emission Standards and Test Procedures for 1998 and Subsequent Model Motor Vehicles." The conditional certification of the listed vehicle models is at the request of the manufacturer using projection of 80,000-mile bench test data to demonstrate durability and determine deterioration factors. The final 100,000-mile data will be obtained and submitted by the manufacturer at a later date to validate the subject conditional certification. If, for any reason, the 100,000-mile data result in non-compliance of the listed vehicle models with the aforementioned evaporative and refueling standards, the certification condition shall not have been met and the listed vehicle models shall not be covered by this Executive Order. In such event, the manufacturer shall assume full Nabilities including recall and possible penalties under the California Health and Safety Code for vehicles sold in connection with this Executive Order. Additionally, in such event all affected vehicles shall be withheld from further sales until full compliance with the applicable evaporative and refueling emission standards is demonstrated to the satisfaction of the Executive Officer.

BE IT FURTHER RESOLVED: That the listed vehicle models also comply with the Board's "Specifications for Fill Pipes and Openings of Motor Vehicle Fuel Tanks" for the aforementioned model year (Title 13, California Code of Regulations, Section 2235).

BE IT FURTHER RESOLVED: That the listed vehicle models also comply with the Board's high-altitude requirements and highway emission standards, and with the California Inspection and Maintenance emission standards in place at the time of certification, as stipulated in "California Exhaust Emission Standards and Test Procedures for 1988 and Subsequent Model Passenger Cars, Light-Duty Trucks, and Medium-Duty Vehicles."

BE IT FURTHER RESOLVED: That the vehicle manufacturer has demonstrated compliance with the exhaust emission standards at 50 degrees Fahrenheit as stipulated in "California Exhaust Emission Standards and Test Procedures for 1988 and Subsequent Model Passenger Cars, Light-Duty Trucks, and Medium-Duty Vehicles."

BE IT FURTHER RESOLVED: That the listed vehicle models also comply with the "California Motor Vehicle Emission Control and Smog Index Label Specifications" for the aforementioned model year (Title 13, California Code of Regulations, Section 1965).

BE IT FURTHER RESOLVED: That the listed vehicle models also comply with the "Malfunction and Diagnostic System Requirements--1994 and Subsequent Model-Year Passenger Cars, Light-Duty Trucks, and Medium-Duty Vehicles and Engines" (Title 13, California Code of Regulations, Section 1968.1) for the aforementioned model year.

BE IT FURTHER RESOLVED: That for the listed vehicles, the manufacturer has submitted and the Executive Officer hereby approves the materials to demonstrate certification compliance with the Board's emission control system warranty provisions (Title 13, California Code of Regulations, Section 2035 et seq.).

Vehicles certified under this Executive Order must conform to all applicable California emission regulations.

The Bureau of Automotive Repair will be notified by copy of this order and attachment.

Executed at El Monte, California this 3 day of October 1997.

R. B. Summerfield, Chief

Mobile Source Operations Division

E.O. # A-3-168-A

Page 1 of 1 1998 MODEL-YEAR AIR RESOURCES BOARD SUPPLEMENTAL DATA SHEET PASSENGER CARS, LIGHT-DUTY TRUCKS AND MEDIUM-DUTY VEHICLES

Manufacturer: Me	rcades-Be	nz	Exh. E	ng Famil	y: WM8	3XV05.0G	NB I	Evap. Fa	amily: WM	BXR0155A	AYY
All Eng Codes in E	ng Fam:	CA	49	S	50S	X	AB9	65	ORVR	Yes X	No
Exh Std:		CA TI	er-1	TLEV _>	(_LEV	U	EVS1	JLEV	_ US E	PA Tier-1	_X_
Veh Class(es):	PG X	LDT1	LI	T2	MDV1	MD	V2	MDV3	MDV4	MDV	5
Single Cert Std for	Multi-Clas	s Eng F	am: N	4_	(specif	y: N/A	, LDT1,	MDV1,	MDV2,	MDV3,	MDV4)
Fuel Type(s):	Dedicated	_X_	Flex-Fue	el le	Dual-F	uel	Bi-Fue	اGء	isoli ne <u>X</u>	Diese	H
	CNG		LNG		LPG_	M8!	5	Other	(specify)		, , (
Exh. Emiss Test F	uel(s); Inde	5	CBG X	CNG		LPG	_ M85 _	Other	(specify)		
	Die	sel: 13	CCR 228	 2		40 (OFR 86.1	13-90	40 CFI	R 88.113-94	4
Evaporative Emlss	Ion Test P	rocedure	a: C	allfornia		Fed	leral	<u>X</u>			
Service Accum:	Std	AMA	M	lod AMA	X	Mir ADP		Other	(specify)		
NMOG Test Proce	dure; N/A	·	Std X	Equi	٧	RVL Test F	Prod.	SHED	X	Pt Source ,	
Engine Configurat	lion: <u>V-8</u>	<u> </u>	Displace	sment: 🔔	-4-2	- 5.0	Liters	-25	6+ 303	Cubic	Inches
Valves per Cylinde	er: 4					Rated HP	275 +3	15 +	700 +5600		_ RPM
Engine: Front	X Mic	<u> </u>	Rear _			Drive: FV	VD		4WD-I	FT4WD)-PT
Exhaust ECS (eg.	, MFI, EG	R, TC,	CAC):	SFL/AIR	/ 2 HO2	S(2) / 2 V	/U-TWC	2 TWC			
						(use abbr	eviations	per SAE	J1930 JU	N93)	

,	Engine Code (also list CA/49ST/50ST)	Vehicle Modela (if coded see attachment)	Trans. Type (A 4, M 5 etc)	ETW or Test Wi	DPA or RLHP	tgnition (ECM/PCM) Part No.	EGR System Part No.	Catalytic Converter Part No.
	M 119-50-2	SL 500	L.5	4 500	6.6	A 021 545 24 32	_	A 140 490 36 36 (underhood) A 140 490 34 36 (underfloor)

Date Issued:

zotVSOgno2.pm\$-bo

Revisions: