(Page 1 of 3)

State of California AIR RESOURCES BOARD

EXECUTIVE ORDER A-16-230 Relating to Certification of New Motor Vehicles

MAZDA MOTOR CORPORATION

Pursuant to the authority vested in the Air Resources Board by the Health and Safety Code, Division 26, Part 5, Chapter 2; and

Pursuant to the authority vested in the undersigned by Health and Safety Code Sections 39515 and 39516 and Executive Order G-45-9;

IT IS ORDERED AND RESOLVED: That 1998 model-year Mazda Motor Corporation exhaust emission control systems are conditionally certified as described below for light-duty trucks:

Fuel Type: Gasoline

Engine Family: WTKXT03.02B2 <u>Displacement</u>: 3.0 Liters (180 Cubic Inches)

Exhaust Emission Control Systems & Special Features:

Three Way Catalytic Converters (two) Heated Oxygen Sensors (two) Sequential Multiport Fuel Injection

Vehicle models, transmissions, engine codes and evaporative emission control families are listed on attachments.

The certification exhaust emission standards for this engine family in grams per mile are:

Loaded Vehicle	<u>Miles</u>	Non-Methane	Carbon	Nitrogen	Carbon
Weight (lbs.)		<u>Hydrocarbons</u>	<u>Monoxide</u>	<u>Oxides</u>	Monoxide (20°F)
3751-5750	50,000	0.32	4.4	0.7	12.5
	100,000	0.40	5.5	0.97	n/a

The certification exhaust emission values for this engine family in grams per mile are:

Loaded Vehicle	<u>Miles</u>	Non-Methane	Carbon	Nitrogen	Carbon
Weight (lbs.)		<u>Hydrocarbons</u>	<u>Monoxide</u>	<u>Oxides</u>	Monoxide (20°F)
3751-5750	50,000	0.18	1.5	0.1	5.2
	100,000	0.20	1.6	0.12	n/a

BE IT FURTHER RESOLVED: That the vehicle manufacturer is certifying the listed vehicle models to the aforementioned exhaust emission standards based on its submitted plan to comply with the fleet average non-methane organic gases (NMOG) exhaust mass emission requirements as set forth in "California Exhaust Emission Standards and Test Procedures for 1988 and Subsequent Model passenger Cars, Light-Duty Trucks, and Medium-Duty Vehicles."

BE IT FURTHER RESOLVED: That under the submitted NMOG fleet average compliance plan, if the manufacturer incurs a NMOG debit for the aforementioned model year based on the projected NMOG fleet average exceeding the value required by the above-referenced standards and test procedures, all incurred NMOG debits by the manufacturer shall be equalized as required by the standards and test procedures.

BE IT FURTHER RESOLVED: That the vehicle manufacturer is certifying the listed vehicle models to the running loss and useful life standards applicable to 1995 and subsequent model-year vehicles in the "California Evaporative Emission Standards and Test Procedures for 1978 and Subsequent Model Motor Vehicles," and the listed vehicle models comply with those standards.

BE IT FURTHER RESOLVED: That the listed vehicle models also comply with the Board's "Specifications for Fill Pipes and Openings of Motor Vehicle Fuel Tanks" for the aforementioned model year (Title 13, California Code of Regulations, Section 2235).

BE IT FURTHER RESOLVED: That the listed vehicle models also comply with the Board's high-altitude requirements and highway emission standards, and with the California Inspection and Maintenance emission standards in place at the time of certification, as stipulated in "California Exhaust Emission Standards and Test Procedures for 1988 and Subsequent Model Passenger Cars, Light-Duty Trucks, and Medium-Duty Vehicles."

BE IT FURTHER RESOLVED: That the listed vehicle models also comply with the "California Motor Vehicle Emission Control and Smog Index Label Specifications" for the aforementioned model year (Title 13, California Code of Regulations, Section 1965).

BE IT FURTHER RESOLVED: That the listed vehicle models are conditionally certified pursuant to Title 13, California Code of Regulations, Section 1968.1(m)(6.2) ("Malfunction and Diagnostic System Requirements--1994 and Subsequent Model-Year Passenger Cars, Light-Duty Trucks, and Medium-Duty Vehicles and Engines") because the on-board diagnostic II system of the listed vehicle models has been determined to have three deficiencies. The listed vehicle models are approved subject to Mazda Motor Corporation paying a fine of fifty dollars (\$50.00) per vehicle for the third deficiency in the listed engine family that is produced and delivered for sale in California.

The vehicle manufacturer shall pay the full fine owed pursuant to this conditional certification to the State Treasurer for deposit in the Air Pollution Control Fund no later than thirty days after the end of the 1998 model year production period; failure to pay the total fine within this period shall be cause for the Executive Officer to rescind the certification ab initio and all vehicles sold in California under this conditional certification shall be deemed uncertified and be subject to a civil penalty of up to \$5,000 per vehicle pursuant to Health and Safety Code Section 43154.

BE IT FURTHER RESOLVED: That for the listed vehicles, the manufacturer has submitted and the Executive Officer hereby approves the materials to demonstrate certification compliance with the Board's emission control system warranty provisions (Title 13, California Code of Regulations, Section 2035 et seq.).

Vehicles certified under this Executive Order must conform to all applicable California emission regulations,

The Bureau of Automotive Repair will be notified by copy of this order and attachment.

Executed at El Monte, California this 44 day of September 1997.

R. B. Summerfield, Chief Mobile Source Operations Division

1998 AIR RES	OURCE	S BOAR	D SUPPLE	EMENTAL DA	TA SHEE	T E.O.#	†=16=230page	4 of 4
Manufacturer	Mazda l	Motor Con	poration	Exh Eng Far	n: <u>WTK</u> X	(T03.02B2 Eva	p Fam: WTKXE	0120BFA
All Engine Code	s in Engi	ne Family	r: CA	49S .	50S X	AB965, C	DRVR: YES	NO X
						SULEV		
						MDV2 MI		
						DT1, MDV1, MDV		
						Bi-Fuel		
,, ,,						Other (s		
Exh Emiss Test F						M85		
	(-, -					6.113-90		
Evaporative Emi	ssion Te						10 01 11 00	
Service Accum :						Other (s	pecify)	
					uiv —	R/L Test Proc :	SHED PI	Source X
						Liters 180		
Valves per Cylino						152		0 RPM
								4WD-PT X
Exhaust ECS (e.c	n. MELE	GR TC	CAC) ·			DRWD_X HO2\$/TWC/SFI,	,	<u></u>
	g., <i>,</i> , _	,,	o, io,			viations per SAE J		
					(000 000.0	ragene per eriz e	**	
Engine Code	Vehicle	Models	Trans. Typ	e ETW	DPA	Ignition	EGR	
(also list CA/	(if cod	led see	(M5, A4	Ŀ	or	(ECM/PCM)		Catalyst
49ST/50ST)	attac	hment)	etc.)	Test Wt.	1	Part No.	Part No.	Part No.
KJEEFAA7	Mazda N	⁄PV 4x4	L4	4500	11.5	Distrubutor:	EGR Control	ЈЕ96
				•		JE96	Valve:	
KJEEFAAV					12.6	ECU:	N/A	
					<u> </u>	JEA9		<u> </u>
Certification S	Standard	s (50,00	0 mile/ 10	00,000 mile/1	20,000 mi	le)		
HC (g/mi)		***	,	, 0.80				
Non-methane HC				,				
CO (g/mi)				-				
NOx (g/mi)		0.7	,0.97	, ***	_			
HWFET NOx (g/m	ıi)	1.4	, 1.94	, ***				
Evap. (EPA : g/te	st)	***	, 2.0	, •••				
Evap. (ARB : g/te	est)	•••	, 2.0	1 ***				
Evap. (Abbrev : g	/test)	***	, 2.5	., ***				
Running Loss (g/	test)		, 0.05	, ***				
Spit Back (g/test)	1		, 1.0	, ***				
Cold CO (g/mi)		12.5	, •••	, 				
Idle CO for LDT (%	6)		, •	, 0.50				
CST-HC			00, at 2500m					
CST-CO		at idle: ()	l.5. at 2500m	m: 0.5				

Revisions:

1290

Issue date:	June 27,	1997		
Rev. No.				
Date				