State of California AIR RESOURCES BOARD

EXECUTIVE ORDER A-16-231 Relating to Certification of New Motor Vehicles

MAZDA MOTOR CORPORATION

Pursuant to the authority vested in the Air Resources Board by the Health and Safety Code, Division 26, Part 5, Chapter 2; and

Pursuant to the authority vested in the undersigned by Health and Safety Code Sections 39515 and 39516 and Executive Order G-45-9:

IT IS ORDERED AND RESOLVED: That 1998 model-year Mazda Motor Corporation exhaust emission control systems are conditionally certified as described below for light-duty trucks:

Emission Standard Category: Transitional Low-Emission Vehicle (TLEV)

Fuel Type: Gasoline

Engine Family: WTKXT03.02DM Displacement: 3.0 Liters (180 Cubic Inches)

Exhaust Emission Control Systems & Special Features:

Three Way Catalytic Converters (two) Heated Oxygen Sensors (two) Sequential Multiport Fuel Injection

Vehicle models, transmissions, engine codes and evaporative emission control families are listed on attachments.

The non-methane organic gases (NMOG), carbon monoxide (CO), oxides of nitrogen (NOx), and formaldehyde (HCHO) TLEV certification exhaust emission standards for this engine family in grams per mile are:

Loaded Vehicle						
Weight (lbs.)	<u>Miles</u>	<u>NMOG</u>	<u></u>	<u>NOx</u>	<u>HCHO</u>	CO (20°F)
3751-5750	50,000	0.160	4.4	0.7	0.018	12.5
	100,000	0.200	5.5	0.9	0.023	n/a

Reactivity Adjustment Factor (RAF) for NMOG Mass Emission: 0.98

The certification exhaust emission values set forth for NMOG reflect application of a 0.98 RAF for 1998 model-year TLEVs. The TLEV certification exhaust emission values for this engine family in grams per mile are:

Loaded Vehicle Weight (lbs.)	<u>Miles</u>	<u>NMOG</u>	<u></u>	NOx	НСНО	CO (20°F)
3751-5750	50,000	0.065	0.7	0.03	0.00049	5.0
	100,000	0.071	0.7	0.03	0.001	n/a

BE IT FURTHER RESOLVED: That the vehicle manufacturer is certifying the listed vehicle models to the aforementioned exhaust emission standards based on its submitted plan to comply with the fleet average NMOG exhaust mass emission requirements as set forth in "California Exhaust Emission Standards and Test Procedures for 1988 and Subsequent Model Passenger Cars, Light-Duty Trucks, and Medium-Duty Vehicles."

BE IT FURTHER RESOLVED: That under the submitted NMOG fleet average compliance plan, if the manufacturer incurs a NMOG debit for the aforementioned model year based on the projected NMOG fleet average exceeding the value required by the above-referenced standards and test procedures, all incurred NMOG debits by the manufacturer shall be equalized as required by the standards and test procedures.

BE IT FURTHER RESOLVED: That the vehicle manufacturer is certifying the listed vehicle models to the running loss and useful life standards applicable to 1995 and subsequent model-year vehicles in the "California Evaporative Emission Standards and Test Procedures for 1978 and Subsequent Model Motor Vehicles," and the listed vehicle models comply with those standards.

BE IT FURTHER RESOLVED: That the listed vehicle models also comply with the Board's "Specifications for Fill Pipes and Openings of Motor Vehicle Fuel Tanks" for the aforementioned model year (Title 13, California Code of Regulations, Section 2235).

BE IT FURTHER RESOLVED: That the listed vehicle models also comply with the Board's high-altitude requirements and highway emission standards, and with the California Inspection and Maintenance emission standards in place at the time of certification, as stipulated in "California Exhaust Emission Standards and Test Procedures for 1988 and Subsequent Model Passenger Cars, Light-Duty Trucks, and Medium-Duty Vehicles."

BE IT FURTHER RESOLVED: That the listed vehicle models are conditionally certified pursuant to Title 13, California Code of Regulations, Section 1968.1(m)(6.2) ("Malfunction and Diagnostic System Requirements--1994 and Subsequent Model-Year Passenger Cars, Light-Duty Trucks, and Medium-Duty Vehicles and Engines") because the on-board diagnostic II system of the listed vehicle models has been determined to have three deficiencies. The listed vehicle models are approved subject to Mazda Motor Corporation paying a fine of fifty dollars (\$50.00) per vehicle for the third deficiency in the listed engine family that is produced and delivered for sale in California.

The vehicle manufacturer shall pay the full fine owed pursuant to this conditional certification to the State Treasurer for deposit in the Air Pollution Control Fund no later than thirty days after the end of the 1998 model year production period; failure to pay the total fine within this period shall be cause for the Executive Officer to rescind the certification ab initio and all vehicles sold in California under this conditional certification shall be deemed uncertified and be subject to a civil penalty of up to \$5,000 per vehicle pursuant to Health and Safety Code Section 43154.

BE IT FURTHER RESOLVED: That the listed vehicle models also comply with the "California Motor Vehicle Emission Control and Smog Index Label Specifications" for the aforementioned model year (Title 13, California Code of Regulations, Section 1965).

BE IT FURTHER RESOLVED: That the vehicle manufacturer has demonstrated compliance with the exhaust emission standards at 50 degrees Fahrenheit as stipulated in "California Exhaust Emission Standards and Test Procedures for 1988 and Subsequent Model Passenger Cars, Light-Duty Trucks, and Medium-Duty Vehicles."

BE IT FURTHER RESOLVED: That for the listed vehicles, the manufacturer has submitted and the Executive Officer hereby approves the materials to demonstrate certification compliance with the Board's emission control system warranty provisions (Title 13, California Code of Regulations, Section 2035 et seq.).

Vehicles certified under this Executive Order must conform to all applicable California emission regulations.

The Bureau of Automotive Repair will be notified by copy of this order and attachment.

Executed at El Monte, California this 4 da

_ day of September 1997.

R. B Summerfie d, Chief

Mobile Source Operations Division

3 of 4

Manufacturer	Mazda N	Motor Cor	poration E	xh Eng Fan	n: WTK	XT03.02DM E	vap Fam: <u>WTKX</u>	Œ0120BFA
All Engine Code	es in Engi	ne Family	y: CA <u>X</u> 4	988	50S	_AB965,	ORVR: YES	NO X
Exh Std: CA	Tier-1	TL	EV X L	.EV	ULEV	SULEV_	. US EPA	A Tier-1
Veh Class (es):	PC	LDT1	LDT2	<u> — м</u> г	DV1	MDV2	MDV3 MDV	MDV5
Single Cert Std f	for Multi-C	- lass End	Fam: N/	A (sne	cify N/A	, LDT1, MDV1, MI	7/3 MD/3 MD/	A MDA2
Fuel Type (s):								
· •• · ·) po (o) .						Bi-Fuel		
Full Emiles Took			LNG				(specify)	
EXITEMISS TEST	ruei (s) :					M85		
_		Diesel:	13 CCR 2282	<u></u>	40CFR	86.113-90	40 CFR 8	36.113-94
Evaporative Emi	ission Tes	st Proced	lure : Californ	ia <u>X</u>	Fede	eral		
Service Accum:	Std. All	MA_X	Mod AMA	·	Mfr ADP	Other	(specify)	
NMOG Test Prod	cedure :	N/A	Std	Eq.	uiv 🦟	R/L Test Proc	: SHED F	PT Source X
Engine Configur	ration:	V-6	Displacement		, —	Liters 180		Pubic Inches
Valves per Cyline			opdoo			170		
			Poor					RPM
Evhaust CO /s		. IVIIU	near		rive: Fv	VD RWD X	. 4WD-F1	4WD-P1
Exhaust ECS (e.	g., Mri, E	GH, IC,	CAC):					
				(Use abbr	eviations per SAE	J1930 MAY91)	
Engine Code	Vehicle	Models	Trans. Type	ETW	DPA	Ignition	ECD	
(also list CA/	(if code		(M5, A4	or	or	1 3	EGR	0-4-1-4
49ST/50ST)	i '	hment)	etc.)	Test Wt.		(ECM/PCM)	1 -	Catalyst
2JEETAA7	Mazda M		·		11211		Part No.	Part No.
MEETAA,	INIAZIA IVI	PV	A4	4000	11.0 *1	Distrubutor:	N/A	JEC4
2JEETAAV				i ,	10.8 *2	JE96 ECU:		
, ,,					11.8 *2	JEC4		
Carrieland								
Certification	Standar	ds (50,0	000 mile/ 100	0,000 mile/	120,000	mile)		
HC (g/mi)			<u>, ,</u>	***			:P195/75R 15 t	
NMOG (g/mi) Non-methane H	IC (+(-))	0.160	, 0.200			*2	:P215/65R 15 t	ires
CO (g/mi)	ic (g/iii)	4.4		***				
NOx (g/mi)		0.7						
HWFET NOx (g		1.4	, 1.8	<u></u> -				
Evap. (EPA : g.	· ·	***		***				
Evap. (ARB : g/test) Evap. (Abbrev : g/test)			, 2.0 , , 2.5 ,	***				
Running Loss (g/test)		, 0.05	***					
Spit Back (g/ter	st)		, 1.0 ,	***				
Cold CO (g/mi) Idle CO for LDT	1941	12.5	, ,	***				
HCHO (mg/mi)	(70)	18	, 23 ,	***				
CST-HC			, ,	•••				
CST-CO								
NMOG (g/mi) *1 HCHO (mg/mi) *		0,32 36	, 	***				
· ···•		*1: for	50° F					
Revisions:								
1290								
	Issue	date:	June	27, 1997				
	Rev. I	No.					1	
	Date			<u> </u>		-		