(Page 1 of 3) Thate

State of California AIR RESOURCES BOARD

EXECUTIVE ORDER A-10-741 Relating to Certification of New Motor Vehicles

FORD MOTOR COMPANY

Pursuant to the authority vested in the Air Resources Board by the Health and Safety Code, Division 26, Part 5, Chapter 2; and

Pursuant to the authority vested in the undersigned by Health and Safety Code Sections 39515 and 39516 and Executive Order G-45-9;

IT IS ORDERED AND RESOLVED: That 1998 model-year Ford Motor Company exhaust emission control systems are certified as described below for passenger cars:

Emission Standard Category: Transitional Low-Emission Vehicle (TLEV)

Fuel Type: Fuel Flexible (M85 Methanol, Gasoline)

Engine Family: WFMXV03.0AMA Displacement: 3.0 Liters (182 Cubic Inches)

Exhaust Emission Control Systems & Special Features:

Dual Three Way Catalytic Converters (two)
Dual Heated Oxygen Sensors
Exhaust Gas Recirculation
Secondary Air Injection
Sequential Multiport Fuel Injection

Vehicle models, transmissions, engine codes and evaporative emission control families are listed on attachments.

The TLEV certification exhaust emission standards for this engine family in grams per mile are: (The standards in parentheses are for gasoline.)

<u>Miles</u>	Non-Methane Organic Gases	Carbon <u>Monoxide</u>	Nitrogen <u>Oxides</u>	<u>Formaldehyde</u>	Carbon <u>Monoxide (20°F)</u>
50,000	0.125 (0.25)	3.4 (3.4)	0.4 (0.4)	0.015 (0.015)	10.0 (10.0)
100,000	0.156 (0.31)	4.2 (4.2)	0.6 (0.6)	0.018 (0.018)	n/a

Reactivity Adjustment Factor for NMOG Mass Emission (M85 Methanol Fuel): 0.41

Reactivity Adjustment Factor for NMOG Mass Emission (Gasoline): 0.98

The certification exhaust emission values set forth for non-methane organic gases (NMOG) reflect application of the above-mentioned reactivity adjustment factors for 1998 model-year TLEVs. The TLEV certification exhaust emission values for this engine family in grams per mile are: (The values in parentheses are for gasoline.)

Miles	Non-Methane Organic Gases	Carbon <u>Monoxide</u>	Nitrogen Oxides	<u>Formaldehyde</u>	Carbon Monoxide (20°F)
50,000	0.063 (0.09)	1.2 (1.8)	0.1 (0.1)	0.011 (0.001)	3.0 (3.0)
100,000	0.084 (0.10)	1.9 (2.8)	0.2 (0.2)	0.015 (0.001)	n/a

BE IT FURTHER RESOLVED: That the vehicle manufacturer is certifying the listed vehicle models to the aforementioned exhaust emission standards based on its submitted plan to comply with the fleet average NMOG exhaust mass emission requirements as set forth in "California Exhaust Emission Standards and Test Procedures for 1988 and Subsequent Model Passenger Cars, Light-Duty Trucks, and Medium-Duty Vehicles."

BE IT FURTHER RESOLVED: That under the submitted NMOG fleet average compliance plan, if the manufacturer incurs a NMOG debit for the aforementioned model year based on the projected NMOG fleet average exceeding the value required by the above-referenced standards and test procedures, all incurred NMOG debits by the manufacturer shall be equalized as required by the standards and test procedures.

BE IT FURTHER RESOLVED: That the vehicle manufacturer is certifying the listed vehicle models to the running loss and useful life standards applicable to 1995 and subsequent model-year vehicles in the "California Evaporative Emission Standards and Test Procedures for 1978 and Subsequent Model Motor Vehicles," and the listed vehicle models comply with those standards.

BE IT FURTHER RESOLVED: That the listed vehicle models also comply with the Board's "Specifications for Fill Pipes and Openings of Motor Vehicle Fuel Tanks" for the aforementioned model year (Title 13, California Code of Regulations, Section 2235).

BE IT FURTHER RESOLVED: That the listed vehicle models also comply with the Board's high-altitude requirements and highway emission standards, and with the California Inspection and Maintenance emission standards in place at the time of certification, as stipulated in "California Exhaust Emission Standards and Test Procedures for 1988 and Subsequent Model Passenger Cars, Light-Duty Trucks, and Medium-Duty Vehicles."

BE IT FURTHER RESOLVED: That the vehicle manufacturer has demonstrated compliance with the exhaust emission standards at 50 degrees Fahrenheit as stipulated in "California Exhaust Emission Standards and Test Procedures for 1988 and Subsequent Model Passenger Cars, Light-Duty Trucks, and Medium-Duty Vehicles."

BE IT FURTHER RESOLVED: That the listed vehicle models also comply with the "California Motor Vehicle Emission Control and Smog Index Label Specifications" for the aforementioned model year (Title 13, California Code of Regulations, Section 1965).

BE IT FURTHER RESOLVED: That the manufacturer is certifying the listed vehicle models with a partially complying on-board diagnostic system for the aforementioned model year pursuant to Title 13, California Code of Regulations, Section 1968.1(m)(5.1) ("Malfunction and Diagnostic System Requirements--1994 and Subsequent Model-Year Passenger Cars, Light-Duty Trucks, and Medium-Duty Vehicles and Engines").

BE IT FURTHER RESOLVED: That for the listed vehicles, the manufacturer has submitted and the Executive Officer hereby approves the materials to demonstrate certification compliance with the Board's emission control system warranty provisions (Title 13, California Code of Regulations, Section 2035 et seq.).

Vehicles certified under this Executive Order must conform to all applicable California emission regulations.

The Bureau of Automotive Repair will be notified by copy of this order and attachment.

Executed at El Monte, California this $\frac{16^{44}}{6}$ day of September 1997.

R. B Summerfield, Chief

Mobile Source Operations Division

E.O.# A-10-741		**	
	+ 11	#	A-10-741

1998 MODEL-YEAR AIR RESOURCES BOARD SUPPLEMENTAL DATA SHEET PASSENGER CARS, LIGHT-DUTY TRUCKS AND MEDIUM-DUTY VEHICLES

Page__1_

All Engine Codes in Engine Fa Exh Std: CA Tier-1 TLEV Veh Class(es): PCX LDT1_ Single Cert Std for Multi-Cla Fuel Type(s): Dedicated	miliy: CA X LEV LDT2 ss Eng Far Flex-Fuel	A <u>X</u> 49SULEV MDVI m:_ <u>N/A</u> (sp _XDual-	50S /S lMD becify: -Fuel	AB965, SULEV DV2 MDV3_ N/A, LDT1, M Bi-Fuel	ORVR: YE US EPA MDV4 MDV1, MDV2, Gasoline_X	S NO_X Tier-1 MDV5 MDV3, MDV4) _ Diesel
CNG LNG Emiss Test Fuel(s): Indo						
				86.113-90		
Service Accum: Std AMA						
Evaporative Test Procedure:					· · · · · · · · · · · · · · · · · · ·	
NMOG Test Procedure: N/A					SHEDP	t Source <u>X</u>
Engine Configuration: V-6						
Valves per Cylinder: 2						
Engine: Front <u>X</u> Mid						4WD-PT
Exhaust ECS (e.g., MFI, EGR,	TC, CAC):	2TW0	(2), 2 l	HO2S, EGR, AIF viations per S	R, SFI	N031
Engine Code Vehicle Models (also list (if coded see A/49ST/50ST attachment)	Trans. (M5, A4 etc.)	or	DPA or RLHP	Ignition (ECM/PCM) Part No.	EGR System Part No.	Catalytic Converter Part No.
810GROOA TAURUS SEDAN	L4	3750	7.4	F8DF-LA	F7DE-BA	F6DC-DE F7DC-KC
(Methanol FFV)						1,50 110
				_		
				_		
				-		
				_		
				_		

Date Issued: 9-11-97 Revisions: