State of California AIR RESOURCES BOARD

EXECUTIVE ORDER A-10-742 Relating to Certification of New Motor Vehicles

FORD MOTOR COMPANY

Pursuant to the authority vested in the Air Resources Board by the Health and Safety Code, Division 26, Part 5, Chapter 2; and

Pursuant to the authority vested in the undersigned by Health and Safety Code Sections 39515 and 39516 and Executive Order G-45-9;

IT IS ORDERED AND RESOLVED: That 1998 model-year Ford Motor Company exhaust emission control systems are certified as described below for passenger cars:

Fuel Type: Fuel Flexible (E85 Ethanol, Gasoline)

Engine Family: WFMXV03.0AEA <u>Displacement</u>: 3.0 Liters (182 Cubic Inches)

Exhaust Emission Control Systems & Special Features:

Dual Three Way Catalytic Converters Dual Heated Oxygen Sensors Exhaust Gas Recirculation Sequential Multiport Fuel Injection

Vehicle models, transmissions, engine codes and evaporative emission control families are listed on attachments.

The certification exhaust emission standards for this engine family in grams per mile are:

Miles	Non-Methane	Carbon	Nitrogen	Carbon	
	<u>Hydrocarbons</u>	<u>Monoxide</u>	Oxides	<u>Monoxide (20°F)</u>	
50,000	0.25	3.4	- 0.4	10.0	
100,000	0.31	4.2	0.6	n/a	

The certification exhaust emission values for this engine family in grams per mile are: (The values in parentheses are for gasoline.)

Miles	Non-Methane	Carbon	Nitrogen	Carbon	
	<u>Hydrocarbons</u>	<u>Monoxide</u>		<u>Monoxide (20°F)</u>	
50,000	0.10 (0.14)	1.1 (1.4)	$0.1 (0.1) \\ 0.1 (0.1)$	4.5 (4.5)	
100,000	0.10 (0.18)	1.1 (1.8)		n/a	

BE IT FURTHER RESOLVED: That the vehicle manufacturer is certifying the listed vehicle models to the aforementioned exhaust emission standards based on its submitted plan to comply with the fleet average non-methane organic gases (NMOG) exhaust mass emission requirements as set forth in "California Exhaust Emission Standards and Test Procedures for 1988 and Subsequent Model Passenger Cars, Light-Duty Trucks, and Medium-Duty Vehicles." BE IT FURTHER RESOLVED: That under the submitted NMOG fleet average compliance plan, if the manufacturer incurs a NMOG debit for the aforementioned model year based on the projected NMOG fleet average exceeding the value required by the above-referenced standards and test procedures, all incurred NMOG debits by the manufacturer shall be equalized as required by the standards and test procedures.

BE IT FURTHER RESOLVED: That the vehicle manufacturer is certifying the listed vehicle models to the running loss and useful life standards applicable to 1995 and subsequent model-year vehicles in the "California Evaporative Emission Standards and Test Procedures for 1978 and Subsequent Model Motor Vehicles," and the listed vehicle models comply with those standards.

BE IT FURTHER RESOLVED: That the listed vehicle models also comply with the Board's "Specifications for Fill Pipes and Openings of Motor Vehicle Fuel Tanks" for the aforementioned model year (Title 13, California Code of Regulations, Section 2235).

BE IT FURTHER RESOLVED: That the listed vehicle models also comply with the Board's high-altitude requirements and highway emission standards, and with the California Inspection and Maintenance emission standards in place at the time of certification, as stipulated in "California Exhaust Emission Standards and Test Procedures for 1988 and Subsequent Model Passenger Cars, Light-Duty Trucks, and Medium-Duty Vehicles."

BE IT FURTHER RESOLVED: That the listed vehicle models also comply with the "California Motor Vehicle Emission Control and Smog Index Label Specifications" for the aforementioned model year (Title 13, California Code of Regulations, Section 1965).

BE IT FURTHER RESOLVED: That the manufacturer is certifying the listed vehicle models with a partially complying on-board diagnostic system for the aforementioned model year pursuant to Title 13, California Code of Regulations, Section 1968.1(m)(5.1) ("Malfunction and Diagnostic System Requirements--1994 and Subsequent Model-Year Passenger Cars, Light-Duty Trucks, and Medium-Duty Vehicles and Engines").

BE IT FURTHER RESOLVED: That for the listed vehicles, the manufacturer has submitted and the Executive Officer hereby approves the materials to demonstrate certification compliance with the Board's emission control system warranty provisions (Title 13, California Code of Regulations, Section 2035 et seq.).

Vehicles certified under this Executive Order must conform to all applicable California emission regulations,

The Bureau of Automotive Repair will be notified by copy of this order and attachment.

Executed at El Monte, California this _____ day of September 1997.

mup U

R. B. Summerfield, Chief Mobile Source Operations Division

E.O.# <u>A-10-742</u>

<u>1998</u> MODEL-YEAR AIR RESOURCES BOARD SUPPLEMENTAL DATA SHEET Page <u>1</u> PASSENGER CARS, LIGHT-DUTY TRUCKS AND MEDIUM-DUTY VEHICLES

TODD NOTOD COMPANY EVE Eng Fame WEMYVO3 OAFA Evan Fame WEMYF0230F0F
anufacturer: FORD MOTOR COMPANY Exh Eng Fam: WFMXV03.0AEA Evap Fam: WFMXE0230F0E
All Engine Codes in Engine Familiy: CA 49S 50S_X_ AB965, ORVR: YES NO_X_
Exh Std: CA Tier-1 X TLEV LEV ULEV SULEV US EPA Tier-1 X
Veh Class(es): PC X LDT1LDT2MDV1MDV2MDV3MDV4MDV5
Single Cert Std for Multi-Class Eng Fam: <u>N/A</u> (specify: N/A, LDT1, MDV1, MDV2, MDV3, MDV4)
Fuel Type(s): DedicatedFlex-Fuel_XDual-FuelBi-FuelGasoline_XDiesel
CNGLNGLPGOther (specify) <u>E85</u>
Fmiss Test Fuel(s): Indo X CBG CNGLPGM85Other (specify) <u>E85</u>
Diesel: 13 CCR 2282 40 CFR 86.113-90 40 CFR 86.113-94
Evaporative Emission Test Procedure: California federal_ <u>X_</u>
Service Accum: Std AMA Mod AMA X Mfr ADP Other (specify)
NMOG Test Procedure: N/A X Std Equiv R/L Test Proc: SHED Pt Source_X
Engine Configuration: <u>V-6</u> Displacement: <u>3.0 / Liters 182 / Cubic Inches</u>
Valves per Cylinder: _ 2 Rated HP: <u>145 @ 5000 RPM</u> (GAS), <u>150 @ 5200 RPM</u> (ETHANOL)
Valves per cylinder: <u>2</u> Rated III. <u>145 c 5000</u> R.H. (arto), <u>et al</u> 4WD-PT
Engine: Front_X_MidRearDrive: FWD_X_RWD4WD-FT4WD-PT
Exhaust ECS (e.g., MFI, EGR, TC, CAC): <u>2TWC, 2HO2S, EGR, SFI</u> (use abbreviations per SAE J1930 JUN93)
Engine Code Vehicle Models Trans. ETW DPA Ignition EGR Catalytic

Engine Code (also list A/49ST/50ST	Vehicle Models (if coded see attachment)	Trans. (M5, A4 etc.)	EIW or Test Wt.	DPA or RLHP	(ECM/PCM) Part No.	System Part No.	Converter Part No.
810CR00A	TAURUS SEDAN	L4	3750	7.4	F8DF-KA	F7DE-BA	F7DC-RC
	(Ethanol FFV)						
					-		
·							

ate Issued: 9/11/97 Revisions:

E.O.# A-10-7 12

1998 MODEL YEAR AIR RESOURCES BOARD SUPPLEMENTAL DATA SHEET Page 1 PASSENGER CARS, LIGHT-DUTY AND MEDIUM-DUTY TRUCKS

Mfgr. FORD MOTOR COMPANY Exh Eng Fam: WFMXV03.0AEA Evap Fam: WFMXER0230F0E
All Engine Codes in Engine Family: CA 49S 50S X AB965 ORVR: Yes No X Exh Std: CA Tier-1_X , TLEV, LEV , ULEV_ , SULEV , EPA TIER-1_X
Veh Class(es): PC_X_LDT1LDT2MDV1MDV2MDV3MDV4MDV5
Single Cert Std for Multi-Class Eng Fam: <u>N/A</u> (specify: N/A, LDT1, MDV1, MDV2, MDV3, MDV4)
Fuel Type(s):DedicatedFlex Fuel XDual-FuelBi-FuelGasoline XDieselM85CNGLPGOther (specify)E85Exh Emiss Test Fuel(s):Indo XCBGCNGLPGM85Other (specify)E85Diesel:13CCR2282or40CFR86.113-90or-94
Evaporative Emission Test Procedure: California Federal_X
Service Accumulation: Std AMA Mod AMA_XMfr. ADP Other (Specify) NMOG Test Procedure: N/A_X_ Std Equiv R/L Test Procedure: SHED Pt SourceX
Engine Configuration:V-6Displacement:3.0L (182)Liters (Cubic Inches)Valves/Cyl:2Rated HP:145 @ 4250 (E-0);155 @ 5000 (E-85)RPMEngine:Front XMidRearDrive:FWD XRWD4WD-FT4WD-PT
Exhaust Control System and Special Features: 2TWC(2),HO2S(2),EGR,SFI (Use abbreviations per SAE J1930 JUN93)
Engine Code Vehicle Models Trans. Type ETW DPA Ignition EGR Catalytic (also list (if coded see A4-Automatic or or (ECM/PCM) System
Converter CA/49ST/50ST attachment) M5-Manual Test Wt RLHP Part No. Part No. Part No.
810CR00A TAURUS SEDAN L4 3750 7.4 F8DF-KA F7DE-BA F7DC-RC

BIOCRO5A

τ.

(Ethanol FFV)

ENGINE FAMILY:WFMXV03.0AEA ISSUED:7/30/97 REVISED:9/15/97

20.09.17.02 - 1