(Page 1 of 2)

Dali

State of California AIR RESOURCES BOARD

EXECUTIVE ORDER A-61-40 Relating to Certification of New Motor Vehicles

WINNEBAGO INDUSTRIES, INC.

Pursuant to the authority vested in the Air Resources Board by the Health and Safety Code, Division 26, Part 5, Chapter 2; and

Pursuant to the authority vested in the undersigned by Health and Safety Code Sections 39515 and 39516 and Executive Order G-45-9;

IT IS ORDERED AND RESOLVED: That 1998 model-year Winnebago Industries, Inc. exhaust emission control systems are certified as described below for medium-duty vehicles:

Fuel Type: Gasoline

Engine Family: WWBXT02.8225 <u>Displacement</u>: 2.8 Liters (170 Cubic Inches)

Exhaust Emission Control Systems and Special Features:

Sequential Multiport Fuel Injection Three Way Catalytic Converter Heated Oxygen Sensors (two) Exhaust Gas Recirculation Secondary Air Injection

Vehicle models, transmissions, engine codes and evaporative emission control families are listed on attachments.

The certification exhaust emission standards for this engine family in grams per mile are:

Test Weight	Miles	Non-Methane	Carbon	Nitrogen	Carbon
(lbs.)		<u>Hydrocarbons</u>	<u>Monoxide</u>	Oxides	<u>Monoxide (20⁰F)</u>
5751-8500	50,000	0.39	5.0	1.1	12.5
	120,000	0.56	7.3	1.53	n/a

The certification exhaust emission values for this engine family in grams per mile are:

Test Weight	_Miles_	Non-Methane	Carbon	Nitrogen	Carbon
(lbs.)		<u>Hydrocarbons</u>	<u>Monoxide</u>	Oxides	<u>Monoxide (20°F)</u>
5751-8500	50,000	0.22	1.4	0.4	9.1
	120,000	0.30	2.1	0.56	n/a

BE IT FURTHER RESOLVED: That the manufacturer shall not be subject to the phase-in requirement specified in Title 13, California Code of Regulations, Section 1960.1(h)(2) Endnotes (10)(d) and (16) applicable to small-volume manufacturers of medium-duty vehicles.

BE IT FURTHER RESOLVED: That the listed vehicle models also comply with the Board's high-altitude requirements and highway emission standards, and with the California Inspection and Maintenance emission standards in place at the time of certification, as stipulated in "California Exhaust Emission Standards and Test Procedures for 1988 and Subsequent Model Passenger Cars, Light-Duty Trucks, and Medium-Duty Vehicles."

BE IT FURTHER RESOLVED: That the listed vehicle models also comply with the Board's "Specifications for Fill Pipes and Openings of Motor Vehicle Fuel Tanks" for the aforementioned model year (Title 13, California Code of Regulations, Section 2235).

BE IT FURTHER RESOLVED: That the listed vehicle models also comply with the "California Motor Vehicle Emission Control and Smog Index Label Specifications" for the aforementioned model year (Title 13, California Code of Regulations, Section 1965).

BE IT FURTHER RESOLVED: That the vehicle manufacturer is certifying the listed vehicle models to the running loss and useful life standards applicable to 1995 and subsequent model-year vehicles in the "California Evaporative Emission Standards and Test Procedures for 1978 and Subsequent Model Motor Vehicles," and the listed vehicle models comply with those standards.

BE IT FURTHER RESOLVED: That the listed vehicle models also comply with the "Malfunction and Diagnostic System Requirements--1994 and Subsequent Model- Year Passenger Cars, Light-Duty Trucks, and Medium-Duty Vehicles and Engines" (Title 13, California Code of Regulations, Section 1968.1) for the aforementioned model year.

BE IT FURTHER RESOLVED: That for the listed vehicles, the manufacturer has submitted and the Executive Officer hereby approves the materials to demonstrate certification compliance with the Board's emission control system warranty provisions (Title 13, California Code of Regulations, Section 2035 et seq.).

Vehicles certified under this Executive Order must conform to all applicable California emission regulations.

The Bureau of Automotive Repair will be notified by copy of this order and attachment.

Executed at El Monte, California this 13th

001/ 1.

R. B. Summerfield, Chief

Mobile Source Operations Division

199 8 MODEL-YEAR AIR RESOURCES BOARD SUPPLEMENTAL DATA SHEET PASSENGER CARS, LIGHT-DUTY TRUCKS AND MEDIUM-DUTY VEHICLES

Page 2

nufacturer	: Winnebago Ind.	, Inc.	Exh Eng F	am: WWB	XT02.8225	Evap Fam: www.	Œ0105233
All Eng Code	es in Eng Fam: Ca	A	49S	50 S	x AB965		
Exh Std: CA	Tier-l <u>X</u> T	LEV	LEV	ULE	V ZEV	; US FP	A Tier-1 X
Evap Std: 5	OK Useful L	ife with 1	R/L <u>x</u>	In-Use	Exh Std: Full	In Use x A	It In Use
ven Class(es): PC LDT1_	LDT:	2 MD\	/1	MDV2MDV	3 X MDV4	MDV5
Single Cert	Std for Multi-Cla	ass Eng Fa	am: <u>N/A</u>	_(speci	fy: N/A, LDT1	, MDV1, MDV2.	MDV3 MDV41
Fuel Type(s)	: Dedicated 1	Flex-Fue	l Dual	-Fuel_	Bi-Fuel	Gasoline X	Diesel
	CNGLNG	_ LPG	M85	Other -	(specify)		_
Emiss Test F	uel(s): Indo	68G <u>K</u>	CNG	.PG	M85 Othe	r (specify)	
	Diesel:	13 CCR 2	2282	40 (CFR 86.113-90	40 CFR 8	36.113-94
Service Accu	m: Std AMA <u>x</u>	Mod AMA	Mfr	ADP	Other (spec	ify)	
NMOG Test Pr	ocedure: N/A <u>X</u>	Std	_ Equiv_		R/L Test Proc	: SHED N. A. F	Pt Source X
Hybrid: Typ	e A B C,	APU Cyc	le (e.g.,	Otto,	Diesel, Turbin	ne): N/A	
Engine Confi	guration: <u>V6</u>	Displace	ment: 2.	8 /	Liters 17	0 / 0	Lubic Inches
Valves per C	ylinder: <u>2</u>		Rate	d HP:_	140	0 4,500	RPM
Valves per Cylinder: 2 Rated HP: 140 @ 4,500 RPM Engine: Front X Mid Rear Drive: FWD X RWD 4WD-FT 4WD-PT							
Exhaust ECS	(e.g., MFI, EGR,	TC, CAC):	SFI/AI	R/EGR/T	wc/ho2S(2)/obd	II	···
			(u	se abbr	eviations per	SAE J1930 SEP	91)
gine Code (also list	Vehicle Models	Trans.	ETW	DPA	Ignition	EGR	Catalytic
CA/49ST/50ST	(if coded see attachment)	(M5, A4 etc.)	or Test Wt	Or	(ECM/PCM)	System	Conventor
A.F.C	·	1	ľ	ŀ	Part No.	1	
AES 50ST	RIALTA	L4	6,500	16.7	021 906 2595		023 131 701s
		1				or 021 131 501G	
						valve	
						054 906 267	
				i	į	}	
		i					
	į	ļ		į	i		
				j	;		
Date Issued:	· <u></u>						

Revisions: