State of California AIR RESOURCES BOARD

EXECUTIVE ORDER A-23-231 Relating to Certification of New Motor Vehicles

HONDA MOTOR CO., LTD.

Pursuant to the authority vested in the Air Resources Board by the Health and Safety Code, Division 26, Part 5, Chapter 2; and

Pursuant to the authority vested in the undersigned by Health and Safety Code Sections 39515 and 39516 and Executive Order G-45-9;

IT IS ORDERED AND RESOLVED: That 1998 model-year Honda Motor Co., Ltd. exhaust emission control systems are certified as described below for passenger cars:

Fuel Type: Gasoline

the state of

Engine Family: WHNXV02.2SAl Displacement: 2.2 Liters (132 Cubic Inches)

Exhaust Emission Control Systems & Special Features:

Three Way Catalytic Converter Heated Oxygen Sensors (two) Exhaust Gas Recirculation Sequential Multiport Fuel Injection

Vehicle models, transmissions, engine codes and evaporative emission control families are listed on attachments.

The certification exhaust emission standards for this engine family in grams per mile are:

Miles	Non-Methane	Carbon	Nitrogen	Carbon	
	<u>Hydrocarbons</u>	<u>Monoxide</u>	<u>Oxides</u>	<u>Monoxide (20°F)</u>	
50,000	0.25	3.4	0. 4	10.0	
100,000	0.31	4.2	0.6	n/a	

The certification exhaust emission values for this engine family in grams per mile are:

Miles	Non-Methane	Carbon	Nitrogen	Carbon	
	<u>Hydrocarbons</u>	<u>Monoxide</u>	Oxides	<u>Monoxide (20°F)</u>	
50,000	0.16	1.4	0.2	5.3	
100,000	0.20	1.6	0.3	n/a	

BE IT FURTHER RESOLVED: That the vehicle manufacturer is certifying the listed vehicle models to the aforementioned exhaust emission standards based on its submitted plan to comply with the fleet average non-methane organic gases (NMOG) exhaust mass emission requirements as set forth in "California Exhaust Emission Standards and Test Procedures for 1988 and Subsequent Model Passenger Cars, Light-Duty Trucks, and Medium-Duty Vehicles."

BE IT FURTHER RESOLVED: That under the submitted NMOG fleet average compliance plan, if the manufacturer incurs a NMOG debit for the aforementioned model year based on the projected NMOG fleet average exceeding the value required by the above-referenced standards and test procedures, all incurred NMOG debits by the manufacturer shall be equalized as required by the standards and test procedures.

BE IT FURTHER RESOLVED: That the vehicle manufacturer is certifying the listed vehicle models to the running loss and useful life standards applicable to 1995 and subsequent model-year vehicles in the "California Evaporative Emission Standards and Test Procedures for 1978 and Subsequent Model Motor Vehicles," and the listed vehicle models comply with those standards.

BE IT FURTHER RESOLVED: That the listed vehicle models also comply with the Board's "Specifications for Fill Pipes and Openings of Motor Vehicle Fuel Tanks" for the aforementioned model year (Title 13, California Code of Regulations, Section 2235).

BE IT FURTHER RESOLVED: That the listed vehicle models also comply with the Board's high-altitude requirements and highway emission standards, and with the California Inspection and Maintenance emission standards in place at the time of certification, as stipulated in "California Exhaust Emission Standards and Test Procedures for 1988 and Subsequent Model Passenger Cars, Light-Duty Trucks, and Medium-Duty Vehicles."

BE IT FURTHER RESOLVED: That the listed vehicle models also comply with the "California Motor Vehicle Emission Control and Smog Index Label Specifications" for the aforementioned model year (Title 13, California Code of Regulations, Section 1965).

BE IT FURTHER RESOLVED: That the listed vehicle models also comply with the "Malfunction and Diagnostic System Requirements--1994 and Subsequent Model-Year Passenger Cars, Light-Duty Trucks, and Medium-Duty Vehicles and Engines" (Title 13, California Code of Regulations, Section 1968.1) for the aforementioned model year.

BE IT FURTHER RESOLVED: That for the listed vehicles, the manufacturer has submitted and the Executive Officer hereby approves the materials to demonstrate certification compliance with the Board's emission control system warranty provisions (Title 13, California Code of Regulations, Section 2035 et seq.).

Vehicles certified under this Executive Order must conform to all applicable California emission regulations.

The Bureau of Automotive Repair will be notified by copy of this order and attachment.

Executed at El Monte, California this ______ day of October 1997.

AR. B. Summerfield, Chief Mobile Source Operations Division

Replace Surrout

1998 MODEL-YEAR AIR RESOURCES BOARD SUPPLEMENTAL DATA SHEET PASSENGER CARS, LIGHT-DUTY TRUCKS AND MEDIUM-DUTY VEHICLES

E.O. # A-23-23 Page 1 of 1

Manufacturer: HONDA Exh Engine Family: WHNXV02.2SA1 EVAP Family: WHNXE0090AAC All Engine Codes in Engine Family: CA 49S 50S X AB965 , ORVR: YES NO X Exh std: CA Tier-1 X TLEV LEV ULEV SULEV , US EPA Tier-1 Veh Class(es): PC X LDT1 LDT2 MDV1 MDV2 MDV3 MDV4 MDV5 Single Cert Std for Multi-Class Eng Fam: N/A (specify: N/A, LDT1, MDV1, MDV2, MDV3, MDV4) Fuel Type(s): Dedicated X Flex-Fuel Dual-Fuel Bi-Fuel Gasoline X Diesel CNG LNG LPG M85 other (specify) Exh Emiss Test Fuel(s): Indo X CBG CNG LPG M85 other (specify) Diesel: 13 CCR 2282 40 CFR 86.113-90 40 CFR 86.113-94
Evaporative Emission Test Procedure: California Federal X Service Accum: Std AMA Mod AMA X Mfr ADP Other (specify) NMOG Test Procedure: N/A X Std AMA Test
EMILY RIL TOCCULE, N/AA SLU EMILY RIL TOCC CUED DE C
Engine Configuration: L-4 Displacement: 2.2/132 Liters/Cubic Inches Valves per Cylinder: 4 Rated HP: 195 @ 7000 RPM (M5), 190 @ 6600 RPM (L4)
Angine, rione A mid Rear Drive, FWD Y DWD Author Box
TAMAGUE BED (8.9., ME), EGR, TC, CAC): TWC/HO2S(2)/EGR/SFI
(use abbreviations per SAE J1930 JUN93)

Engine Code (also list CA/49ST/50ST)	Vehicle Models (if coded see attachment)	Trans. (M5, A4 etc.)	ETW or Test Wt.	DPA or RLHP	Ignition (ECM/PCM) Part No.	EGR System Part No.	Catalytic Converter Part No.
WSA1/1 (50ST)	Prelude VTEC	М5	3375	7.7 (BS		EGR Valve:	CX
WSA3/1 (50ST)	Prelude VTEC	1.4	3375	7.7 (BS			
WSB1/1 (50ST)	Prelude VTEC-R	м5	3375	7.9 (BS			