#### State of California AIR RESOURCES BOARD

## EXECUTIVE ORDER A-86-218 Relating to Certification of New Motor Vehicles

#### MITSUBISHI MOTORS CORPORATION

Pursuant to the authority vested in the Air Resources Board by the Health and Safety Code, Division 26, Part 5, Chapter 2; and

Pursuant to the authority vested in the undersigned by Health and Safety Code Sections 39515 and 39516 and Executive Order G-45-9;

IT IS ORDERED AND RESOLVED: That 1998 model-year Mitsubishi Motors Corporation exhaust emission control systems are certified as described below for passenger cars:

Fuel Type: Gasoline

Engine Family: WMTXV03.0GBP Displacement: 3.0 Liters (181.3 Cubic Inches)

#### Exhaust Emission Control Systems and Special Features:

Three Way Catalytic Converter
Dual Heated Oxygen Sensors (two)
Sequential Multiport Fuel Injection
Dual Warm Up Three Way Catalytic Converters
Dual Turbochargers
Dual Charge Air Coolers
Exhaust Gas Recirculation

Vehicle models, transmissions, engine codes and evaporative emission control families are listed on attachments.

The certification exhaust emission standards for this engine family in grams per mile are:

Miles	Non-Methane	Carbon	Nitrogen	Carbon
	<u>Hydrocarbons</u>	<u>Monoxide</u>	Oxides	<u>Monoxide (20<sup>0</sup>F)</u>
50,000	0.25	3.4	0.4	10.0
100,000	0.31	4.2	0.6	n/a

The certification exhaust emission values for this engine family in grams per mile are:

_Miles_	Non-Methane	Carbon	Nitrogen	Carbon
	<u>Hydrocarbons</u>	<u>Monoxide</u>	<u>Oxides</u>	Monoxide (20°F)
50,000 100,000	0.14 0.16	1.7	0.1 0.2	, 7.6 n/a

BE IT FURTHER RESOLVED: That the listed vehicle models also comply with the Board's "Specifications for Fill Pipes and Openings of Motor Vehicle Fuel Tanks" for the aforementioned model year (Title 13, California Code of Regulations, Section 2235).

BE IT FURTHER RESOLVED: That the vehicle manufacturer is certifying the listed vehicle models to the aforementioned exhaust emission standards based on its submitted plan to comply with the fleet average non-methane organic gas (NMOG) exhaust mass emission requirements as set forth in "California Exhaust Emission Standards and Test Procedures for 1988 and Subsequent Model Passenger Cars, Light-Duty Trucks, and Medium-Duty Vehicles."

BE IT FURTHER RESOLVED: That under the submitted NMOG fleet average compliance plan, if the manufacturer incurs a NMOG debit for the aforementioned model year based on the projected NMOG fleet average exceeding the value required by the above-referenced standards and test procedures, all incurred NMOG debits by the manufacturer shall be equalized as required by the standards and test procedures.

BE IT FURTHER RESOLVED: That the listed vehicle models also comply with the "California Motor Vehicle Emission Control and Smog Index Label Specifications" for the aforementioned model year (Title 13, California Code of Regulations, Section 1965).

BE IT FURTHER RESOLVED: That the vehicle manufacturer is certifying the listed vehicle models to the running loss and useful life standards applicable to 1995 and subsequent model-year vehicles in the "California Evaporative Emission Standards and Test Procedures for 1978 and Subsequent Model Motor Vehicles," and the listed vehicle models comply with those standards.

BE IT FURTHER RESOLVED: That the listed vehicle models also comply with the Board's high-altitude requirements and highway emission standards, and with the California Inspection and Maintenance emission standards in place at the time of certification, as stipulated in "California Exhaust Emission Standards and Test Procedures for 1988 and Subsequent Model Passenger Cars, Light-Duty Trucks, and Medium-Duty Vehicles."

BE IT FURTHER RESOLVED: That the listed vehicle models also comply with the "Malfunction and Diagnostic System Requirements--1994 and Subsequent Model-Year Passenger Cars, Light-Duty Trucks, and Medium-Duty Vehicles and Engines" (Title 13, California Code of Regulations, Section 1968.1) for the aforementioned model year.

BE IT FURTHER RESOLVED: That for the listed vehicles, the manufacturer has submitted and the Executive Officer hereby approves the materials to demonstrate certification compliance with the Board's emission control system warranty provisions (Title 13, California Code of Regulations, Section 2035 et seq.).

Vehicles certified under this Executive Order must conform to all applicable California emission regulations.

The Bureau of Automotive Repair will be notified by copy of this order and attachment.

Executed at El Monte, California this 4 day of August 1997.

Mobile Source Operations Division

### 17.16.02

E.O.# A-86-218

# 1998 AIR RESOURCES BOARD SUPPLEMENTAL DATA SHEET PASSENGER CARS, LIGHT-DUTY TRUCKS

Manufacturer : Mitsubishi Motors Corporation Exh Engine Family : WMTXV03.0GBP(3.0B-T) Evap Engine Family: WMTXE0200A1A
All Eng Codes in Eng Fam: CA 49S 50S X  ORVR: Yes No_X  Exh Std: CA Tier-1_X TLEV LEV ULEV SULEV; EPA Tier-0_Tier-1_X  In-Use Exh Std: Full in Use X Alt In Use
\$ Veh Class(es): PC_X LDT1_ LDT2_ Single Cert Std for Multi-Class Eng Fam: N/A (specify: N/A, LDT1) Fuel Type(s): Dedicated X Flex-Fuel_ Dual-Fuel_ Bi-Fuel_ Gasoline X  Diesel_ CNG_ LNG_ LPG_ M85_ Other (specify)  Emis Test Fuel: Indo_ Ph2_X CNG_ LPG_ M85_ Other (specify)  Diesel: 13 CCR 2282_ or 40 CFR 86.113-90_ or -94_  Evaporative Emission Test Procedure: California_ Federal X
Service Accum : Std AMA Mod AMA X Mfr ADP Other (specify)  NMOG Test Proc : N/A X Std Equiv  R/L Test Proc : SHED X Pt Source
Engine Configuration: V6 Displacement: 3.0 Liters/ 181.3 Cubric Inches  Valves per Cylinder: 4 Rated HP: 320 @ 6000 RPM  Engine : Front X Mid Rear  Drive : FWD RWD 4WD-FT X 4WD-PT  Exhaust ECS (eg., EGR, MFI, TC, CAC): EGR+2HO2S(2)+TWC+2WUTWC+(SFI+2TC+2CAC)  (use abbreviations per SAE J1930 SEP91)

## E.O.#\_ A-86-218

#### 1998 AIR RESOURCES BOARD SUPPLEMENTAL DATA SHEET PASSENGER CARS, LIGHT-DUTY TRUCKS

Manufacturer

: Mitsubishi Motors Corporation

Exh Engine Family : WMTXV03.0GBP(3.0B-T)

Evap Engine Family: WMTXE0200A1A

Engine Code (also list CAL/FED/BOTH)	Vehicle Models (if coded see attachment)	Trans. type *1	ETW	DPA or RLHP	Ignition (ECM/PCM) Part No.	EGR System Part No.	Catalytic Converter Part No.
ABM-F (BOTH)	Mitsubishi 3000GT	-Мб	4000	8.6	Distributor: N/A	Valve: MD198257 (K5T58886)	Front: (Right)
ABM-CF (BOTH)	Mitsubishi 3000GT Spyder	45	4500 8.5	l	Solenoid: MR187000 (K5T49683)	(C8) (Left)	
							(N1) or MR224996 (NI)*2

\*1: M-Manual transmission

L-Automatic transmisson with lock-up

\*2: With Ni

N/A: Not Applicable