

*File*

State of California  
AIR RESOURCES BOARD

EXECUTIVE ORDER A-8-110  
Relating to Certification of New Motor Vehicles

BAYERISCHE MOTOREN WERKE AG

Pursuant to the authority vested in the Air Resources Board by the Health and Safety Code, Division 26, Part 5, Chapter 2; and

Pursuant to the authority vested in the undersigned by Health and Safety Code Sections 39515 and 39516 and Executive Order G-45-9;

IT IS ORDERED AND RESOLVED: That 1999 model-year Bayerische Motoren Werke AG exhaust emission control systems are certified as described below for passenger cars:

Emission Standard Category: Low-Emission Vehicle (LEV)

Fuel Type: Gasoline

Engine Family: XBMXV02.8LEV Displacement: 2.8 Liters (170.4 Cubic Inches)  
2.5 Liters (152.2 Cubic Inches)

Exhaust Emission Control Systems and Special Features:

- Dual Three Way Catalytic Converters
- Dual Heated Oxygen Sensors (two)
- Sequential Multiport Fuel Injection
- Secondary Air Injection

Vehicle models, transmissions, engine codes and evaporative emission control families are listed on attachments.

The LEV certification exhaust emission standards for this engine family in grams per mile are:

<u>Miles</u>	<u>Non-Methane Organic Gas</u>	<u>Carbon Monoxide</u>	<u>Nitrogen Oxides</u>	<u>Formaldehyde</u>	<u>Carbon Monoxide (20°F)</u>
50,000	0.075	3.4	0.2	0.015	10.0
100,000	0.090	4.2	0.3	0.018	n/a

Reactivity Adjustment Factor (RAF) for NMOG Mass Emission: 0.94

The certification exhaust emission values set forth for non-methane organic gas (NMOG) reflect application of a 0.94 RAF for 1999 model-year LEVs. The LEV certification exhaust emission values for this engine family in grams per mile are:

<u>Miles</u>	<u>Non-Methane Organic Gas</u>	<u>Carbon Monoxide</u>	<u>Nitrogen Oxides</u>	<u>Formaldehyde</u>	<u>Carbon Monoxide (20°F)</u>
50,000	0.052	0.6	0.1	0.0002	2.8
100,000	0.054	0.6	0.1	0.0002	n/a

BE IT FURTHER RESOLVED: That the vehicle manufacturer is certifying the listed vehicle models to the aforementioned exhaust emission standards based on its submitted plan to comply with the fleet average NMOG exhaust mass emission requirements as set forth in "California Exhaust Emission Standards and Test Procedures for 1988 and Subsequent Model Passenger Cars, Light-Duty Trucks, and Medium-Duty Vehicles."

BE IT FURTHER RESOLVED: That under the submitted NMOG fleet average compliance plan, if the manufacturer incurs a NMOG debit for the aforementioned model year based on the projected NMOG fleet average exceeding the value required by the above-referenced standards and test procedures, all incurred NMOG debits by the manufacturer shall be equalized as required by the standards and test procedures.

BE IT FURTHER RESOLVED: That the vehicle manufacturer is certifying the listed vehicle models to the running loss and useful life standards applicable to 1995 and subsequent model-year vehicles in the "California Evaporative Emission Standards and Test Procedures for 1978 and Subsequent Model Motor Vehicles," and the listed vehicle models comply with those standards.

BE IT FURTHER RESOLVED: That the vehicle manufacturer is certifying the listed vehicle models to the "California Refueling Emission Standards and Test Procedures for 1998 and Subsequent Model Motor Vehicles," Title 13, California Code of Regulations, Section 1978, and the listed vehicle models comply with those standards.

BE IT FURTHER RESOLVED: That the listed vehicle models also comply with the Board's "Specifications for Fill Pipes and Openings of Motor Vehicle Fuel Tanks" for the aforementioned model year (Title 13, California Code of Regulations, Section 2235).

BE IT FURTHER RESOLVED: That the listed vehicle models also comply with the Board's high-altitude requirements and highway emission standards, and with the California Inspection and Maintenance emission standards in place at the time of certification, as stipulated in "California Exhaust Emission Standards and Test Procedures for 1988 and Subsequent Model Passenger Cars, Light-Duty Trucks, and Medium-Duty Vehicles."

BE IT FURTHER RESOLVED: That the listed vehicle models also comply with the "California Motor Vehicle Emission Control and Smog Index Label Specifications" for the aforementioned model year (Title 13, California Code of Regulations, Section 1965).

BE IT FURTHER RESOLVED: That the listed vehicle models also comply with the "Malfunction and Diagnostic System Requirements--1994 and Subsequent Model- Year Passenger Cars, Light-Duty Trucks, and Medium-Duty Vehicles and Engines" (Title 13, California Code of Regulations, Section 1968.1) for the aforementioned model year.

BE IT FURTHER RESOLVED: That for the listed vehicles, the manufacturer has submitted and the Executive Officer hereby approves the materials to demonstrate certification compliance with the Board's emission control system warranty provisions (Title 13, California Code of Regulations, Section 2035 et seq.).

BE IT FURTHER RESOLVED: That the vehicle manufacturer has demonstrated compliance with the exhaust emission standards at 50 degrees Fahrenheit as stipulated in "California Exhaust Emission Standards and Test Procedures for 1988 and Subsequent Model Passenger Cars, Light-Duty Trucks, and Medium-Duty Vehicles."

Vehicles certified under this Executive Order must conform to all applicable California emission regulations.

The Bureau of Automotive Repair will be notified by copy of this order and attachment.

Executed at El Monte, California this 13<sup>th</sup> day of July 1998.



R. B. Summerfield, Chief  
Mobile Source Operations Division

**1999 AIR RESOURCES BOARD SUPPLEMENTAL DATA SHEET**  
**PASSENGER CARS, LIGHT DUTY TRUCKS AND MEDIUM DUTY VEHICLES**

Manufacturer : BMW Exh. Engine Family : XBMXV02.8LEV Evap. Fam: XBMR0136E46  
 All Eng Codes in Eng Fam: CA \_\_\_ 49S \_\_\_ 50S X AB965 \_\_\_ ORVR: YES X NO \_\_\_  
 Exh Std: CA Tier-1 \_\_\_ TLEV \_\_\_ LEV X ULEV \_\_\_ SULEV \_\_\_ ; US EPA Tier-1 X  
 Veh Class: PC X LDT1 \_\_\_ LDT2 \_\_\_ MDV1 \_\_\_ MDV2 \_\_\_ MDV3 \_\_\_ MDV4 \_\_\_ MDV5 \_\_\_  
 Single Cert Std for Multi - Class Eng Fam: N/A  
 Fuel Type (s): Dedicated X Flex-Fuel \_\_\_ Dual Fuel \_\_\_ Bi - Fuel \_\_\_ Gasoline X Diesel \_\_\_  
                   CNG \_\_\_ LNG \_\_\_ LPG \_\_\_ M85 \_\_\_ Other (specify) \_\_\_  
 Emiss Test Fuel (s): Indo \_\_\_ CBG X CNG \_\_\_ LPG \_\_\_ M85 \_\_\_ Other (specify) \_\_\_  
                   Diesel: 13 CCR 2282 \_\_\_ 40 CFR86.113-90 \_\_\_ 40 CFR86.113-94 \_\_\_  
 Evaporative Test Procedure: California \_\_\_ Federal X  
 Service Accum: Std AMA X Mod AMA \_\_\_ Mfr ADP \_\_\_ Other (specify) \_\_\_  
 NMOG Test Procedure: N/A \_\_\_ Std \_\_\_ Equip X R/L Test Proc: SHED X Pt Source \_\_\_  
 Hybrid: Type A \_\_\_ B \_\_\_ C \_\_\_ , APU Cycle (e.g., Otto, Diesel, Turbine) \_\_\_  
 Engine Configuration: inline-6 Displacement: 2.5 Liters 152.2 Cubic Inches  
   2.8 Liters 170.4 Cubic Inches  
 Valves per Cylinder: 4 Rated HP: 168 @ 5 500 RPM  
   190 @ 5 300 RPM  
 Engine: Front X Mid \_\_\_ Rear \_\_\_ Drive: FWD \_\_\_ RWD X 4WD-FT \_\_\_ 4WD-PT \_\_\_  
 Exhaust ECS: 2TWC, 2HO2S(2), SFI, AIR

Engine Code (50 ST)	Vehicle Models	Trans. Type	ETW (lbs.)	DPA or RLHP (hp)	Ignition (ECM/PCM) Part No.	EGR System Part No.	Catalytic Converter Part No.
2.5-LEV	Z3	M5	3 250	7.6	1 429 765	n.a.	1 732 953 left
	323i	M5	3 500	6.9	1 430 391		1 732 955 right
2.5-A-LEV	Z3 A	L4	3 250	7.6	1 438 300		
	323iA	L5	3 500	6.9			
2.8-LEV	Z3	M5	3 250	7.6			
	Z3 Coupe	M5	3 250	7.0			
	328i	M5	3 500	6.9			
	528iT	M5	4 000	7.4			
2.8-A-LEV	Z3 A	L4	3 250	7.6			
	Z3Coupe A	L4	3 375	7.0			
	328i A	L5	3 500	6.9			
	528iAT	L4	4 000	7.4			

**1999 AIR RESOURCES BOARD SUPPLEMENTAL DATA SHEET**  
**PASSENGER CARS, LIGHT DUTY TRUCKS AND MEDIUM DUTY VEHICLES**

Manufacturer : BMW    Exh. Engine Family : XBMXV02.8LEV    Evap. Fam: XBMR0160E39  
 All Eng Codes In Eng Fam: CA \_\_\_ 49S \_\_\_ 50S X AB965 \_\_\_ ORVR: YES X NO \_\_\_  
 Exh Std: CA Tier-1 \_\_\_ TLEV \_\_\_ LEV X ULEV \_\_\_ SULEV \_\_\_ ; US EPA Tier-1 X  
 Veh Class: PC X LDT1 \_\_\_ LDT2 \_\_\_ MDV1 \_\_\_ MDV2 \_\_\_ MDV3 \_\_\_ MDV4 \_\_\_ MDV5 \_\_\_  
 Single Cert Std for Multi - Class Eng Fam: N/A  
 Fuel Type (s): Dedicated X Flex-Fuel \_\_\_ Dual Fuel \_\_\_ Bi - Fuel \_\_\_ Gasoline X Diesel \_\_\_  
                   CNG \_\_\_ LNG \_\_\_ LPG \_\_\_ M85 \_\_\_ Other (specify) \_\_\_  
 Emiss Test Fuel (s): Indo \_\_\_ CBG X CNG \_\_\_ LPG \_\_\_ M85 \_\_\_ Other (specify) \_\_\_  
                   Diesel: 13 CCR 2282 \_\_\_ 40 CFR86.113-90 \_\_\_ 40 CFR86.113-94 \_\_\_  
 Evaporative Test Procedure: California \_\_\_ Federal X  
 Service Accum: Std AMA X Mod AMA \_\_\_ Mfr ADP \_\_\_ Other (specify) \_\_\_  
 NMOG Test Procedure: N/A \_\_\_ Std \_\_\_ Equiv X R/L Test Proc: SHED X Pt Source \_\_\_  
 Hybrid: Type A \_\_\_ B \_\_\_ C \_\_\_ , APU Cycle (e.g., Otto, Diesel, Turbine) \_\_\_  
 Engine Configuration: inline-6 Displacement: 2.8 Liters 170.4 Cubic Inches  
 Valves per Cylinder: 4 Rated HP: 190 @ 5 300 RPM  
 Engine: Front X Mid \_\_\_ Rear \_\_\_ Drive: FWD \_\_\_ RWD X 4WD-FT \_\_\_ 4WD-PT \_\_\_  
 Exhaust ECS: 2TWC, 2HO2S(2), SFI, AIR

Engine Code (50 ST)	Vehicle Models	Trans. Type	ETW (lbs.)	DPA or RLHP (hp)	Ignition (ECM/PCM) Part No.	EGR System Part No.	Catalytic Converter Part No.
2.8-LEV	528i	M5	3 750	7.1	1 429 765	n.a.	1 732 953 left
2.8-A-LEV	528iA	L4	3 875	7.3	1 430 391 1 438 300		1 732 955 right