## State of California AIR RESOURCES BOARD

## EXECUTIVE ORDER A-8-111-B Relating to Certification of New Motor Vehicles

## BAYERISCHE MOTOREN WERKE AG

Pursuant to the authority vested in the Air Resources Board by the Health and Safety Gode, Division 26, Part 5, Chapter 2; and

Pursuant to the authority vested in the undersigned by Health and Safety Code Sections 39515 and 39516 and Executive Order G-45-9;

IT IS ORDERED AND RESOLVED: That 1999 model-year Bayerische Motoren Werke AG exhaust emission control systems are certified as described below for passenger cars:

Emission Standard Category: Transitional Low-Emission Vehicle (TLEV)

Fuel Type: Gasoline

Engine Family: XBMXV02.8M52 Displacement: 3.2 Liters (192.3 Cubic Inches)

Exhaust Emission Control Systems and Special Features:

Dual Three Way Catalytic Converters Dual Heated Oxygen Sensors (two) Sequential Multiport Fuel Injection Secondary Air Injection

Vehicle models, transmissions, engine codes and evaporative emission control families are listed on attachments.

The TLEV certification exhaust emission standards for this engine family in grams per mile are:

Miles	Non-Methane Organic Gas	Carbon <u>Monoxide</u>	Nitrogen Oxides	<u>Formaldehyde</u>	Carbon Monoxide (20°F)
50,000	0.125	3.4	0.4	0.015	10.0
100,000	0.156	4.2	0.6	0.018	n/a

Reactivity Adjustment Factor (RAF) for NMOG Mass Emission: 0.98

The certification exhaust emission values set forth for non-methane organic gas (NMOG) reflect application of a 0.98 RAF for 1999 model-year TLEVs. The TLEV certification exhaust emission values for this engine family in grams per mile are:

<u>Miles</u>	Non-Methane Organic Gas	Carbon <u>Monoxide</u>	Nitrogen Oxides	<u>Formaldehyde</u>	Carbon <u>Monoxide (20°F)</u>
50,000	0.083	1.1	0.2	0.002	2.5
100,000	0.093	1.2	0.2	0.003	n/a

BE IT FURTHER RESOLVED: That the vehicle manufacturer is certifying the listed vehicle models to the aforementioned exhaust emission standards based on its submitted plan to comply with the fleet average NMOG exhaust mass emission requirements as set forth in "California Exhaust Emission Standards and Test Procedures for 1988 and Subsequent Model Passenger Cars, Light-Duty Trucks, and Medium-Duty Vehicles."

BE IT FURTHER RESOLVED: That under the submitted NMOG fleet average compliance plan, if the manufacturer incurs a NMOG debit for the aforementioned model year based on the projected NMOG fleet average exceeding the value required by the above-referenced standards and test procedures, all incurred NMOG debits by the manufacturer shall be equalized as required by the standards and test procedures.

BE IT FURTHER RESOLVED: That the vehicle manufacturer is certifying the listed vehicle models to the running loss and useful life standards applicable to 1995 and subsequent model-year vehicles in the "California Evaporative Emission Standards and Test Procedures for 1978 and Subsequent Model Motor Vehicles," and the listed vehicle models comply with those standards.

BE IT FURTHER RESOLVED: That the vehicle manufacturer is certifying the listed vehicle models to the "California Refueling Emission Standards and Test Procedures for 1998 and Subsequent Model Motor Vehicles," Title 13, California Code of Regulations, Section 1978, and the listed vehicle models comply with those standards.

BE IT FURTHER RESOLVED: That the listed vehicle models also comply with the Board's "Specifications for Fill Pipes and Openings of Motor Vehicle Fuel Tanks" for the aforementioned model year (Title 13, California Code of Regulations, Section 2235).

BE IT FURTHER RESOLVED: That the listed vehicle models also comply with the Board's high-altitude requirements and highway emission standards, and with the California Inspection and Maintenance emission standards in place at the time of certification, as stipulated in "California Exhaust Emission Standards and Test Procedures for 1988 and Subsequent Model Passenger Cars, Light-Duty Trucks, and Medium-Duty Vehicles."

BE IT FURTHER RESOLVED: That the listed vehicle models also comply with the "California Motor Vehicle Emission Control and Smog Index Label Specifications" for the aforementioned model year (Title 13, California Code of Regulations, Section 1965).

BE IT FURTHER RESOLVED: That the listed vehicle models also comply with the "Malfunction and Diagnostic System Requirements--1994 and Subsequent Model-Year Passenger Cars, Light-Duty Trucks, and Medium-Duty Vehicles and Engines" (Title 13, California Code of Regulations, Section 1968.1) for the aforementioned model year.

BE IT FURTHER RESOLVED: That for the listed vehicles, the manufacturer has submitted and the Executive Officer hereby approves the materials to demonstrate certification compliance with the Board's emission control system warranty provisions (Title 13, California Code of Regulations, Section 2035 et seq.).

BE IT FURTHER RESOLVED: That the vehicle manufacturer has demonstrated compliance with the exhaust emission standards at 50 degrees Fahrenheit as stipulated in "California Exhaust Emission Standards and Test Procedures for 1988 and Subsequent Model Passenger Cars, Light-Duty Trucks, and Medium-Duty Vehicles."

Vehicles certified under this Executive Order must conform to all applicable California emission regulations.

The Bureau of Automotive Repair will be notified by copy of this order and attachment.

Executed at El Monte, California this

day of July 1998.

R. B. Summerfield, Chief

Mobile Source Operations Division



E.O.# A-8-111-E

## 1999 AIR RESOURCES BOARD SUPPLEMENTAL DATA SHEET PASSENGER CARS, LIGHT DUTY TRUCKS AND MEDIUM DUTY VEHICLES

Manufacturer: BMVV Exh. Engine Family: XBMXV02.8M52 Evap. Fam: XBMXR0136E46					
All Eng Codes in Eng Fam: CA 49S 50S X AB965 ORVR: YES X NO					
Exh Std: CA Tier-1 TLEV X LEV ULEV ;US EPA Tier-1 X					
Veh Class: PC X LDT1 LDT2 MDV1 MDV2 MDV3 MDV4 MDV5					
Single Cert Std for Multi - Class Eng Fam: N/A					
Fuel Type (s): Dedicated Flex-Fuel Dual Fuel Bi - Fuel Gasoline X Diesel					
CNG LNG LPG M85 Other (specify)					
Emiss Test Fuel (s): Indo CBG _X CNG LPG M85 Other (specify) Diesel: 13 CCR 2282 40 CFR86.113-90 40 CFR86.113-94					
Evaporative Test Procedure: California Federal X					
Service Accum: Std AMA Mod AMA Mfr ADP X Other (specify)					
NMOG Test Procedure: N/A Std Equiv X R/L Test Proc: SHED X Pt Source					
Hybrid: Type A B C, APU Cycle (e.g., Otto, Diesel, Turbine)					
Engine Configuration: inline-6 Displacement: 3.2 Liters 192.3 Cubic Inches					
Valves per Cylinder: 4 Rated HP: 240 @ 6 000 RPM					
Engine: Front X Mid Rear Drive: FWD RWD X 4WD-FT 4WD-PT					
Exhaust ECS: 2TWC, 2HO2S(2), SFI, AIR					

Engine Code (50 ST)	Vehicle Models	Trans. Type	ETW (lbs.)	DPA or RLHP (hp)	Ignition (ECM/PCM) Part No.	EGR System Part No.	Catalytic Converter Part No.
3.2 MS 3.2 MS	M Roadster M Coupe	M5 M5	3 375 3 375	7.8 7.8	1 406 680	n.a.	1 744 164 left 1 744 163 right 1 432 455 left 1 432 456 right