

State of California
AIR RESOURCES BOARD

EXECUTIVE ORDER A-8-113
Relating to Certification of New Motor Vehicles

BAYERISCHE MOTOREN WERKE AG

Pursuant to the authority vested in the Air Resources Board by the Health and Safety Code, Division 26, Part 5, Chapter 2; and

Pursuant to the authority vested in the undersigned by Health and Safety Code Sections 39515 and 39516 and Executive Order G-45-9;

IT IS ORDERED AND RESOLVED: That 1999 model-year Bayerische Motoren Werke AG exhaust emission control systems are certified as described below for passenger cars:

Emission Standard Category: Transitional Low-Emission Vehicle (TLEV)

Fuel Type: Gasoline

Engine Family: XBMXV02.5M52 Displacement: 2.5 Liters (152.2 Cubic Inches)

Exhaust Emission Control Systems and Special Features:

- Three Way Catalytic Converter
- Heated Oxygen Sensors (two)
- Sequential Multiport Fuel Injection
- Secondary Air Injection

Vehicle models, transmissions, engine codes and evaporative emission control families are listed on attachments.

The TLEV certification exhaust emission standards for this engine family in grams per mile are:

<u>Miles</u>	<u>Non-Methane Organic Gas</u>	<u>Carbon Monoxide</u>	<u>Nitrogen Oxides</u>	<u>Formaldehyde</u>	<u>Carbon Monoxide (20°F)</u>
50,000	0.125	3.4	0.4	0.015	10.0
100,000	0.156	4.2	0.6	0.018	n/a

Reactivity Adjustment Factor (RAF) for NMOG Mass Emission: 0.98

The certification exhaust emission values set forth for non-methane organic gas (NMOG) reflect application of a 0.98 RAF for 1999 model-year TLEVs. The TLEV certification exhaust emission values for this engine family in grams per mile are:

<u>Miles</u>	<u>Non-Methane Organic Gas</u>	<u>Carbon Monoxide</u>	<u>Nitrogen Oxides</u>	<u>Formaldehyde</u>	<u>Carbon Monoxide (20°F)</u>
50,000	0.088	1.3	0.2	0.001	6.3
100,000	0.095	1.6	0.2	0.002	n/a

BE IT FURTHER RESOLVED: That the vehicle manufacturer is certifying the listed vehicle models to the aforementioned exhaust emission standards based on its submitted plan to comply with the fleet average NMOG exhaust mass emission requirements as set forth in "California Exhaust Emission Standards and Test Procedures for 1988 and Subsequent Model Passenger Cars, Light-Duty Trucks, and Medium-Duty Vehicles."

BE IT FURTHER RESOLVED: That under the submitted NMOG fleet average compliance plan, if the manufacturer incurs a NMOG debit for the aforementioned model year based on the projected NMOG fleet average exceeding the value required by the above-referenced standards and test procedures, all incurred NMOG debits by the manufacturer shall be equalized as required by the standards and test procedures.

BE IT FURTHER RESOLVED: That the vehicle manufacturer is certifying the listed vehicle models to the running loss and useful life standards applicable to 1995 and subsequent model-year vehicles in the "California Evaporative Emission Standards and Test Procedures for 1978 and Subsequent Model Motor Vehicles," and the listed vehicle models comply with those standards.

BE IT FURTHER RESOLVED: That the listed vehicle models also comply with the Board's "Specifications for Fill Pipes and Openings of Motor Vehicle Fuel Tanks" for the aforementioned model year (Title 13, California Code of Regulations, Section 2235).

BE IT FURTHER RESOLVED: That the listed vehicle models also comply with the Board's high-altitude requirements and highway emission standards, and with the California Inspection and Maintenance emission standards in place at the time of certification, as stipulated in "California Exhaust Emission Standards and Test Procedures for 1988 and Subsequent Model Passenger Cars, Light-Duty Trucks, and Medium-Duty Vehicles."

BE IT FURTHER RESOLVED: That the listed vehicle models also comply with the "California Motor Vehicle Emission Control and Smog Index Label Specifications" for the aforementioned model year (Title 13, California Code of Regulations, Section 1965).

BE IT FURTHER RESOLVED: That the listed vehicle models also comply with the "Malfunction and Diagnostic System Requirements--1994 and Subsequent Model-Year Passenger Cars, Light-Duty Trucks, and Medium-Duty Vehicles and Engines" (Title 13, California Code of Regulations, Section 1968.1) for the aforementioned model year.

BE IT FURTHER RESOLVED: That for the listed vehicles, the manufacturer has submitted and the Executive Officer hereby approves the materials to demonstrate certification compliance with the Board's emission control system warranty provisions (Title 13, California Code of Regulations, Section 2035 et seq.).

BE IT FURTHER RESOLVED: That the vehicle manufacturer has demonstrated compliance with the exhaust emission standards at 50 degrees Fahrenheit as stipulated in "California Exhaust Emission Standards and Test Procedures for 1988 and Subsequent Model Passenger Cars, Light-Duty Trucks, and Medium-Duty Vehicles."

Vehicles certified under this Executive Order must conform to all applicable California emission regulations.

The Bureau of Automotive Repair will be notified by copy of this order and attachment.

Executed at El Monte, California this 24th day of September 1998.



R. B. Summerfield, Chief
Mobile Source Operations Division

E.O.# A-8-113

**1999 AIR RESOURCES BOARD SUPPLEMENTAL DATA SHEET
PASSENGER CARS, LIGHT DUTY TRUCKS AND MEDIUM DUTY VEHICLES**

Manufacturer : BMW Exh. Engine Family : XBMXV02.5M52 Evap. Fam: XBMXE0156E36
 All Eng Codes in Eng Fam: CA ___ 49S ___ 50S X AB965 ___ ORVR: YES ___ NO X
 Exh Std: CA Tier-1 ___ TLEV X LEV ___ ULEV ___ SULEV ___ US EPA NLEV X
 Veh Class: PC X LDT1 ___ LDT2 ___ MDV1 ___ MDV2 ___ MDV3 ___ MDV4 ___ MDV5 ___
 Single Cert Std for Multi - Class Eng Fam: N/A
 Fuel Type (s): Dedicated X Flex-Fuel ___ Dual Fuel ___ Bi - Fuel ___ Gasoline X Diesel ___
 CNG ___ LNG ___ LPG ___ M85 ___ Other (specify) ___
 Emiss Test Fuel (s): Indo ___ CBG X CNG ___ LPG ___ M85 ___ Other (specify) ___
 Diesel: 13 CCR 2282 ___ 40 CFR86.113-90 ___ 40 CFR86.113-94 ___
 Evaporative Test Procedure: California X Federal ___
 Service Accum: Std AMA ___ Mod AMA ___ Mfr ADP X Other (specify) ___
 NMOG Test Procedure: N/A ___ Std ___ Equiv X R/L Test Proc: SHED X Pt Source ___
 Engine Configuration: inline-6 Displacement: 2.5 Liters 152.2 Cubic Inches
 Valves per Cylinder: 4 Rated HP: 168 @ 5 500 RPM
 Engine: Front X Mid ___ Rear ___ Drive: FWD ___ RWD X 4WD-FT ___ 4WD-PT ___
 Exhaust ECS: TWC, HO2S(2), SFI, AIR

Engine Code (50 ST)	Vehicle Models	Trans. Type	ETW (lbs.)	DPA or RLHP (hp)	Ignition (ECM/PCM) Part No.	EGR System Part No.	Catalytic Converter Part No.
2.5/3 M5	323is	M5	3 375	6.2	1 429 546	n.a.	1 432 130
2.5/3 M5	323iConv	M5	3 500	6.8	1 430 252		1 433 691
2.5/3 A4	323isA	L4	3 625	6.2	1 430 110		1 740 060
2.5/3 A4	323iAConv	L4	3 625	6.8	1 430 250		7 500 214