

State of California
AIR RESOURCES BOARD

EXECUTIVE ORDER A-8-115
Relating to Certification of New Motor Vehicles

BAYERISCHE MOTOREN WERKE AG

Pursuant to the authority vested in the Air Resources Board by the Health and Safety Code, Division 26, Part 5, Chapter 2; and

Pursuant to the authority vested in the undersigned by Health and Safety Code Sections 39515 and 39516 and Executive Order G-45-9;

IT IS ORDERED AND RESOLVED: That 1999 model-year Bayerische Motoren Werke AG exhaust emission control systems are certified as described below for passenger cars:

Emission Standard Category: Low-Emission Vehicle (LEV)

Fuel Type: Gasoline

Engine Family: XBMXV05.4LEV Displacement: 5.4 Liters (328.2 Cubic Inches)

Exhaust Emission Control Systems and Special Features:

Dual Adsorber Three Way Catalytic Converters
Dual Electrically Heated Three Way Catalytic Converters
Dual Three Way Catalytic Converters
Dual Heated Oxygen Sensors (two)
Sequential Multiport Fuel Injection
Secondary Air Injection

Vehicle models, transmissions, engine codes and evaporative emission control families are listed on attachments.

The LEV certification exhaust emission standards for this engine family in grams per mile are:

| <u>Miles</u> | <u>Non-Methane Organic Gas</u> | <u>Carbon Monoxide</u> | <u>Nitrogen Oxides</u> | <u>Formaldehyde</u> | <u>Carbon Monoxide (20°F)</u> |
|--------------|------------------------------------|----------------------------|----------------------------|---------------------|-----------------------------------|
| 50,000 | 0.075 | 3.4 | 0.2 | 0.015 | 10.0 |
| 100,000 | 0.090 | 4.2 | 0.3 | 0.018 | n/a |

Reactivity Adjustment Factor (RAF) for NMOG Mass Emission: 0.94

The certification exhaust emission values set forth for non-methane organic gas (NMOG) reflect application of a 0.94 RAF for 1999 model-year LEVs. The LEV certification exhaust emission values for this engine family in grams per mile are:

| <u>Miles</u> | <u>Non-Methane Organic Gas</u> | <u>Carbon Monoxide</u> | <u>Nitrogen Oxides</u> | <u>Formaldehyde</u> | <u>Carbon Monoxide (20°F)</u> |
|--------------|------------------------------------|----------------------------|----------------------------|---------------------|-----------------------------------|
| 50,000 | 0.042 | 0.9 | 0.1 | 0.0003 | 5.2 |
| 100,000 | 0.047 | 1.1 | 0.1 | 0.0003 | n/a |

BE IT FURTHER RESOLVED: That the vehicle manufacturer is certifying the listed vehicle models to the aforementioned exhaust emission standards based on its submitted plan to comply with the fleet average NMOG exhaust mass emission requirements as set forth in "California Exhaust Emission Standards and Test Procedures for 1988 and Subsequent Model Passenger Cars, Light-Duty Trucks, and Medium-Duty Vehicles."

BE IT FURTHER RESOLVED: That under the submitted NMOG fleet average compliance plan, if the manufacturer incurs a NMOG debit for the aforementioned model year based on the projected NMOG fleet average exceeding the value required by the above-referenced standards and test procedures, all incurred NMOG debits by the manufacturer shall be equalized as required by the standards and test procedures.

BE IT FURTHER RESOLVED: That the vehicle manufacturer is certifying the listed vehicle models to the running loss and useful life standards applicable to 1995 and subsequent model-year vehicles in the "California Evaporative Emission Standards and Test Procedures for 1978 and Subsequent Model Motor Vehicles," and the listed vehicle models comply with those standards.

BE IT FURTHER RESOLVED: That the vehicle manufacturer is certifying the listed vehicle models to the "California Refueling Emission Standards and Test Procedures for 1998 and Subsequent Model Motor Vehicles," Title 13, California Code of Regulations, Section 1978, and the listed vehicle models comply with those standards.

BE IT FURTHER RESOLVED: That the listed vehicle models also comply with the Board's "Specifications for Fill Pipes and Openings of Motor Vehicle Fuel Tanks" for the aforementioned model year (Title 13, California Code of Regulations, Section 2235).

BE IT FURTHER RESOLVED: That the listed vehicle models also comply with the Board's high-altitude requirements and highway emission standards, and with the California Inspection and Maintenance emission standards in place at the time of certification, as stipulated in "California Exhaust Emission Standards and Test Procedures for 1988 and Subsequent Model Passenger Cars, Light-Duty Trucks, and Medium-Duty Vehicles."

BE IT FURTHER RESOLVED: That the listed vehicle models also comply with the "California Motor Vehicle Emission Control and Smog Index Label Specifications" for the aforementioned model year (Title 13, California Code of Regulations, Section 1965).

BE IT FURTHER RESOLVED: That the listed vehicle models also comply with the "Malfunction and Diagnostic System Requirements--1994 and Subsequent Model-Year Passenger Cars, Light-Duty Trucks, and Medium-Duty Vehicles and Engines" (Title 13, California Code of Regulations, Section 1968.1) for the aforementioned model year.

BE IT FURTHER RESOLVED: That for the listed vehicles, the manufacturer has submitted and the Executive Officer hereby approves the materials to demonstrate certification compliance with the Board's emission control system warranty provisions (Title 13, California Code of Regulations, Section 2035 et seq.).

BE IT FURTHER RESOLVED: That the vehicle manufacturer has demonstrated compliance with the exhaust emission standards at 50 degrees Fahrenheit as stipulated in "California Exhaust Emission Standards and Test Procedures for 1988 and Subsequent Model Passenger Cars, Light-Duty Trucks, and Medium-Duty Vehicles."

Vehicles certified under this Executive Order must conform to all applicable California emission regulations.

The Bureau of Automotive Repair will be notified by copy of this order and attachment.

Executed at El Monte, California this 30th day of September 1998.

A handwritten signature in cursive script, appearing to read "R. B. Summerfield".

R. B. Summerfield, Chief
Mobile Source Operations Division

**1999 AIR RESOURCES BOARD SUPPLEMENTAL DATA SHEET
PASSENGER CARS, LIGHT DUTY TRUCKS AND MEDIUM DUTY VEHICLES**

Manufacturer : BMW Exh. Engine Family : XBMXV05.4LEV Evap. Fam: XBMXR0160E38
 All Eng Codes in Eng Fam: CA ___ 49S ___ 50S X AB965 ___ ORVR YES
 Exh Std: CA Tier-1 ___ TLEV ___ LEV X ULEV ___ ZEV ___ ; US EPA NLEV (LEV) X
 Evap Std: 50K ___ Useful Life with R/L x In-Use Exh Std: Full In Use ___ Alt In Use X
 Veh Class: PC X LDT1 ___ LDT2 ___ MDV1 ___ MDV2 ___ MDV3 ___ MDV4 ___ MDV5 ___
 Single Cert Std for Multi - Class Eng Fam: N/A
 Fuel Type (s): Dedicated X Flex-Fuel ___ Dual Fuel ___ Bi - Fuel ___ Gasoline X Diesel ___
 CNG ___ LNG ___ LPG ___ M85 ___ Other (specify) ___
 Emiss Test Fuel (s): Indo CBA X CNG ___ LPG ___ M85 ___ Other (specify) ___
 Diesel: 13 CCR 2282 ___ 40 CFR86.113-90 ___ 40 CFR86.113-94 ___
 Service Accum: Std AMA ___ Mod AMA ___ Mfr ADP X Other (specify) ___ Evap. T. P. Federal
 NMOG Test Procedure: N/A ___ Std ___ Equiv X R/L Test Proc: SHED X Pt Source ___
 Hybrid: Type A ___ B ___ C ___ , APU Cycle (e.g., Otto, Diesel, Turbine) ___
 Engine Configuration: V-12 Displacement: 5.4 Liters 328.2 Cubic Inches
 Valves per Cylinder: 2 Rated HP: 322 @ 5 000 RPM
 Engine: Front X Mid ___ Rear ___ Drive: FWD ___ RWD X 4WD-FT ___ 4WD-PT ___
 Exhaust ECS: 2ADS-TWC, 2EHC, 2TWC, 2HO2S(2), SFI, AIR

| Engine Code | Vehicle Models | Trans. Type | ETW (lbs.) | DPA or RLHP (hp) | Ignition (ECM/PCM) Part No. | EGR System Part No. | Catalytic Converter Part No. |
|-------------|----------------|-------------|----------------|------------------|-----------------------------|---------------------|------------------------------|
| 5.4-A | 750iL | L5 | 5 000 5 250 | 8.6 | 1 430 175 | n.a. | 1 732 979 1 732 980 |