State of California AIR RESOURCES BOARD

EXECUTIVE ORDER A-10-842 Relating to Certification of New Motor Vehicles

FORD MOTOR COMPANY

Pursuant to the authority vested in the Air Resources Board by the Health and Safety Code, Division 26, Part 5, Chapter 2; and

Pursuant to the authority vested in the undersigned by Health and Safety Code Sections 39515 and 39516 and Executive Order G-45-9;

IT IS ORDERED AND RESOLVED: That 1999 model-year Ford Motor Company exhaust emission control systems are certified as described below for medium-duty vehicles:

Emission Standard Category: Low-Emission Vehicle (LEV)

Fuel Type (Certification Fuel): Gasoline (Indolene)

۰.

4 .

Engine Family: XFMXA04.2HGC Displacement: 4.2 Liters (256 Cubic Inches)

Exhaust Emission Control Systems and Special Features:

Dual Three Way Catalytic Converters (two) Dual Heated Oxygen Sensors (two) Exhaust Gas Recirculation Sequential Multiport Fuel Injection

Vehicle models, transmissions, engine codes and evaporative emission control families are listed on attachments.

The non-methane organic gas (NMOG), carbon monoxide (CO), oxides of nitrogen (NOx), and formaldehyde (HCHO) LEV certification exhaust emission standards for this engine family in grams per mile are:

Test Weight (1bs.)	<u>Miles</u>	NMOG	CO	<u>NOx</u>	НСНО	<u>CO (20°F)</u>
3751-5750	50,000	0.160	4.4	0.4	0.018	12.5
	120,000	0.230	6.4	0.6	0.027	n/a

The LEV certification exhaust emission values for this engine family in grams per mile are:

Test Weight (1bs.)	Miles	NMOG	<u></u> CO	<u>NOx</u>	НСНО	<u>CO (20°F)</u>
3751-5750	50,000	0.095	1.3	0.1	0.001	1.0
	120,000	0.105	1.4	0.1	0.001	n/a

FORD MOTOR COMPANY

BE IT FURTHER RESOLVED: That the vehicle manufacturer is certifying the listed vehicle models to the aforementioned exhaust emission standards based on its submitted plan to comply with the medium-duty vehicle phase-in requirements as set forth in "California Exhaust Emission Standards and Test Procedures for 1988 and Subsequent Model Passenger Cars, Light-Duty Trucks, and Medium-Duty Vehicles" (Title 13, California Code of Regulations, Section 1960.1(h)(2)).

BE IT FURTHER RESOLVED: That under the submitted medium-duty vehicle phase-in compliance plan, if the manufacturer incurs "Vehicle Equivalent Debits" for the aforementioned model year due to the manufacturer's failure to produce and deliver for sale in California the equivalent quantity of medium-duty vehicles certified to low-emission vehicle and/or ultra-low-emission vehicle exhaust emission standards required by the above-referenced standards and test procedures, all "Vehicle Equivalent Debits" incurred by the manufacturer shall be equalized as required by the standards and test procedures.

BE IT FURTHER RESOLVED: That the vehicle manufacturer is certifying the listed vehicle models to the running loss and useful life standards applicable to 1995 and subsequent model-year vehicles in the "California Evaporative Emission Standards and Test Procedures for 1978 and Subsequent Model Motor Vehicles," and the listed vehicle models comply with those standards.

BE IT FURTHER RESOLVED: That the listed vehicle models also comply with the Board's "Specifications for Fill Pipes and Openings of Motor Vehicle Fuel Tanks" for the aforementioned model year (Title 13, California Code of Regulations, Section 2235).

BE IT FURTHER RESOLVED: That the listed vehicle models also comply with the Board's high-altitude requirements and highway emission standards, and with the California Inspection and Maintenance emission standards in place at the time of certification, as stipulated in "California Exhaust Emission Standards and Test Procedures for 1988 and Subsequent Model Passenger Cars, Light-Duty Trucks, and Medium-Duty Vehicles."

BE IT FURTHER RESOLVED: That the listed vehicle models also comply with the "California Motor Vehicle Emission Control and Smog Index Label Specifications" for the aforementioned model year (Title 13, California Code of Regulations, Section 1965).

BE IT FURTHER RESOLVED: That the vehicle manufacturer has demonstrated compliance with the exhaust emission standards at 50 degrees Fahrenheit as stipulated in "California Exhaust Emission Standards and Test Procedures for 1988 and Subsequent Model Passenger Cars, Light-Duty Trucks, and Medium-Duty Vehicles."

BE IT FURTHER RESOLVED: That for the listed vehicles, the manufacturer has submitted and the Executive Officer hereby approves the materials to demonstrate certification compliance with the Board's emission control system warranty provisions (Title 13, California Code of Regulations, Section 2035 et seq.).

BE IT FURTHER RESOLVED: That the listed vehicle models also comply with the "Malfunction and Diagnostic System Requirements--1994 and Subsequent Model-Year Passenger Cars, Light-Duty Trucks, and Medium-Duty Vehicles and Engines" (Title 13, California Code of Regulations, Section 1968.1) for the aforementioned model year. FORD MOTOR COMPANY

ι

EXECUTIVE ORDER A-10-842 (Page 3 of 3)

Vehicles certified under this Executive Order must conform to all applicable California emission regulations.

The Bureau of Automotive Repair will be notified by copy of this order and attachment.

Executed at El Monte, California this $/2^{\alpha}$ day of June 1998.

un

R. B. Summerfield, Chief Mobile Source Operations Division

. •

• •

E.O.#A-10-842

1999 AIR RESOURCES BOARD SUPPLEMENTAL DATA SHEET

PASSENGER CARS, LIGHT-DUTY TRUCKS AND MEDIUM-DUTY VEHICLES

Manufacturer <u>Fo</u>	ord Motor Compan	<u>y.</u> Ex	h. Eng. Fo	im.: <u>XFMX</u> A	NO4.2HGC EV	ap. Fam.: <u>XFN</u>	IXE0155BAG
Engine Code Types: CA_XXX_ 49S 50S ORVR: Yes No_XXX							
Exhaust Std: CA Tier-1 TLEV LEV_XXX_ ULEV ZEV U.S. EPA TIER-1							
Vehicle Class(es): PC LDT1 LDT2 MDV1 MDV2_XXX_ MDV3 MDV4 MDV5							
Single Cert Std fo	or Multi-Class Eng Fo	am: (specify: N/A	A,LDT1,MDV1,	MDV2,MDV3,MDV4	1)	
Exhaust Emiss. Test Fuel: Indolene Clear XXX Fuel Type: Gasoline XXX							
Evaporative Emission Test Procedure: California Federal_XXX_							
Service Accumulation: Std AMA Mod AMA Mfr ADP_XXX Other							
NMOG Test Procedure: N/AStd_XXX EquivR/L Test Procedure: SHEDPt.Source_XXX							
Engine Configuration <u>V-6</u> Displacement: <u>4.2 L</u> (256 in ³)							
Valves/Cyl: <u>02</u> Rated HP: <u>205 @ 4400</u> RPM							
Engine: Front_XXX Mid Rear Drive: Fwd RWD_XXX 4WD-FT 4WD-PT							
Exhaust Control System and Special Features 2TWC(2),2HO2S(2),EGR,SFI (Use abbreviations per SAE J1930 SEP91)							
					······		
EngineCode	Vehicle Models	Trans. A-Auto			Ignition Part No	EGR System	,
(California)			ETW	DPA		Part No	
	E-150 VAN	A4	5250	15.1	XC2F-FA	F65E-AA	XC25-BA
	E-150 VAN E-150 VAN	A A	5500 5500	17.7 17.7			
YLTADUAA	E-100 VAIN Econoline	A	5500	17.7			

20.09.17.02 - 1