(Page 1 of 2)

State of California AIR RESOURCES BOARD

EXECUTIVE ORDER A-22-84-A Relating to Certification of New Motor Vehicles

SAAB AUTOMOBILE AB

Pursuant to the authority vested in the Air Resources Board by the Health and Safety Code, Division 26, Part 5, Chapter 2; and

Pursuant to the authority vested in the undersigned by Health and Safety Code Sections 39515 and 39516 and Executive Order G-45-9;

IT IS ORDERED AND RESOLVED: That 1999 model-year Saab Automobile AB exhaust emission control systems are certified as described below for passenger cars:

Fuel Type: Gasoline

should be 1 <u>Engine Family</u>: XSAXV03.0TEI <u>Displacement</u>: 3.0 Liters (181 Cubic Inches)

Exhaust Emission Control Systems & Special Features:

Sequential Multiport Fuel Injection Heated Oxygen Sensors (two) Three Way Catalytic Converter Turbocharger Charge Air Cooler

Vehicle models, transmissions, engine codes and evaporative emission control families are listed on attachments.

The certification exhaust emission standards for this engine family in grams per mile are:

Miles	Non-Methane	Carbon	Nitrogen	Carbon	
	<u>Hydrocarbons</u>	<u>Monoxide</u>	Oxides	Monoxide (20°F)	
50,000	0.25	3.4	0.4	10.0	
100,000	0.31	4.2	0.6	n/a	

The certification exhaust emission values for this engine family in grams per mile are:

Miles	Non-Methane	Carbon	Nitrogen	Carbon
	Hydrocarbons	<u>Monoxide</u>	Oxides	<u>Monoxide (20°F)</u>
50,000	0.10	1.1	0.2	8.7
100,000	0.14	1.2	0.3	n/a

BE IT FURTHER RESOLVED: That the vehicle manufacturer is certifying the listed vehicle models to the running loss and useful life standards applicable to 1995 and subsequent model-year vehicles in the "California Evaporative Emission Standards and Test Procedures for 1978 and Subsequent Model Motor Vehicles," and the listed vehicle models comply with those standards.

BE IT FURTHER RESOLVED: That the listed vehicle models also comply with the Board's "Specifications for Fill Pipes and Openings of Motor Vehicle Fuel Tanks" for the aforementioned model year (Title 13, California Code of Regulations, Section 2235).

BE IT FURTHER_RESOLVED: That the listed vehicle models also comply with the Board's high-altitude requirements and highway emission standards, and with the California Inspection and Maintenance emission standards in place at the time of certification, as stipulated in "California Exhaust Emission Standards and Test Procedures for 1988 and Subsequent Model Passenger Cars, Light-Duty Trucks, and Medium-Duty Vehicles."

BE IT FURTHER RESOLVED: That the manufacturer is certifying the listed vehicle models with a partially complying on-board diagnostic system for the aforementioned model year pursuant to Title 13, California Code of Regulations, Section 1968.1(m)(6.2) ("Malfunction and Diagnostic System Requirements--1994 and Subsequent Model-Year Passenger Cars, Light-Duty Trucks, and Medium-Duty Vehicles and Engines.")

BE IT FURTHER RESOLVED: That the vehicle manufacturer is certifying the listed vehicle models to the "California Refueling Emission Standards and Test Procedures for 1998 and Subsequent Model Motor Vehicles," Title 13, California Code of Regulations, Section 1978, and the listed vehicle models comply with those standards.

BE IT FURTHER RESOLVED: That the listed vehicle models also comply with the "California Motor Vehicle Emission Control and Smog Index Label Specifications" for the aforementioned model year (Title 13, California Code of Regulations, Section 1965).

BE IT FURTHER RESOLVED: That for the listed vehicles, the manufacturer has submitted and the Executive Officer hereby approves the materials to demonstrate certification compliance with the Board's emission control system warranty provisions (Title 13, California Code of Regulations, Section 2035 et seq.).

Vehicles certified under this Executive Order must conform to all applicable California emission regulations.

The Bureau of Automotive Repair will be notified by copy of this order and attachment.

Executed at El Monte, California this _____day of August 1998.

Jehn Konsteln' f-

R.)B. Summerfield, Chief Mobile Source Operations Division

E.O.# A- 22.84-A

. .

	•					E.O. ≢	00 04 //
	1999 MODEL-Y	EAR AIR	RESOURCES	BOARD	SUPPLEMENTAL	DATA SHEET	Page_1_
· •	PASSENGER CAP	RS, LIGHT	-DUTY TRU	CKS AND	MEDIUM-DUTY	VEHICLES	raye
· ·	·,						
Manufactur	er: SAAB AUTOMOBILE	AB	Exh Eng	Fam:_X5	AXV01.0TEI	Evan Fam• Y	SAYPONOVEL
All Engine	Codes in Engine Fa	miliy:	CA_X_ 495	505	BRASE		
Exh Std:	CA Tier-1 X TLE	- v :		UT.RV	,	ORVR:	
Veh Class(es): PC <u>X</u> LDT1_	 [.DT	2 MD1	v		_, USEI	A Tier-1_A
Single Cer	t Std for Multi-Cla	es Fra F	- <u> </u>	· · · · · · · · · · · · · · · · · · ·		3 MDV4_	MDV5
Fuel Type()	s): Dedicated V	DD Big Fo	2003 <u>INVA</u> (1	abecrià	: N/A, LDT1,	MDV1, MDV2,	MDV3, MDV4)
	s): Dedicated <u>X</u>	fiex-fue:	L Dua.	-ruei_	Bi-Fuel	_ Gasoline_	X_ Diesel
Evh Emiga	CNGLNG		M85	Other	(specify)		
DAN DELES .	Test Fuel(s): Indo	X CBG	CNG	LPG	M85	Other (spec	ify)
B	Dies	el: 13 C	CR 2282_	40 (CFR 86.113-90_	40 CFR	86.113-94
Evaporative	Emission Test Prop	cedure:	Californi	a X	Federal		
Service Acc	um: Std AMA <u>X</u>	Nod AMA	Mfr	ADP	Other (spec	;ify)	
NMOG Test P	rocedure: N/A <u>X</u>	Std	Equiv_	F	L/L Test Proc:	SHED	Pt Source X
Engine Conr	iguration: <u>V6</u>	Displace	ment: <u>3</u>	0/	Liters	1817	Cubic Inches
vaives per	Cylinder: <u>1</u>		Rated	HP:	2.00	a 50.00	DDM
Engine: Fr	ont X Mid F	lear	Drive	: FWD	X RWD	4WD-FT	
Exhaust ECS	(e.g., MFI, EGR, I	C, CAC):	TWC, HO	- 25(z) 5	FE TC. CAC	400 TI	480-21
			(us	e abbre	viations per	SAE J1930 JT	JN93)
gine Cod	e Vehicle Models	Trans.	ETW	DPA			
(also list	(if coded see	(M5, A4	or	or	Ignition (ECM/PCM)	EGR System	Catalytic Converter
	T) attachment)	etc.)	Test Wt.	RLHP	Part No.	Part No.	Part No.
B308ES	4-5 DEDAN	1	1 · ·	1	i I		1
(5ØST)	9-5 SE SEDAN	L4	400¢	7.3	45 71 ZIZ	N/A	
				 (45 74 638
		1 8 1	•••				
							1 1 1
					1		
				ļ			
			i I				
		ĺ		1			
							i 1 1
			i	ľ			1 1 1
		1					
			1	4 1 1			
				i			
\sim			1	Ì	1		
		i	i	l l	ļ		
		İ				Ĩ	
						1	

۰.

- .