(Page 1 of 2)

State of California AIR RESOURCES BOARD

EXECUTIVE ORDER A-22-84 Relating to Certification of New Motor Vehicles

SAAB AUTOMOBILE AB

Pursuant to the authority vested in the Air Resources Board by the Health and Safety Code, Division 26, Part 5, Chapter 2; and

Pursuant to the authority vested in the undersigned by Health and Safety Code Sections 39515 and 39516 and Executive Order G-45-9;

IT IS ORDERED AND RESOLVED: That 1999 model-year Saab Automobile AB exhaust emission control systems are certified as described below for passenger cars: should be 1

Fuel Type: Gasoline

Dr S Engine Family: XSAXVO3.0TE() Displacement: 3.0 Liters (181 Cubic Inches)

Exhaust Emission Control Systems & Special Features:

Sequential Multiport Fuel Injection Heated Oxygen Sensors (two) Three Way Catalytic Converter Turbocharger Charge Air Cooler

Vehicle models, transmissions, engine codes and evaporative emission control families are listed on attachments.

The certification exhaust emission standards for this engine family in grams per mile are:

<u>Miles</u>	Non-Methane	Carbon	Nitrogen	Carbon	
	<u>Hydrocarbons</u>	<u>Monoxide</u>	<u>Oxides</u>	<u>Monoxide (20°F)</u>	
50,000	0.25	3.4	0.4	10.0	
100,000	0.31	4.2	0.6	n/a	

The certification exhaust emission values for this engine family in grams per mile are:

Miles	Non-Methane	Carbon	Nitrogen	Carbon	
	Hydrocarbons	<u>Monoxide</u>	<u>Oxides</u>	Monoxide (20°F)	
50,000	0.09	1.5	0.2	7.5	
100,000	0.12	1.2	0.2	n/a	

BE IT FURTHER RESOLVED: That the vehicle manufacturer is certifying the listed vehicle models to the running loss and useful life standards applicable to 1995 and subsequent model-year vehicles in the "California Evaporative Emission Standards and Test Procedures for 1978 and Subsequent Model Motor Vehicles," and the listed vehicle models comply with those standards.

BE IT FURTHER RESOLVED: That the listed vehicle models also comply with the Board's "Specifications for Fill Pipes and Openings of Motor Vehicle Fuel Tanks" for the aforementioned model year (Title 13, California Code of Regulations, Section 2235).

BE IT FURTHER RESOLVED: That the listed vehicle models also comply with the Board's high-altitude requirements and highway emission standards, and with the California Inspection and Maintenance emission standards in place at the time of certification, as stipulated in "California Exhaust Emission Standards and Test Procedures for 1988 and Subsequent Model Passenger Cars, Light-Duty Trucks, and Medium-Duty Vehicles."

BE IT FURTHER RESOLVED: That the manufacturer is certifying the listed vehicle models with a partially complying on-board diagnostic system for the aforementioned model year pursuant to Title 13, California Code of Regulations, Section 1968.1(m)(6.2) ("Malfunction and Diagnostic System Requirements--1994 and Subsequent Model-Year Passenger Cars, Light-Duty Trucks, and Medium-Duty Vehicles and Engines.")

BE IT FURTHER RESOLVED: That the listed vehicle models also comply with the "California Motor Vehicle Emission Control and Smog Index Label Specifications" for the aforementioned model year (Title 13, California Code of Regulations, Section 1965).

BE IT FURTHER RESOLVED: That for the listed vehicles, the manufacturer has submitted and the Executive Officer hereby approves the materials to demonstrate certification compliance with the Board's emission control system warranty provisions (Title 13, California Code of Regulations, Section 2035 et seq.).

Vehicles certified under this Executive Order must conform to all applicable California emission regulations.

The Bureau of Automotive Repair will be notified by copy of this order and attachment.

Executed at El Monte, California this $\frac{7^{1/4}}{2}$

R. B. Summerfield, Chief

Mobile Source Operations Division

E.O.#_	A-88.	84
--------	-------	----

1999 MODEL-YEAR AIR RESOURCES BOARD SUPPLEMENTAL DATA SHEET PASSENGER CARS, LIGHT-DUTY TRUCKS AND MEDIUM-DUTY VEHICLES

Page 1

Manufacturer:	SAAB AUTOMOBILE	AB :	Exh Eng Fa	am: <u>XSA</u>	XVO3.OTE 1	Evap Fam: X5/	XEQUBONE
All Engine Cod	des in Engine Fam:	iliy: c	A 49S_	50s_	X_ AB965,	ORVR: YE	s no x
Exh Std: CA	Tier-1 <u>X</u> TLEV	L	EV t	JLEV	SULEV	, US EPA	Tier-1 x
	PC_X_LDT1						
Single Cert St	td for Multi-Class	s Eng Far	n: <u>N/A</u> (s	pecify:	N/A, LDT1, 1	IDV1, MDV2,	MDV3, MDV4)
Fuel Type(s):	Dedicated X F	lex-Fuel	Dual-	-Fuel	Bi-Fuel	Gasoline X	_ Diesel
	CNGLNG	LPG	M85	Other (specify)		
Exh Emiss Test	Fuel(s): Indo_	K CBG_	CNG	_ LPĠ	м85 с	Other (speci	fy)
					FR 86.113-90_		6.113-94
	nission Test Proce						
Service Accum:	x Std AMA X Mo	AMA bo	Mfr /	ADP	Other (speci	fy)	
NMOG Test Prod	cedure: N/A <u>X</u>	Std	Equiv_	R,	/L Test Proc:	SHED P	t Source X
Engine Configu	ration: <u>Y6</u> I	Displacer	ment: <u>3</u>	Φ /	Liters <u>18</u>	/ /C	ubic Inches
Valves per Cyl	linder: 4		Rated	HP:	200	<u>@50co</u>	RPM
Engine: Front	X Mid Re	ear	Drive:	FWD_	X RWD	4WD-FT	4WD-PT
Exhaust ECS (e.g., MFI, EGR, TO	C, CAC):_	TWC	HO25(2	2) SFI TC, C	AC	
<u> </u>			(use	abbre	viations per s	SAE J1930 JU	N93)
falso list	Vehicle Models (if coded see	•		DPA	Ignition	EGR	Catalytic
CA/49ST/50ST)	· ·	(M5, A4 etc.)		or RLHP	(ECM/PCM) Part No.		Converter
B306 <i>ES</i>	95 SEOAN	L4			91 86 990		44 74 638
(≉ 5057)	9-5 SE SEDAN	11	t,				
•				11	"	1.	1 1 1
							1 1 !
							! !
							į !
							1
							! ! t
							1 1 1
							! !
							l 5 6
							[[
					L E]
					1]] }
					! !		! ! !
						1 1 1	; } {
İ					! ! !	! ! !	
					1 [!	(!