(Page 1 of 3)

State of California AIR RESOURCES BOARD

EXECUTIVE ORDER A-254-59 Relating to Certification of New Motor Vehicles

HYUNDAI MOTOR COMPANY

Pursuant to the authority vested in the Air Resources Board by the Health and Safety Code, Division 26, Part 5, Chapter 2; and

Pursuant to the authority vested in the undersigned by Health and Safety Code Sections 39515 and 39516 and Executive Order G-45-9;

IT IS ORDERED AND RESOLVED: That 1999 model-year Hyundai Motor Company exhaust emission control systems are certified as described below for passenger cars:

Emission Standard Category: Low-Emission Vehicle (LEV)

Fuel Type: Gasoline

Engine Family: XHYXV02.03RC Displacement: 2.0 Liters (120 Cubic Inches)

Exhaust Emission Control Systems & Special Features:

Sequential Multiport Fuel Injection Three Way Catalytic Converter Heated Oxygen Sensors (two) Warm Up Three Way Catalytic Converter

Vehicle models, transmissions, engine codes and evaporative emission control families are listed on attachments.

The LEV certification exhaust emission standards for this engine family in grams per mile are:

<u>Miles</u>	Non-Methane <u>Organic Gas</u>	Carbon <u>Monoxide</u>	Nitrogen <u>Oxides</u>	<u>Formaldehyde</u>	Carbon Monoxide (20°F)	
50,000	0.075	3.4	0.2	0.015	10.0	
100,000	0.090	4.2	0.3	0.018	n/a	

Reactivity Adjustment Factor (RAF) for NMOG Mass Emission: 0.94

The certification exhaust emission values set forth for non-methane organic gas (NMOG) reflect application of a 0.94 RAF for 1999 model-year LEVs. The LEV certification exhaust emission values for this engine family in grams per mile are:

Miles	Non-Methane Organic Gas	Carbon <u>Monoxide</u>	Nitrogen <u>Oxides</u>	<u>Formaldehyde</u>	Carbon Monoxide (20°F)	
50,000	0.049	0.4	0.02	0.001	3.5	
100,000	0.052	0.4	0.02	0.001	n/a	

BE IT FURTHER RESOLVED: That the vehicle manufacturer is certifying the listed vehicle models to the aforementioned exhaust emission standards based on its submitted plan to comply with the fleet average NMOG exhaust mass emission requirements as set forth in "California Exhaust Emission Standards and Test Procedures for 1988 and Subsequent Model Passenger Cars, Light-Duty Trucks, and Medium-Duty Vehicles."

BE IT FURTHER RESOLVED: That under the submitted NMOG fleet average compliance plan, if the manufacturer incurs a NMOG debit for the aforementioned model year based on the projected NMOG fleet average exceeding the value required by the above-referenced standards and test procedures, all incurred NMOG debits by the manufacturer shall be equalized as required by the standards and test procedures.

BE IT FURTHER RESOLVED: That the vehicle manufacturer is certifying the listed vehicle models to the running loss and useful life standards applicable to 1995 and subsequent model-year vehicles in the "California Evaporative Emission Standards and Test Procedures for 1978 and Subsequent Model Motor Vehicles," and the listed vehicle models comply with those standards.

BE IT FURTHER RESOLVED: That the vehicle manufacturer is certifying the listed vehicle models to the "California Refueling Emission Standards and Test Procedures for 1998 and Subsequent Model Motor Vehicles," Title 13, California Code of Regulations, Section 1978, and the listed vehicle models comply with those standards.

E IT FURTHER RESOLVED: That the listed vehicle models also comply with the Board's "Specifications for Fill Pipes and Openings of Motor Vehicle Fuel Tanks" for the aforementioned model year (Title 13, California Code of Regulations, Section 2235).

BE IT FURTHER RESOLVED: That the listed vehicle models also comply with the Board's high-altitude requirements and highway emission standards, and with the California Inspection and Maintenance emission standards in place at the time of certification, as stipulated in "California Exhaust Emission Standards and Test Procedures for 1988 and Subsequent Model Passenger Cars, Light-Duty Trucks, and Medium-Duty Vehicles."

BE IT FURTHER RESOLVED: That the vehicle manufacturer has demonstrated compliance with the exhaust emission standards at 50 degrees Fahrenheit as stipulated in "California Exhaust Emission Standards and Test Procedures for 1988 and Subsequent Model Passenger Cars, Light-Duty Trucks, and Medium-Duty Vehicles."

BE IT FURTHER RESOLVED: That the listed models also comply with the "Malfunction and Diagnostic System Requirements--1994 and Subsequent Model-Year Passenger Cars, Light-Duty Trucks, and Medium-Duty Vehicles and Engines" (Title 13, California Code of Regulations, Section 1968.1) for the aforementioned model year.

BE IT FURTHER RESOLVED: That the listed vehicle models also comply with the "California Motor Vehicle Emission Control and Smog Index Label Specifications" for the aforementioned model year (Title 13, California Code of Regulations, Section 1965).

BE IT FURTHER RESOLVED: That for the listed vehicles, the manufacturer has submitted and the Executive Officer hereby approves the materials to demonstrate certification compliance with the Board's emission control system warranty provisions (Title 13, California Code of Regulations, Section 2035 et seq.).

Vehicles certified under this Executive Order must conform to all applicable California emission regulations.

The Bureau of Automotive Repair will be notified by copy of this order and attachment.

Executed at El Monte, California this _____ day of July 1998.

R. B. Summerfield, Chief

Mobile Source Operations Division

1998 MODEL-YEAR AIR RESOURCES SUPPLEMENTAL DATA SHEET PASSENGER CARS, LIGHT-DUTY TRUCKS AND MEDIUM-DUTY VEHICLES

Manufacturer: <u>HYUNDAI MOTOR CO.</u> Exh Eng Fam: <u>XHYXV02.03RC</u> Evap Fam: <u>XHYXR0134PER</u>
All Eng Codes in Eng Fam: CAX 49S 50S AB965, ORVR: YesX No
Exh Std : CA Tier-1_ TLEV_ LEV_X ULEV_ ZEV_ ; US EPA Tier-1_
Veh Class(es): PC_X LDT1_ LDT2_ MDV1_ MDV2_ MDV3_ MDV4_ MDV5_
Single Cert Std for Muli-Class Eng Fam: N/A (specify: N/A, LDT1, MDV1, MDV2, MDV3, MDV4)
Fuel Type(s) : Dedicated X Flex-Fuel Dual-Fuel Bi-Fuel Gasoline X Diesel CNG LNG LPG M85 Other (specify)
Emiss Test Fuel(s): Indo X CBG(PH2) X CNG LPG M85 Other (specify)
Diesel: 13 CCR 2282 40 CFR 86.113-90 40 CFR 86.113-94
Evaporative Emission Test Procedure: California Federal_X_
Service Accum: Std AMA_X
NMOG Test procedure: N/A Std X Equiv R/L Test Proc: SHED X Pt Source
Engine Configuration : <u>I-4</u> Displacement : <u>2.0</u> / Liters <u>120.5</u> / Cubic Inches
Valves Per Cylinder: 4 Rated HP: 133 @ 6,000 RPM
Engine: Front_X Mid_ Rear Drive: FWD_X RWD_ 4WD-FT_ 4WD-PT_
Exhaust ECS (e.g., MFI EGR., TC, CAC, : HO2S(2) + WU-TWC + TWC+ SFI + OBD II
(use abbreviations per SAE J1930 JUN93)

Eng. Code (also list CA/ 49ST/50ST)	Veh. Models (If coded see Attachment)	Trans. (M5-Man, L4-Auto)		DPA or RLHP	Ignition (ECM/PCM) Part No.	EGR System Part No.	Catalystic Converter Part No.
ACM5-Q2 /CM5-Q2(CA)	ELANTRA (Sedan)	M5	3000	5.6	39150-23955 (9 030 930 068) or 39110-23955 (9 030 930 069)	N/A	28510-23310 & 28950-23130
ACL4-Q2 /CL4-Q2(CA)	1	L4	3000	†	<u></u>	1	1
ACM5-W2 /CM5-W2(CA)	ELANTRA (Wagon)	M5	↑	6.1	<u></u>	↑	1
ACL4-W2 /CL4-W2(CA)	<u></u>	L4	3125	6.3	<u></u>	<u></u>	<u>†</u>
ACM5-U1 /CM5-U1CA)	TIBURON (Coupe)	M5	3000	6.8	<u></u>	<u> </u>	1
ACL4-U1 /CL4-U1CA)	1	L4	3000	6.6	<u> </u>	1	<u></u>

Issued : 6-1-98

Revised: