Tili

(Page 1 of 2)

State of California AIR RESOURCES BOARD

EXECUTIVE ORDER A-7-214 Relating to Certification of New Motor Vehicles

VOLKSWAGEN AG

Pursuant to the authority vested in the Air Resources Board by the Health and Safety Code, Division 26, Part 5, Chapter 2; and

Pursuant to the authority vested in the undersigned by Health and Safety Code Sections 39515 and 39516 and Executive Order G-45-9;

IT IS ORDERED AND RESOLVED: That 2000 model-year Volkswagen AG exhaust emission control systems are certified as described below for light-duty trucks:

Fuel Type: Gasoline

Engine Family: YXVWXT02.8225 Displacement: 2.8 Liters (170 Cubic Inches)

Exhaust Emission Control Systems & Special Features:

Three Way Catalytic Converter Secondary Air Injection Heated Oxygen Sensors (two) Exhaust Gas Recirculation Sequential Multiport Fuel Injection

Vehicle models, transmissions, engine codes and evaporative emission control families are listed on attachments.

The certification exhaust emission standards for this engine family in grams per mile are:

Loaded Vehicle	Miles	Non-Methane	Carbon	Nitrogen	Carbon
Weight (lbs.)		<u>Hydrocarbons</u>	<u>Monoxide</u>	<u>Oxides</u>	<u>Monoxide (20°F)</u>
3751-5750	50,000	0.32	4.4	0.7	12.5
	100,000	0.40	5.5	0.97	n/a

The certification exhaust emission values for this engine family in grams per mile are:

Loaded Vehicle	Miles	Non-Methane	Carbon	Nitrogen	Carbon
Weight (1bs.)		<u>Hydrocarbons</u>	<u>Monoxide</u>	<u>Oxides</u>	<u>Monoxide (20°F)</u>
3751-5750	50,000	0.12	0.8	0.3	5.6
	100,000	0.12	0.8	0.30	n/a

BE IT FURTHER RESOLVED: That the vehicle manufacturer is certifying the listed vehicle models to the aforementioned exhaust emission standards based on its submitted plan to comply with the fleet average non-methane organic gases (NMOG) exhaust mass emission requirements as set forth in "California Exhaust Emission Standards and Test Procedures for 1988 and Subsequent Model Passenger Cars, Light-Duty Trucks, and Medium-Duty Vehicles."

VOLKSWAGEN AG

BE IT FURTHER RESOLVED: That under the submitted NMOG fleet average compliance plan, if the manufacturer incurs a NMOG debit for the aforementioned model year based on the projected NMOG fleet average exceeding the value required by the above-referenced standards and test procedures, all incurred NMOG debits by the manufacturer shall be equalized as required by the standards and test procedures.

BE IT FURTHER RESOLVED: That the vehicle manufacturer is certifying the listed vehicle models to the running loss and useful life standards applicable to 1995 and subsequent model-year vehicles in the "California Evaporative Emission Standards and Test Procedures for 1978 and Subsequent Model Motor Vehicles," and the listed vehicle models comply with those standards.

BE IT FURTHER RESOLVED: That the listed vehicle models also comply with the Board's "Specifications for Fill Pipes and Openings of Motor Vehicle Fuel Tanks" for the aforementioned model year (Title 13, California Code of Regulations, Section 2235).

BE IT FURTHER RESOLVED: That the listed vehicle models also comply with the Board's high-altitude requirements and highway emission standards, and with the California Inspection and Maintenance emission standards in place at the time of certification, as stipulated in "California Exhaust Emission Standards and Test Procedures for 1988 and Subsequent Model Passenger Cars, Light-Duty Trucks, and Medium-Duty Vehicles."

BE IT FURTHER RESOLVED: That the listed vehicle models also comply with the "California Motor Vehicle Emission Control and Smog Index Label Specifications" for the aforementioned model year (Title 13, California Code of Regulations, Section 1965).

BE IT FURTHER RESOLVED: That the listed vehicle models also comply with the "Malfunction and Diagnostic System Requirements--1994 and Subsequent Model-Year Passenger Cars, Light-Duty Trucks, and Medium-Duty Vehicles and Engines" (Title 13, California Code of Regulations, Section 1968.1) for the aforementioned model year.

BE IT FURTHER RESOLVED: That for the listed vehicles, the manufacturer has submitted and the Executive Officer hereby approves the materials to demonstrate certification compliance with the Board's emission control system warranty provisions (Title 13, California Code of Regulations, Section 2035 et seq.).

Vehicles certified under this Executive Order must conform to all applicable California emission regulations.

The Bureau of Automotive Repair will be notified by copy of this order and attachment.

Executed at El Monte, California this 29 day of July 1999.

R.) B. Summerfield, Chief

_Mobile Source Operations Division

PAGE NO.: 17.05. -01 E.O.# 1-7-214 Page 1 of 1

2000 AIR RESOURCES BOARD SUPPLEMENTAL DATA SHEET PASSENGER CARS, LIGHT-DUTY TRUCKS AND MEDUM-DUTY VEHICLES

Manufacturer: VOLKSWAGEN Exh Eng Fam: YVWXT02.8225 Evap Fam: YVWXE0105233 All Eng Codes in Eng Fam: CA 49S 50S X AB965 ORVR: YES NO X Exh Std: CA Tier-1 X TLEV LEV ULEV SULEV; US EPA Tier-1 X Veh Class(es): PC LDT1 LDT2 X MDV1 MDV2 MDV3 MDV4 MDV5 Single Cert Std for Multi-Class Eng Fam: N/A (specify: N/A, LDT1, MDV1, MDV2, MDV3, MDV4) Fuel Type(s): Dedicated X Flex-Fuel Dual-Fuel Bi-Fuel Gasoline X Diesel CNG LNG LPG M85 Other (specify) Exh Emiss Test Fuel(s): Indo CBG X CNG LPG M85 Other (specify) Diesel: 13 CCR 2282 40 CFR 86.113-90 40 CFR 86.113-94 Evaporative Emission Test Procedure: California Federal X Service Accum: Std AMA X Mod AMA Mfr ADP Other (specify) NMCG Test Procedure: N/A X Std Equiv R/L Test Proc: SHED n.a Pt Source X Engine Config. 6, V in line Displacement: 2.8 Liters 170 Cubic Inches Valves per Cylinder: 2 Engine: Front X Mid. Rear Drive: FWD X RWD 4WD-FT 4WD-PT Exhaust ECS (eg., EGR, MFI, TC, CAC, etc.) SFI / AIR / EGR / TWC / HO2S(2) / OEDII (use abbreviations per SAE 1930 JUN93) Engine Code Vehicles Trans. ETW DFA Ignition EGR Converter
Exh Std: CA Tier-1
Veh Class(es): PC LDT1 LDT2_X MDV1 MDV2 MDV3 MDV4 MDV5 Single Cert Std for Multi-Class Eng Fam: N/A (specify: N/A, LDT1, MDV1, MDV2, MDV3, MDV4) MDV4 MDV4 MDV5 Fuel Type(s): Dedicated X Flex-Fuel Dual-Fuel Bi-Fuel Gasoline X Diesel CNG LNG LPG M85 Other (specify) Other (specify) Exin Emiss Test Fuel(s): Indo CBG X CNG LPG M85 Other (specify) Exin Emiss Test Fuel(s): Indo CBG X CNG LPG M85 Other (specify) Evaporative Emission Test Procedure: California Federal X Service Accum: Std AMA X Mod AMA Mfr ADP Other (specify) NMOG Test Procedure: N/A X Std Equiv R/L Test Proc: SHED n.a Pt Source X Engine Config. 6, V in line Displacement: 2.8 Liters 170 Cubic Inches Valves per Cylinder: 2 Rated HP:
Single Cert Std for Multi-Class Eng Fam: N/A (specify: N/A, LDT1, MDV1, MDV2, MDV3, MDV4) Fuel Type(s): Dedicated X Flex-Fuel
Fuel Type(s): Dedicated X Flex-Fuel Dual-Fuel Bi-Fuel Gasoline X Diesel CNG LNG LPG M85 Other (specify) Exh Emiss Test Fuel(s): Indo CBG X CNG LPG M85 Other (specify) Diesel: 13 CCR 2282 40 CFR 86.113-90 40 CFR 86.113-94 Evaporative Emission Test Procedure: California Federal X Service Accum: Std AMA X Mod AMA Mfr ADP Other (specify) NMOG Test Procedure: N/A X Std Equiv R/L Test Proc: SHED n.a Pt Source X Engine Config. 6, V in line Displacement: 2.8 Liters 170 Cubic Inches Valves per Cylinder: 2 Engine: Front X Mid. Rear Drive: FWD X RWD 4WD-FT 4WD-PT Exhaust ECS (eg., EGR, MFI, TC, CAC, etc.) SFI / AIR / EGR / TWC / HO2S(2) / OBDII (use abbreviations per SAE 1930 JUN93)
CNG LNG LPG M85 Other (specify) Exh Emiss Test Fuel(s): Indo CBG X CNG LPG M85 Other (specify) Diesel: 13 CCR 2282 40 CFR 86.113-90 40 CFR 86.113-94 Evaporative Emission Test Procedure: California Federal X Service Accum: Std AMA X Mod AMA Mfr ADP Other (specify) NMOG Test Procedure: N/A X Std Equiv R/L Test Proc: SHED n.a Pt Source X Engine Config. 6, V in line Displacement: 2.8 Liters 170 Cubic Inches Valves per Cylinder: 2 Rated HP: 140 @ 4,500 RPM Engine: Front X Mid. Rear Drive: FWD X RWD 4WD-FT 4WD-PT Exhaust ECS (eg., EGR, MFI, TC, CAC, etc.) SFI / AIR / EGR / TWC / HO2S(2) / OBDII (use abbreviations per SAE 1930 JUN93)
Exh Emiss Test Fuel(s): Indo CBG X CNG LPG M85 Other (specify) Diesel: 13 CCR 2282 40 CFR 86.113-90 40 CFR 86.113-94 Evaporative Emission Test Procedure: California Federal X Service Accum: Std AMA X Mod AMA Mfr ADP Other (specify) NMOG Test Procedure: N/A X Std Equiv R/L Test Proc: SHED n.a Pt Source X Engine Config. 6, V in line Displacement: 2.8 Liters 170 Cubic Inches Valves per Cylinder: 2 Rated HP: 140 @ 4,500 RPM Engine: Front X Mid. Rear Drive: FWD X RWD 4WD-FT 4WD-PT Exhaust ECS (eg., EGR, MFI, TC, CAC, etc.) SFI / AIR / EGR / TWC / HO2S(2) / OBDII (use abbreviations per SAE 1930 JUN93)
Diesel: 13 CCR 2282 40 CFR 86.113-90 40 CFR 86.113-94 Evaporative Emission Test Procedure: California Federal _ X Service Accum: Std AMA X
Evaporative Emission Test Procedure: California Federal X Service Accum: Std AMA X Mod AMA Mfr ADP Other (specify) NMOG Test Procedure: N/A X Std Equiv R/L Test Proc: SHED n.a Pt Source X Engine Config. 6, V in line Displacement: 2.8 Liters 170 Cubic Inches Valves per Cylinder: 2 Rated HP: 140 @ 4,500 RPM Engine: Front X Mid. Rear Drive: FWD X RWD 4WD-FT 4WD-PT Exhaust ECS (eg., EGR, MFI, TC, CAC, etc.) SFI / AIR / EGR / TWC / HO2S(2) / OBDII (use abbreviations per SAE 1930 JUN93)
Service Accum: Std AMA X Mod AMA Mfr ADP Other (specify) NMOG Test Procedure: N/A X Std Equiv R/L Test Proc: SHED n.a Pt Source X Engine Config. 6, V in line Displacement: 2.8 Liters 170 Cubic Inches Valves per Cylinder: 2 Rated HP: 140 @ 4,500 RPM Engine: Front X Mid. Rear Drive: FWD X RWD 4WD-FT 4WD-PT Exhaust ECS (eg., EGR, MFI, TC, CAC, etc.) SFI / AIR / EGR / TWC / HO2S(2) / OBDII (use abbreviations per SAE 1930 JUN93) Fingine Code Vehicles Trans. ETW DPA Ignition EGR Catalytic
NMOG Test Procedure: N/A X Std Equiv R/L Test Proc: SHED n.a Pt Source X Engine Config. 6, V in line Displacement: 2.8 Liters 170 Cubic Inches Valves per Cylinder: 2 Rated HP: 140 @ 4,500 RPM Engine: Front X Mid. Rear Drive: FWD X RWD 4WD-FT 4WD-PT Exhaust ECS (eg., EGR, MFI, TC, CAC, etc.) SFI / AIR / EGR / TWC / HO2S(2) / OBDII (use abbreviations per SAE 1930 JUN93) Fingine Code Vehicles Trans. ETW DPA Ignition EGR Catalytic
Engine Config. 6, V in line Displacement: 2.8 Liters 170 Cubic Inches Valves per Cylinder: 2 Rated HP: 140 9 4,500 RPM Engine: Front X Mid. Rear Drive: FWD X RWD 4WD-FT 4WD-PT Exhaust ECS (eg., EGR, MFI, TC, CAC, etc.) SFI / AIR / EGR / TWC / HO2S(2) / OBDII (use abbreviations per SAE 1930 JUN93) Fingine Code Vehicles Trans. ETW DPA Ignition EGR Catalytic
Valves per Cylinder: 2 Rated HP: 140 @ 4,500 RPM Engine: Front X Mid. Rear Drive: FWD X RWD 4WD-FT 4WD-PT Exhaust ECS (eg., EGR, MFI, TC, CAC, etc.) SFI / AIR / EGR / TWC / HO2S(2) / OBDII (use abbreviations per SAE 1930 JUN93) Fngine Code Vehicles Trans. ETW DPA Ignition EGR Catalytic
Engine: Front X Mid. Rear Drive: FWD X RWD 4WD-FT 4WD-PT Exhaust ECS (eg., EGR, MFI, TC, CAC, etc.) SFI / AIR / EGR / TWC / HO2S(2) / OBDII (use abbreviations per SAE 1930 JUN93) Fingine Code Vehicles Trans. ETW DPA Ignition EGR Catalytic
Exhaust ECS (eg., EGR, MFI, TC, CAC, etc.) SFI / AIR / EGR / TWC / HO2S(2) / OBDII (use abbreviations per SAE 1930 JUN93) Fingine Code Vehicles Trans. ETW DPA Ignition EGR Catalytic
(use abbreviations per SAE 1930 JUN93) Fingine Code Vehicles Trans. ETW DPA Ignition EGR Catalytic
ENOTHE COME ACTIONS LIEUTON
ENOTHE COME ACTIONS LIEUTON
(also list Models Type or or (ECM/PCM) System CONVERCES
CA/49ST/50ST (if codded see A-auto Test RLHP attachment) M-man. WT Part No. Part No. Part No.
accaciment) 11 mai.
AFS EUROVAN VR6 A 5,500 11.8 021 906 259 P 021 131 501 E 023 131 701 S
50 ST 021 131 501 G
054 906 267
AES Eurovan MV A 4,750 10.5 - " - " - " - " - " -
50 ST / Eurovan MV
pop top + w.p.
AES Eurovan GLS A 4,500 10.5 - " - " - " - " - " - " - " - " - " -
50 ST van
Date Issued: 03-08-99
Revisions: