State of California AIR RESOURCES BOARD

EXECUTIVE ORDER A-3-196 Relating to Certification of New Motor Vehicles

DAIMLERCHRYSLER AG

Pursuant to the authority vested in the Air Resources Board by the Health and Safety Code, Division 26, Part 5, Chapter 2; and

Pursuant to the authority vested in the undersigned by Health and Safety Code Sections 39515 and 39516 and Executive Order G-45-9;

IT IS ORDERED AND RESOLVED: That 2000 model-year DaimlerChrysler AG exhaust emission control systems are certified as described below for medium-duty vehicles:

Emission Standard Category: Low-Emission Vehicle (LEV)

Fuel Type: Gasoline

Engine Family: YMBXT04.3GNB Displacement: 4.3 Liters (260 Cubic Inches)

Exhaust Emission Control Systems & Special Features:

Dual Warm Up Three Way Catalytic Converters Dual Three Way Catalytic Converters Dual Heated Oxygen Sensors (two) Exhaust Gas Recirculation Secondary Air Injection Sequential Multiport Fuel Injection

Vehicle models, transmissions, engine codes and evaporative emission control families are listed on attachments.

The non-methane organic gases (NMOG), carbon monoxide (CO), oxides of nitrogen (NOx), and formaldehyde (HCHO) LEV certification exhaust emission standards for this engine family in grams per mile are:

Test Weight (1bs.)	<u>Miles</u>	NMOG	<u></u>	<u>NOx</u>	НСНО	CO (20°F)
3751-5750	50,000	0.160	4.4	0.4	0.018	12.5
	120,000	0.230	6.4	0.6	0.027	n/a

Reactivity Adjustment Factor (RAF) for NMOG Mass Emission: 0.94

The certification exhaust emission values set forth for NMOG reflect application of a 0.94 RAF for 2000 model-year LEVs. The LEV certification exhaust emission values for this engine family in grams per mile are:

Test Weight (lbs.)	Miles	NMOG	<u></u>	<u>N0x</u>	<u>НСНО</u>	<u>CO (20°F)</u>
3751-5750	50,000 120,000	0.026 0.035	0.3 0.5	0.1 0.1	0.0002	1.3 n/a

BE IT FURTHER RESOLVED: That the vehicle manufacturer is certifying the listed vehicle models to the aforementioned exhaust emission standards based on its submitted plan to comply with the medium-duty vehicle phase-in requirements as set forth in "California Exhaust Emission Standards and Test Procedures for 1988 and Subsequent Model Passenger Cars, Light-Duty Trucks, and Medium-Duty Vehicles" (Title 13, California Code of Regulations, Section 1960.1(h)(2)).

BE IT FURTHER RESOLVED: That under the submitted medium-duty vehicle phase-in compliance plan, if the manufacturer incurs "Vehicle Equivalent Debits" for the aforementioned model year due to the manufacturer's failure to produce and deliver for sale in California the equivalent quantity of medium-duty vehicles certified to low-emission vehicle and/or ultra-low-emission vehicle exhaust emission standards required by the above-referenced standards and test procedures, all "Vehicle Equivalent Debits" incurred by the manufacturer shall be equalized as required by the standards and test procedures.

BE IT FURTHER RESOLVED: That the vehicle manufacturer is certifying the listed vehicle models to the running loss and useful life standards applicable to 1995 and subsequent model-year vehicles in the "California Evaporative Emission Standards and Test Procedures for 1978 and Subsequent Model Motor Vehicles," and the listed vehicle models comply with those standards.

BE IT FURTHER RESOLVED: That the listed vehicle models also comply with the Board's "Specifications for Fill Pipes and Openings of Motor Vehicle Fuel Tanks" for the aforementioned model year (Title 13, California Code of Regulations, Section 2235).

BE IT FURTHER RESOLVED: That the listed vehicle models also comply with the Board's high-altitude requirements and highway emission standards, and with the California Inspection and Maintenance emission standards in place at the time of certification, as stipulated in "California Exhaust Emission Standards and Test Procedures for 1988 and Subsequent Model Passenger Cars, Light-Duty Trucks, and Medium-Duty Vehicles."

BE IT FURTHER RESOLVED: That the listed vehicle models also comply with the "California Motor Vehicle Emission Control and Smog Index Label Specifications" for the aforementioned model year (Title 13, California Code of Regulations, Section 1965).

BE IT FURTHER RESOLVED: That the listed vehicle models also comply with the "Malfunction and Diagnostic System Requirements--1994 and Subsequent Model-Year Passenger Cars, Light-Duty Trucks, and Medium-Duty Vehicles and Engines" (Title 13, California Code of Regulations, Section 1968.1) for the aforementioned model year.

BE IT FURTHER RESOLVED: That the vehicle manufacturer has demonstrated compliance with the exhaust emission standards at 50 degrees Fahrenheit as stipulated in "California Exhaust Emission Standards and Test Procedures for 1988 and Subsequent Model Passenger Cars, Light-Duty Trucks, and Medium-Duty Vehicles."

BE IT FURTHER RESOLVED: That for the listed vehicles, the manufacturer has submitted and the Executive Officer hereby approves the materials to demonstrate certification compliance with the Board's emission control system warranty provisions (Title 13, California Code of Regulations, Section 2035 et seq.).

Vehicles certified under this Executive Order must conform to all applicable California emission regulations.

The Bureau of Automotive Repair will be notified by copy of this order and attachment.

Executed at El Monte, California this

R. B Summerfield, Chief

Mobile Source Operations Division

2000 MODEL YEAR AIR RESOURCES BOARD SUPPLEMENTAL DATA SHEET PASSENGER CARS, LIGHT-DUTY TRUCKS AND MEDIUM-DUTY VEHICLES

Manufacturer:	DaimlerChrysle	r AG Exh. Engi	ne Family	/: YMBXT	04.3GNB E	Evap. Family: <u>YN</u>	BXE0153NNZ
Ail Eng. Codes	in Eng. Fam.:	CA	49S	_50S	X AB965	OVRV Ye	s NO x
Exh. Std.: CA	A Tier-1	TLEVL	.EV <u>X</u>	_ULEV_	SULEV	US EPA	Tier-1 NLEV
Veh. Class(es)	: PC_	LDT1	LDT2	_MDV1_	MDV2_x_!	MDV3 MDV	4MDV5
Single Cert. Sto	d. for Multi-Class	Eng. Fam.:	N/A (sp	ecify: N/	A, LDT1, MDV	1, MDV2, MD	/3, MDV4)
Fuel Type(s):	Dedicated _	X Flex-Fuel	Dua	l-Fuel	Bi-Fuel	Gasoline X	Diesel
	CNG	LNG LPG	5 N	185	Other (specify	-	
Emiss. Test Fu		CBG X					
		13 CCR 22				_	
Evaporative E		rocedure: Ca			_		
Service Accum	: Std. AMA	X Mod. AMA	·	Mfr ADP	Other (:	specify)	
NMOG Test Pro	ocedure:	N/A Std.	_X_ Eq	uiv	R/L Test Proc.	: SHED X	Pt Source
Engine Configu	ration:	V-8 Di	splaceme	nt:4	4.3 Liters	260	Cubic Inches
Valves per Cylin	nder:	3		Rated	d HP:268@55	00 / 215@	5700 RPM
		Rear_					
Exhaust ECS (e	g., MFI, EGR, T	C, CAC):	SI	FI/AIR/	EGR / 2H02S (2)	/ 2 WU-TWC / 2	TWC
				(use ab	breviations per S	AE J1930 JUN9	3)
	1		r		1		T
1	Vehicle Models	1 * '	1	DPA	Ignition	EGR	Catalytic
T'	ł'	(A 4, M 5, etc.)		or	1	System	Converter
CA/49ST/ <u>50ST</u>)	T		Test Wt	1		Part No.	Part No.
M 113-43D	ML 430	L-5	5 500	12.5	A0265456932	A1121400060	A1634901514
				ĺ			(underhood)
				İ]	A1634901814
						Ì	or
							A1634901914
	:						(underfloor)
					,		
	İ						
]				:			- i
		İ					ļ
			ŀ				
Date Issued:	I		Revision	٠. د		i	