State of California AIR RESOURCES BOARD

EXECUTIVE ORDER A-3-192-1 Relating to Certification of New Motor Vehicles

DAIMLERCHRYSLER AG

Pursuant to the authority vested in the Air Resources Board by the Health and Safety Code, Division 26, Part 5, Chapter 2; and

Pursuant to the authority vested in the undersigned by Health and Safety Code Sections 39515 and 39516 and Executive Order G-45-9;

IT IS ORDERED AND RESOLVED: That 2000 model-year DaimlerChrysler AG exhaust emission control systems are certified as described below for passenger cars:

Emission Standard Category: Transitional Low-Emission Vehicle (TLEV)

Fuel Type: Gasoline

Engine Family: YMBXV05.8GNB <u>Displacement</u>: 5.8 Liters (350 Cubic Inches)

Exhaust Emission Control Systems & Special Features:

Sequential Multiport Fuel Injection
Quadruple Warm Up Three Way Catalytic Converters
Dual Three Way Catalytic Converters
Quadruple Heated Oxygen Sensors (two)
Secondary Air Injection

Vehicle models, transmissions, engine codes and evaporative emission control families are listed on attachments.

The TLEV certification exhaust emission standards for this engine family in grams per mile are:

Miles	Non-Methane Organic Gases	Carbon <u>Monoxide</u>	Nitrogen Oxides	Formaldehyde	Carbon Monoxide (20°F)
50,000	0.125	3.4	0.4	0.015	10.0
100,000	0.156	4.2	0.6	0.018	n/a

Reactivity Adjustment Factor (RAF) for NMOG Mass Emission: 0.98

The certification exhaust emission values set forth for non-methane organic gases (NMOG) reflect application of a 0.98 RAF for 2000 model-year TLEVs. The TLEV certification exhaust emission values for this engine family in grams per mile are:

Miles	Non-Methane Organic Gases			Formaldehyde	Carbon Monoxide (20°F)
50,000	0.028	0.3	0.1	0.001	1.1
100,000	0.028	0.3	0.1		n/a

BE IT FURTHER RESOLVED: That the vehicle manufacturer is certifying the listed vehicle models to the aforementioned exhaust emission standards based on its submitted plan to comply with the fleet average NMOG exhaust mass emission requirements as set forth in "California Exhaust Emission Standards and Test Procedures for 1988 Through 2000 Model Passenger Cars, Light-Duty Trucks, and Medium-Duty Vehicles."

BE IT FURTHER RESOLVED: That under the submitted NMOG fleet average compliance plan, if the manufacturer incurs a NMOG debit for the aforementioned model year based on the projected NMOG fleet average exceeding the value required by the above-referenced standards and test procedures, all incurred NMOG debits by the manufacturer shall be equalized as required by the standards and test procedures.

BE IT FURTHER RESOLVED: That the vehicle manufacturer is certifying the listed vehicle models to the running loss and useful life standards applicable to 1995 and subsequent model-year vehicles in the "California Evaporative Emission Standards and Test Procedures for 1978 Through 2000 Model Motor Vehicles," and the listed vehicle models comply with those standards.

BE IT FURTHER RESOLVED: That the vehicle manufacturer is certifying the listed vehicle models to the "California Refueling Emission Standards and Test Procedures for 1998 Through 2000 Model Motor Vehicles," Title 13, California Code of Regulations, Section 1978, and the listed vehicle models comply with those standards.

BE IT FURTHER RESOLVED: That the listed vehicle models also comply with the Board's "Specifications for Fill Pipes and Openings of Motor Vehicle Fuel Tanks" for the aforementioned model year (Title 13, California Code of Regulations, Section 2235).

BE IT FURTHER RESOLVED: That the listed vehicle models also comply with the Board's high-altitude requirements and highway emission standards, and with the California Inspection and Maintenance emission standards in place at the time of certification, as stipulated in "California Exhaust Emission Standards and Test Procedures for 1988 Through 2000 Model Passenger Cars, Light-Duty Trucks, and Medium-Duty Vehicles."

BE IT FURTHER RESOLVED: That the vehicle manufacturer has demonstrated compliance with the exhaust emission standards at 50 degrees Fahrenheit as stipulated in "California Exhaust Emission Standards and Test Procedures for 1988 Through 2000 Model Passenger Cars, Light-Duty Trucks, and Medium-Duty Vehicles."

BE IT FURTHER RESOLVED: That the listed vehicle models also comply with the "California Motor Vehicle Emission Control and Smog Index Label Specifications" for the aforementioned model year (Title 13, California Code of Regulations, Section 1965).

BE IT FURTHER RESOLVED: That the listed vehicle models also comply with the "Malfunction and Diagnostic System Requirements--1994 and Subsequent Model-Year Passenger Cars, Light-Duty Trucks, and Medium-Duty Vehicles and Engines" (Title 13, California Code of Regulations, Section 1968.1) for the aforementioned model year.

BE IT FURTHER RESOLVED: That for the listed vehicles, the manufacturer has submitted and the Executive Officer hereby approves the materials to demonstrate certification compliance with the Board's emission control system warranty provisions (Title 13, California Code of Regulations, Section 2035 et seq.).

Vehicles certified under this Executive Order must conform to all applicable California emission regulations.

The Bureau of Automotive Repair will be notified by copy of this order and attachment.

Executive Order A-3-192 dated March 6, 2000, is superseded and replaced by Executive Order A-3-192-1.

Executed at El Monte, California this 6th day of July 2000.

R. B. Śummerfield, Chief

Mobile Source Operations Division

E.O: # AS-192 Page 1 of 1

2000 MODEL YEAR AIR RESOURCES BOARD SUPPLEMENTAL DATA SHEET PASSENGER CARS, LIGHT-DUTY TRUCKS AND MEDIUM-DUTY VEHICLES

Manufacturer	DaimlerChrysler /	AG Exh. Engin	e Family:	YMBXVO	5.8GNB E	vap. Family: YME	BXR0155MNZ
All Eng. Codes in	n Eng. Fam.:	CA 49	s	50S X	AB965	OVRV Yes	X NO
Evh Std: CA	Tier-1 T	TLEV X LE	.V	ULEV	SULEV	US EPA	Tier-1 NLEV
Veh Class(es):	PC 2	X LDT1 L	DT2	MDV1	MDV2 M	IDV3 MDV4	MDV5
Single Cert Std.	for Multi-Class B	ng. Fam.:	V/A (spe	cify: N/A	, LDT1, MDV1	, MDV2, MDV	3, MDV4)
Fuel Type(s):	Dedicated	X Flex-Fuel	Dual-	Fuel	Bi-Fuel	Gasoline X	Diesel
, uc. ()pc(o).		 LNG LPG					
Emiss, Test Fue							
	Diesel:	13 CCR 228	32	40 C	FR 86.113-90	40 CFF	R 86.113-94
Evaporative E	mission Test Pro	cedure: Ca	lifornia		Federal	<u>X</u>	
Service Accum:	Std. AMA	X Mod. AMA		Mfr ADP	Other (s	pecify)	
NMOG Test Pro	cedure:	N/A Std.	X Equ	ıiv	R/L Test Proc.:	SHED_X_	Pt Source
Fraine Configur	ration:	/-12 Dis	placeme	nt:5	.8 Liters	350	Cubic Inches
Valves per Cylin	ider:	3		Rated	HP: 362@55	00	RPM
Fooine: From	nt X Middle	Rear	Drive	: FWD	RWD X.	4WD-FT	4WD-PT
Exhaust FCS (e	a. MFI. EGR. TO	C, CAC):	_ s	FI / AIR 🚜	EFRY 4H02S (2) / 4 WU-TWC / 2	TWC
Exhibiting (o	9., , ===,			(use at	breviations per	SAE J1930 JUNS	3)
		<u></u>					T
Engine Code	Vehicle Model	Trans. Type	ETW		1.5	EGR	Catalytic
(also list	(If coded see	(A 4, M 5, etc.)	or	Of	(ECM/PCM)	1	Converter
CA/49ST/50ST)	attachment)		Test Wt		Part No.	Part No.	Part No.
M117-58	S 600	L-5	4750	8,6	A0255457432		A2204901114 or
}	CL600				-		A2204901214
							(underhood-le)
							A2204901314 or
							A2204901414
		[(underhood-ri)
						-	:
							A2204901614
	1					•.	(underfloor-le)
							A2204901714
					1		(underfloor-ri)
			1		.]		(andermoor,
						*	
			1				
	1						
	1		1				,
						-	
						-	
						-	

Revisions: