State of California AIR RESOURCES BOARD

EXECUTIVE ORDER A-8-116 Relating to Certification of New Motor Vehicles

BAYERISCHE MOTOREN WERKE AG

Pursuant to the authority vested in the Air Resources Board by the Health and Safety Code, Division 26, Part 5, Chapter 2; and

Pursuant to the authority vested in the undersigned by Health and Safety Code Sections 39515 and 39516 and Executive Order G-45-9;

IT IS ORDERED AND RESOLVED: That 2000 model-year Bayerische Motoren Werke AG exhaust emission control systems are certified as described below for passenger cars:

Emission Standard Category: Low-Emission Vehicle (LEV)

Fuel Type: Gasoline

Engine Family: YBMXV04.4LEV Displacement: 4.4 Liters (268.4 Cubic Inches)

Exhaust Emission Control Systems and Special Features:

Dual Warm Up Three Way Catalytic Converters Dual Three Way Catalytic Converters Dual Heated Oxygen Sensors (two) Sequential Multiport Fuel Injection Secondary Air Injection

Vehicle models, transmissions, engine codes and evaporative emission control families are listed on attachments.

The LEV certification exhaust emission standards for this engine family in grams per mile are:

Miles	Non-Methane Organic Gas	Carbon <u>Monoxide</u>	Nitrogen Oxides	Formaldehyde	Carbon Monoxide (20 ⁰ F)
50,000	0.075	3.4	0.2	0.015	10.0
100,000	0.090	4.2		0.018	n/a

Reactivity Adjustment Factor (RAF) for NMOG Mass Emission: 0.94

The certification exhaust emission values set forth for non-methane organic gas (NMOG) reflect application of a 0.94 RAF for 2000 model-year LEVs. The LEV certification exhaust emission values for this engine family in grams per mile are:

Miles	Non-Methane Organic Gas	Carbon <u>Monoxide</u>	Nitrogen _Oxides_	Formaldehyde	Carbon <u>Monoxide (20⁰F)</u>
50,000	0.063	0.8	0.1	0.001	4.1
100,000	0.069	1.0	0.1	0.001	n/a

BE IT FURTHER RESOLVED: That the vehicle manufacturer is certifying the listed vehicle models to the aforementioned exhaust emission standards based on its submitted plan to comply with the fleet average NMOG exhaust mass emission requirements as set forth in "California Exhaust Emission Standards and Test Procedures for 1988 and Subsequent Model Passenger Cars, Light-Duty Trucks, and Medium-Duty Vehicles."

BE IT FURTHER RESOLVED: That under the submitted NMOG fleet average compliance plan, if the manufacturer incurs a NMOG debit for the aforementioned model year based on the projected NMOG fleet average exceeding the value required by the above-referenced standards and test procedures, all incurred NMOG debits by the manufacturer shall be equalized as required by the standards and test procedures.

BE IT FURTHER RESOLVED: That the vehicle manufacturer is certifying the listed vehicle models to the running loss and useful life standards applicable to 1995 and subsequent model-year vehicles in the "California Evaporative Emission Standards and Test Procedures for 1978 and Subsequent Model Motor Vehicles," and the listed vehicle models comply with those standards.

BE IT FURTHER RESOLVED: That the vehicle manufacturer is certifying the listed vehicle models to the "California Refueling Emission Standards and Test Procedures for 1998 and Subsequent Model Motor Vehicles," Title 13, California Code of Regulations, Section 1978, and the listed vehicle models comply with those standards.

BE IT FURTHER RESOLVED: That the listed vehicle models also comply with the Board's "Specifications for Fill Pipes and Openings of Motor Vehicle Fuel Tanks" for the aforementioned model year (Title 13, California Code of Regulations, Section 2235).

BE IT FURTHER RESOLVED: That the listed vehicle models also comply with the Board's high-altitude requirements and highway emission standards, and with the California Inspection and Maintenance emission standards in place at the time of certification, as stipulated in "California Exhaust Emission Standards and Test Procedures for 1988 and Subsequent Model Passenger Cars, Light-Duty Trucks, and Medium-Duty Vehicles."

BE IT FURTHER RESOLVED: That the listed vehicle models also comply with the "California Motor Vehicle Emission Control and Smog Index Label Specifications" for the aforementioned model year (Title 13, California Code of Regulations, Section 1965).

BE IT FURTHER RESOLVED: That the listed vehicle models also comply with the "Malfunction and Diagnostic System Requirements--1994 and Subsequent Model- Year Passenger Cars, Light-Duty Trucks, and Medium-Duty Vehicles and Engines" (Title 13, California Code of Regulations, Section 1968.1) for the aforementioned model year.

BE IT FURTHER RESOLVED: That for the listed vehicles, the manufacturer has submitted and the Executive Officer hereby approves the materials to demonstrate certification compliance with the Board's emission control system warranty provisions (Title 13, California Code of Regulations, Section 2035 et seq.).

EXECUTIVE ORDER A-8-116 (Page 3 of 3)

BE IT FURTHER RESOLVED: That the vehicle manufacturer has demonstrated compliance with the exhaust emission standards at 50 degrees Fahrenheit as stipulated in "California Exhaust Emission Standards and Test Procedures for 1988 and Subsequent. Model Passenger Cars, Light-Duty Trucks, and Medium-Duty Vehicles."

Vehicles certified under this Executive Order must conform to all applicable California emission regulations.

The Bureau of Automotive Repair will be notified by copy of this order and attachment.

Executed at El Monte, California this ______ day of March 1999.

ouxleli' f

R. B. Summerfield, Chief Mobile Source Operations Division

 \mathbf{V}

E.O.#<u>A</u>

2000 AIR RESOURCES BOARD SUPPLEMENTAL DATA SHEET PASSENGER CARS, LIGHT DUTY TRUCKS AND MEDIUM DUTY VEHICLES

Manufacturer : BMW Exh. Engine Family : YBMXV04.4LEV Evap. Fam: YBMXR0160E38								
All Eng Codes in Eng Fam: CA 49S 50S _X AB965 ORVR: YES X NO								
Exh Std: CA Tier-1 TLEV LEV X ULEV SULEV US EPA NLEV X								
Evap Std: 50K Useful Life with R/L In-Use Exh Std: Full In Use X Alt In Use								
Veh Class: PC X LDT1LDT2MDV1MDV2MDV3MDV4 MDV5								
Single Cert Std for Multi - Class Eng Fam: N/A								
Fuel Type (s): Dedicated X Flex-Fuel Dual Fuel Bi - Fuel Gasoline X Diesel CNG LNG LPG M85 Other (specify)								
Emiss Test Fuel (s): Indo CBG X CNG LPG M85 Other (specify) Diesel: 13 CCR 2282 40 CFR86.113-90 40 CFR86.113-94 40 CFR86.113-94								
Evaporative Test Procedure: California Federal X								
Service Accum: Std AMA Mod AMA Mfr ADP X Other (specify)								
NMOG Test Procedure: N/A Std Equiv X R/L Test Proc: SHED X Pt Source								
Engine Configuration: V - 8 Displacement: 4.4 Liters 268.4 Cubic Inches								
Valves per Cylinder: 4 Rated HP: 282 @ 5 700 RPM								
Engine: Front X Mid Rear Drive: FWD RWD X 4WD-FT 4WD-PT								
Exhaust ECS: 2WU-TWC,2TWC, 2HO2S(2), SFI, AIR								

Engine Code (50 ST)	Vehicle Models	Trans. Type	ETW (lbs.)	DPA or RLHP (hp)	lgnition (ECM/PCM) Part No.	EGR System Part No.	Catalytic Converter Part No.
4.4-A-LEV // // //	740iA 740iAL 740iAL (Protection Line) 740iA (Sports Version)	L5 L5 L5 L5	4 500 4 500 5 000 4 500	7.5 7.5 7.7 8.0	1 429 894 1 438 454 1 430 145		1 716 491/492 (Main catalyst) 1 437 529 (WU catalyst)

V

E.O.#<u>A-8-116</u> Pg. 20f3

2000 AIR RESOURCES BOARD SUPPLEMENTAL DATA SHEET PASSENGER CARS, LIGHT DUTY TRUCKS AND MEDIUM DUTY VEHICLES

Manufacturer : BMW Exh. Engine Family : YBMXV04.4LEV Evap. Fam: YBMXR0160E39							
All Eng Codes in Eng Fam: CA 49S 50S _X AB965 ORVR: YES _X NO							
Exh Std: CA Tier-1 TLEV LEV X ULEV US EPA NLEV X							
Evap Std: 50K Useful Life with R/L In-Use Exh Std: Full In Use Alt In Use							
Veh Class: PC X LDT1 LDT2 MDV1 MDV2 MDV3 MDV4 MDV5							
Single Cert Std for Multi - Class Eng Fam: N/A							
Fuel Type (s): Dedicated X Flex-Fuel Dual Fuel Bi - Fuel Gasoline X Diesel CNG LNG LPG M85 Other (specify)							
Emiss Test Fuel (s):IndoCBGXCNGLPGM85Other (specify)Diesel:13 CCR 228240 CFR86.113-9040 CFR86.113-94							
Evaporative Test Procedure: California Federal _X							
Service Accum: Std AMA Mod AMA Mfr ADP X Other (specify)							
NMOG Test Procedure: N/A Std Equiv X R/L Test Proc: SHED X Pt Source							
Engine Configuration: V - 8 Displacement: 4.4 Liters 268.4 Cubic Inches							
Valves per Cylinder: 4 Rated HP: 282 @ 5700 RPM							
Engine: Front X Mid Rear Drive: FWD RWD X 4WD-FT 4WD-PT							
Exhaust ECS: 2WU-TWC, 2TWC, 2HO2S(2), SFI, AIR							

Engine Code (50 ST)	Vehicle Models	Trans. Type	ETW (ibs.)	DPA or RLHP (hp)	Ignition (ECM/PCM) Part No.	EGR System Part No.	Catalytic Converter Part No.
4.4-A-LEV // //	540iA 540iA (Sports version) 540iA (Protection Line)	L5 L5 L5	4 000 4 000 4 500	7.3 7.9 7.4	1 429 894 1 438 454 1 430 145		1 716 491/492 (Main catalyst) 1 437 529 (WU catalyst)
4.4-LEV	540i	M6	4 000	7.9	1 429 893		



E.O.#<u>A-8-116</u> Pq. 30f3

2000 AIR RESOURCES BOARD SUPPLEMENTAL DATA SHEET PASSENGER CARS, LIGHT DUTY TRUCKS AND MEDIUM DUTY VEHICLES

Manufacturer : BMW Exh. Engine Family : YBMXV04.4LEV Evap. Fam: YBMXR0136E46								
All Eng Codes in Eng Fam: CA 49S 50S _X AB965 ORVR: YES _X NO								
Exh Std: CA Tier-1 TLEV LEV X ULEV SULEV US EPA NLEV X								
Evap Std: 50K Useful Life with R/L x In-Use Exh Std: Full In Use Alt In Use								
Veh Class: PC X LDT1 LDT2 MDV1 MDV2 MDV3 MDV4 MDV5								
Single Cert Std for Multi - Class Eng Fam:N/A								
Fuel Type (s): Dedicated X Flex-Fuel Dual Fuel Bi - Fuel Gasoline X Diesel CNG LNG LPG M85 Other (specify)								
Emiss Test Fuel (s): Indo CBG X CNG LPG M85 Other (specify) Diesel: 13 CCR 2282 40 CFR86.113-90 40 CFR86.113-94								
Evaporative Test Procedure: California Federal X								
Service Accum: Std AMA Mod AMA Mfr ADP X Other (specify)								
NMOG Test Procedure: N/A Std Equiv X R/L Test Proc: SHED X Pt Source								
Engine Configuration: V - 8 Displacement: 4.4 Liters 268.4 Cubic Inches								
Valves per Cylinder: 4 Rated HP: 282 @ 5700 RPM								
Engine: Front X Mid Rear Drive: FWD RWD X 4WD-FT 4WD-PT								
Exhaust ECS: 2WU-TWC, 2TWC, 2HO2S(2), SFI, AIR								

Engine Code (50 ST)	Vehicle Models	Trans. Type	ETW (lbs.)	DPA or RLHP (hp)	Ignition (ECM/PCM) Part No.	EGR System Part No.	Catalytic Converter Part No.
4.4-A-LEV	540IAT	L5	4 250	7.5	1 429 894 1 438 454 1 430 145		1 716 491/492 (Main catalyst) 1 437 529 (WU catalyst)