

State of California
AIR RESOURCES BOARD

EXECUTIVE ORDER A-9-444
Relating to Certification of New Motor Vehicles

DAIMLERCHRYSLER CORPORATION

Pursuant to the authority vested in the Air Resources Board by the Health and Safety Code, Division 26, Part 5, Chapter 2; and

Pursuant to the authority vested in the undersigned by Health and Safety Code Sections 39515 and 39516 and Executive Order G-45-9;

IT IS ORDERED AND RESOLVED: That 2000 model-year DaimlerChrysler Corporation exhaust emission control systems are certified as described below for passenger cars:

Emission Standard Category: Ultra-Low-Emission Vehicle (ULEV)

Fuel Type: Gasoline

Engine Family: YCRXV0122V41 Displacement: 2.0 Liters (122 Cubic Inches)

Exhaust Emission Control Systems & Special Features:

- Three Way Catalytic Converters (two)
- Heated Oxygen Sensors (two)
- Sequential Multiport Fuel Injection

Vehicle models, transmissions, engine codes and evaporative emission control families are listed on attachments.

The ULEV certification exhaust emission standards for this engine family in grams per mile are:

<u>Miles</u>	<u>Non-Methane Organic Gases</u>	<u>Carbon Monoxide</u>	<u>Nitrogen Oxides</u>	<u>Formaldehyde</u>	<u>Carbon Monoxide (20°F)</u>
50,000	0.040	1.7	0.2	0.008	10.0
100,000	0.055	2.1	0.3	0.011	n/a

Reactivity Adjustment Factor (RAF) for NMOG Mass Emission: 0.94

The certification exhaust emission values set forth for non-methane organic gases (NMOG) reflect application of a 0.94 RAF for 2000 model-year ULEVs. The ULEV certification exhaust emission values for this engine family in grams per mile are:

<u>Miles</u>	<u>Non-Methane Organic Gases</u>	<u>Carbon Monoxide</u>	<u>Nitrogen Oxides</u>	<u>Formaldehyde</u>	<u>Carbon Monoxide (20°F)</u>
50,000	0.029	0.4	0.02	0.001	2.3
100,000	0.034	0.6	0.02	0.001	n/a

BE IT FURTHER RESOLVED: That the vehicle manufacturer is certifying the listed vehicle models to the aforementioned exhaust emission standards based on its submitted plan to comply with the fleet average NMOG exhaust mass emission requirements as set forth in "California Exhaust Emission Standards and Test Procedures for 1988 and Subsequent Model Passenger Cars, Light-Duty Trucks, and Medium-Duty Vehicles."

BE IT FURTHER RESOLVED: That under the submitted NMOG fleet average compliance plan, if the manufacturer incurs a NMOG debit for the aforementioned model year based on the projected NMOG fleet average exceeding the value required by the above-referenced standards and test procedures, all incurred NMOG debits by the manufacturer shall be equalized as required by the standards and test procedures.

BE IT FURTHER RESOLVED: That the vehicle manufacturer is certifying the listed vehicle models to the running loss and useful life standards applicable to 1995 and subsequent model-year vehicles in the "California Evaporative Emission Standards and Test Procedures for 1978 and Subsequent Model Motor Vehicles," and the listed vehicle models comply with those standards.

BE IT FURTHER RESOLVED: That the vehicle manufacturer is certifying the listed vehicle models to the "California Refueling Emission Standards and Test Procedures for 1998 and Subsequent Model Motor Vehicles," Title 13, California Code of Regulations, Section 1978, and the listed vehicle models comply with those standards.

BE IT FURTHER RESOLVED: That the listed vehicle models also comply with the Board's "Specifications for Fill Pipes and Openings of Motor Vehicle Fuel Tanks" for the aforementioned model year (Title 13, California Code of Regulations, Section 2235).

BE IT FURTHER RESOLVED: That the listed vehicle models also comply with the Board's high-altitude requirements and highway emission standards, and with the California Inspection and Maintenance emission standards in place at the time of certification, as stipulated in "California Exhaust Emission Standards and Test Procedures for 1988 and Subsequent Model Passenger Cars, Light-Duty Trucks, and Medium-Duty Vehicles."

BE IT FURTHER RESOLVED: That the listed vehicle models also comply with the "California Motor Vehicle Emission Control and Smog Index Label Specifications" for the aforementioned model year (Title 13, California Code of Regulations, Section 1965).

BE IT FURTHER RESOLVED: That the vehicle manufacturer has demonstrated compliance with the exhaust emission standards at 50 degrees Fahrenheit as stipulated in "California Exhaust Emission Standards and Test Procedures for 1988 and Subsequent Model Passenger Cars, Light-Duty Trucks, and Medium-Duty Vehicles."

BE IT FURTHER RESOLVED: That the listed vehicle models also comply with the "Malfunction and Diagnostic System Requirements--1994 and Subsequent Model-Year Passenger Cars, Light-Duty Trucks, and Medium-Duty Vehicles and Engines" (Title 13, California Code of Regulations, Section 1968.1) for the aforementioned model year.

BE IT FURTHER RESOLVED: That for the listed vehicles, the manufacturer has submitted and the Executive Officer hereby approves the materials to demonstrate certification compliance with the Board's emission control system warranty provisions (Title 13, California Code of Regulations, Section 2035 et seq.).

Vehicles certified under this Executive Order must conform to all applicable California emission regulations,

The Bureau of Automotive Repair will be notified by copy of this order and attachment.

Executed at El Monte, California this 28th day of April 1999.



R. B. Summerfield, Chief
Mobile Source Operations Division

2000 MODEL YEAR AIR RESOURCES BOARD SUPPLEMENTAL DATA SHEET
PASSENGER CARS, LIGHT-DUTY TRUCKS AND MEDIUM-DUTY VEHICLES

E.O. # A-9-444
Page 1 of 1

Manufacturer: DaimlerChrysler Corporation Exh Eng Fam: YCRXV0122V41 Evap Fam: YCRXR0101G1A
 All Eng Codes in Eng Fam: CA X 49S X 50S _____ AB965 _____ ORVR: YES X NO _____
 Exh Std: CA Tier-1 _____ TLEV _____ LEV _____ ULEV X SULEV _____; US EPA ~~Final~~ ^{NLEV} unrestricted
 Veh Class(es): PC X LDT1 _____ LDT2 _____ MDV1 _____ MDV2 _____ MDV3 _____ MDV4 _____ MDV5 _____
 Single Cert Std for Multi-Class Eng Fam: N/A (Specify: N/A, LDT1, MDV1, MDV2, MDV3, MDV4)
 Fuel Type(s): Dedicated X Flex-Fuel _____ Dual-Fuel _____ Bi-Level _____ Gasoline X Diesel _____
 CNG _____ LNG _____ LPG _____ M85 _____ Other (specify) _____
 Emis Test Fuel(s): Indo _____ CBG X CNG _____ LPG _____ M85 _____ Other(specify) _____
 Diesel: 13 CCR 2282 _____ or 40 CFR 86.113-90 _____ or 40 CFR 86.113-94 _____
 Evaporative Emission Test Procedure: California _____ Federal X _____
 Service Accum: Std AMA _____ Mod AMA X Mfr ADP _____ Other (Specify) _____
 NMOG Test Procedure: N/A _____ Std _____ Equiv X R/L Test Proce: SHED _____ Pt Source X _____
 Engine Configuration: I-4 Displacement: _____ / 2.0 Liters _____ / 122 Cubic Inches
 Valves per Cylinder: 4 Rated HP: _____ 132 @ 5600 RPM
 Engine: Front X Mid _____ Rear _____ Drive: FWD X RWD _____ 4WD-FT _____ 4WD-PT _____
 Exhaust ECS (eg., EGR, MFI, TC, CAC): _____ H02S(2), SFI, TWC(2), OBDII
 (use abbreviations per SAE J1930 JUN93)

Engine Code (also list CA/49ST/50ST)	Vehicle Models (if coded see attachment)	Trans. Type M5 A4	ETW or Test Wt.	DPA or RLHP	Ignition (ECM/PCM) Part No.	EGR System Part No.	Catalyst Converter Part No.
NA-100 (CA, 49S)	PLDH41 PLPH41	A3	2875	S E E A T T A C H M E N T	05293018AP	N/A	04777904AC/ 05278345

Date Issued: 2/23/99

(49S = NLEV)

Revisions: _____

MODELS COVERED BY CERTIFICATE

Vehicle MFR: CHRYSLER Engine Family: YCRXV0122V41 Certificate #:
Evaporative Fam: YCRXR0101G1A

Model ID	Car Line	California
PLDH41	Neon	Sales
PLPH41	Neon	YES
		YES

* - For U.S. Possessions the nameplate will read Chrysler

Model Codes
JA CH 41

--- Body Style
22=2 door coupe
27=2 door convertible
41=4 door sedan
42=4 door subcompact sedan

----- Trim Level
H=High Line S=Sport
P=Premium L=Low Line

----- Division
L=C=Chrysler D=Dodge
X=Eagle P=Plymouth

----- Car Line
JA=Cirrus, Stratus, Breeze PL=Neon
JX=Sebring Convertible
LH=Concorde, New Yorker, LHS, Vision, Intrepid
SR=Viper, PR=Prowler

2000
YCRXV0122V41

Chrysler Corporation
Family Tire Usage

ATTACHMENT TO SDS PAGE 1
OF EXECUTIVE ORDER A-9-444

ADJUSTED LOADED VEHICLE WGT

LOADED VEHICLE WEIGHT

MODEL	ENG	TRANS	A	MKT	LVM	TIRE	DESCRIPTION	COAST	*DYNO	TIRE	TARGET A	COLD CO	ELECTRIC	DYNO	COEFFICIENTS	SET A	B	C	ALVM	DOWN	*DYNO	TIRE		
			C	GVM	TYPE	ETM	USE	YR	COD	MFG	OPT	TIME	HP	F	R	(LINE 1 IS 20 DEG	COEFFS,	LINE 2 IS 50 DEG	WHEN NEEDED)	ETM	TIME	HP	F	R
PLDHA1	ECB	DGC	FW	Y	0	C	2875	STD	00	TJY	TZA	14.22	6.1	32	32	37.63								
								OPT	00	TOK	TZA	13.95	6.6	32	32	33.12								
PLPHA1	ECB	DGC	FW	Y	0	C	2875	STD	00	TJY	TZA	14.22	6.1	32	32	37.63								
								OPT	00	TOK	TZA	13.95	6.6	32	32	33.12								

* - FOR DYNO HP = 0.00
REF TO FRONTAL AREA

/ 10. - VA04 - 400 /

Report Date: 03/02/99
Time: 10:52:15