State of California AIR RESOURCES BOARD

EXECUTIVE ORDER A-16-242 Relating to Certification of New Motor Vehicles

MAZDA MOTOR CORPORATION

Pursuant to the authority vested in the Air Resources Board by the Health and Safety Code, Division 26, Part 5, Chapter 2; and

Pursuant to the authority vested in the undersigned by Health and Safety Code Sections 39515 and 39516 and Executive Order G-45-9;

IT IS ORDERED AND RESOLVED: That 2000 model-year Mazda Motor Corporation exhaust emission control systems are certified as described below for passenger cars:

Emission Standard Category: Low-Emission Vehicle (LEV)

Fuel Type: Gasoline

Engine Family: YTKXV01.8VFM Displacement: 1.8 Liters (112 Cubic Inches)

Exhaust Emission Control Systems & Special Features:

Warm Up Three Way Catalytic Converter Three Way Catalytic Converter Heated Oxygen Sensors (two) Exhaust Gas Recirculation Sequential Multiport Fuel Injection

Vehicle models, transmissions, engine codes and evaporative emission control families are listed on attachments.

The LEV certification exhaust emission standards for this engine family in grams per mile are:

Miles	Non-Methane Organic Gases	Carbon <u>Monoxide</u>	Oxides of <u>Nitrogen</u>	<u>Formaldehyde</u>	Carbon Monoxide (20°F)
50,000	0.075	3.4	0.2	0.015	10.0
100,000	0.090	4.2	0.3	0.018	n/a

Reactivity Adjustment Factor (RAF) for NMOG Mass Emission: 0.94

The certification exhaust emission values set forth for non-methane organic gases (NMOG) reflect application of a 0.94 RAF for 2000 model-year LEVs. The LEV certification exhaust emission values for this engine family in grams per mile are:

Miles	Non-Methane Organic Gases	Carbon <u>Monoxide</u>	Oxides of <u>Nitrogen</u>	<u>Formaldehyde</u>	Carbon Monoxide (20°F)
50,000	0.039	0.5	0.04	0.001	4.1
100,000	0.040	0.5		0.001	n/a

BE IT FURTHER RESOLVED: That the vehicle manufacturer is certifying the listed vehicle models to the aforementioned exhaust emission standards based on its submitted plan to comply with the fleet average NMOG exhaust mass emission requirements as set forth in "California Exhaust Emission Standards and Test Procedures for 1988 and Subsequent Model Passenger Cars, Light-Duty Trucks, and Medium-Duty Vehicles."

BE IT FURTHER RESOLVED: That under the submitted NMOG fleet average compliance plan, if the manufacturer incurs a NMOG debit for the aforementioned model year based on the projected NMOG fleet average exceeding the value required by the above-referenced standards and test procedures, all incurred NMOG debits by the manufacturer shall be equalized as required by the standards and test procedures.

BE IT FURTHER RESOLVED: That the vehicle manufacturer is certifying the listed vehicle models to the running loss and useful life standards applicable to 1995 and subsequent model-year vehicles in the "California Evaporative Emission Standards and Test Procedures for 1978 and Subsequent Model Motor Vehicles," and the listed vehicle models comply with those standards.

BE IT FURTHER RESOLVED: That the vehicle manufacturer is certifying the listed vehicle models to the "California Refueling Emission Standards and Test Procedures for 1998 and Subsequent Model Motor Vehicles," Title 13, California Code of Regulations, Section 1978, and the listed vehicle models comply with those standards.

BE IT FURTHER RESOLVED: That the listed vehicle models also comply with the Board's "Specifications for Fill Pipes and Openings of Motor Vehicle Fuel Tanks" for the aforementioned model year (Title 13, California Code of Regulations, Section 2235).

BE IT FURTHER RESOLVED: That the listed vehicle models also comply with the Board's high-altitude requirements and highway emission standards, and with the California Inspection and Maintenance emission standards in place at the time of certification, as stipulated in "California Exhaust Emission Standards and Test Procedures for 1988 and Subsequent Model Passenger Cars, Light-Duty Trucks, and Medium-Duty Vehicles."

BE IT FURTHER RESOLVED: That the listed vehicle models also comply with the "California Motor Vehicle Emission Control and Smog Index Label Specifications" for the aforementioned model year (Title 13, California Code of Regulations, Section 1965).

BE IT FURTHER RESOLVED: That the vehicle manufacturer has demonstrated compliance with the exhaust emission standards at 50 degrees Fahrenheit as stipulated in "California Exhaust Emission Standards and Test Procedures for 1988 and Subsequent Model Passenger Cars, Light-Duty Trucks, and Medium-Duty Vehicles."

BE IT FURTHER RESOLVED: That the listed vehicle models also comply with the "Malfunction and Diagnostic System Requirements--1994 and Subsequent Model-Year Passenger Cars, Light-Duty Trucks, and Medium-Duty Vehicles and Engines" (Title 13, California Code of Regulations, Section 1968.1) for the aforementioned model year.

BE IT FURTHER RESOLVED: That for the listed vehicles, the manufacturer has submitted and the Executive Officer hereby approves the materials to demonstrate certification compliance with the Board's emission control system warranty provisions (Title 13, California Code of Regulations, Section 2035 et seq.).

Vehicles certified under this Executive Order must conform to all applicable California emission regulations.

The Bureau of Automotive Repair will be notified by copy of this order and attachment.

Executed at El Monte, California this ______

day of August 1999.

R. B. Summerfield, Chief

Mobile Source Operations Division

Manufacturer:	Mazda Motor Corpor	ation Ext	n Eng Fam:	YTKXV01.	SVFM E	ap Fam: YTKXF	0125BFB
All Engine Codes in	Engine Family:	CA 4	9S 5	0S X	AB965 ,	ORVR: YES_	X NO
Exh Std: CA	Tier-1 TL	EV Li	EV X	ULEV	SULEV	, US EF	A Tier-1
Veh Class (es):	PC X LDT1	LDT2	 MD	·V1	MDV2	MDV3 MDV	/4 MDV5
Single Cert Std for i	Multi-Class Eng Far	N/A	(speci	fv : N/A, LD	T1. MDV1. MDV2	MDV3, MDV4)	
Fuel Type (s):	Dedicated	Fley-Firel	— Oue	el-Euel	Bi-Fuel	Gasoline X	Diesel
ruel Type (s) .	CNC	LNG	LPG	M85	Othe	r (specify)	
Exh Emiss Test Fu	-1 (-) - lade	CDC	r CVIG	. IPG	M85	Other (specif	v1
EXIT EMISS LEST FU	er (s): Indo	40.000.000	<u> </u>	L' U	113.00	40 CER 86	3113-04
	and the second s					40 CFR 86	
Evaporative Emissi						- /if-\	
Service Accum:	Std. AMA X	Mod AMA		MIT AUP_	Othe	r (specity)	DT Carrage V
NMOG Test Proces	dure: N/A	Std_2	(Eq	uiv	R/L Test Proc :	SHED	PI Source X
Engine Configuration	on: <u>I-4</u>	Displacement:	1.8		_Liters112	.3 /	Judic Inches
Valves per Cylinder	r: <u>4</u>		Ra	ited HP: _	120	@60	000 RPM
Engine : Front	XMid	Rear	Dri	ive: ÆWI	<u> </u>	- 4WD-FT	4WD-PT
Exhaust ECS (e.g.,	MFI, EGR, TC, CA	C):	1	HOŽŠ/W	/U-TWC/TWC/SFI	ÆGR	
				(Use abbr	eviations per SAE	J1930 MAY91)	
		-		•			
·			ETIA	DDA	Ignition	EGR	Catalyst
Engine Code	Vehicle Models	rans. Type (M5, A4	Dr E1VV	DPA or		i) System	Part No.
(also fist CA/ 49ST/50ST)	(if coded see attachment)	etc.)		RLHP			
FFPD2AAA	Protege	M5	2875	5.7 *1		EGR Control	ZM01
1112-11				6.3 *2] N/A	Valve:	ZM02
FFPD2AAY				6.3 *1	_IECU:	FP34	
(A/C)			0077	6.9 *2	FPA3		
FFPDTAAA		A4	2875	5.7 *1 6.3 *2	Distrubutor: N/A		
FFPDTAAY				6.3 *1	ECU:	-	
(A/C)				6.9 *2	FPA4		
	Standards (50,000	mile / 100.000	mile / 120	.000 mil			
			,	_			
HC (g/mi) NMOG (g/ml)	<u>.</u>	.075 / 0.09			İ		
NMHC (g/mi)	÷	. /	<u>/ ··</u>			-	
CQ (g/mi) NOx (g/mi)		.4 / 4.2 .2 / 0.3	7				
HWFET NOX (.3 / 0.4	/				[
Evap. (EPA : g		·· / ···	<u> </u>				. 1
Evap. (ARE: 9		·· / 2.0 ·· / 2.5	/ ::		1	1	
Evap. (Abbrev Running Loss		·· / 2.5 · / 0.0:			+		
Spit Back (g/test)			1				
ORVR (g/gallon)					1		
Cold CO (g/mi)		/	, ,		1		
HCHO (mg/mi)	<u> </u>	5 / 18	,	•			
CST -HC (ppm		t laie: 100, at 25 t laie: 0.5, at 25]
CST +CO (%) NMOG (g/mi) f	_	.150 / ***	/		1		:
HCHO (mg/ml)		υ /	/	•			
Revisions:	*1: 185 Tire, *2: 1	95 Tire					

Issue Date: May 21, 1999	<u> </u>
Rev. No.	
Date	