State of California AIR RESOURCES BOARD

EXECUTIVE ORDER A-259-79 Relating to Certification of New Motor Vehicles

SUZUKI MOTOR CORPORATION

Pursuant to the authority vested in the Air Resources Board by the Health and Safety Code, Division 26, Part 5, Chapter 2; and

Pursuant to the authority vested in the undersigned by Health and Safety Code Sections 39515 and 39516 and Executive Order G-45-9;

IT IS ORDERED AND RESOLVED: That 2000 model-year Suzuki Motor Corporation exhaust emission control systems are certified as described below for lightduty trucks:

Emission Standard Category: Low-Emission Vehicle (LEV)

Fuel Type: Gasoline

Engine Family: YSKXT2.49LHA Displacement: 2.5 Liters (152 Cubic Inches)

Exhaust Emission Control Systems & Special Features:

Three Way Catalytic Converter Dual Warm Up Three Way Catalytic Converters Dual Heated Oxygen Sensors Heated Oxygen Sensor Exhaust Gas Recirculation Sequential Multiport Fuel Injection

Vehicle models, transmissions, engine codes and evaporative emission control families are listed on attachments.

The non-methane organic gases (NMOG), carbon monoxide (CO), oxides of nitrogen (NOx), and formaldehyde (HCHO) LEV certification exhaust emission standards for this engine family in grams per mile are:

Loaded Vehicle <u>Weight (lbs.)</u>	<u>Miles</u>	NMOG	_00_	<u>NOx</u>	<u>HCHO</u>	<u>CO (20°F)</u>	
0-3750	50,000	0.075	3.4	0.2	0.015	10.0	
	100,000	0.090	4.2	0.3	0.018	n/a	

Reactivity Adjustment factor (RAF) for NMOG Mass Emission: 0.94

The certification exhaust emission values set forth for NMOG reflect application of a 0.94 RAF for 2000 model-year LEVs. The LEV certification exhaust emission values for this engine family in grams per mile are: SUZUKI MOTOR CORPORATION

Loaded Vehicle <u>Weight (lbs.)</u>	<u>Miles</u>	NMOG	<u>_co</u>	<u>NOx</u>	<u>HCHO</u>	<u>CO (20°F)</u>	
0-3750	50,000	0.055	1.9	· 0.2	0.001	4.9	
	100,000	0.069	2.7	0.2	0.001	n/a	

BE IT FURTHER RESOLVED: That the vehicle manufacturer is certifying the listed vehicle models to the aforementioned exhaust emission standards based on its submitted plan to comply with the fleet average NMOG exhaust mass emission requirements as set forth in "California Exhaust Emission Standards and Test Procedures for 1988 and Subsequent Model Passenger Cars, Light-Duty Trucks, and Medium-Duty Vehicles."

BE IT FURTHER RESOLVED: That under the submitted NMOG fleet average compliance plan, if the manufacturer incurs a NMOG debit for the aforementioned model year based on the projected NMOG fleet average exceeding the value required by the above-referenced standards and test procedures, all incurred NMOG debits by the manufacturer shall be equalized as required by the standards and test procedures.

BE IT FURTHER RESOLVED: That the vehicle manufacturer is certifying the listed vehicle models to the running loss and useful life standards applicable to 1995 and subsequent model-year vehicles in the "California Evaporative Emission Standards and Test Procedures for 1978 and Subsequent Model Motor Vehicles," and the listed vehicle models comply with those standards.

BE IT FURTHER RESOLVED: That the listed vehicle models also comply with the Board's "Specifications for Fill Pipes and Openings of Motor Vehicle Fuel Tanks" for the aforementioned model year (Title 13, California Code of Regulations, Section 2235).

BE IT FURTHER RESOLVED: That the listed vehicle models also comply with the Board's high-altitude requirements and highway emission standards, and with the California Inspection and Maintenance emission standards in place at the time of certification, as stipulated in "California Exhaust Emission Standards and Test Procedures for 1988 and Subsequent Model Passenger Cars, Light-Duty Trucks, and Medium-Duty Vehicles."

BE IT FURTHER RESOLVED: That the listed vehicle models also comply with the "California Motor Vehicle Emission Control and Smog Index Label Specifications" for the aforementioned model year (Title 13, California Code of Regulations, Section 1965).

BE IT FURTHER RESOLVED: That the listed vehicle models also comply with the "Malfunction and Diagnostic System Requirements--1994 and Subsequent Model-Year Passenger Cars, Light-Duty Trucks, and Medium-Duty Vehicles and Engines" (Title 13, California Code of Regulations, Section 1968.1) for the aforementioned model year. SUZUKI MOTOR CORPORATION

EXECUTIVE ORDER A-259-79 (Page 3 of 3)

BE IT FURTHER RESOLVED: That the vehicle manufacturer has demonstrated compliance with the exhaust emission standards at 50 degrees Fahrenheit as stipulated in "California Exhaust Emission Standards and Test Procedures for 1988 and Subsequent Model Passenger Cars, Light-Duty Trucks, and Medium-Duty Vehicles."

BE IT FURTHER RESOLVED: That for the listed vehicles, the manufacturer has submitted and the Executive Officer hereby approves the materials to demonstrate certification compliance with the Board's emission control system warranty provisions (Title 13, California Code of Regulations, Section 2035 et seq.).

Vehicles certified under this Executive Order must conform to all applicable California emission regulations.

The Bureau of Automotive Repair will be notified by copy of this order and attachment.

Executed at El Monte, California this _/___ day of July 1999.

R. B. Summerfield, Chief Mobile Source Operations Division

2000 MODEL YEAR AIR RESOURCE BOARD SUPPLEMENTAL DATA SHEET PASSENGER CARS, LIGHT DUTY TRUCKS AND MEDIUM DUTY VEHICLES

All Engine Codes in Eng Fam: CA_49S_50S_XORVR: YESNOX Exh Std: Tier 0Tier 1_TLEVLEV_X_ULEVZEV; US EPANLEV (All States) EVAP Std :50KUseful Life with R/LXIn Use Exh Std: FULL In UseX Alt In Use Veh Class(es): PCLDT1_X_LDT2MDV1MDV2MDV3MDV4MDV5 Single Cert Std for Multi-Class Eng Fam: <u>MA</u> (specify: N/A, LDT1, LDT2, MDV1, MDV2, MDV3, MDV4, MDV5) Fuel Type (s): DedicatedXFlex-FuelDual-FuelBI-FuelGasolineXDiesel CNGLNGLPGM85Other (specify) Emiss Test Fuel (s): IndoPh2_X_CNGLPGM85Other (specify) Diesel: 13CCR 2282 40CFR 86.113-90 40CFR 86.113-94 Service Accum: Std AMA Mod AMAMfr ADPX_Other (specify) EVAP Emission Test Procedures: CaliforniaFederalX NMOG Test Procedure: N/A StdX EquivR/L Test Proc: SHED Pt SourceX Hybrid: Type A B C, APU Cycle (e.g. Otto, Diesel, Turbine) Engine configuration: V6 Displacement: 2.5 Liters or 152 cubic inches Valves per Cylinder: 4 Rated HP155 @ 6.500 _RPM Engine: FrontX_ Mid Rear Drive: FWD RWD _X4WD-FT4WD-PT Exhaust ECS (eg., EGR, MFI, TC, CAC):SI / 2HO2S / HO2S / 2WU-TWC / TWC / EGR(per SAE J1930 SEP95)	Manufacturer: SUZUKI MOTOR CORP Exh Eng Fam: YSKXT2.49LHA EVAP Fam: YSKXE00892JA
Exh Std: Tier 0Tier 1_TLEVLEV X_ULEVZEV, GS ErX(ALLO (ALLOBARD)) EVAP Std :50KUseful Life with R/LXIn Use Exh Std: FULL in UseX Alt in Use Veh Class(es): PCLDT1_X_LDT2MDV1MDV2MDV3MDV4MDV5 Single Cert Std for Multi-Class Eng Fam: <u>MA</u> (specify: N/A, LDT1, LDT2, MDV1, MDV2, MDV3, MDV4, MDV5) Fuel Type (s): Dedicated _XFlex-FuelDual-FuelBI-FuelGasolineXDiesel CNGLNGLPGM85Other (specify) Emiss Test Fuel (s): IndoPh2_X_CNGLPGM85Other (specify) Diesel: 13CCR 228240CFR 86.113-9040CFR 86.113-94 Service Accum: Std AMA Mod AMA Mfr ADPXOther (specify)	All Engine Codes in Eng Fam: CA_49S_50S_XORVR: YESNOX
EVAP Std :50KUseful Life with R/LXMI Use EXH std. FULL in UseX At in Use Veh Class(es): PCLDT1_X_LDT2MDV1MDV2MDV3MDV4MDV5 Single Cert Std for Multi-Class Eng Fam: MA (specify: N/A, LDT1, LDT2, MDV1, MDV2, MDV3, MDV4, MDV5) Fuel Type (s): DedicatedXFlex-Fuel Dual-FuelBI-FuelGasolineXDiesel CNGLNGLPGM85Other (specify) Emiss Test Fuel (s): IndoPh2_X_CNGLPGM85Other (specify) Diesel: 13CCR 228240CFR 86.113-9040CFR 86.113-94 Service Accum: Std AMAMod AMAMfr ADPX_Other (specify) EVAP Emission Test Procedures: CaliforniaFederalX NMOG Test Procedure: N/AStdX EquivR/L Test Proc: SHEDPt Source Hybrid: Type ABC, APU Cycle (e.g. Otto, Diesel, Turbine) Engine configuration:V6Displacement: 2.5 Liters or	Exh Std: Tier 0 Tier 1_ILEV LEV X_ULEVZEV, US CFA ALLY religions
Veh Class(es): PCLDT1_X_LDT2MDV1MDV2MDV3MDV4MDV5 Single Cert Std for Multi-Class Eng Fam: //A (specify: N/A, LDT1, LDT2, MDV1, MDV2, MDV3, MDV4, MDV5) Fuel Type (s): DedicatedXFlex-FuelDual-FuelBi-FuelGasolineXDiesel CNGLNGLPGM85Other (specify) Emiss Test Fuel (s): IndoPh2_X_CNGLPGM85Other (specify) Diesel: 13CCR 228240CFR 86.113-9040CFR 86.113-94 Service Accum: Std AMAMod AMAMfr ADPXOther (specify)	EVAP Std :50K Useful Life with R/L X III Use Exh Std. FULL III Use An III Use
Single Cert Std for Multi-Class Eng Fam: <u>MA</u> (specify: N/A, LDT1, LDT2, MDV1, MDV2, MDV3, MDV4, MDV5) Fuel Type (s): Dedicated X_Flex-Fuel Dual-Fuel Bi-Fuel Gasoline X Diesel CNG LNG LPG M85 Other (specify) Emiss Test Fuel (s): Indo Ph2_X_CNG LPG M85 Other (specify) Diesel: 13CCR 2282 40CFR 86.113-90 40CFR 86.113-94 Service Accum: Std AMA Mod AMA Mfr ADPX Other (specify) EVAP Emission Test Procedures: California FederalX NMOG Test Procedure: N/A StdX R/L Test Proc: SHED Pt Source Hybrid: Type A B C, APU Cycle (e.g. Otto, Diesel, Turbine) Engine configuration: V6 Displacement: 2.5 Liters or 152 cubic inches Valves per Cylinder: Arated HP	Veh Class(es): PCLDT1_X_LDT2 MDV1 MDV2 MDV3 MDV4MDV5
Fuel Type (s): Dedicated X_Flex-Fuel Dual-Fuel BI-Fuel Gasoline X_Diesel Diesel Diesel CNG_LNG_LPG_M85_Other (specify) Emiss Test Fuel (s): Indo Ph2_X_CNG LPG M85_Other (specify) Diesel: 13CCR 2282 40CFR 86.113-90 40CFR 86.113-94 Service Accum: Std AMA Mod AMA Mfr ADP_X_Other (specify) EVAP Emission Test Procedures: California Federal NMOG Test Procedure: N/A Std X Hybrid: Type A B_C_, APU Cycle (e.g. Otto, Diesel, Turbine) Pt Source Engine configuration: V6 Displacement: 2.5 Liters or 152 cubic inches Valves per Cylinder: 4 Rated HP 155 6.500 RPM Engine: Front X Mid Rear Drive: FWD RWD X 4WD-PT X Exhaust ECS (eg., EGR, MFI, TC, CAC): SFI / 2HO2S / HO2S / 2WU-TWC / TWC / EGR (per SAE J1930 SEP95) (per SAE J1930 SEP95)	Single Cert Std for Multi-Class Eng Fam: <u>NA</u> (specify: N/A, LDT1, LDT2, MDV1, MDV2, MDV3, MDV4, MDV5)
CNGLNGLPGM85Other (specify) Emiss Test Fuel (s): IndoPh2_X_CNGLPGM85Other (specify) Diesel: 13CCR 228240CFR 86.113-9040CFR 86.113-94 Service Accum: Std AMAMod AMAMfr ADPX_Other (specify) EVAP Emission Test Procedures: CaliforniaFederalX NMOG Test Procedure: N/AStdX_EquivR/L Test Proc: SHEDPt SourceX Hybrid: Type ABC, APU Cycle (e.g. Otto, Diesel, Turbine) Engine configuration: V6Displacement: 2.5 Liters or 152 cubic inches Valves per Cylinder: 4 Rated HP155 @6.500 RPM Engine: Front _X_MidRearDrive: FWDRWDX_4WD-FT4WD-PTX Exhaust ECS (eg., EGR, MFI, TC, CAC): SFI / 2HO2S / HO2S / 2WU-TWC / TWC / EGR(per SAE J1930 SEP95)	Fuel Type (S): Dedicated X Flex-Fuel Dual-Fuel Bi-Fuel Gasoline X Diesel
Emiss Test Fuel (s): Indo Ph2_X_CNG LPG M85Other (specify) Diesel: 13CCR 2282 40CFR 86.113-90 40CFR 86.113-94 Service Accum: Std AMA Mod AMA Mfr ADP_X_Other (specify) EVAP Emission Test Procedures: California Federal X	CNG LNG LPG M85 Other (specify)
Diesel: 13CCR 2282	Emiss Test Fuel (s): Indo Ph2X_CNG LPG M85 Other (specify)
Service Accum: Std AMA Mod AMA Mfr ADPXOther (specify) EVAP Emission Test Procedures: CaliforniaFederalX NMOG Test Procedure: N/A StdX Equiv R/L Test Proc: SHED Pt SourceX Hybrid: Type A B C, APU Cycle (e.g. Otto, Diesel, Turbine) Engine configuration: V6 Displacement: 2.5 Liters or 152 cubic inches Valves per Cylinder: 4 Rated HP 155 @ 6,500 RPM Engine: Front Mid Rear Drive: FWD RWD 4WD-FT 4WD-PT X Exhaust ECS (eg., EGR, MFI, TC, CAC): SFI / 2HO2S / HO2S / 2WU-TWC / TWC / EGR (per SAE J193C SEP95)	Diesel: 13CCR 2282 40CFR 86.113-90 40CFR 86.113-94
EVAP Emission Test Procedures: CaliforniaFederalX NMOG Test Procedure: N/AStd X Equiv R/L Test Proc: SHEDPt Source X Hybrid: Type AB C, APU Cycle (e.g. Otto, Diesel, Turbine) Engine configuration: V6Displacement: 2.5 Liters or 152 cubic inches Valves per Cylinder: Arated HPDrive: FWDRWDAWD-FTAWD-PTX Engine: FrontMidRearDrive: FWDRWDAWD-FTAWD-PTX Exhaust ECS (eg., EGR, MFI, TC, CAC): SFI / 2HO2S / HO2S / 2WU-TWC / TWC / EGR(per SAE J193C SEP95)	Service Accum: Std AMA Mod AMA Mfr ADPX Other (specify)
NMOG Test Procedure: N/AStd _X EquivR/L Test Proc: SHEDPt SourceX Hybrid: Type ABC, APU Cycle (e.g. Otto, Diesel, Turbine) Engine configuration:V6Displacement: 2.5 Liters or 152 cubic inches Valves per Cylinder:4Rated HP55	EVAP Emission Test Procedures: CaliforniaFederalX
Hybrid: Type ABC, APU Cycle (e.g. Otto, Diesel, Turbine) Engine configuration: V6Displacement: 2.5 Liters or 152 cubic inches Valves per Cylinder:4Rated HP155@6,500 RPM Engine: Front _XMidRearDrive: FWDRWDX 4WD-FT4WD-PTX Exhaust ECS (eg., EGR, MFI, TC, CAC):SFI / 2HO2S / HO2S / 2WU-TWC / TWC / EGR(per SAE J193C SEP95)	NMOG Test Procedure: N/A Std X Equiv R/L Test Proc: SHED Pt Source X
Engine configuration: <u>V6</u> Displacement: <u>2.5</u> Liters or <u>152</u> cubic inches Valves per Cylinder: <u>4</u> Rated HP <u>155</u> @ <u>6.500</u> RPM Engine: Front <u>X</u> MidRear Drive: FWD RWD <u>X</u> 4WD-FT <u>4WD-PT X</u> Exhaust ECS (eg., EGR, MFI, TC, CAC): <u>SFI / 2HO2S / HO2S / 2WU-TWC / TWC / EGR</u> (per SAE J193C SEP95)	Hybrid: Type A B C , APU Cycle (e.g. Otto, Diesel, Turbine)
Valves per Cylinder: 4 Rated HP 155 @ 6,500 RPM Engine: Front X Mid Rear Drive: FWD RWD X 4WD-FT 4WD-PT X Exhaust ECS (eg., EGR, MFI, TC, CAC): SFI / 2HO2S / HO2S / 2WU-TWC / TWC / EGR (per SAE J1930 SEP95) (per SAE J1930 SEP95)	Engine configuration: V6 Displacement: 2.5 Liters or 152 cubic inches
Engine: Front <u>X</u> MidRearDrive: FWDRWD <u>X</u> 4WD-FT4WD-PT <u>X</u> Exhaust ECS (eg., EGR, MFI, TC, CAC): <u>SFI / 2HO2S / HO2S / 2WU-TWC / TWC / EGR</u> (per SAE J1930 SEP95)	Valves per Cylinder: 4 Rated HP 155 @ 6,500 RPM
Exhaust ECS (eg., EGR, MFI, TC, CAC): <u>SFI / 2HO2S / HO2S / 2WU-TWC / TWC / EGR</u> (per SAE J1930 SEP95)	Valves per cymreit Mith Part Drive: EWD RWD X 4WD-FT 4WD-PT X
(per SAE J1930 SEP95)	Engine: Front Y Mid Real Ulive. LVD
	Engine: Front <u>X</u> MidReal Drive: FWBRCB
	Engine: Front <u>X</u> MidReal Drive: FWDRUD_

Engine Code (also list CA/49ST/50ST)	Vehicle Models (re: p.21.00)	Trans Type	ETW	RLHP	Ignition Part No. (ECM/PCM)	EGR System Part No.	Catalytic Converter Part No.
BTLMM (50ST)	Grand VITARA	M5	3500	14.0	33920-67D42	18111-77500	14250-65D20 (Under) 14110-67D00 (Ex-R) 14110-67D10 (Ex-L)
BTLMB (50ST)	Grand VITARA	A4	3500	14.0	33920-67D52		

Date Issued: April 28, 1999 Revised:

Application
Rrocessed by: _____ Date ____ Reviewed by : _____ Date: _____