State of California AIR RESOURCES BOARD

EXECUTIVE ORDER A-23-265 Relating to Certification of New Motor Vehicles

HONDA MOTOR CO., LTD.

Pursuant to the authority vested in the Air Resources Board by the Health and Safety Code, Division 26, Part 5, Chapter 2; and

Pursuant to the authority vested in the undersigned by Health and Safety Code Sections 39515 and 39516 and Executive Order G-45-9;

IT IS ORDERED AND RESOLVED: That 2000 model-year Honda Motor Co., Ltd. exhaust emission control systems are certified as described below for passenger cars:

Emission Standard Category: Low-Emission Vehicle (LEV)

Fuel Type: Gasoline

Engine Family: YHNXV02.3PA3 <u>Displacement</u>: 2.3 Liters (138 Cubic Inches)

Exhaust Emission Control Systems & Special Features:

Three Way Catalytic Converter Heated Oxygen Sensors (two) Exhaust Gas Recirculation Sequential Multiport Fuel Injection

Vehicle models, transmissions, engine codes and evaporative emission control families are listed on attachments.

The LEV certification exhaust emission standards for this engine family in grams per mile are:

<u>Miles</u>	Non-Methane Organic Gases	Carbon <u>Monoxide</u>	Nitrogen Oxides	<u>Formaldehyde</u>	Carbon <u>Monoxide (20°F)</u>	
50,000	0.075	3.4	0.2	0.015	10.0	
100,000	0.090	4.2	0.3	0.018	n/a	

Reactivity Adjustment Factor (RAF) for NMOG Mass Emission: 0.94

The certification exhaust emission values set forth for non-methane organic gases (NMOG) reflect application of a 0.94 RAF for 2000 model-year LEVs. The LEV certification exhaust emission values for this engine family in grams per mile are:

<u>Miles</u>	Non-Methane Organic Gases	Carbon <u>Monoxide</u>	Nitrogen <u>Oxides</u>	<u>Formaldehyde</u>	Carbon Monoxide (20°F)
50,000	0.035	0.9	0.05	0.001	3.7
100,000	0.041		0.1	0.001	n/a

BE IT FURTHER RESOLVED: That the vehicle manufacturer is certifying the listed vehicle models to the aforementioned exhaust emission standards based on its submitted plan to comply with the fleet average NMOG exhaust mass emission requirements as set forth in "California Exhaust Emission Standards and Test Procedures for 1988 and Subsequent Model Passenger Cars, Light-Duty Trucks, and Medium-Duty Vehicles."

BE IT FURTHER RESOLVED: That under the submitted NMOG fleet average compliance plan, if the manufacturer incurs a NMOG debit for the aforementioned model year based on the projected NMOG fleet average exceeding the value required by the above-referenced standards and test procedures, all incurred NMOG debits by the manufacturer shall be equalized as required by the standards and test procedures.

BE IT FURTHER RESOLVED: That the vehicle manufacturer is certifying the listed vehicle models to the running loss and useful life standards applicable to 1995 and subsequent model-year vehicles in the "California Evaporative Emission Standards and Test Procedures for 1978 and Subsequent Model Motor Vehicles," and the listed vehicle models comply with those standards.

BE IT FURTHER RESOLVED: That the vehicle manufacturer is certifying the listed vehicle models to the "California Refueling Emission Standards and Test Procedures for 1998 and Subsequent Model Motor Vehicles," Title 13, California Code of Regulations, Section 1978, and the listed vehicle models comply with those standards.

BE IT FURTHER RESOLVED: That the listed vehicle models also comply with the Board's "Specifications for Fill Pipes and Openings of Motor Vehicle Fuel Tanks" for the aforementioned model year (Title 13, California Code of Regulations, Section 2235).

BE IT FURTHER RESOLVED: That the listed vehicle models also comply with the Board's high-altitude requirements and highway emission standards, and with the California Inspection and Maintenance emission standards in place at the time of certification, as stipulated in "California Exhaust Emission Standards and Test Procedures for 1988 and Subsequent Model Passenger Cars, Light-Duty Trucks, and Medium-Duty Vehicles."

BE IT FURTHER RESOLVED: That the listed vehicle models also comply with the "California Motor Vehicle Emission Control and Smog Index Label Specifications" for the aforementioned model year (Title 13, California Code of Regulations, Section 1965).

BE IT FURTHER RESOLVED: That the vehicle manufacturer has demonstrated compliance with the exhaust emission standards at 50 degrees Fahrenheit as stipulated in "California Exhaust Emission Standards and Test Procedures for 1988 and Subsequent Model Passenger Cars, Light-Duty Trucks, and Medium-Duty Vehicles."

BE IT FURTHER RESOLVED: That the listed vehicle models also comply with the "Malfunction and Diagnostic System Requirements--1994 and Subsequent Model-Year Passenger Cars, Light-Duty Trucks, and Medium-Duty Vehicles and Engines" (Title 13, California Code of Regulations, Section 1968.1) for the aforementioned model year.

BE IT FURTHER RESOLVED: That for the listed vehicles, the manufacturer has submitted and the Executive Officer hereby approves the materials to demonstrate certification compliance with the Board's emission control system warranty provisions (Title 13, California Code of Regulations, Section 2035 et seq.).

Vehicles certified under this Executive Order must conform to all applicable California emission regulations.

The Bureau of Automotive Repair will be notified by copy of this order and attachment.

Executed at El Monte, California this 3th day of August 1999.

R. B. Summerfield, Chief

Mobile Source Operations Division

2000 MODEL-YEAR AIR RESOURCES BOARD SUPPLEMENTAL DATA SHEET PASSENGER CARS, LIGHT-DUTY TRUCKS AND MEDIUM-DUTY VEHICLES

E.O. # A-23-265 Page 1 of 1

Manufacturer: HONDA Exh Engine Family: YHNXV02.3PA3 EVAP Family: YHNXR0130AAA All Engine Codes in Engine Family: CA 49S 50S X AB965 ORVR: YES X NO Exh std: CA Tier-1 TLEV LEV X ULEV SULEV US US EPA Tier-1 MDV4 MDV4 MDV4 MDV4 MDV5 MDV4 MDV5 MDV4 MDV2 MDV1 MDV2 MDV3 MDV4 MDV4 MDV4 MDV4 MDV4 MDV4 MDV3 MDV4 MDV3 MDV4 MDV4
Evaporative Emission Test Procedure: California Federal X Service Accum: Std AMA Mod AMA Mfr ADP X Other (specify) NMOG Test Procedure: N/A Std Equiv X, R/L Test Proc: SHED X Pt Source NMOG Test Procedure: N/A Std Equiv X, R/L Test Proc: SHED X Pt Source Engine Configuration: L-4 Displacement: 2.3/138 Liters/Cubic Inches For Valves per Cylinder: 4 Rated HP: 135 @ 5400 RPM, Engine: Front X Mid Rear Valves per Cylinder: 4 AWD-FT AWD-PT Drive: FWD X RWD 4WD-FT (use abbreviations per SAE J1930 MAY98)

(also list	Vehicle Models (if coded see attachment) Accord DX Sedan	Trans. (M5, A4 etc.) M5	eTW or Test Wt. 3250	DPA or RLHP 6.9	(ECM/PCM)	W Z = = =	Catalytic Converter Part No.
YPA1/1 (50ST)			3250	7.6	ECM: 37820-PAB-A01		
YPA3 (50ST)		L4	3250	6.9	EI Distributor: TD-91U		
YPA3/1 (50ST)			3375	7.6	PCM: 37820-PAB-A51		