## State of California AIR RESOURCES BOARD

## EXECUTIVE ORDER A-254-63 Relating to Certification of New Motor Vehicles

## HYUNDAI MOTOR COMPANY

Pursuant to the authority vested in the Air Resources Board by the Health and Safety Code, Division 26, Part 5, Chapter 2; and

Pursuant to the authority vested in the undersigned by Health and Safety Code Sections 39515 and 39516 and Executive Order G-45-9;

IT IS ORDERED AND RESOLVED: That 2000 model-year Hyundai Motor Company exhaust emission control systems are certified as described below for passenger cars:

Emission Standard Category: Low-Emission Vehicle (LEV)

Fuel Type: Gasoline

Engine Family: YHYXV01.5G3S Displacement: 1.5 Liters (91.2 Cubic Inches)

Exhaust Emission Control Systems & Special Features:

Sequential Multiport Fuel Injection Three Way Catalytic Converter Heated Oxygen Sensors (two)

Vehicle models, transmissions, engine codes and evaporative emission control families are listed on attachments.

The LEV certification exhaust emission standards for this engine family in grams per mile are:

Miles	Non-Methane Organic Gas	Carbon <u>Monoxide</u>	Nitrogen <u>Oxides</u>	<u>Formaldehyde</u>	Carbon Monoxide (20°F)
50,000	0.075	3.4	0.2	0.015	10.0
100,000	0.090	4.2	0.3	0.018	n/a

Reactivity Adjustment Factor (RAF) for NMOG Mass Emission: 0.94

The certification exhaust emission values set forth for non-methane organic gas (NMOG) reflect application of a 0.94 RAF for 2000 model-year LEVs. The LEV certification exhaust emission values for this engine family in grams per mile are:

Miles	Non-Methane Organic Gas	Carbon <u>Monoxide</u>	Nitrogen <u>Oxides</u>	<u>Formaldehyde</u>	Carbon <u>Monoxide (20°F)</u>
50,000	0.033	0.3	0.1	0.001	3.5
100,000	0.034		0.1	0.002	n/a

BE IT FURTHER RESOLVED: That the vehicle manufacturer is certifying the listed vehicle models to the aforementioned exhaust emission standards based on its submitted plan to comply with the fleet average NMOG exhaust mass emission requirements as set forth in "California Exhaust Emission Standards Trucks, and Medium-Duty Vehicles."

BE IT FURTHER RESOLVED: That under the submitted NMOG fleet average compliance plan, if the manufacturer incurs a NMOG debit for the aforementioned model year based on the projected NMOG fleet average exceeding the value required by the above-referenced standards and test procedures, all standards and test procedures.

BE IT FURTHER RESOLVED: That the vehicle manufacturer is certifying the listed vehicle models to the running loss and useful life standards applicable to 1995 and subsequent model-year vehicles in the "California Evaporative Emission Standards and Test Procedures for 1978 and Subsequent Model Motor Vehicles," and the listed vehicle models comply with those standards.

BE IT FURTHER RESOLVED: That the vehicle manufacturer is certifying the listed vehicle models to the "California Refueling Emission Standards and Test Code of Regulations, Section 1978, and the listed vehicles," Title 13, California those standards.

E IT FURTHER RESOLVED: That the listed vehicle models also comply with the Board's "Specifications for Fill Pipes and Openings of Motor Vehicle Fuel Regulations, Section 2235).

BE IT FURTHER RESOLVED: That the listed vehicle models also comply with the Board's high-altitude requirements and highway emission standards, and with time of certification, as stipulated in "California Exhaust Emission Standards and Test Procedures for 1988 and Subsequent Model Passenger Cars, Light-Duty

BE IT FURTHER RESOLVED: That the vehicle manufacturer has demonstrated compliance with the exhaust emission standards at 50 degrees Fahrenheit as stipulated in "California Exhaust Emission Standards and Test Procedures for Vehicles."

BE IT FURTHER RESOLVED: That the listed models also comply with the "Malfunction and Diagnostic System Requirements--1994 and Subsequent Model-Year Passenger Cars, Light-Duty Trucks, and Medium-Duty Vehicles and Engines" (Title 13, California Code of Regulations, Section 1968.1) for the

BE IT FURTHER RESOLVED: That the listed vehicle models also comply with the "California Motor Vehicle Emission Control and Smog Index Label Specifications" for the aforementioned model year (Title 13, California Code of Regulations, Section 1965).

BE IT FURTHER RESOLVED: That for the listed vehicles, the manufacturer has submitted and the Executive Officer hereby approves the materials to demonstrate certification compliance with the Board's emission control system warranty provisions (Title 13, California Code of Regulations, Section 2035

Vehicles certified under this Executive Order must conform to all applicable

The Bureau of Automotive Repair will be notified by copy of this order and

Executed at El Monte, California this 30 day

R. B. Summerfield, Chief

Mobile Source Operations Division

day of September 1999.

E.O.#	A-2	54	63	_
Page	_ 1_	of	3	

2000 MODEL-YEAR AIR RESOURCES SUPPLEMENTAL DATA SHEET PASSENGER CARS, LIGHT-DUTY TRUCKS AND MEDIUM-DUTY VEHICLES

Manufacturer: H	YUNDAI MOTOF	R CO. E.	ch Eng Fam	ı : Y <u>HYX</u>	<u>V01.5G3S</u> Eva	p Fam: <u>Y</u>	HYXR0105PEL
All Eng Codes in							
Exh Std : CA							
	Veh Class(es): PC_X LDT1 LDT2 MDV1 MDV2 MDV3 MDV4 MDV5 Single Cert Std for Muli-Class Eng Fam: N/A (specify: N/A, LDT1, MDV1, MDV2, MDV3, MDV4)						
Fuel Type(s) :	Dedicated X F	Flex-Fuel_	Dual-	Fuel	Bi-Fuel	Gasoline X	Diesel
	CNG LNO	G L1	PG M8	5Oth	ner (specify)		
Emiss Test Fuel	(s): Indo P	H2 <u>X</u> C	NG LP	'G M	85 Other (s	pecify)	
	Diesel: 13	CCR 228:	2	40 CFR	86.113-90	40 CF	R 86.113-94
Evaporative Emis	sion Test Proce	edure :	California_	F	ederal <u>X</u>		
Service Accum: Std AMA_X Mod AMA_ Mfr ADV_ Other (specify)							
NMOG Test procedure: N/A Std X Equiv R/L Test Proc: SHED X Pt Source							
Engine Configuration: I-4 Displacement: 1.5 / Liters 91.2 / Cubic Inches							
Valves Per Cylinder: 3 Rated HP: 90 @ 5,500 RPM							
Engine: Front X Mid_ Rear_ Drive: FWD_X RWD_ 4WD-FT_ 4WD-PT_							
Exhaust ECS (e.g., MFI EGR., TC, CAC, : HO2S(2) + TWC+ SFI							
(use abbreviations per SAE J1930 JUN93)							
Eng. Code	Veh. Models	Trans	ETW	DPA	Ignition	FCR	Catalystic
(also list CA/	(If coded see	į	OR		(ECU/PCM)	ļ	
49ST/50ST)	Attachment)	etc,)	Test Wt		i '	Part No.	
4001/0001/	/ Ittacimient)		Test III	IUIII	rate 140.	rait No.	Tatt No.
ACM5-L2	ACCENT	M5	2625	6.8	39110-22560	N/A	28510-22660
/CM5-L1(50ST)	ACCENT	1410	2020	0.8	(9030930080)	14/71	28310 22000
ACL4-L2			0.550	2.0			

2750

6.8

L4

Issued : 7-1-99

/CL4-L1(50ST)

Revised: