State of California AIR RESOURCES BOARD

EXECUTIVE ORDER A-30-126 Relating to Certification of New Motor Vehicles

AUDI AG

Pursuant to the authority vested in the Air Resources Board by the Health and Safety Code, Division 26, Part 5, Chapter 2; and

Pursuant to the authority vested in the undersigned by Health and Safety Code Sections 39515 and 39516 and Executive Order G-45-9;

IT IS ORDERED AND RESOLVED: That 2000 model-year Audi AG exhaust emission control systems are certified as described below for passenger cars:

<u>Emission Standard Category</u>: Low-Emission Vehicle (LEV)

Fuel Type (Certification Fuel): Gasoline (Indolene)

Engine Family: YADXV01.8332 Displacement: 1.8 Liters (109 Cubic Inches)

Exhaust Emission Control Systems & Special Features:

Sequential Multiport Fuel Injection Secondary Air Injection Three Way Catalytic Converter Heated Oxygen Sensors (two) Turbocharger Charge Air Cooler

Vehicle models, transmissions, engine codes and evaporative emission control families are listed on attachments.

The LEV certification exhaust emission standards for this engine family in grams per mile are:

<u>Miles</u>	Non-Methane <u>Organic Gas</u>	Carbon <u>Monoxide</u>	Nitrogen Oxides	<u>Formaldehyde</u>	Carbon <u>Monoxide (20°F)</u>
50,000	0.075	3.4	0.2	0.015	10.0
100,000	0.090	4.2	0.3	0.018	n/a

The LEV certification exhaust emission values for this engine family in grams per mile are:

Miles	Non-Methane <u>Organic Gas</u>	Carbon <u>Monoxide</u>	Nitrogen Oxides	<u>Formaldehyde</u>	Carbon <u>Monoxide (20°F)</u>
50,000	0.051	1.1	0.1	0.001	1.6
100,000	0.073	1.4	0.2	0.002	n/a

BE IT FURTHER RESOLVED: That the vehicle manufacturer is certifying the listed vehicle models to the aforementioned exhaust emission standards based on its submitted plan to comply with the fleet average NMOG exhaust mass emission requirements as set forth in "California Exhaust Emission Standards and Test Procedures for 1988 and Subsequent Model Passenger Cars, Light-Duty Trucks, and Medium-Duty Vehicles."

BE IT FURTHER RESOLVED: That under the submitted NMOG fleet average compliance plan, if the manufacturer incurs a NMOG debit for the aforementioned model year based on the projected NMOG fleet average exceeding the value required by the above-referenced standards and test procedures, all incurred NMOG debits by the manufacturer shall be equalized as required by the standards and test procedures.

BE IT FURTHER RESOLVED: That the vehicle manufacturer is certifying the listed vehicle models to the running loss and useful life standards applicable to 1995 and subsequent model-year vehicles in the "California Evaporative Emission Standards and Test Procedures for 1978 and Subsequent Model Motor Vehicles," and the listed vehicle models comply with those standards.

BE IT FURTHER RESOLVED: That the vehicle manufacturer is certifying the listed vehicle models to the "California Refueling Emission Standards and Test Procedures for the 1998 and Subsequent Model Motor Vehicles," Title 13, California Code of Regulations, Section 1978, and the listed models comply with those standards.

BE IT FURTHER RESOLVED: That the listed vehicle models also comply with the Board's "Specifications for Fill Pipes and Openings of Motor Vehicle Fuel Tanks" for the aforementioned model year (Title 13, California Code of Regulations, Section 2235).

BE IT FURTHER RESOLVED: That the listed vehicle models also comply with the Board's high-altitude requirements and highway emission standards, and with the California Inspection and Maintenance emission standards in place at the time of certification, as stipulated in "California Exhaust Emission Standards and Test Procedures for 1988 and Subsequent Model Passenger Cars, Light-Duty Trucks, and Medium-Duty Vehicles."

BE IT FURTHER RESOLVED: That the vehicle manufacturer has demonstrated compliance with the exhaust emission standards at 50 degrees Fahrenheit as stipulated in "California Exhaust Emission Standards and Test Procedures for 1988 and Subsequent Model Passenger Cars, Light-Duty Trucks, and Medium-Duty Vehicles."

BE IT FURTHER RESOLVED: That the listed vehicle models also comply with the "Malfunction and Diagnostic System Requirements--1994 and Subsequent Model-Year Passenger Cars, Light-Duty Trucks, and Medium-Duty Vehicles and Engines" (Title 13, California Code of Regulations, Section 1968.1) for the aforementioned model year.

BE IT FURTHER RESOLVED: That the listed vehicle models also comply with the "California Motor Vehicle Emission Control and Smog Index Label Specifications" for the aforementioned model year (Title 13, California Code of Regulations, Section 1965).

BE IT FURTHER RESOLVED: That for the listed vehicles, the manufacturer has submitted and the Executive Officer hereby approves the materials to demonstrate certification compliance with the Board's emission control system warranty provisions (Title 13, California Code of Regulations, Section 2035 et seq.).

Vehicles certified under this Executive Order must conform to all applicable California emission regulations.

The Bureau of Automotive Repair will be notified by copy of this order and attachment.

Executed at El Monte, California this day of September 1999.

R. B. Summerfield, Chief Mobile Source Operations Division

PAGE NO. 16.SS. -01 E.O.# $A - 30 - 121_0$ 1998 AIR RESOURCES BOARD SUPPLEMENTAL DATA SHEET Page 1 of 1 PASSENGER CARS, LIGHT-DUTY TRUCKS AND MEDUM-DUTY VEHICLES

Manufacturer:AUDI AGExh Eng Fam: _YADXV01.8332_ Evap Fam: _YADXR0140232
All Engine Codes in Engine Family: CA 495 505 X AB965 OFUR: Yes Y No
Exh Std: CA Tier-1 TLEV LEV_X_ ULEV SULEV; US EPA Tier 1_X
Veh Class(es): PC X LDT1 LDT2 MDV1 MDV2 MDV3 MDV4 MDV5
Single Cert Std for Multi-Class Eng Fam: N/A (specify: N/A, LDT1, MDV1, MDV2, MDV3, MDV4)
Fuel Type(s): Dedicated X Flex-Fuel Dual-Fuel Bi-Fuel Gasoline X Diesel
CNGLNGLPGM85Other (specify)
Exh Emiss Test Fuel(s): Indo X CBG CNG LPG M85 Other (specify)
Diesel: 13 CCR 2282 40 CFR 86.113-90 40 CFR 86.113-94
Evaporative Emission Test Procedure: California Federal X
Service Accum: Std AMA Mod AMA Mfr ADP X Other (specify)
NMOG Test Procedure: N/AStd_XEquivR/L Test Proc: SHEDPt Source_X
Engine Config. <u>L4 Turbo</u> Displacement: <u>1.8</u> Liters <u>109</u> Cubic Inches
Valves per Cylinder: 5 Rated HP: 150 @ 3700 RPM
Engine: Front X Mid Rear Drive: FWD X RWD 4WD-FT X 4WD-PT
Exhaust ECS (e.g., MFI, EGR, TC, CAC, etc.)

Engine Code	Vehicles Models	Trans.	ETW	DPA	Ignition	EGR	Catalytic
(also list	(if codded see	Type	or	or	(ECM/PCM)	System	Converter
CA/49ST/50ST)	attachment)	(M5, A4		RLHP	Part No.	Part No.	Part No.
		ect.)	WT				
ANB ZK	A4	M5	3250	5.7	4B0 906 018 P/BG	n.a.	8D0 131 702 GK
*		L5	3375	5.7	4Bo 906 018 Q/BH	H	. "
4	A4 Quattro	M5Q	3500	6.8	″ P/BG		
v		L5Q	3625	6.8	°Q∕BH	H	· · ·
a	Passat	MS	3500	6.4	″ P/BG	"	
#		L5	3625	6.1	″ Q/BH	a	
"	Passat Wagon	MS	3500	6.4	"P/BG	u	-
"		L5	3625	6.1	* Q/BH	#	e e
	A4 Wagon Quattro	MSQ	3625	6,8	" P/BG	Ħ	#
		L5Q	3750	6,8	″ Q/ВН	"	
				•			
							• •

Date Issued: 07-01-99

* ⁷

.4

Revisions: