

State of California  
AIR RESOURCES BOARD

EXECUTIVE ORDER A-48-43  
Relating to Certification of New Motor Vehicles

ROLLS-ROYCE & BENTLEY MOTOR CARS LIMITED

Pursuant to the authority vested in the Air Resources Board by the Health and Safety Code, Division 26, Part 5, Chapter 2; and

Pursuant to the authority vested in the undersigned by Health and Safety Code Sections 39515 and 39516 and Executive Order G-45-9;

IT IS ORDERED AND RESOLVED: That 2000 model-year Rolls-Royce & Bentley Motor Cars Limited exhaust emission control systems are certified as described below for passenger cars:

Fuel Type: Gasoline

Engine Family: YRRXV05.4NAT Displacement: 5.4 Liters (328 Cubic Inches)

Exhaust Emission Control Systems and Special Features:

Dual Three Way Catalytic Converters  
Dual Heated Oxygen Sensors (two)  
Sequential Multiport Fuel Injection  
Secondary Air Injection

Vehicle models, transmissions, engine codes and evaporative emission control families are listed on attachments.

The certification exhaust emission standards for this engine family in grams per mile are:

<u>Miles</u>	<u>Non-Methane Hydrocarbons</u>	<u>Carbon Monoxide</u>	<u>Nitrogen Oxides</u>	<u>Carbon Monoxide (20°F)</u>
50,000	0.25	3.4	0.4	10.0
100,000	0.31	4.2	0.6	n/a

The certification exhaust emission values for this engine family in grams per mile are:

<u>Miles</u>	<u>Non-Methane Hydrocarbons</u>	<u>Carbon Monoxide</u>	<u>Nitrogen Oxides</u>	<u>Carbon Monoxide (20°F)</u>
50,000	0.15	1.8	0.3	4.4
100,000	0.19	2.6	0.3	n/a

BE IT FURTHER RESOLVED: That the vehicle manufacturer is certifying the listed vehicle models to the aforementioned exhaust emission standards based on its submitted plan to comply with the fleet average NMOG exhaust mass emission requirements as set forth in "California Exhaust Emission Standards and Test Procedures for 1988-2000 Model Passenger Cars, Light-Duty Trucks, and Medium-Duty Vehicles."

BE IT FURTHER RESOLVED: That under the submitted NMOG fleet average compliance plan, if the manufacturer incurs a NMOG debit for the aforementioned model year based on the projected NMOG fleet average exceeding the value required by the above-referenced standards and test procedures, all incurred NMOG debits by the manufacturer shall be equalized as required by the standards and test procedures.

BE IT FURTHER RESOLVED: That the listed vehicle models also comply with the Board's "Specifications for Fill Pipes and Openings of Motor Vehicle Fuel Tanks" for the aforementioned model year (Title 13, California Code of Regulations, Section 2235.)

BE IT FURTHER RESOLVED: That the listed vehicle models also comply with the "California Motor Vehicle Emission Control and Smog Index Label Specifications" for the aforementioned model year (Title 13, California Code of Regulations, Section 1965.)

BE IT FURTHER RESOLVED: That the listed vehicle models also comply with the Board's high-altitude requirements and highway emission standards, and with the California Inspection and Maintenance emission standards in place at the time of certification, as stipulated in "California Exhaust Emission Standards and Test Procedures for 1988-2000 Model Passenger Cars, Light-Duty Trucks, and Medium-Duty Vehicles."

BE IT FURTHER RESOLVED: That the vehicle manufacturer is certifying the listed vehicle models to the running loss and useful life standards applicable to 1995-2005 model-year vehicles in the "California Evaporative Emission Standards and Test Procedures for 1978-2000 Model Motor Vehicles," and the listed vehicle models comply with those standards.

BE IT FURTHER RESOLVED: That the vehicle manufacturer is certifying the listed vehicle models to the "California Refueling Emission Standards and Test Procedures for 1998-2000 Model Motor Vehicles," Title 13, California Code of Regulations, Section 1978, and the listed vehicle models comply with those standards.

BE IT FURTHER RESOLVED: That the manufacturer is certifying the listed vehicle models with a partially complying on-board diagnostic system for the aforementioned model year pursuant to Title 13, California Code of Regulations, Section 1968.1(m)(6.2) ("Malfunction and Diagnostic System Requirements--1994 and Subsequent Model-Year Passenger Cars, Light-Duty Trucks, and Medium-Duty Vehicles and Engines").

BE IT FURTHER RESOLVED: That for the listed vehicles, the manufacturer has submitted and the Executive Officer hereby approves the materials to demonstrate certification compliance with the Board's emission control system warranty provisions (Title 13, California Code of Regulations, Section 2035 et seq.)

Vehicles certified under this Executive Order must conform to all applicable California emission regulations.

The Bureau of Automotive Repair will be notified by copy of this order and attachment.

Executed at El Monte, California this 9<sup>th</sup> day of December 1999.



*for* R. B. Summerfield, Chief  
Mobile Source Operations Division



ROLLS-ROYCE MOTOR CARS  
&  
BENTLEY MOTOR CARS



17 - 13

E.O. # A-48-43  
Page \_\_\_\_\_

**2000 MODEL-YEAR AIR RESOURCES BOARD SUPPLEMENTAL DATA SHEET  
PASSENGER CARS, LIGHT-DUTY TRUCKS AND MEDIUM-DUTY VEHICLES**

Manufacturer: Rolls-Royce & Bentley Motor Cars Ltd Exh Eng Fam : YRRXV05.4NAT Evap Fam : YRRXR0200E96  
 All Engine Codes in Engine Family: CA \_\_\_\_\_ 49S \_\_\_\_\_ 50S X AB965 \_\_\_\_\_, ORVR: YES X NO \_\_\_\_\_  
 Exh Std: CA Tier-1 X TLEV \_\_\_\_\_ LEV \_\_\_\_\_ ULEV \_\_\_\_\_ SULEV \_\_\_\_\_ US EPA Tier-1 X \_\_\_\_\_  
 Veh Class(es): PC X LDT1 \_\_\_\_\_ MDV1 \_\_\_\_\_ MDV2 \_\_\_\_\_ MDV3 \_\_\_\_\_ MDV4 \_\_\_\_\_ MDV5 \_\_\_\_\_  
 Single Cert Std for Multi-Class Eng Fam: N/A (specify: N/A, LDT1, MDV1, MDV2, MDV3, MDV4)  
 Fuel Type(s): Dedicated X Flex-Fuel \_\_\_\_\_ Dual-Fuel \_\_\_\_\_ Bi-Fuel \_\_\_\_\_ Gasoline X Diesel \_\_\_\_\_  
 CNG \_\_\_\_\_ LNG \_\_\_\_\_ LPG \_\_\_\_\_ M85 \_\_\_\_\_ Other (specify) \_\_\_\_\_  
 Exh Emiss Test Fuel(s): Indo X CBG \_\_\_\_\_ CNG \_\_\_\_\_ LPG \_\_\_\_\_ M85 \_\_\_\_\_ Other (specify) \_\_\_\_\_  
 Diesel: 13 CCR 2282 \_\_\_\_\_  
 Evaporative Emission Test Procedure: California \_\_\_\_\_ Federal X \_\_\_\_\_  
 Service Accum: Std AMA \_\_\_\_\_ Mod AMA \_\_\_\_\_ Mfr ADP \_\_\_\_\_ Other (specify) ADF X \_\_\_\_\_  
 NMOG Test Procedure: N/A N/A Std \_\_\_\_\_ Equip \_\_\_\_\_ R/L Test Proc: SHED \_\_\_\_\_ Pt Source X \_\_\_\_\_  
 Hybrid: Type A \_\_\_\_\_ B \_\_\_\_\_ C \_\_\_\_\_, APU Cycle (e.g., Otto, Diesel, Turbine)  
 Engine Configuration: V-12 Displacement: 5.4 \_\_\_\_\_ Liters 328.2/ \_\_\_\_\_ Cubic Inches  
 Valves per Cylinder: 2 Rated HP: 322 @ 5000 RPM  
 Engine: Front X Mid \_\_\_\_\_ Rear \_\_\_\_\_ Drive: FWD \_\_\_\_\_ RWD X 4WD-FT \_\_\_\_\_ 4WD-PT \_\_\_\_\_  
 Exhaust ECS (e.g., MFI, EGR, TC, CAC): 2TWC 2HO2S(2) SFI AIR  
 (use abbreviations per SAE J1930 JUN93)

Engine Code (Also list CA/49ST/50ST)	Vehicle Models (if coded see attachment)	Trans. (M5,A4 etc)	ETW or Test Wt.	DPA or RLHP	Ignition (ECM/PCM) Part No.	EGR System Part No.	Catalytic Converter Part No.
54 12 RA/50ST	Rolls-Royce Silver Seraph Rolls-Royce Park Ward	L5	5500	11.84  19.1	PB 20359	N/A	TWC PJ 20469 PJ 20470

Issue Date	31.08.99	Revision Date			YRR54N17.lwp
------------	----------	---------------	--	--	--------------