

State of California
AIR RESOURCES BOARD

EXECUTIVE ORDER A-9-497
Relating to Certification of New Motor Vehicles

DAIMLERCHRYSLER CORPORATION

Pursuant to the authority vested in the Air Resources Board by the Health and Safety Code, Division 26, Part 5, Chapter 2; and

Pursuant to the authority vested in the undersigned by Health and Safety Code Sections 39515 and 39516 and Executive Order G-45-9;

IT IS ORDERED AND RESOLVED: That the following exhaust and evaporative emission control systems produced by the manufacturer are certified as described below:

Model Year: 2001

Vehicle Type: 5751-8500 Pound Test Weight Medium-Duty Vehicle

Exhaust Emission Standard Category: Tier 1

Fuel Type: Gasoline

Test Group: 1CRXA0360J11

Engine Displacement: 5.2 and 5.9 Liters

Evaporative Family (Evap):

1. 1CRXE0174G5L
2. 1CRXE0174G6L
3. 1CRXE0174GDL
4. 1CRXE0174GEL

Special Features and Exhaust Emission Control Systems:

Sequential Multiport Fuel Injection
Three Way Catalytic Converter
Heated Oxygen Sensors (two)

Models Covered: Evap 1 (5.2/5.9 Liters): Dodge Ram 2500 Pickup 2WD/4WD
 Dodge Ram 3500 Pickup 2WD/4WD; Dodge Ram 3500 Van
 2WD; Dodge Ram Wagon 3500 2WD
 Evap 2 (5.2/5.9 Liters): Dodge Ram 2500 Cab Chassis 4WD
 Dodge Ram 2500 Pickup 2WD
 Evap 3 (5.2/5.9 Liters): Dodge Ram 1500 Pickup 4WD
 Evap 4 (5.2/5.9 Liters): Dodge Ram 1500 Pickup 4WD
 Dodge Ram Van 1500/2500 2WD; Dodge Ram Wagon 2500 2WD

The exhaust certification emission levels and standards, in grams per mile, of non-methane hydrocarbon (NMHC), carbon monoxide (CO), and oxides of nitrogen (NOx) for the listed vehicle models are as follows.

The evaporative hydrocarbon (HC) certification emission levels and standards for three-day diurnal plus hot soak (3D) and two-day diurnal plus hot soak (2D) in grams per test, running loss (RL) in grams per mile, and onboard refueling vapor recovery (ORVR) in grams per gallon of fuel dispensed, for the listed vehicle models are as follows.

<u>Type of Emissions</u>	<u>Miles</u>	<u>Certification Level</u>	<u>Certification Standards</u>			
<u>EXHAUST</u>						
..... NMHC	50,000	0.16	0.39			
NMHC	120,000	0.21	0.56			
CO	50,000	3.2	5.0			
CO	120,000	5.3	7.3			
NOx	50,000	0.9	1.1			
NOx	120,000	1.27	1.53			
NOx (highway)	50,000	0.5	2.2			
NOx (highway)	120,000	0.5	3.1			
CO (20°F)	50,000	9.4	12.5			
		<u>Certification Level</u>	<u>Certification Standards</u>			
<u>EVAPORATIVE</u>		<u>EVAP 1-4</u>	<u>EVAP1& 2</u>	<u>EVAP 3</u>	<u>EVAP 4</u>	
HC-2D	120,000	0.7	3.5	2.5	3.0	
HC-3D	120,000	1.1	3.0	2.0	2.5	
HC-RL	120,000	0.001	0.05	0.05	0.05	
HC-ORVR	120,000	n/a	n/a	n/a	n/a	

BE IT FURTHER RESOLVED: That any "Vehicle Equivalent Debit" in the manufacturer's medium-duty vehicle phase-in compliance plan shall be equalized as required by the "California Exhaust Emission Standards and Test Procedures for 2001 and Subsequent Model Passenger Cars, Light-Duty Trucks, and Medium-Duty Vehicles."


BE IT FURTHER RESOLVED: That the manufacturer is certifying the listed vehicle models with a partially complying on-board diagnostic system for the aforementioned model year pursuant to Title 13, California Code of Regulations, Section 1968.1(m)(6.2) ("Malfunction and Diagnostic System Requirements--1994 and Subsequent Model-Year Passenger Cars, Light-Duty Trucks, and Medium-Duty Vehicles and Engines.")

BE IT FURTHER RESOLVED: That for the listed vehicle models, the manufacturer has attested to compliance with the following California emission regulations and requirements. Vehicles certified under this Executive Order shall conform to all applicable California emission regulations and requirements.

- Specifications for Fill Pipes and Openings of Motor Vehicle Fuel Tanks (Title 13, California Code of Regulations, Section 2235)
- Motor Vehicle Emission Control and Smog Index Label Specifications (Title 13, California Code of Regulations, Section 1965)
- Emission Control System Warranty (Title 13, California Code of Regulations, Sections 2035 et seq.)
- High-Altitude Requirements and California Inspection and Maintenance Emission Standards (California Exhaust Emission Standards and Test Procedures for 2001 and Subsequent Model Passenger Cars, Light-Duty Trucks, and Medium-Duty Vehicles)

The Bureau of Automotive Repair will be notified by copy of this order.

Executed at El Monte, California this 22nd day of June 2000.



R. B. Summerfield, Chief
Mobile Source Operations Division