FORD MOTOR COMPANY

EXECUTIVE ORDER A-010-1006-1 New Passenger Cars, Light-Duty Trucks and Medium-Duty Vehicles

Pursuant to the authority vested in the Air Resources Board by Health and Safety Code (HSC), Div. 26, Part 5, Chap. 2; and pursuant to the authority vested in the undersigned by HSC Sections 39515 and 39516 and Executive Order G-45-9;

IT IS ORDERED AND RESOLVED: That the following exhaust and evaporative emission control systems produced by the manufacturer are certified as described below. Production vehicles shall be in all material respects the same as those for which certification is granted.

MODE		GROUP		VEHICLE TYPE		ST EMISSION RD CATEGORY	FUEL TYPE Gasoline (Indolene)						
2001		V04.6VF7		Passenger Car	Low En	ission Vehicle (LEV)							
No.	EVAPORA FAMILY (E		No.	SPECIAL FEATURES & EMISSION CONTROL SYSTEM	S (ECS)	* = not applicable	TWC = 3-way catalytic converter WUTWC = warm-up TWC ADSTWC = adsorber TWC OC = oxidation catalytic converter O2S = oxygen sensor						
1		FMXR0115BAE		2TWC(2), 2HO2S(2), 1	EGR, SFI, OBI	O (P)	HO2S = heated O2S EGR = exhaust gas recirculation AIR = secondary air injection PAIR = pulsed AII MEI = multiport fuel injection SFI = sequential MFI						
2	1			*									
3	•		3	•			TC/SC = turbo/super charger CAC = charge air coole OBD (F) / OBD (P) = on-board diagnosis; full / partial						
4				*		compliance (prefix) 2 = parallel (2) (suffix) = serie							
EVAI		ENGIN SIZE (L		4470	IDADDO ADE		ABBREVIATIONS: /F/ = Ford /L/ = Lincoln /W = Mercury						
-1	1	4.6		MAKES & MODELS STANDANDS ARE DINCETTED AND STANDARD STAND									
•	-	+ + +											
•	-												
		•	_			•							

The exhaust and evaporative emission standards (STD) and certification emission levels (CERT) for the listed vehicles are as follows. Any debit in the manufacturer's compliance plan for "NMOG Fleet Average" (passenger cars and light-duty trucks) or "Vehicle Equivalent Credit" (medium-duty vehicles) shall be equalized as required. The 50° Fahrenheit standards and CERT levels are listed below or compliance has been met based on the manufacturer's submitted compliance plan in lieu of actual testing.

NMOG FLEET NMOG [g/mi] AVERAGE [g/mi] @RAF = 1.00				CH4 = methane NMOG = non-CH4 organic gas NMHC = non-CH4 hydrocarbon CO = carbon monoxide NOx = oxides of nitrogen HCHO = formaldehyde PM = particulate matter RAF = reactivity adjustment factor NOx = oxides of nitrogen HCHO = formaldehyde PM = particulate matter RAF = reactivity adjustment factor													
CERT STD		_	CH4 RAF = 1			CO [g/mi]			NOx [g/mi]		HCHO [mg/mi]		PM [g/mi]				
				CERT STD		CERT	STD	CE	RT	STD	CERT	STD	CERT	ST	ם	CERT	STD
0.070	 	Ø 50K		0.046 0.075		0.7 3.4		0.	0.1	0.2	1 15	•			0.1	0.3	
										0.3	1	18				0.2	0.4
K = 1000 miles	@ 10	00K	0.	.057	0.090	0.9	4.2		0.2				+				•
	@ 50°F,	4K	•		•	*	*		*	•		<u> </u>				1	<u></u>
CO [g/mi] g = gram					NMHC+NOx [g/mi] NMHC+NOx [g/mi] (composite) [US06]					[g/mi] 306]	NMHC+NOx (g/mi) [SC03]		/mi]	CO [g/mi] [SC03]			
)°F, 50K			mg = milligram mi = mile		CERT	STD	CF	RT	STD	CERT 0.2	STD 8.0	CERT	0.01 0.20		CERT	STD
CERT	r STD		M) = Mil										0.01			0.1	2,7
6.2 10.0)		@ 4K		L		• 0.02		0.14			-		-		
F = degree Fahrenheit @ 100K			@ 100K	•	*		•	<u> </u>	•								
	EVAPORATIVE FAMILY 1					EVAPORATIVE FAMILY 2				/APORATI	Y 3	EV	APORA	ATIVE FAMILY 4			
9 100K						3-D	2-D	RL	ORV	R 3-D	2-D	RL	ORVR	3-D	2-D	RL	ORVE
	3-D	2-D		RL	ORVR	L				" "	+	 			:	•	•
CERT	1.4	1.0		0.003	0.13	•	*		ļ								•
STD	2.0	2.5		0.05	0.20	-	*	•	•		1 - 1	1	لـــــــــــــــــــــــــــــــــــــ		<u> </u>		
	#a=#1 = 7-d	au 2-0	iav (ilurnal a	nd hot-soal		RL [g/mi]	= runnir	ng loss	,	ORVR [g/g	allon of fue	l dispense	d] = on-b	pard rei	ueling vapo	IL LECOAR

BE IT FURTHER RESOLVED: That for the listed vehicle models, the manufacturer has attested to compliance with Title 13, California Code of Regulations, (13 CCR) Sections 1965 (labeling), 1968.1 or 1968.1(m)(6.2) (on-board diagnostic systems; full or partial compliance), 2035 et seq. (emission control warranty), 2235 (fuel tank fill pipes and openings), and "High-Altitude Requirements" and "Inspection and Maintenance Emission Standards" (California Exhaust Emission Standards and Test Procedures for 2001 and Subsequent Model Passenger Cars, Light-Duty Trucks, and Medium-Duty Vehicles).

Vehicles certified under this Executive Order shall conform to all applicable California emission regulations.

The Bureau of Automotive Repair will be notified by copy of this Executive Order.

This Executive Order hereby supersedes Executive Order A-010-1006 dated March 13/

Executed at El Monte, California on this 22

day of May 2001.

R. B. Symmerfield, Chief Mobile Souffce Operations Division