(Page 1 of 3)

State of California

EXECUTIVE ORDER A-23-301 Relating to Certification of New Motor Vehicles

HONDA MOTOR CO., LTD.

Pursuant to the authority vested in the Air Resources Board by the Health and Safety Code, Division 26, Part 5, Chapter 2; and

Pursuant to the authority vested in the undersigned by Health and Safety Code Sections 39515 and 39516 and Executive Order G-45-9;

IT IS ORDERED AND RESOLVED: That the following exhaust and evaporative emission control systems produced by the manufacturer are certified as described below:

Model Year: 2001

<u>Vehicle Type</u>: 3751-5750 Pound Loaded Vehicle Weight Light-Duty Truck

Exhaust Emission Standard Category: Ultra-Low-Emission Vehicle (ULEV)

Fuel Type: Gasoline

Test Group: 1HNXT03.5K86

Engine Displacements: 3.5 Liters

Evaporative Family: 1HNXR0160AAA

Special Features and Exhaust Emission Control Systems:

Three Way Catalytic Converter Exhaust Gas Recirculation Heated Oxygen Sensors (two) Sequential Multiport Fuel Injection

Models Covered: Acura MDX

The exhaust certification emission levels and standards, in grams per mile, of nonmethane organic gases (NMOG), carbon monoxide (CO), oxides of nitrogen (NOx), and formaldehyde (HCHO) for the listed vehicle models are as follows. The NMOG exhaust certification emission levels include application of the reactivity adjustment factor (RAF) as specified.

HONDA MOTOR CO., LTD.

The evaporative hydrocarbon (HC) certification emission levels and standards for three-day diurnal plus hot soak (3D) and two-day diurnal plus hot soak (2D) in grams per test, running loss (RL) in grams per mile, and onboard refueling vapor recovery (ORVR) in grams per gallon of fuel dispensed, for the listed vehicle models are as follows.

<u>Type of</u> <u>Emissions</u>	<u>Miles</u>	Certification Level	<u>Certification</u> <u>Standards</u>
EXHAUST @ NMOG RAF = 0.94			
NMOG fleet average		0.087 (projected)	0.098
NMOG	50,000	0.021	0.050
NMOG	100,000	0.022	0.070
CO	50,000	0.1	2.2
CO	100,000	0.1	2.8
NOx	50,000	0.04	0.4
NOx	100,000	0.04	0.5
NOx (highway)	50,000	0.02	0.5
NOx (highway)	100,000	0.02	0.7
HCHO	50,000	0.0005	0.009
HCHO	100,000	0.0005	0.013
CO (20°F)	50,000	1.6	12.5
NMOG (50°F)	4,000	0.077	0.100
CO (50°F)	4,000	0.7	2.2
NOx (50°F)	4,000	0.04	0.4
HCHO (50°F)	4,000	0.001	0.018
EVAPORATIVE			
HC-2D	100,000	1.3	2.5
HC-3D	100,000	1.6	2.0
HC-RL	100,000	0.02	0.05
HC-ORVR	100,000	0.02	0.20

BE IT FURTHER RESOLVED: That any debit in the manufacturer's NMOG fleet average compliance plan shall be equalized as required by the "California Exhaust Emission Standards and Test Procedures for 2001 and Subsequent Model Passenger Cars, Light-Duty Trucks, and Medium-Duty Vehicles."

BE IT FURTHER RESOLVED: That the listed vehicle models also comply with the "Malfunction and Diagnostic System Requirements--1994 and Subsequent Model-Year Passenger Cars, Light-Duty Trucks, and Medium-Duty Vehicles and Engines" (Title 13, California Code of Regulations, Section 1968.1). HONDA MOTOR CO., LTD.

BE IT FURTHER RESOLVED: That for the listed vehicle models, the manufacturer has attested to compliance with the following California emission regulations and requirements. Vehicles certified under this Executive Order shall conform to all applicable California emission regulations and requirements.

- Specifications for Fill Pipes and Openings of Motor Vehicle Fuel Tanks (Title 13, California Code of Regulations, Section 2235)

- Motor Vehicle Emission Control and Smog Index Label Specifications (Title 13, California Code of Regulations, Section 1965)

- Emission Control System Warranty (Title 13, California Code of Regulations, Sections 2035 et seq.)

- High-Altitude Requirements and California Inspection and Maintenance Emission Standards (California Exhaust Emission Standards and Test Procedures for 2001 and Subsequent Model Passenger Cars, Light-Duty Trucks, and Medium-Duty Vehicles)

The Bureau of Automotive Repair will be notified by copy of this order.

Executed at El Monte, California this _//___day of September 2000.

mapield

R. B. Summerfield, Chief Mobile Source Operations Division